

Company: Aruba Networks, Inc.

Test of: APEX0100, APEX0101  
To: FCC CFR 47 Part 15 Subpart E 15.407

Report No.: ARUB190-MPE Rev A

**MPE TEST REPORT**



# MPE TEST REPORT

FROM



Test of: Aruba Networks, Inc. APEX0100, APEX0101

to

To: FCC CFR 47 Part 15 Subpart E 15.407

Test Report Serial No.: ARUB190-MPE Rev A

This report supersedes: NONE

Applicant: Aruba Networks, Inc.  
1344 Crossman Ave.  
Sunnyvale, California 94089  
USA

Product Function: Wireless Access Point

Issue Date: 3<sup>rd</sup> May 2016

## **This Test Report is Issued Under the Authority of:**

**MiCOM Labs, Inc.**  
575 Boulder Court  
Pleasanton California 94566  
USA  
Phone: +1 (925) 462-0304  
Fax: +1 (925) 462-0306  
[www.micomlabs.com](http://www.micomlabs.com)



**MiCOM Labs is an ISO 17025 Accredited Testing Laboratory**



## 1. MAXIMUM PERMISSABLE EXPOSURE

### Calculations for Maximum Permissible Exposure Levels

Power Density = Pd (mW/cm<sup>2</sup>) = EIRP/(4\*π\*d<sup>2</sup>)

EIRP = P \* G

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

Numeric Gain = 10 ^ (G (dBi)/10)

Because the EUT belongs to the General Population/Uncontrolled Exposure the limit of power density is 1.0 mW/cm<sup>2</sup>

The calculations in the table below use the highest conducted power values together with the lowest antenna gain specified for the EUT. These calculations represent worst case in terms of the exposure levels.

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Safe Distance @ 1mW/cm <sup>2</sup>	Calculated Power Density @ 20cm	Minimum Separation Distance (cm)
2400 – 2483.5	5.00	3.16	29.92	981.75	15.71	0.62	20.00
5150.0 - 5250.0	5.00	3.16	29.77	949.20	15.46	0.60	20.00
5725.0 - 5850.0	5.00	3.16	29.99	998.65	15.85	0.63	20.00

**Note:** for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

### Assessment for simultaneous operation in 2.4 GHz and 5 GHz bands

The Aruba APEX0100, APEX0101 has two radio modules and can transmit simultaneously in the 2.4 GHz and 5 GHz bands. The following assessment is based on simultaneous operation in the 2.4 GHz and 5 GHz bands.

Freq. Band (MHz)	Antenna Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Safe Distance @ 1mW/cm <sup>2</sup> Limit (cm)	Minimum Separation Distance (cm)
2400 – 2483.5	5.00	3.16	29.92	981.75	15.71	20.00
5725.0 - 5850.0	5.00	3.16	29.99	998.65	15.85	20.00
<b>Combined EIRP Total</b>			6258.1 mW/EIRP		22.32	22.32

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** Aruba Networks, Inc. APIN0224, APIN0225  
**To:** FCC CFR 47 Part 15 Subpart E 15.407  
**Serial #:** ARUB190-MPE Rev A  
**Issue Date:** 3<sup>rd</sup> May 2016  
**Page:** 4 of 5

---

**Specification**  
**Maximum Permissible Exposure Limits**

**FCC §1.1310** Limit =  $1\text{mW} / \text{cm}^2$  from 1.310 Table 1

**RSS-Gen §3.2** In addition to RSS-Gen, the requirements in Radio Standards Specification RSS-102 shall be met.

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



575 Boulder Court  
Pleasanton, California 94566, USA  
Tel: +1 (925) 462 0304  
Fax: +1 (925) 462 0306  
[www.micomlabs.com](http://www.micomlabs.com)