



中国认可
国际互认
检测
TESTING
CNAS L5313



DEKRA

RF Exposure Evaluation Declaration

Product Name : Access Point
Model No. : APEX0365 ,APEX0367
FCC ID : Q9DAPEX0365367

Applicant : Hewlett Packard Enterprise Company
Address : 3000 Hanover St. Palo Alto,CA 94304,USA

Date of Receipt : Nov. 29, 2016
Test Date : Nov. 29, 2016~ Dec. 26, 2016
Issued Date : July. 10, 2017
Report No. : 1762138R-RF-US-P20V01
Report Version : V1.0

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF, CNAS or any agency of the government.

The test report shall not be reproduced without the written approval of DEKRA Testing and Certification (Suzhou) Co., Ltd. Corporation.

Test Report Certification

Issued Date : July. 10, 2017

Report No. : 1762138R-RF-US-P20V01



Product Name : Access Point
 Applicant : Hewlett Packard Enterprise Company
 Address : 3000 Hanover St. Palo Alto,CA 94304,USA
 Manufacturer : Hewlett Packard Enterprise Company
 Address : 3000 Hanover St. Palo Alto,CA 94304,USA
 Model No. : APEX0365 ,APEX0367
 FCC ID : Q9DAPEX0365367
 Brand Name :



EUT Voltage : PoE 57V
 Applicable Standard : KDB 447498D01V06
 FCC Part1.1310
 Test Result : Complied
 Performed Location : DEKRA Testing and Certification (Suzhou) Co., Ltd.
 No.99 Hongye Rd., Suzhou Industrial Park, Suzhou,
 215006, Jiangsu, China
 TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098
 FCC Registration Number: 800392

Documented By : Kitty Li
 (Adm. Specialist: Kitty Li)

Reviewed By : Frank He
 (Senior Engineer: Frank He)

Approved By : Harry Zhao
 (Engineering Manager : Harry Zhao)

1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18 and 78% RH.

1.3. Test Result of RF Exposure Evaluation

Product	:	Access Point
Test Item	:	RF Exposure Evaluation
Test Site	:	AC-6

Antenna Information:

APEX0365:

Antenna Model No.	N/A		
Antenna manufacturer	N/A		
Antenna Delivery	<input type="checkbox"/>	1*TX+1*RX	<input checked="" type="checkbox"/> 2*TX+2*RX <input type="checkbox"/> 3*TX+3*RX
Antenna technology	<input type="checkbox"/>	SISO	
	<input checked="" type="checkbox"/>	MIMO	<input type="checkbox"/> Basic
			<input type="checkbox"/> Sectorized antenna systems
			<input checked="" type="checkbox"/> Cross-polarized antennas
			<input type="checkbox"/> Unequal antenna gains, with equal transmit powers
			<input type="checkbox"/> Spatial Multiplexing
			<input type="checkbox"/> CDD
		<input checked="" type="checkbox"/> Beam-forming	
Antenna Type	<input type="checkbox"/>	External	<input type="checkbox"/> Dipole
	<input checked="" type="checkbox"/>	Internal	<input type="checkbox"/> PIFA
			<input type="checkbox"/> PCB
			<input type="checkbox"/> Ceramic Chip Antenna
			<input type="checkbox"/> Metal plate type F antenna
			<input checked="" type="checkbox"/> Cross-polarize Antenna
Antenna Gain #0	4.3dBi		
Antenna Gain #1	4.3dBi		
Beamforming Gain	0dBi		
Antenna Gain #0*(Note1)	-0.9dBi		
Antenna Gain #1*(Note1)	-0.9dBi		
Note1: The antenna gain show above is the highest gain which has highest radiation pattern between 30 ° and 90 ° according to KDB 789033D02v01r03.			

APEX0367:

Antenna Model No.	N/A		
Antenna manufacturer	N/A		
Antenna Delivery	<input type="checkbox"/> 1*TX+1*RX	<input checked="" type="checkbox"/> 2*TX+2*RX	<input type="checkbox"/> 3*TX+3*RX
Antenna technology	<input type="checkbox"/> SISO		
	<input checked="" type="checkbox"/> MIMO	<input type="checkbox"/> Basic	
		<input type="checkbox"/> Sectorized antenna systems	
		<input checked="" type="checkbox"/> Cross-polarized antennas	
		<input type="checkbox"/> Unequal antenna gains, with equal transmit powers	
		<input type="checkbox"/> Spatial Multiplexing	
		<input checked="" type="checkbox"/> Beam-forming	
Antenna Type	<input type="checkbox"/> External		<input type="checkbox"/> Dipole
	<input checked="" type="checkbox"/> Internal	<input type="checkbox"/> PIFA	
		<input type="checkbox"/> PCB	
		<input type="checkbox"/> Ceramic Chip Antenna	
		<input type="checkbox"/> Metal plate type F antenna	
		<input checked="" type="checkbox"/> Cross-polarize Antenna	
Antenna Gain #0	6.5dBi		
Antenna Gain #1	6.5dBi		
Beamforming Gain	0dBi		
Antenna Gain #0*(Note1)	3.8dBi		
Antenna Gain #1*(Note1)	3.8dBi		
Note1: The antenna gain show above is the highest gain which has highest radiation pattern between 30 ° and 90 ° according to KDB 789033D02v01r03.			

- Output Power into Antenna & RF Exposure Evaluation Distance:

Standalone modes

APEX0365:

Test Mode	Frequency Band (MHz)	Maximum Output Power to Antenna (dBm)	Directional Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Power Density Limit at R = 20 cm (mW/cm ²)
802.11a/n/ac (20MHz) with CDD	5150-5250MHz 5725-5850 MHz	23.58	4.3	0.1221	1.0
802.11n/ac (40MHz) with CDD	5150-5250MHz 5725-5850 MHz	23.69	4.3	0.1252	1.0
802.11ac(80MHz) with CDD	5150-5250MHz 5725-5850 MHz	23.62	4.3	0.1232	1.0
802.11ac (20MHz) with Beamforming	5150-5250MHz 5725-5850 MHz	22.15	4.3	0.0878	1.0
802.11ac (40MHz) with Beamforming	5150-5250MHz 5725-5850 MHz	23.64	4.3	0.1238	1.0
802.11ac(80MHz) with Beamforming	5150-5250MHz 5725-5850 MHz	23.56	4.3	0.1215	1.0

APEX0367:

Test Mode	Frequency Band (MHz)	Maximum Output Power to Antenna (dBm)	Directional Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Power Density Limit at R = 20 cm (mW/cm ²)
802.11a/n/ac (20MHz) with CDD	5150-5250MHz 5725-5850 MHz	21.63	6.5	0.1293	1.0
802.11n/ac (40MHz) with CDD	5150-5250MHz 5725-5850 MHz	23.12	6.5	0.1823	1.0
802.11ac(80MHz) with CDD	5150-5250MHz 5725-5850 MHz	23.16	6.5	0.1840	1.0
802.11ac (20MHz) with Beamforming	5150-5250MHz 5725-5850 MHz	21.60	6.5	0.1284	1.0
802.11ac (40MHz) with Beamforming	5150-5250MHz 5725-5850 MHz	23.25	6.5	0.1878	1.0
802.11ac(80MHz) with Beamforming	5150-5250MHz 5725-5850 MHz	23.21	6.5	0.1861	1.0

Simultaneous transmission:

APEX0365:

Mode	Frequency Band (MHz)	Maximum Output Power to Antenna (dBm)	Directional Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Power Density Limit at R = 20 cm (mW/cm ²)
WIFI	2400 ~ 2483.5	21.26	2.7	0.0495	1.0
WIFI	5150-5350 5470-5850	25.24	4.3	0.1789	1.0
BLE	2400 ~ 2483.5	2.78	2.7	0.0007	1.0
Simultaneous transmission power density				0.2291	1.0

APEX0367:

Mode	Frequency Band (MHz)	Maximum Output Power to Antenna (dBm)	Directional Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Power Density Limit at R = 20 cm (mW/cm ²)
WIFI	2400 ~ 2483.5	20.87	6.3	0.1037	1.0
WIFI	5150-5350 5470-5850	25.24	6.5	0.2970	1.0
BLE	2400 ~ 2483.5	2.87	4.3	0.0010	1.0
Simultaneous transmission power density				0.4017	1.0

Note: The simultaneous transmission power density is 0.4017mW/cm² for Access Point without any other radio equipment.

_____ The End _____