

# ARUB148

### Maximum Permissible Exposure

FCC, Part 15 §1.1310 Industry Canada RSS-Gen §5.6

## Calculations for Maximum Permissible Exposure Levels

Power Density = Pd (mW/cm<sup>2</sup>) = EIRP/( $4\pi d^2$ ) EIRP = P \* G P = Peak output power (mW) G = Antenna numeric gain (numeric) d = Separation distance (cm)

Numeric Gain =  $10 \wedge (G (dBi)/10)$ 

Because the EUT belongs to the General Population/Uncontrolled Exposure the limit of power density is 1.0 mW/cm<sup>2</sup>

The calculations in the table below use highest gain antennas for the client EUT. Where the antenna gain exceeds 6dBi the transmitter power is reduced where necessary to meet the EIRP requirements. These calculations represent worst case in terms of the exposure levels.

Freq. Band (MHz)	Antenna Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Safe Distance @ 1mW/cm <sup>2</sup> Limit(cm)	Minimum Separation Distance (cm)
2400 - 2483.5	7.5	5.62	27.61	577	16.1	20
5725 - 5850	7.5	5.62	27.06	509	15.1	20
5150 - 5250	7.5	5.62	15.5	35.5	4.0	20

### Assessment for simultaneous operation in 2.4 GHz and 5 GHz bands

The Aruba APIN0114, APIN0115 has two identical radio modules. Each module is dual band, but each one is dedicated to operate ONLY in 1 band (2.4 GHz or 5 GHz). The following assessment is based on simultaneous operation in the 2.4 GHz and 5 GHz bands.

Freq. Band (MHz)	Antenna Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Safe Distance @ 1mW/cm <sup>2</sup> Limit(cm)	Minimum Separation Distance (cm)
2400 - 2483.5	7.5	5.62	27.61	577	16.1	20
5725 - 5850	7.5	5.62	27.06	509	15.1	20
Combined Total	7.5	5.62	30.35	1086	22.0	22.0



<u>Note:</u> for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

### Specification Maximum Permissible Exposure Limits

FCC §1.1310 Limit = 1mW / cm<sup>2</sup> from 1.310 Table 1

**RSS-Gen §5.6** Category I and Category II equipment shall comply with the applicable requirements of RSS-102.

# Laboratory Measurement Uncertainty for Power Measurements

Measurement uncertainty	±1.33 dB
-------------------------	----------