



RF Exposure Evaluation Report

APPLICANT : Hewlett Packard Enterprise Company
EQUIPMENT : Wireless Access Point
BRAND NAME : aruba, Hewlett Packard Enterprise
MODEL NAME : APIN0304, APIN0305
MARKETING NAME : APIN0304, APIN0305
FCC ID : Q9DAPIN0304305
STANDARD : 47 CFR Part 2.1091

We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091, and pass the limit. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Prepared by: Mark Qu / Manager

Approved by: Jones Tsai / Manager

SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China



Table of Contents

1. ADMINISTRATION DATA	4
1.1. Testing Laboratory	4
2. GENERAL INFORMATION	5
2.1. Description of Equipment Under Test (EUT)	5
2.2. Sample List	6
3. MAXIMUM RF AVERAGE OUTPUT POWER AMONG PRODUCTION UNITS	7
4. RF EXPOSURE LIMIT INTRODUCTION	9
5. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION	10
5.1. Standalone Power Density Calculation	10
5.2. Collocated Power Density Calculation.....	12



1. Administration Data

1.1. Testing Laboratory

Testing Laboratory	
Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958

Applicant	
Company Name	Hewlett Packard Enterprise Company
Address	3000 Hanover Street, Palo Alto, CA 94304

Manufacturer	
Company Name	Hewlett Packard Enterprise Company
Address	3000 Hanover Street, Palo Alto, CA 94304

2. General Information

2.1. Description of Equipment Under Test (EUT)

Product Feature & Specification																																					
EUT Type	Wireless Access Point																																				
Brand Name	aruba, Hewlett Packard Enterprise																																				
Model Name	APIN0304, APIN0305																																				
Marketing Name	APIN0304, APIN0305																																				
FCC ID	Q9DAPIN0304305																																				
Wireless Technology and Frequency Range	WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz WLAN 5.5GHz Band: 5500 MHz ~ 5720 MHz WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz																																				
Mode	<ul style="list-style-type: none"> WLAN 2.4GHz 802.11b/g/n HT20/HT40 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth v4.0 LE 																																				
Antenna Type	<table border="1"> <thead> <tr> <th>Model Name</th> <th colspan="2">Antenna Type</th> </tr> </thead> <tbody> <tr> <td rowspan="2">APIN0304</td> <td>WLAN</td> <td>Omnidirectional Antenna</td> </tr> <tr> <td>Bluetooth</td> <td>Directional Antenna</td> </tr> <tr> <td rowspan="2">APIN0305</td> <td>WLAN</td> <td>Internal Antenna</td> </tr> <tr> <td>Bluetooth</td> <td>Internal Antenna</td> </tr> </tbody> </table>	Model Name	Antenna Type		APIN0304	WLAN	Omnidirectional Antenna	Bluetooth	Directional Antenna	APIN0305	WLAN	Internal Antenna	Bluetooth	Internal Antenna																							
Model Name	Antenna Type																																				
APIN0304	WLAN	Omnidirectional Antenna																																			
	Bluetooth	Directional Antenna																																			
APIN0305	WLAN	Internal Antenna																																			
	Bluetooth	Internal Antenna																																			
SW Version	6.5.1.0 build 56684																																				
Antenna Function for Transmitter	<p><APIN0304>:</p> <table border="1"> <thead> <tr> <th></th> <th>BT antenna</th> <th>Ant. 1</th> <th>Ant. 2</th> <th>Ant. 3</th> </tr> </thead> <tbody> <tr> <td>Bluetooth</td> <td>V</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>WLAN 2.4GHz 802.11 b/g/n MIMO</td> <td>-</td> <td>-</td> <td>V</td> <td>V</td> </tr> <tr> <td>WLAN 5GHz 802.11 a/n/ac MIMO</td> <td>-</td> <td>V</td> <td>V</td> <td>V</td> </tr> </tbody> </table> <p><APIN0305>:</p> <table border="1"> <thead> <tr> <th></th> <th>Ant. 1</th> <th>Ant. 2</th> <th>Ant. 3</th> </tr> </thead> <tbody> <tr> <td>Bluetooth</td> <td>-</td> <td>V</td> <td>-</td> </tr> <tr> <td>WLAN 2.4GHz 802.11 b/g/n MIMO</td> <td>V</td> <td>-</td> <td>V</td> </tr> <tr> <td>WLAN 5GHz 802.11 a/n/ac MIMO</td> <td>V</td> <td>V</td> <td>V</td> </tr> </tbody> </table>		BT antenna	Ant. 1	Ant. 2	Ant. 3	Bluetooth	V	-	-	-	WLAN 2.4GHz 802.11 b/g/n MIMO	-	-	V	V	WLAN 5GHz 802.11 a/n/ac MIMO	-	V	V	V		Ant. 1	Ant. 2	Ant. 3	Bluetooth	-	V	-	WLAN 2.4GHz 802.11 b/g/n MIMO	V	-	V	WLAN 5GHz 802.11 a/n/ac MIMO	V	V	V
	BT antenna	Ant. 1	Ant. 2	Ant. 3																																	
Bluetooth	V	-	-	-																																	
WLAN 2.4GHz 802.11 b/g/n MIMO	-	-	V	V																																	
WLAN 5GHz 802.11 a/n/ac MIMO	-	V	V	V																																	
	Ant. 1	Ant. 2	Ant. 3																																		
Bluetooth	-	V	-																																		
WLAN 2.4GHz 802.11 b/g/n MIMO	V	-	V																																		
WLAN 5GHz 802.11 a/n/ac MIMO	V	V	V																																		
EUT Stage	Identical Prototype																																				
Remark:	<ol style="list-style-type: none"> The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description. WLAN 2.4GHz and WLAN 5GHz can transmit in MIMO antenna mode only, and it has no SISO antenna mode. 																																				

2.2. Sample List

There are two model names of EUT. Model APIN0305 is designed with built in antennas, and model APIN0304 with three RP-SMA connectors for external antennas. For model APIN0304, it has nine types of antenna as below table:

	type	Description	Gain	Polorization
1	AP-ANT-1W	2.4-2.5GHz/5GHz, 5.0dBi Tri-Band, Omni-Directional Antenna	3.8dBi @2.4GHz; 5.8dB @5.8GHz	Linear vertical
2	AP-ANT-13B	downtilt omni, dual-band	4.4dBi @2.4GHz; 3.3dB @5.8GHz	Linear vertical
3	AP-ANT-19,	Dual Band Omnidirectional	3dBi @2.4GHz; 6dB @5.8GHz	vertical
4	AP-ANT-20W,	2.4- and 5-GHz dual-band omni directional	2dBi @2.4GHz; 2dB @5.8GHz	Linear vertical
5	AP-ANT-16,	Triple Element Downtilt Omni, Dual-Band	3.9dBi @2.4GHz; 4.7dB @5.8GHz	vertical
6	AP-ANT-25A	2.4- and 5-GHz dual polarized sector antenna	5dBi @2.4GHz; 5dB @5.8GHz	slant +/-45°
7	AP-ANT-35A	2.4- and 5-GHz dual polarized sector antenna	5dBi @2.4GHz; 5dB @5.8GHz	slant +/-45°
8	AP-ANT-28	2.4- and 5-GHz dual-polarized sector antenna	7.5dBi @2.4GHz; 7.5dB @5.8GHz	slant +/-45°
9	AP-ANT-38	2.4- and 5-GHz dual-polarized sector antenna	7.5dBi @2.4GHz; 7.5dB @5.8GHz	slant +/-45°

For model APIN0304, we only evaluate the antenna (AP-ANT-19 and AP-ANT-28) with the maximum antenna gain for MPE evaluation.



3. Maximum RF average output power among production units

<WLAN 2.4GHz>

Model Name	Mode	Maximum Average Power (dBm)
APIN0304	802.11b	21.5
	802.11g	21.0
	802.11n-HT20	17.0
	802.11n-HT40	17.0
APIN0305	802.11b	21.5
	802.11g	21.0
	802.11n-HT20	20.0
	802.11n-HT40	18.0

<WLAN 5GHz>

Model Name	Mode	Maximum Average Power (dBm)	
APIN0304	WLAN 5.2GHz	802.11a	23.5
		802.11n-HT20	23.0
		802.11n-HT40	21.0
		802.11ac-VHT20	23.0
		802.11ac-VHT40	21.0
		802.11ac-VHT80	17.5
	WLAN 5.3GHz	802.11a	18.0
		802.11n-HT20	19.0
		802.11n-HT40	20.5
		802.11ac-VHT20	19.0
		802.11ac-VHT40	20.5
		802.11ac-VHT80	16.5
	WLAN 5.5GHz	802.11a	17.5
		802.11n-HT20	18.5
		802.11n-HT40	20.5
		802.11ac-VHT20	18.5
		802.11ac-VHT40	20.5
		802.11ac-VHT80	23.0
	WLAN 5.8GHz	802.11a	23.5
		802.11n-HT20	23.0
		802.11n-HT40	23.5
		802.11ac-VHT20	23.0
		802.11ac-VHT40	23.5
		802.11ac-VHT80	23.0



Model Name		Mode	Maximum Average Power (dBm)
APIN0305	WLAN 5.2GHz	802.11a	23.5
		802.11n-HT20	23.0
		802.11n-HT40	21.5
		802.11ac-VHT20	23.0
		802.11ac-VHT40	21.5
		802.11ac-VHT80	19.5
	WLAN 5.3GHz	802.11a	21.0
		802.11n-HT20	22.5
		802.11n-HT40	23.5
		802.11ac-VHT20	22.5
		802.11ac-VHT80	21.0
	WLAN 5.5GHz	802.11a	21.0
		802.11n-HT20	21.5
		802.11n-HT40	23.5
		802.11ac-VHT20	21.5
		802.11ac-VHT80	23.0
	WLAN 5.8GHz	802.11a	23.5
		802.11n-HT20	23.0
		802.11n-HT40	23.5
		802.11ac-VHT20	23.0
		802.11ac-VHT80	23.0

<Bluetooth>

Model Name	Mode	Maximum Average Power (dBm)
APIN0304	Bluetooth v4.0 LE	0.5
APIN0305	Bluetooth v4.0 LE	0.5



4. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna

5. Radio Frequency Radiation Exposure Evaluation

5.1. Standalone Power Density Calculation

Model Name	Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Maximum EIRP (W)	Average EIRP (mW)	Power Density at 20cm (mW/mW ²)	Limit (mW/mW ²)	Power Density / Limit
APIN0304	WLAN 2.4GHz	2412.0	7.50	21.5	29.000	0.794	794.328	0.1581	1.000	0.1581
	WLAN 5.2GHz	5180.0	6.00	23.5	29.500	0.891	891.251	0.1774	1.000	0.1774
	WLAN 5.3GHz	5260.0	6.00	20.5	26.500	0.447	446.684	0.0889	1.000	0.0889
	WLAN 5.5GHz	5500.0	6.00	23.0	29.000	0.794	794.328	0.1581	1.000	0.1581
	WLAN 5.8GHz	5745.0	6.00	23.5	29.500	0.891	891.251	0.1774	1.000	0.1774
	Bluetooth	2402.0	4.50	0.5	5.000	0.003	3.162	0.0006	1.000	0.0006
APIN0305	WLAN 2.4GHz	2412.0	2.40	21.5	23.900	0.245	245.471	0.0489	1.000	0.0489
	WLAN 5.2GHz	5180.0	2.80	23.5	26.300	0.427	426.580	0.0849	1.000	0.0849
	WLAN 5.3GHz	5260.0	2.80	23.5	26.300	0.427	426.580	0.0849	1.000	0.0849
	WLAN 5.5GHz	5500.0	2.80	23.5	26.300	0.427	426.580	0.0849	1.000	0.0849
	WLAN 5.8GHz	5745.0	2.80	23.5	26.300	0.427	426.580	0.0849	1.000	0.0849
	Bluetooth	2402.0	3.40	0.5	3.900	0.002	2.455	0.0005	1.000	0.0005

Note:

1. For conservativeness, the lowest uplink frequency of each band is used to determine the MPE limit of that band.
2. In the above table have assessed WLAN 2.4GHz, WLAN 5GHz and Bluetooth by referring to their maximum antenna gain and maximum output power.



<For Beamforming mode>

Model Name	Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Maximum EIRP (W)	Average EIRP (mW)	Power Density at 20cm (mW/mW ²)	Limit (mW/mW ²)	Power Density / Limit
APIN0304	WLAN 2.4GHz	2412.0	7.50	17.0	24.500	0.282	281.838	0.0561	1.000	0.0561
	WLAN 5.2GHz	5180.0	10.77	23.0	33.770	2.382	2382.319	0.4742	1.000	0.4742
	WLAN 5.3GHz	5260.0	10.77	20.5	31.270	1.340	1339.677	0.2667	1.000	0.2667
	WLAN 5.5GHz	5500.0	10.77	23.0	33.770	2.382	2382.319	0.4742	1.000	0.4742
	WLAN 5.8GHz	5745.0	10.77	23.5	34.270	2.673	2673.006	0.5320	1.000	0.5320
APIN0305	WLAN 2.4GHz	2412.0	5.41	20.0	25.410	0.348	347.536	0.0692	1.000	0.0692
	WLAN 5.2GHz	5180.0	7.57	23.0	30.570	1.140	1140.250	0.2270	1.000	0.2270
	WLAN 5.3GHz	5260.0	7.57	23.5	31.070	1.279	1279.381	0.2547	1.000	0.2547
	WLAN 5.5GHz	5500.0	7.57	23.5	31.070	1.279	1279.381	0.2547	1.000	0.2547
	WLAN 5.8GHz	5745.0	7.57	23.5	31.070	1.279	1279.381	0.2547	1.000	0.2547

Note:

1. For conservativeness, the lowest uplink frequency of each band is used to determine the MPE limit of that band.
2. This device support beamforming for WLAN 2.4GHz 802.11n HT20/HT40 and WLAN 5GHz 802.11n/ac HT20/HT40/VHT20/VHT40/VHT80.
3. In the above table have assessed WLAN 2.4GHz and WLAN 5GHz by referring to their maximum direction gain and maximum output power.
4. For model APIN0304 with WLAN 2.4GHz, the dual-polarized sector antenna with maximum antenna gain 7.5dBi which we choosed without beamforming antenna gain because of irrelevant of polarization. So for beamforming mode, we also use 7.5dBi to evaluate MPE test. For model APIN0304 with WLAN 5GHz on the maximum antenna gain 7.5dBi, the beamforming antenna gain is not equal to add $10\log(3)=4.77$ dBi but 3.01 dBi because of the dual-polarization. So we choose the secondary antenna with antenna gain 6dBi to evaluate MPE test.
5. For model APIN0305, composited gain for each antenna is 2.4dBi in 2.4GHz and 2.8dBi in 5GHz. And the beamforming gain is equal to each antenna add $10 \log (N)$ dB, where N is the number of outputs.



5.2. Collocated Power Density Calculation

Model Name	Band	Maximum WLAN Power Density / Limit	Maximum Bluetooth Power Density / Limit	Σ (Power Density / Limit) of WLAN 2.4GHz + WLAN 5GHz + Bluetooth
APIN0304	WLAN2.4GHz Band	0.1581	0.0006	0.6907
	WLAN5GHz Band	0.5320		
APIN0305	WLAN2.4GHz Band	0.0692	0.0005	0.3244
	WLAN5GHz Band	0.2547		

Note:

1. Σ (Power Density / Limit): This is a summation of [(power density for each transmitter/antenna included in the simultaneous transmission)/ (corresponding MPE limit)], for WLAN 2.4GHz+WLAN 5GHz + Bluetooth.
2. Considering the all antennas collocation of the EIRP performance listed in the table above, the aggregated (power density /limit) is smaller than 1, and MPE of 3 collocated transmitters is compliant.

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.