

Company: Aruba Networks, Inc.

Test of: APIN0334 & APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407

Report No.: ARUB204-MPE Inc DFS Bands Rev A

MPE REPORT



MPE TEST REPORT

FROM



Test of: Aruba Networks, Inc. APIN0334 & APIN0335

to

To: FCC CFR 47 Part 15 Subpart E 15.407

Test Report Serial No.: ARUB204-MPE Inc DFS Bands Rev A

This report supersedes: NONE

Applicant: Aruba Networks, Inc.
1344 Crossman Ave.
Sunnyvale, California 94089
USA

Product Function: Wireless Access Point

Issue Date: 9th June 2016

This Test Report is Issued Under the Authority of:

MiCOM Labs, Inc.
575 Boulder Court
Pleasanton California 94566
USA
Phone: +1 (925) 462-0304
Fax: +1 (925) 462-0306
www.micomlabs.com



MiCOM Labs is an ISO 17025 Accredited Testing Laboratory

1. MAXIMUM PERMISSABLE EXPOSURE

Calculations for Maximum Permissible Exposure Levels

Power Density = Pd (mW/cm²) = EIRP/(4*π*d²)

EIRP = P * G

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

Numeric Gain = 10 ^ (G (dBi)/10)

Because the EUT belongs to the General Population/Uncontrolled Exposure the limit of power density is 1.0 mW/cm²

The calculations in the table below use the highest conducted power values together with the lowest antenna gain specified for the EUT. These calculations represent worst case in terms of the exposure levels.

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Safe Distance @ 1mW/cm ²	Calculated Power Density @ 20cm	Minimum Separation Distance (cm)
2400.0 - 2483.5	1.90	1.55	24.14	259.66	5.65	0.08	20.00
2400.0 - 2483.5 ^{BLE}	1.50	1.41	4.49	2.81	0.56	0.0008	20.00
5150.0 - 5250.0	8.50	7.08	27.67	584.93	18.15	0.82	20.00
5725.0 - 5850.0	8.50	7.08	27.30	527.43	17.40	0.76	20.00
5250.0 – 5350.0	8.50	7.08	22.54	179.47	10.06	0.25	20.00
5470.0 - 5725.0	8.50	7.08	22.51	178.24	10.02	0.25	20.00

Assessment for simultaneous operation:

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Safe Distance @ 1mW/cm ²	Calculated Power Density @ 20cm	Minimum Separation Distance (cm)
5150.0 - 5250.0	8.50	7.08	27.67	584.93			20.00
2400.0 - 2483.5	1.90	1.55	24.14	259.66			20.00
2400.0 - 2483.5 ^{BLE}	1.50	1.41	4.49	2.81			20.00
EIRP TOTAL (mW/EIRP) : 4547.73					19.02	0.90	20.00

Note: for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

Specification

Maximum Permissible Exposure Limits

FCC §1.1310 Limit = 1mW / cm² from 1.310 Table 1



575 Boulder Court
Pleasanton, California 94566, USA
Tel: +1 (925) 462 0304
Fax: +1 (925) 462 0306
www.micomlabs.com