



Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 157 of 297

A. APPENDIX - GRAPHICAL IMAGES

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



A.1. Radiated Emissions


A.1.1. Restricted Band Emissions

A.1.1.1. AP-ANT-13B



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5260.00 MHz, Antenna: AP-ANT-13B, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail
1	5257.28	83.91	3.64	-11.30	76.25	Fundamental	Horizontal	151	1	--	--	
2	10511.46	54.34	5.48	-4.26	55.56	Peak (NRB)	Vertical	200	1	--	--	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 159 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5300.00 MHz, Antenna: AP-ANT-13B, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5295.76	82.83	3.79	-11.11	75.51	Fundamental	Horizontal	101	1	--	--	
2	10598.43	60.71	5.59	-3.93	62.37	Peak (NRB)	Vertical	200	360	--	--	Pass
3	10600.52	48.47	5.58	-3.93	50.12	Max Avg	Vertical	196	223	54.0	-3.9	Pass
4	10600.52	63.50	5.58	-3.93	65.15	Max Peak	Vertical	196	223	74.0	-8.9	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 160 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5320.00 MHz, Antenna: AP-ANT-13B, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5322.28	81.01	3.75	-11.06	73.70	Fundamental	Horizontal	101	1	--	--	
2	10637.55	49.18	5.43	-3.89	50.72	Max Avg	Vertical	186	221	54.0	-3.3	Pass
3	10637.55	62.94	5.43	-3.89	64.48	Max Peak	Vertical	186	221	74.0	-9.5	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 161 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5500.00 MHz, Antenna: AP-ANT-13B, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5503.84	69.02	3.75	-11.18	61.59	Fundamental	Vertical	101	0	--	--	
2	11002.28	51.61	5.59	-4.24	52.96	Max Avg	Vertical	186	278	54.0	-1.0	Pass
3	11002.28	65.13	5.59	-4.24	66.48	Max Peak	Vertical	186	278	74.0	-7.5	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 162 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5580.00 MHz, Antenna: AP-ANT-13B, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5583.69	80.16	3.79	-11.19	72.76	Fundamental	Horizontal	101	1	--	--	
2	11162.28	50.27	5.76	-4.06	51.97	Max Avg	Vertical	192	229	54.0	-2.0	Pass
3	11162.28	63.89	5.76	-4.06	65.59	Max Peak	Vertical	192	229	74.0	-8.4	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 163 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5720.00 MHz, Antenna: AP-ANT-13B, Power Setting: 14, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5723.84	65.75	3.79	-10.72	58.82	Fundamental	Horizontal	101	0	--	--	
2	11430.90	51.78	5.48	-4.92	52.34	Max Avg	Vertical	161	248	54.0	-1.7	Pass
3	11430.90	66.65	5.48	-4.92	67.21	Max Peak	Vertical	161	248	74.0	-6.8	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR. Power reduced to 14 due to 11.4 GHz harmonic

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




A.1.1.2. AP-ANT-19



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5260.00 MHz, Antenna: AP-ANT-19, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail
1	5266.42	85.70	3.68	-11.26	78.12	Fundamental	Vertical	101	1	--	--	
2	5266.42	85.70	3.68	-11.26	78.12	Peak (NRB)	Vertical	101	1	--	--	Pass
3	5266.42	85.70	3.68	-11.26	78.12	Peak (NRB)	Vertical	101	1	--	--	Pass
4	10520.56	47.06	5.43	-4.21	48.28	Max Avg	Vertical	189	232	54.0	-5.7	Pass
5	10520.56	61.78	5.43	-4.21	63.00	Max Peak	Vertical	189	232	74.0	-11.0	Pass
6	10520.56	51.84	5.43	-4.21	53.06	Peak (NRB)	Vertical	101	59	--	--	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 165 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5300.00 MHz, Antenna: AP-ANT-19, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5293.67	83.99	3.78	-11.12	76.65	Fundamental	Vertical	101	1	--	--	
2	5293.67	83.99	3.78	-11.12	76.65	Peak (NRB)	Vertical	101	1	--	--	Pass
3	10600.52	47.81	5.58	-3.93	49.46	Max Avg	Vertical	187	276	54.0	-4.5	Pass
4	10600.52	62.87	5.58	-3.93	64.52	Max Peak	Vertical	187	276	74.0	-9.5	Pass
5	10600.52	45.49	5.58	-3.93	47.14	Max Avg	Horizontal	141	228	54.0	-6.9	Pass
6	10600.52	61.00	5.58	-3.93	62.65	Max Peak	Horizontal	141	228	74.0	-11.4	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 166 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5320.00 MHz, Antenna: AP-ANT-19, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5321.45	83.83	3.75	-11.06	76.52	Fundamental	Vertical	101	1	--	--	
2	5321.45	83.83	3.75	-11.06	76.52	Peak (NRB)	Vertical	101	1	--	--	Pass
3	10638.35	46.16	5.43	-3.89	47.70	Max Avg	Vertical	169	222	54.0	-6.3	Pass
4	10638.35	60.23	5.43	-3.89	61.77	Max Peak	Vertical	169	222	74.0	-12.2	Pass
5	10638.35	45.61	5.43	-3.89	47.15	Max Avg	Horizontal	168	228	54.0	-6.9	Pass
6	10638.35	59.31	5.43	-3.89	60.85	Max Peak	Horizontal	168	228	74.0	-13.2	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 167 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5500.00 MHz, Antenna: AP-ANT-19, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5502.24	76.46	3.75	-11.17	69.04	Fundamental	Vertical	101	1	--	--	
2	5502.24	76.46	3.75	-11.17	69.04	Peak (NRB)	Vertical	101	1	--	--	Pass
3	11000.56	47.97	5.59	-4.24	49.32	Max Avg	Horizontal	121	231	54.0	-4.7	Pass
4	11000.56	62.93	5.59	-4.24	64.28	Max Peak	Horizontal	121	231	74.0	-9.7	Pass
5	11000.56	51.92	5.59	-4.24	53.27	Max Avg	Vertical	198	269	54.0	-0.7	Pass
6	11000.56	66.39	5.59	-4.24	67.74	Max Peak	Vertical	198	269	74.0	-6.3	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 168 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5580.00 MHz, Antenna: AP-ANT-19, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5580.68	84.96	3.80	-11.20	77.56	Fundamental	Vertical	101	1	--	--	
2	5580.68	84.96	3.80	-11.20	77.56	Peak (NRB)	Vertical	101	1	--	--	Pass
3	11162.40	52.06	5.76	-4.06	53.76	Max Avg	Vertical	178	250	54.0	-0.2	Pass
4	11162.40	65.72	5.76	-4.06	67.42	Max Peak	Vertical	178	250	74.0	-6.6	Pass
5	11162.40	51.88	5.76	-4.06	53.58	Max Avg	Horizontal	134	247	54	-0.42	Pass
6	11162.40	67.43	5.76	-4.06	69.13	Max Peak	Horizontal	134	247	74.0	-4.9	Pass
7	11162.41	51.56	5.76	-4.06	53.26	Max Avg	Vertical	176	251	54	-0.74	Pass
8	11162.41	66.10	5.76	-4.06	67.80	Max Peak	Vertical	176	251	74.0	-6.2	Pass
9	11162.41	50.99	5.76	-4.06	52.69	Max Avg	Horizontal	128	250	54.0	-1.3	Pass
10	11162.41	65.07	5.76	-4.06	66.77	Max Peak	Horizontal	128	250	74.0	-7.2	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 169 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5720.00 MHz, Antenna: AP-ANT-19, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5714.15	60.05	3.82	-10.76	53.11	Fundamental	Vertical	101	1	--	--	
2	5714.15	60.05	3.82	-10.76	53.11	Peak (NRB)	Vertical	101	1	--	--	Pass
3	11431.10	52.57	5.48	-4.92	53.13	Max Avg	Vertical	184	253	54	-0.87	Pass
4	11431.10	71.90	5.48	-4.92	72.46	Max Peak	Vertical	184	253	74.0	-1.5	Pass
5	11431.10	51.60	5.48	-4.92	52.16	Max Avg	Horizontal	128	247	54.0	-1.8	Pass
6	11431.10	67.02	5.48	-4.92	67.58	Max Peak	Horizontal	128	247	74.0	-6.4	Pass
7	11431.11	51.72	5.48	-4.92	52.28	Max Avg	Horizontal	148	247	54.0	-1.7	Pass
8	11431.11	67.14	5.48	-4.92	67.70	Max Peak	Horizontal	148	247	74.0	-6.3	Pass
9	11431.11	52.78	5.48	-4.92	53.34	Max Avg	Vertical	191	250	54	-0.66	Pass
10	11431.11	70.87	5.48	-4.92	71.43	Max Peak	Vertical	191	250	74.0	-2.6	Pass
11	11431.12	49.92	5.48	-4.92	50.48	Max Avg	Vertical	100	76	54.0	-3.5	Pass
12	11431.12	64.86	5.48	-4.92	65.42	Max Peak	Vertical	100	76	74.0	-8.6	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



A.1.1.3. AP-ANT-1W



Variant: 802.11a, Test Freq: 5260.00 MHz, Antenna: 1W, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5257.12	83.60	3.64	-11.30	75.94	Fundamental	Horizontal	101	1	--	--	
2	10522.12	54.83	5.43	-4.20	56.06	Peak (NRB)	Horizontal	101	1	--	--	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 171 of 297



Variant: 802.11a, Test Freq: 5300.00 MHz, Antenna: 1W, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5293.99	79.09	3.78	-11.12	71.75	Fundamental	Horizontal	200	1	--	--	
2	5293.99	79.09	3.78	-11.12	71.75	Peak (NRB)	Horizontal	200	1	--	--	Pass
3	10604.08	47.30	5.56	-3.92	48.94	Max Avg	Horizontal	192	284	54.0	-5.1	Pass
4	10604.08	61.41	5.56	-3.92	63.05	Max Peak	Horizontal	192	284	74.0	-11.0	Pass
5	10604.08	42.63	5.56	-3.92	44.27	Max Avg	Vertical	118	342	54.0	-9.7	Pass
6	10604.08	56.98	5.56	-3.92	58.62	Max Peak	Vertical	118	342	74.0	-15.4	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 172 of 297



Variant: 802.11a, Test Freq: 5320.00 MHz, Antenna: 1W, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5321.96	74.25	3.75	-11.06	66.94	Fundamental	Horizontal	200	1	--	--	
2	5321.96	74.25	3.75	-11.06	66.94	Peak (NRB)	Horizontal	200	1	--	--	Pass
3	10644.97	47.12	5.32	-3.89	48.55	Max Avg	Horizontal	190	286	54.0	-5.5	Pass
4	10644.97	61.15	5.32	-3.89	62.58	Max Peak	Horizontal	190	286	74.0	-11.4	Pass
5	10644.97	43.34	5.32	-3.89	44.77	Max Avg	Vertical	151	339	54.0	-9.2	Pass
6	10644.97	57.49	5.32	-3.89	58.92	Max Peak	Vertical	151	339	74.0	-15.1	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 173 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5500.00 MHz, Antenna: AP-ANT-1W, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	0.00	60.90	0.00	0.00	60.90	Peak (NRB)	Vertical	138	336	--	--	Pass
2	5503.92	66.24	3.75	-11.18	58.81	Fundamental	Horizontal	200	0	--	--	
3	5503.92	66.24	3.75	-11.18	58.81	Peak (NRB)	Horizontal	200	0	--	--	Pass
8	10991.43	47.93	5.61	-4.27	49.27	Max Avg	Horizontal	141	38	54.0	-4.7	Pass
9	10991.43	62.22	5.61	-4.27	63.56	Max Peak	Horizontal	141	38	74.0	-10.4	Pass
10	10991.43	44.47	5.61	-4.27	45.81	Max Avg	Vertical	110	333	54.0	-8.2	Pass
11	10991.43	59.12	5.61	-4.27	60.46	Max Peak	Vertical	110	333	74.0	-13.5	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 174 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5580.00 MHz, Antenna: AP-ANT-1W, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5502.88	66.84	3.75	-11.17	59.42	Fundamental	Horizontal	200	1	--	--	
2	5502.88	66.84	3.75	-11.17	59.42	Peak (NRB)	Horizontal	200	1	--	--	Pass
9	11005.09	50.29	5.58	-4.23	51.64	Max Avg	Vertical	105	328	54.0	-2.4	Pass
10	11005.09	64.23	5.58	-4.23	65.58	Max Peak	Vertical	105	328	74.0	-8.4	Pass
11	11009.22	47.57	5.57	-4.22	48.92	Max Avg	Horizontal	198	284	54.0	-5.1	Pass
12	11009.22	61.79	5.57	-4.22	63.14	Max Peak	Horizontal	198	284	74.0	-10.9	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 175 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5720.00 MHz, Antenna: AP-ANT-1W, Power Setting: 20, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5723.93	55.38	3.79	-10.72	48.45	Fundamental	Horizontal	200	1	--	--	
2	5723.93	55.38	3.79	-10.72	48.45	Peak (NRB)	Horizontal	200	1	--	--	Pass
9	11434.07	52.05	5.41	-4.92	52.54	Max Avg	Vertical	194	259	54.0	-1.46	Pass
10	11434.07	68.48	5.41	-4.92	68.97	Max Peak	Vertical	194	259	74.0	-5.0	Pass
11	11434.07	50.09	5.41	-4.92	50.58	Max Avg	Horizontal	137	252	54.0	-3.4	Pass
12	11434.07	63.70	5.41	-4.92	64.19	Max Peak	Horizontal	137	252	74.0	-9.8	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




A.1.1.4. AP-ANT-20W



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5260.00 MHz, Antenna: AP-ANT-20W, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail
1	5255.35	80.33	3.64	-11.32	72.65	Fundamental	Horizontal	101	1	--	--	
2	5255.35	80.33	3.64	-11.32	72.65	Peak (NRB)	Horizontal	101	1	--	--	Pass
3	10524.01	52.01	5.43	-4.19	53.25	Peak (NRB)	Horizontal	100	29	--	--	Pass
4	10524.01	44.77	5.43	-4.19	46.01	Max Avg	Horizontal	104	277	54.0	-8.0	Pass
5	10524.01	58.71	5.43	-4.19	59.95	Max Peak	Horizontal	104	277	74.0	-14.1	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 177 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5300.00 MHz, Antenna: AP-ANT-20W, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5292.87	72.21	3.77	-11.13	64.85	Fundamental	Vertical	200	1	--	--	
2	5292.87	72.21	3.77	-11.13	64.85	Peak (NRB)	Vertical	200	1	--	--	Pass
3	10603.44	43.60	5.57	-3.93	45.24	Max Avg	Horizontal	196	296	54.0	-8.8	Pass
4	10603.44	57.23	5.57	-3.93	58.87	Max Peak	Horizontal	196	296	74.0	-15.1	Pass
5	10603.44	41.62	5.57	-3.93	43.26	Max Avg	Vertical	119	340	54.0	-10.7	Pass
6	10603.44	55.97	5.57	-3.93	57.61	Max Peak	Vertical	119	340	74.0	-16.4	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 178 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5320.00 MHz, Antenna: AP-ANT-20W, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5301.21	72.91	3.81	-11.09	65.63	Fundamental	Horizontal	200	1	--	--	
2	5301.21	72.91	3.81	-11.09	65.63	Peak (NRB)	Horizontal	200	1	--	--	Pass
3	10605.69	43.23	5.55	-3.92	44.86	Max Avg	Horizontal	162	280	54.0	-9.1	Pass
4	10605.69	57.74	5.55	-3.92	59.37	Max Peak	Horizontal	162	280	74.0	-14.6	Pass
5	10605.69	41.61	5.55	-3.92	43.24	Max Avg	Vertical	117	340	54.0	-10.8	Pass
6	10605.69	56.10	5.55	-3.92	57.73	Max Peak	Vertical	117	340	74.0	-16.3	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 179 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5500.00 MHz, Antenna: AP-ANT-20W, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5497.99	71.68	3.74	-11.17	64.25	Fundamental	Horizontal	101	0	--	--	
2	5497.99	71.68	3.74	-11.17	64.25	Peak (NRB)	Horizontal	101	0	--	--	Pass
5	11000.32	52.47	5.59	-4.24	53.82	Max Avg	Horizontal	116	300	54.0	-0.18	Pass
6	11000.32	69.39	5.59	-4.24	70.74	Max Peak	Horizontal	116	300	74.0	-3.3	Pass
7	11000.32	47.92	5.59	-4.24	49.27	Max Avg	Vertical	120	315	54.0	-4.7	Pass
8	11000.32	62.92	5.59	-4.24	64.27	Max Peak	Vertical	120	315	74.0	-9.7	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 180 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5580.00 MHz, Antenna: AP-ANT-20W, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5584.29	73.26	3.79	-11.19	65.86	Fundamental	Horizontal	101	0	--	--	
2	5584.29	73.26	3.79	-11.19	65.86	Peak (NRB)	Horizontal	101	0	--	--	Pass
3	11156.07	49.68	5.96	-4.05	51.59	Max Avg	Horizontal	115	298	54.0	-2.4	Pass
4	11156.07	63.55	5.96	-4.05	65.46	Max Peak	Horizontal	115	298	74.0	-8.5	Pass
5	11156.07	46.78	5.96	-4.05	48.69	Max Avg	Vertical	115	26	54.0	-5.3	Pass
6	11156.07	61.07	5.96	-4.05	62.98	Max Peak	Vertical	115	26	74.0	-11.0	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 181 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5720.00 MHz, Antenna: AP-ANT-20W, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5726.09	62.72	3.79	-10.72	55.79	Fundamental	Horizontal	101	1	--	--	
2	5726.09	62.72	3.79	-10.72	55.79	Peak (NRB)	Horizontal	101	1	--	--	Pass
3	11437.52	52.09	5.34	-4.92	52.51	Max Avg	Horizontal	114	267	54.0	-1.5	Pass
4	11437.52	65.54	5.34	-4.92	65.96	Max Peak	Horizontal	114	267	74.0	-8.0	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




A.1.1.5. AP-ANT-40



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5260.00 MHz, Antenna: AP-ANT-40, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail
1	5259.04	80.33	3.65	-11.29	72.69	Fundamental	Horizontal	101	1	--	--	
2	5259.04	80.33	3.65	-11.29	72.69	Peak (NRB)	Horizontal	101	1	--	--	Pass
3	10514.55	48.53	5.45	-4.23	49.75	Peak (NRB)	Vertical	101	82	--	--	Pass
4	10514.55	46.29	5.45	-4.23	47.51	Max Avg	Vertical	170	243	54.0	-6.5	Pass
5	10514.55	60.38	5.45	-4.23	61.60	Max Peak	Vertical	170	243	74.0	-12.4	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 183 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5300.00 MHz, Antenna: AP-ANT-40, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5292.47	75.21	3.76	-11.13	67.84	Fundamental	Horizontal	200	1	--	--	
2	5292.47	75.21	3.76	-11.13	67.84	Peak (NRB)	Horizontal	200	1	--	--	Pass
3	10596.71	50.35	5.60	-3.93	52.02	Peak (NRB)	Vertical	198	55	--	--	Pass
4	10596.71	48.49	5.60	-3.93	50.16	Max Avg	Vertical	190	300	54.0	-3.8	Pass
5	10596.71	62.33	5.60	-3.93	64.00	Max Peak	Vertical	190	300	74.0	-10.0	Pass
6	10596.71	44.79	5.60	-3.93	46.46	Max Avg	Horizontal	191	224	54.0	-7.5	Pass
7	10596.71	58.72	5.60	-3.93	60.39	Max Peak	Horizontal	191	224	74.0	-13.6	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 184 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5320.00 MHz, Antenna: AP-ANT-40, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5325.46	74.01	3.73	-11.06	66.68	Fundamental	Horizontal	200	110	--	--	
2	5325.46	74.01	3.73	-11.06	66.68	Peak (NRB)	Horizontal	200	110	--	--	Pass
3	10636.75	48.97	5.45	-3.89	50.53	Max Avg	Vertical	147	100	54.0	-3.5	Pass
4	10636.75	63.30	5.45	-3.89	64.86	Max Peak	Vertical	147	100	74.0	-9.1	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 185 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5500.00 MHz, Antenna: AP-ANT-40, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5504.97	65.38	3.75	-11.18	57.95	Fundamental	Horizontal	151	1	--	--	
2	5504.97	65.38	3.75	-11.18	57.95	Peak (NRB)	Horizontal	151	1	--	--	Pass
3	11000.32	51.46	5.59	-4.24	52.81	Max Avg	Horizontal	137	240	54.0	-1.2	Pass
4	11000.32	66.02	5.59	-4.24	67.37	Max Peak	Horizontal	137	240	74.0	-6.6	Pass
5	11000.32	50.38	5.59	-4.24	51.73	Max Avg	Vertical	195	260	54.0	-2.3	Pass
6	11000.32	65.25	5.59	-4.24	66.60	Max Peak	Vertical	195	260	74.0	-7.4	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 186 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5580.00 MHz, Antenna: AP-ANT-40, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5584.85	67.62	3.79	-11.19	60.22	Fundamental	Horizontal	101	1	--	--	
2	5584.85	67.62	3.79	-11.19	60.22	Peak (NRB)	Horizontal	101	1	--	--	Pass
3	11159.75	51.39	5.85	-4.07	53.17	Max Avg	Horizontal	134	242	54.0	-0.8	Pass
4	11159.75	65.12	5.85	-4.07	66.90	Max Peak	Horizontal	134	242	74.0	-7.1	Pass
5	11159.75	46.27	5.85	-4.07	48.05	Max Avg	Vertical	114	257	54.0	-6.0	Pass
6	11159.75	60.38	5.85	-4.07	62.16	Max Peak	Vertical	114	257	74.0	-11.8	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 187 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5720.00 MHz, Antenna: AP-ANT-40, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5713.99	49.50	3.82	-10.76	42.56	Fundamental	Horizontal	101	1	--	--	
2	5713.99	49.50	3.82	-10.76	42.56	Peak (NRB)	Horizontal	101	1	--	--	Pass
5	11447.46	51.05	5.41	-4.92	51.54	Max Avg	Vertical	156	272	54.0	-2.5	Pass
6	11447.46	66.09	5.41	-4.92	66.58	Max Peak	Vertical	156	272	74.0	-7.4	Pass
7	11447.46	48.69	5.41	-4.92	49.18	Max Avg	Horizontal	128	238	54.0	-4.8	Pass
8	11447.46	63.63	5.41	-4.92	64.12	Max Peak	Horizontal	128	238	74.0	-9.9	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




A.1.1.6. AP-ANT-45



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5260.00 MHz, Antenna: AP-ANT-45, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail
1	5262.49	91.50	3.66	-11.28	83.88	Fundamental	Vertical	101	0	--	--	
2	10526.57	51.84	5.42	-4.18	53.08	Peak (NRB)	Vertical	200	0	--	--	Pass
3	15776.51	38.27	5.98	0.10	44.35	Max Avg	Horizontal	160	23	54.0	-9.7	Pass
4	15776.51	53.43	5.98	0.10	59.51	Max Peak	Horizontal	160	23	74.0	-14.5	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 189 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5300.00 MHz, Antenna: AP-ANT-45, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5294.07	88.54	3.78	-11.12	81.20	Fundamental	Vertical	101	1	--	--	
2	10600.28	47.95	5.58	-3.94	49.59	Max Avg	Vertical	198	217	54.0	-4.4	Pass
3	10600.28	63.39	5.58	-3.94	65.03	Max Peak	Vertical	198	217	74.0	-9.0	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 190 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5320.00 MHz, Antenna: AP-ANT-45, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5321.72	85.92	3.75	-11.06	78.61	Fundamental	Vertical	151	1	--	--	
2	10639.08	47.12	5.42	-3.90	48.64	Max Avg	Vertical	152	103	54.0	-5.4	Pass
3	10639.08	61.21	5.42	-3.90	62.73	Max Peak	Vertical	152	103	74.0	-11.3	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 191 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5500.00 MHz, Antenna: AP-ANT-45, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5503.92	75.26	3.75	-11.18	67.83	Fundamental	Horizontal	101	1	--	--	
2	11001.72	52.29	5.59	-4.24	53.64	Max Avg	Horizontal	157	237	54.0	-0.4	Pass
3	11001.72	65.77	5.59	-4.24	67.12	Max Peak	Horizontal	157	237	74.0	-6.9	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 192 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5580.00 MHz, Antenna: AP-ANT-45, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5581.84	84.80	3.80	-11.20	77.40	Fundamental	Vertical	101	1	--	--	
2	11159.07	50.62	5.89	-4.06	52.45	Max Avg	Vertical	168	245	54.0	-1.6	Pass
3	11159.07	64.68	5.89	-4.06	66.51	Max Peak	Vertical	168	245	74.0	-7.5	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 193 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5720.00 MHz, Antenna: AP-ANT-45, Power Setting: 16, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5721.32	68.92	3.80	-10.73	61.99	Fundamental	Vertical	101	1	--	--	
2	11433.22	51.76	5.43	-4.92	52.27	Max Avg	Vertical	196	239	54.0	-1.7	Pass
3	11433.22	66.16	5.43	-4.92	66.67	Max Peak	Vertical	196	239	74.0	-7.3	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR. Power reduced to 16 due to 11.4 GHz harmonic

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




A.1.1.7. AP-ANT-48



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5260.00 MHz, Antenna: AP-ANT-48, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5266.82	92.45	3.68	-11.25	84.88	Fundamental	Vertical	101	1	--	--	
2	10512.55	53.51	5.47	-4.24	54.74	Peak (NRB)	Vertical	101	32	--	--	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 195 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5300.00 MHz, Antenna: AP-ANT-48, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5298.80	94.08	3.81	-11.09	86.80	Fundamental	Horizontal	100	0	--	--	
2	10600.52	47.61	5.58	-3.93	49.26	Max Avg	Vertical	196	283	54.0	-4.7	Pass
3	10600.52	62.74	5.58	-3.93	64.39	Max Peak	Vertical	196	283	74.0	-9.6	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 196 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5320.00 MHz, Antenna: AP-ANT-48, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5318.16	90.36	3.75	-11.07	83.04	Fundamental	Horizontal	101	1	--	--	
2	10637.35	49.74	5.45	-3.89	51.30	Max Avg	Vertical	177	315	54.0	-2.7	Pass
3	10637.35	63.42	5.45	-3.89	64.98	Max Peak	Vertical	177	315	74.0	-9.0	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 197 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5500.00 MHz, Antenna: AP-ANT-48, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	PoI	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5501.68	90.78	3.75	-11.17	83.36	Fundamental	Horizontal	101	1	--	--	
2	11000.52	52.16	5.59	-4.24	53.51	Max Avg	Vertical	188	315	54.0	-0.5	Pass
3	11000.52	66.64	5.59	-4.24	67.99	Max Peak	Vertical	188	315	74.0	-6.0	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 198 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5580.00 MHz, Antenna: AP-ANT-48, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5578.48	92.68	3.81	-11.20	85.29	Fundamental	Vertical	101	1	--	--	
2	11154.99	46.94	5.93	-4.05	48.82	Max Avg	Vertical	158	246	54.0	-5.2	Pass
3	11154.99	60.96	5.93	-4.05	62.84	Max Peak	Vertical	158	246	74.0	-11.2	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 199 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5720.00 MHz, Antenna: AP-ANT-48, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5718.67	92.22	3.80	-10.75	85.27	Fundamental	Horizontal	101	1	--	--	
2	11431.02	53.18	5.48	-4.92	53.74	Max Avg	Vertical	171	263	54	-0.26	Pass
3	11431.02	72.82	5.48	-4.92	73.38	Max Peak	Vertical	171	263	74.0	-0.6	Pass

Test Notes: EUT on 150cm Table powered by PDSine 9001GR.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




A.1.1.8. Metal Sheet



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5260.00 MHz, Antenna: Metal Sheet, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail
1	5255.83	86.01	3.64	-11.31	78.34	Fundamental	Vertical	101	0	--	--	
2	5255.83	86.01	3.64	-11.31	78.34	Peak (NRB)	Vertical	101	0	--	--	Pass
3	10510.90	48.99	5.48	-4.26	50.21	Peak (NRB)	Horizontal	101	0	--	--	Pass

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 201 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5300.00 MHz, Antenna: Metal Sheet, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5299.44	73.60	3.81	-11.09	66.32	Fundamental	Vertical	101	1	--	--	
2	5299.44	73.60	3.81	-11.09	66.32	Peak (NRB)	Vertical	101	1	--	--	Pass
3	10587.81	42.05	5.71	-3.95	43.81	Max Avg	Horizontal	166	78	54.0	-10.2	Pass
4	10587.81	57.61	5.71	-3.95	59.37	Max Peak	Horizontal	166	78	74.0	-14.6	Pass
5	10587.81	38.80	5.71	-3.95	40.56	Max Avg	Vertical	111	0	54.0	-13.4	Pass
6	10587.81	53.55	5.71	-3.95	55.31	Max Peak	Vertical	111	0	74.0	-18.7	Pass
7	10587.81	47.67	5.71	-3.95	49.43	Peak (NRB)	Horizontal	101	1	--	--	Pass

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 202 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5320.00 MHz, Antenna: Metal Sheet, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5323.77	73.63	3.74	-11.06	66.31	Fundamental	Vertical	101	1	--	--	
2	5323.77	73.63	3.74	-11.06	66.31	Peak (NRB)	Vertical	101	1	--	--	Pass
3	10645.89	43.55	5.30	-3.90	44.95	Max Avg	Horizontal	122	48	54.0	-9.1	Pass
4	10645.89	57.89	5.30	-3.90	59.29	Max Peak	Horizontal	122	48	74.0	-14.7	Pass
5	10645.89	42.55	5.30	-3.90	43.95	Max Avg	Vertical	122	65	54.0	-10.1	Pass
6	10645.89	57.64	5.30	-3.90	59.04	Max Peak	Vertical	122	65	74.0	-15.0	Pass

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 203 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5500.00 MHz, Antenna: Metal Sheet, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5492.46	91.04	3.71	-11.18	83.57	Fundamental	Horizontal	101	1	--	--	
2	5492.46	91.04	3.71	-11.18	83.57	Peak (NRB)	Horizontal	101	1	--	--	Pass
3	10993.18	45.66	5.60	-4.26	47.00	Max Avg	Horizontal	100	50	54.0	-7.0	Pass
4	10993.18	59.91	5.60	-4.26	61.25	Max Peak	Horizontal	100	50	74.0	-12.8	Pass
5	10993.18	44.42	5.60	-4.26	45.76	Max Avg	Vertical	100	19	54.0	-8.2	Pass
6	10993.18	58.75	5.60	-4.26	60.09	Max Peak	Vertical	100	19	74.0	-13.9	Pass

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 204 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5580.00 MHz, Antenna: Metal Sheet, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5578.28	87.99	3.81	-11.20	80.60	Fundamental	Horizontal	101	1	--	--	
2	5578.28	87.99	3.81	-11.20	80.60	Peak (NRB)	Horizontal	101	1	--	--	Pass
3	11159.51	41.38	5.85	-4.07	43.16	Max Avg	Vertical	144	20	54.0	-10.8	Pass
4	11159.51	53.46	5.85	-4.07	55.24	Max Peak	Vertical	144	20	74.0	-18.8	Pass
5	11159.51	38.83	5.85	-4.07	40.61	Max Avg	Horizontal	190	351	54.0	-13.4	Pass
6	11159.51	52.55	5.85	-4.07	54.33	Max Peak	Horizontal	190	351	74.0	-19.7	Pass

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 205 of 297



RADIATED SPURIOUS - RESTRICTED BAND EMISSIONS

Variant: 802.11a, Test Freq: 5720.00 MHz, Antenna: Metal Sheet, Power Setting: 21, Duty Cycle (%): 100



Num	Frequency MHz	Raw dB μ V	Cable Loss	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
1	5715.75	67.90	3.81	-10.76	60.95	Fundamental	Vertical	101	1	--	--	
2	5715.75	67.90	3.81	-10.76	60.95	Peak (NRB)	Vertical	101	1	--	--	Pass
3	11445.21	49.83	5.40	-4.92	50.31	Max Avg	Horizontal	166	75	54.0	-3.7	Pass
4	11445.21	64.01	5.40	-4.92	64.49	Max Peak	Horizontal	166	75	74.0	-9.5	Pass
5	11445.21	43.96	5.40	-4.92	44.44	Max Avg	Vertical	100	355	54.0	-9.6	Pass
6	11445.21	57.60	5.40	-4.92	58.08	Max Peak	Vertical	100	355	74.0	-15.9	Pass

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 206 of 297


A.1.2. Restricted Band and Band-Edge Emissions

A.1.2.9. AP-ANT-13B



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11a, Test Freq: 5500.00 MHz, Antenna: AP-ANT-13B, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5458.52	22.29	3.79	34.31	60.39	Max Peak	Vertical	147	17	74.0	-13.6	Pass
2	5460.00	7.53	3.79	34.31	45.63	Max Avg	Vertical	147	17	54.0	-8.4	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5466.15	12.67	3.79	34.31	50.77	Max Avg	Horizontal	153	30	68.2*	-17.5	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

*Note 68.2 dBμV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 207 of 297



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5530.00 MHz, Antenna: AP-ANT-13B, Power Setting: 15.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	PoI	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5459.78	14.68	3.79	34.31	52.78	Max Avg	Vertical	147	17	54.0	-1.2	Pass
2	5460.00	30.79	3.79	34.31	68.89	Max Peak	Vertical	147	17	74.0	-5.1	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5460.54	14.68	3.79	34.31	52.78	Max Avg	Horizontal	153	30	68.2*	-15.5	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 208 of 297



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11n HT-20, Test Freq: 5500.00 MHz, Antenna: AP-ANT-13B, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5458.50	21.89	3.80	34.30	59.99	Max Peak	Vertical	147	17	74.0	-14.0	Pass
2	5459.24	8.00	3.79	34.31	46.10	Max Avg	Vertical	147	17	54.0	-7.9	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5465.87	13.19	3.79	34.31	51.29	Max Avg	--	--	--	68.2*	-16.9	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 209 of 297



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11n HT-40, Test Freq: 5510.00 MHz, Antenna: AP-ANT-13B, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5455.75	10.89	3.80	34.30	48.99	Max Avg	Vertical	147	17	54.0	-5.0	Pass
2	5455.93	26.03	3.80	34.30	64.13	Max Peak	Vertical	147	17	74.0	-9.9	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5463.35	14.02	3.79	34.31	52.12	Max Avg	Horizontal	153	30	68.2	-16.1	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

*Note 68.2 dBμV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 210 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11a, Test Freq: 5320.00 MHz, Antenna: AP-ANT-13B, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5350.00	0.00	0.00	0.00	--	Band-Edge		0	0	--	--	
2	5356.97	11.20	3.71	34.49	49.40	Max Avg	Vertical	155	6	54.0	-4.6	Pass
3	5358.60	24.83	3.71	34.49	63.03	Max Peak	Vertical	155	6	74.0	-11.0	Pass

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 211 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5290.00 MHz, Antenna: AP-ANT-13B, Power Setting: 15, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5350.00	0.00	0.00	0.00	--	Band-Edge		0	0	--	--	
2	5354.27	34.59	3.71	34.50	72.80	Max Peak	Vertical	147	17	74.0	-1.2	Pass
3	5360.98	15.78	3.70	34.48	53.96	Max Avg	Vertical	147	17	54.0	0.0	Pass

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 212 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11n HT-20, Test Freq: 5320.00 MHz, Antenna: AP-ANT-13B, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5350.00	0.00	0.00	0.00	--	Band-Edge		0	0	--	--	
2	5350.26	26.65	3.70	34.51	64.86	Max Peak	Vertical	147	17	74.0	-9.1	Pass
3	5350.78	12.63	3.71	34.51	50.85	Max Avg	Vertical	147	17	54.0	-3.2	Pass

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 213 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11n HT-40, Test Freq: 5310.00 MHz, Antenna: AP-ANT-13B, Power Setting: 17, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5350.00	0.00	0.00	0.00	--	Band-Edge		0	0	--	--	
2	5353.31	14.66	3.71	34.50	52.87	Max Avg	Vertical	147	17	54.0	-1.1	Pass
3	5354.65	30.77	3.71	34.50	68.98	Max Peak	Vertical	147	17	74.0	-5.0	Pass

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 214 of 297



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5210.00 MHz, Antenna: AP-ANT-13B, Power Setting: 16, Duty Cycle (%): 95



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5150.00	15.85	3.67	34.11	53.63	Max Avg	Vertical	200	-2	54.0	-0.4	Pass
2	5150.00	33.30	3.67	34.11	71.08	Max Peak	Vertical	200	-2	74.0	-2.9	Pass
3	5150.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 215 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5290.00 MHz, Antenna: AP-ANT-13B, Power Setting: 16, Duty Cycle (%): 95



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
2	5361.84	31.38	3.70	34.48	69.56	Max Peak	Vertical	200	-2	74.0	-4.4	Pass
3	5364.19	13.44	3.70	34.48	51.62	Max Avg	Vertical	200	-2	54.0	-2.4	Pass
1	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 216 of 297



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5530.00 MHz, Antenna: AP-ANT-13B, Power Setting: 15.5, Duty Cycle (%): 95



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5452.26	32.95	3.78	34.30	71.03	Max Peak	Vertical	199	-3	74.0	-3.0	Pass
2	5452.48	15.21	3.78	34.30	53.29	Max Avg	Vertical	199	-3	54.0	-0.7	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5469.94	16.66	3.79	34.32	54.77	Max Avg	Horizontal	153	30	68.2*	-13.5	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




A.1.2.10. AP-ANT-19



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11a, Test Freq: 5500.00 MHz, Antenna: AP-ANT-19, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5456.07	10.38	3.80	34.30	48.48	Max Avg	Vertical	166	118	54.0	-5.5	Pass
2	5456.35	24.64	3.80	34.30	62.74	Max Peak	Vertical	166	118	74.0	-11.3	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5469.52	14.35	3.79	34.32	52.46	Max Avg	Horizontal	153	30	68.2*	-15.8	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

*Note 68.2 dBμV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 218 of 297



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5530.00 MHz, Antenna: AP-ANT-19, Power Setting: 15.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5449.34	32.55	3.77	34.30	70.62	Max Peak	Vertical	166	118	74.0	-3.4	Pass
2	5449.62	15.61	3.77	34.30	53.68	Max Avg	Vertical	166	118	54.0	-0.3	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5469.24	18.27	3.79	34.32	56.38	Max Avg	Horizontal	153	30	68.2	-11.9	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

*Note 68.2 dBμV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 219 of 297



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11n HT-20, Test Freq: 5500.00 MHz, Antenna: AP-ANT-19, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5454.53	25.63	3.79	34.30	63.72	Max Peak	Vertical	166	118	74.0	-10.3	Pass
2	5455.65	10.55	3.80	34.30	48.65	Max Avg	Vertical	166	118	54.0	-5.4	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5469.24	14.01	3.79	34.32	52.12	Max Avg	Horizontal	153	30	68.2	-16.1	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

*Note 68.2 dBμV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 220 of 297



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11n HT-40, Test Freq: 5510.00 MHz, Antenna: AP-ANT-19, Power Setting: 17, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5458.84	28.91	3.79	34.31	67.01	Max Peak	Vertical	166	118	74.0	-7.0	Pass
2	5459.02	14.02	3.79	34.31	52.12	Max Avg	Vertical	166	118	54.0	-1.9	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5465.59	18.48	3.79	34.32	56.58	Max Avg	Horizontal	153	30	68.2	-11.7	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 221 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11a, Test Freq: 5320.00 MHz, Antenna: AP-ANT-19, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5353.53	13.77	3.71	34.50	51.98	Max Avg	Vertical	166	102	54.0	-2.0	Pass
2	5355.05	28.62	3.71	34.50	66.83	Max Peak	Vertical	166	102	74.0	-7.2	Pass
3	--	--	--	--	--	Band Edge	--	--	--	--	--	--

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 222 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5290.00 MHz, Antenna: AP-ANT-19, Power Setting: 14, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	--
2	5363.65	15.69	3.70	34.48	53.87	Max Avg	Vertical	166	118	54.0	-0.1	Pass
3	5364.65	34.28	3.69	34.47	72.44	Max Peak	Vertical	166	118	74.0	-1.6	Pass

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 223 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11n HT-20, Test Freq: 5320.00 MHz, Antenna: AP-ANT-19, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5352.95	27.07	3.71	34.50	65.28	Max Peak	Vertical	166	118	74.0	-8.7	Pass
2	5353.31	13.41	3.71	34.50	51.62	Max Avg	Vertical	166	118	54.0	-2.4	Pass
3	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 224 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11n HT-40, Test Freq: 5310.00 MHz, Antenna: AP-ANT-19, Power Setting: 17, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	--
2	5357.78	30.86	3.71	34.49	69.06	Max Peak	Vertical	166	118	74.0	-4.9	Pass
3	5363.57	15.10	3.70	34.48	53.28	Max Avg	Vertical	166	118	54.0	-0.7	Pass

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 225 of 297



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5250.00 MHz, Antenna: AP-ANT-19, Power Setting: 12.5, Duty Cycle (%): 95



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5140.13	15.80	3.70	34.12	53.62	Max Avg	Vertical	153	346	54.0	-0.4	Pass
2	5147.39	35.10	3.68	34.11	72.89	Max Peak	Vertical	153	346	74.0	-1.1	Pass
3	5150.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 226 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5250.00 MHz, Antenna: AP-ANT-19, Power Setting: 11.5, Duty Cycle (%): 95



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
2	5353.91	13.77	3.71	34.50	51.98	Max Avg	Vertical	153	346	54.0	-2.0	Pass
3	5354.55	31.90	3.71	34.50	70.11	Max Peak	Vertical	153	346	74.0	-3.9	Pass
1	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 227 of 297



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5570.00 MHz, Antenna: AP-ANT-19, Power Setting: 12.5, Duty Cycle (%): 95



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5452.51	15.78	3.79	34.30	53.87	Max Avg	Vertical	144	312	54.0	-0.1	Pass
2	5455.81	34.78	3.80	34.30	72.88	Max Peak	Vertical	144	312	74.0	-1.1	Pass
4	5469.94	17.07	3.79	34.32	55.18	Max Avg	Horizontal	153	30	68.2*	-13.1	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.

*Note 68.2 dBμV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




A.1.2.11. AP-ANT-1W



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11a, Test Freq: 5500.00 MHz, Antenna: AP-ANT-1W, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	PoI	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5456.89	8.66	3.80	34.30	46.76	Max Avg	Vertical	148	44	54.0	-7.2	Pass
2	5458.02	23.21	3.80	34.30	61.31	Max Peak	Vertical	148	44	74.0	-12.7	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5469.79	7.76	3.79	34.32	45.87	Max Avg	Horizontal	153	30	68.2	-22.4	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 229 of 297



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5530.00 MHz, Antenna: AP-ANT-1W, Power Setting: 16, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5444.77	32.16	3.76	34.30	70.22	Max Peak	Vertical	148	44	74.0	-3.8	Pass
2	5445.77	15.33	3.76	34.30	53.39	Max Avg	Vertical	148	44	54.0	-0.6	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5466.15	16.75	3.79	34.31	54.85	Max Avg	Horizontal	153	30	68.2*	-13.4	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 230 of 297



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11n HT-20, Test Freq: 5500.00 MHz, Antenna: AP-ANT-1W, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5455.27	23.30	3.79	34.30	61.39	Max Peak	Vertical	148	44	74.0	-12.6	Pass
2	5456.21	8.66	3.80	34.30	46.76	Max Avg	Vertical	148	44	54.0	-7.2	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5469.80	6.77	3.79	34.32	44.88	Max Avg	Horizontal	153	30	68.2	-23.4	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 231 of 297



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11n HT-40, Test Freq: 5510.00 MHz, Antenna: AP-ANT-1W, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5445.67	28.30	3.76	34.30	66.36	Max Peak	Vertical	148	44	74.0	-7.6	Pass
2	5446.51	12.56	3.76	34.30	50.62	Max Avg	Vertical	148	44	54.0	-3.4	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5466.43	20.05	3.79	34.32	58.15	Max Avg	Horizontal	153	30	68.2	-10.1	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11a, Test Freq: 5320.00 MHz, Antenna: AP-ANT-1W, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5350.00	0.00	0.00	0.00	--	Band-Edge		0	0	--	--	
2	5350.22	7.75	3.70	34.51	45.96	Max Avg	Vertical	150	54	54.0	-8.0	Pass
3	5351.00	20.93	3.71	34.51	59.15	Max Peak	Vertical	150	54	74.0	-14.9	Pass

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 233 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5290.00 MHz, Antenna: AP-ANT-1W, Power Setting: 16.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5350.00	0.00	0.00	0.00	--	Band-Edge		0	0	--	--	
2	5358.10	13.54	3.71	34.49	51.74	Max Avg	Vertical	150	57	54.0	-2.3	Pass
3	5358.66	29.57	3.71	34.49	67.77	Max Peak	Vertical	150	57	74.0	-6.2	Pass

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 234 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11n HT-20, Test Freq: 5320.00 MHz, Antenna: AP-ANT-1W, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5350.00	7.27	3.70	34.51	45.48	Max Avg	Vertical	150	57	54.0	-8.5	Pass
2	5350.00	0.00	0.00	0.00	--	Band-Edge		0	0	--	--	
3	5353.53	17.75	3.71	34.50	55.96	Max Peak	Vertical	150	57	74.0	-18.0	Pass

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 235 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11n HT-40, Test Freq: 5310.00 MHz, Antenna: AP-ANT-1W, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5350.00	7.27	3.70	34.51	45.48	Max Avg	Vertical	150	57	54.0	-8.5	Pass
2	5350.00	20.19	3.70	34.51	58.40	Max Peak	Vertical	150	57	74.0	-15.6	Pass
3	5350.00	0.00	0.00	0.00	--	Band-Edge		0	0	--	--	

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 236 of 297



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5250.00 MHz, Antenna: AP-ANT-1W, Power Setting: 14.5, Duty Cycle (%): 95



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5148.55	32.62	3.67	34.11	70.40	Max Peak	Horizontal	158	31	74.0	-3.6	Pass
2	5150.00	15.67	3.67	34.11	53.45	Max Avg	Horizontal	158	31	54.0	-0.6	Pass
3	5150.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 237 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5250.00 MHz, Antenna: AP-ANT-1W, Power Setting: 16, Duty Cycle (%): 95



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
2	5351.44	30.99	3.71	34.51	69.21	Max Peak	Horizontal	158	31	74.0	-4.8	Pass
3	5369.94	14.92	3.69	34.46	53.07	Max Avg	Horizontal	158	31	54.0	-0.9	Pass
1	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE.


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5570.00 MHz, Antenna: AP-ANT-1W, Power Setting: 16, Duty Cycle (%): 95



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5459.96	32.90	3.79	34.31	71.00	Max Peak	Horizontal	170	304	74.0	-3.0	Pass
2	5460.00	15.49	3.79	34.31	53.59	Max Avg	Horizontal	170	304	54.0	-0.4	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5464.83	16.05	3.79	34.31	54.15	Max Avg	Horizontal	153	30	68.2	-14.1	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE.

[back to matrix](#)

*Note 68.2 dBμV/m is band edge average limit for 5470 MHz per FCC 407

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




A.1.2.12. AP-ANT-20W



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11a, Test Freq: 5500.00 MHz, Antenna: AP-ANT-20W, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5459.72	19.75	3.79	34.31	57.85	Max Peak	Horizontal	141	51	74.0	-16.2	Pass
2	5460.00	6.51	3.79	34.31	44.61	Max Avg	Horizontal	141	51	54.0	-9.4	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5461.14	7.04	3.79	34.31	45.14	Max Avg	Horizontal	153	30	68.2	-23.1	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

*Note 68.2 dBμV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 240 of 297



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5530.00 MHz, Antenna: AP-ANT-20W, Power Setting: 16.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5457.74	14.79	3.80	34.30	52.89	Max Avg	Horizontal	141	298	54.0	-1.1	Pass
2	5458.02	32.93	3.80	34.30	71.03	Max Peak	Horizontal	141	298	74.0	-3.0	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5465.03	12.26	3.79	34.31	50.36	Max Avg	Horizontal	153	30	68.2	-17.9	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

*Note 68.2 dBμV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 241 of 297



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11n HT-20, Test Freq: 5500.00 MHz, Antenna: AP-ANT-20W, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5460.00	6.51	3.79	34.31	44.61	Max Avg	Horizontal	141	51	54.0	-9.4	Pass
2	5460.00	19.33	3.79	34.31	57.43	Max Peak	Horizontal	141	51	74.0	-16.6	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5461.66	7.04	3.79	34.31	45.14	Max Avg	Horizontal	153	30	68.2*	-23.1	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 242 of 297



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11n HT-40, Test Freq: 5510.00 MHz, Antenna: AP-ANT-20W, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5450.72	25.33	3.78	34.30	63.41	Max Peak	Horizontal	141	51	74.0	-10.6	Pass
2	5451.84	9.29	3.78	34.30	47.37	Max Avg	Horizontal	141	51	54.0	-6.6	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5469.80	16.57	3.79	34.32	54.68	Max Avg	Horizontal	153	30	68.2	-13.6	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 243 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11a, Test Freq: 5320.00 MHz, Antenna: AP-ANT-20W, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5351.82	26.17	3.71	34.51	64.39	Max Peak	Horizontal	141	297	74.0	-9.6	Pass
2	5351.98	12.22	3.71	34.51	50.44	Max Avg	Horizontal	141	297	54.0	-3.6	Pass
3	53500.00	0.00	0.00	0.00	--	Band-Edge		0	0	--	--	

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 244 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5290.00 MHz, Antenna: AP-ANT-20W, Power Setting: 15, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5355.51	15.66	3.71	34.50	53.87	Max Avg	Horizontal	141	298	54.0	-0.1	Pass
2	5355.95	35.26	3.71	34.50	73.47	Max Peak	Horizontal	141	298	74.0	-0.5	Pass
3	53500.00	0.00	0.00	0.00	--	Band-Edge		0	0	--	--	

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 245 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11n HT-20, Test Freq: 5320.00 MHz, Antenna: AP-ANT-20W, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5351.16	26.23	3.71	34.51	64.45	Max Peak	Horizontal	141	297	74.0	-9.6	Pass
2	5351.62	12.50	3.71	34.51	50.72	Max Avg	Horizontal	141	297	54.0	-3.3	Pass
3	53500.00	0.00	0.00	0.00	--	Band-Edge		0	0	--	--	

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 246 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11n HT-40, Test Freq: 5310.00 MHz, Antenna: AP-ANT-20W, Power Setting: 17, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5354.39	30.60	3.71	34.50	68.81	Max Peak	Horizontal	141	297	74.0	-5.2	Pass
2	5355.65	15.07	3.71	34.50	53.28	Max Avg	Horizontal	141	297	54.0	-0.7	Pass
3	53500.00	0.00	0.00	0.00	--	Band-Edge		0	0	--	--	

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 247 of 297



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5250.00 MHz, Antenna: AP-ANT-20W, Power Setting: 16, Duty Cycle (%): 95



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5138.68	10.75	3.70	34.12	48.57	Max Avg	Horizontal	150	323	54.0	-5.4	Pass
2	5141.58	26.99	3.70	34.12	64.81	Max Peak	Horizontal	150	323	74.0	-9.2	Pass
3	5150.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 248 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5290.00 MHz, Antenna: AP-ANT-20W, Power Setting: 16, Duty Cycle (%): 95



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	--
2	5353.11	15.66	3.71	34.50	53.87	Max Avg	Horizontal	150	323	54.0	-0.1	Pass
3	5354.97	34.36	3.71	34.50	72.57	Max Peak	Horizontal	150	323	74.0	-1.4	Pass

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 249 of 297



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5530.00 MHz, Antenna: AP-ANT-20W, Power Setting: 16, Duty Cycle (%): 95



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5444.07	29.84	3.75	34.31	67.90	Max Peak	Horizontal	150	312	74.0	-6.1	Pass
2	5460.00	12.66	3.79	34.31	50.76	Max Avg	Horizontal	150	312	54.0	-3.2	Pass
4	5464.83	14.99	3.79	34.31	53.09	Max Avg	Horizontal	153	30	68.2	-15.1	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




A.1.2.13. AP-ANT-40



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11a, Test Freq: 5500.00 MHz, Antenna: AP-ANT-40, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5454.97	12.12	3.79	34.30	50.21	Max Avg	Horizontal	153	330	54.0	-3.8	Pass
2	5454.97	28.17	3.79	34.30	66.26	Max Peak	Horizontal	153	330	74.0	-7.7	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5468.40	16.40	3.79	34.32	54.51	Max Avg	Horizontal	153	30	68.2*	-13.7	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

*Note 68.2 dBμV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 251 of 297



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5530.00 MHz, Antenna: AP-ANT-40, Power Setting: 14.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5460.00	15.10	3.79	34.31	53.20	Max Avg	Horizontal	153	330	54.0	-0.8	Pass
2	5460.00	32.89	3.79	34.31	70.99	Max Peak	Horizontal	153	330	74.0	-3.0	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5461.94	17.08	3.79	34.31	55.18	Max Avg	Horizontal	153	30	68.2	-13.1	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

*Note 68.2 dBμV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 252 of 297



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11n HT-20, Test Freq: 5500.00 MHz, Antenna: AP-ANT-40, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5455.23	12.40	3.79	34.30	50.49	Max Avg	Horizontal	153	330	54.0	-3.5	Pass
2	5455.23	26.68	3.79	34.30	64.77	Max Peak	Horizontal	153	330	74.0	-9.2	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5467.55	15.58	3.79	34.32	53.69	Max Avg	Horizontal	153	30	68.2	-14.5	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

*Note 68.2 dBμV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 253 of 297



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11n HT-40, Test Freq: 5510.00 MHz, Antenna: AP-ANT-40, Power Setting: 17, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5457.39	14.99	3.80	34.30	53.09	Max Avg	Horizontal	153	330	54.0	-0.9	Pass
2	5458.24	29.47	3.80	34.30	67.57	Max Peak	Horizontal	153	330	74.0	-6.4	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5464.75	19.57	3.79	34.31	57.67	Max Avg	Horizontal	153	30	68.2	-10.6	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 254 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11a, Test Freq: 5320.00 MHz, Antenna: AP-ANT-40, Power Setting: 17.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	--
2	5351.82	27.43	3.71	34.51	65.65	Max Peak	Horizontal	153	331	74.0	-8.4	Pass
3	5352.61	14.00	3.71	34.50	52.21	Max Avg	Horizontal	153	331	54.0	-1.8	Pass

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 255 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5290.00 MHz, Antenna: AP-ANT-40, Power Setting: 13, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	--
2	5362.06	35.28	3.70	34.48	73.46	Max Peak	Horizontal	153	331	74.0	-0.5	Pass
3	5362.32	15.50	3.70	34.48	53.68	Max Avg	Horizontal	153	331	54.0	-0.3	Pass

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 256 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11n HT-20, Test Freq: 5320.00 MHz, Antenna: AP-ANT-40, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	--
2	5352.30	14.65	3.71	34.51	52.87	Max Avg	Horizontal	153	331	54.0	-1.1	Pass
3	5354.35	29.21	3.71	34.50	67.42	Max Peak	Horizontal	153	331	74.0	-6.6	Pass

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 257 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11n HT-40, Test Freq: 5310.00 MHz, Antenna: AP-ANT-40, Power Setting: 16.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	--
2	5354.39	15.37	3.71	34.50	53.58	Max Avg	Horizontal	153	331	54.0	-0.4	Pass
3	5355.03	30.98	3.71	34.50	69.19	Max Peak	Horizontal	153	331	74.0	-4.8	Pass

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 258 of 297



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5250.00 MHz, Antenna: AP-ANT-40, Power Setting: 12.5, Duty Cycle (%): 95



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5143.09	15.02	3.70	34.12	52.84	Max Avg	Horizontal	199	41	54.0	-1.2	Pass
2	5147.44	31.77	3.68	34.11	69.56	Max Peak	Horizontal	199	41	74.0	-4.4	Pass
3	5150.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 259 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5250.00 MHz, Antenna: AP-ANT-40, Power Setting: 14, Duty Cycle (%): 95



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	--
2	5361.58	15.20	3.70	34.48	53.38	Max Avg	Horizontal	199	41	54.0	-0.6	Pass
3	5362.04	32.76	3.70	34.48	70.94	Max Peak	Horizontal	199	41	74.0	-3.1	Pass

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5570.00 MHz, Antenna: AP-ANT-40, Power Setting: 15, Duty Cycle (%): 95



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5459.40	30.83	3.79	34.31	68.93	Max Peak	Horizontal	200	41	74.0	-5.1	Pass
2	5460.00	14.99	3.79	34.31	53.09	Max Avg	Horizontal	200	41	54.0	-0.9	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5465.13	16.82	3.79	34.32	54.93	Max Avg	Horizontal	153	30	68.2	-13.3	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




A.1.2.14. AP-ANT-45



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11a, Test Freq: 5500.00 MHz, Antenna: AP-ANT-45, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5458.64	31.82	3.79	34.31	69.92	Max Peak	Horizontal	160	42	74.0	-4.1	Pass
2	5459.68	14.89	3.79	34.31	52.99	Max Avg	Horizontal	160	42	54.0	-1.0	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5460.72	14.79	3.79	34.31	52.89	Max Avg	Horizontal	153	30	68.2	-15.3	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

*Note 68.2 dBμV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 262 of 297



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5530.00 MHz, Antenna: AP-ANT-45, Power Setting: 14, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5449.24	15.61	3.77	34.30	53.68	Max Avg	Horizontal	160	42	54.0	-0.3	Pass
2	5449.76	32.96	3.77	34.30	71.03	Max Peak	Horizontal	160	42	74.0	-3.0	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5469.58	18.05	3.79	34.32	56.16	Max Avg	Horizontal	153	30	68.2	-12.1	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 263 of 297



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11n HT-20, Test Freq: 5500.00 MHz, Antenna: AP-ANT-45, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5459.38	13.91	3.79	34.31	52.01	Max Avg	Horizontal	160	42	54.0	-2.0	Pass
2	5459.64	28.93	3.79	34.31	67.03	Max Peak	Horizontal	160	42	74.0	-7.0	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5460.20	13.67	3.79	34.31	51.77	Max Avg	Horizontal	153	30	68.2	-16.5	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 264 of 297



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11n HT-40, Test Freq: 5510.00 MHz, Antenna: AP-ANT-45, Power Setting: 17, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5456.03	14.02	3.80	34.30	52.12	Max Avg	Horizontal	160	42	54.0	-1.9	Pass
2	5456.87	31.40	3.80	34.30	69.50	Max Peak	Horizontal	160	42	74.0	-4.5	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5469.84	23.67	3.79	34.32	61.78	Max Avg	Horizontal	153	30	68.2	-6.5	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 265 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11a, Test Freq: 5320.00 MHz, Antenna: AP-ANT-45, Power Setting: 17, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5350.00	14.87	3.70	34.51	53.08	Max Avg	Vertical	161	5	54.0	-0.9	Pass
2	5350.00	28.73	3.70	34.51	66.94	Max Peak	Vertical	161	5	74.0	-7.1	Pass
3	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	--

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 266 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5290.00 MHz, Antenna: AP-ANT-45, Power Setting: 10.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	--
2	5358.92	14.46	3.71	34.49	52.66	Max Avg	Vertical	161	5	54.0	-1.3	Pass
3	5358.92	35.08	3.71	34.49	73.28	Max Peak	Vertical	161	5	74.0	-0.7	Pass

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 267 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11n HT-20, Test Freq: 5320.00 MHz, Antenna: AP-ANT-45, Power Setting: 17, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	--
2	5350.44	14.66	3.70	34.51	52.87	Max Avg	Vertical	161	5	54.0	-1.1	Pass
3	5350.44	28.25	3.70	34.51	66.46	Max Peak	Vertical	161	5	74.0	-7.5	Pass

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 268 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11n HT-40, Test Freq: 5310.00 MHz, Antenna: AP-ANT-45, Power Setting: 15.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	--
2	5358.14	31.15	3.71	34.49	69.35	Max Peak	Vertical	161	5	74.0	-4.7	Pass
3	5358.66	14.98	3.71	34.49	53.18	Max Avg	Vertical	161	5	54.0	-0.8	Pass

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 269 of 297



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5250.00 MHz, Antenna: AP-ANT-45, Power Setting: 15, Duty Cycle (%): 95



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5141.58	15.80	3.70	34.12	53.62	Max Avg	Horizontal	162	8	54.0	-0.4	Pass
2	5141.58	31.58	3.70	34.12	69.40	Max Peak	Horizontal	162	8	74.0	-4.6	Pass
3	5150.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 270 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5290.00 MHz, Antenna: AP-ANT-45, Power Setting: 15.5, Duty Cycle (%): 95



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	--
2	5354.93	15.57	3.71	34.50	53.78	Max Avg	Horizontal	162	8	54.0	-0.2	Pass
3	5355.25	34.58	3.71	34.50	72.79	Max Peak	Horizontal	162	8	74.0	-1.2	Pass

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5530.00 MHz, Antenna: AP-ANT-45, Power Setting: 14.5, Duty Cycle (%): 95



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5460.00	15.20	3.79	34.31	53.30	Max Avg	Horizontal	162	8	54.0	-0.7	Pass
2	5460.00	32.32	3.79	34.31	70.42	Max Peak	Horizontal	162	8	74.0	-3.6	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5461.52	15.49	3.79	34.32	53.59	Max Avg	Horizontal	153	30	68.2*	-14.6	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.

*Note 68.2 dBμV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




A.1.2.15. AP-ANT-48



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11a, Test Freq: 5500.00 MHz, Antenna: AP-ANT-48, Power Setting: 16, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5452.00	28.80	3.78	34.30	66.88	Max Peak	Horizontal	162	362	74.0	-7.1	Pass
2	5455.95	15.09	3.80	34.30	53.19	Max Avg	Horizontal	162	362	54.0	-0.8	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5469.84	17.07	3.79	34.32	55.18	Max Avg	Horizontal	153	30	68.2	-13.1	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

*Note 68.2 dBμV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 273 of 297



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5530.00 MHz, Antenna: AP-ANT-48, Power Setting: 8, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5458.04	15.68	3.80	34.30	53.78	Max Avg	Horizontal	149	368	54.0	-0.2	Pass
2	5458.32	30.40	3.80	34.30	68.50	Max Peak	Horizontal	149	368	74.0	-5.5	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5469.80	15.87	3.79	34.32	53.98	Max Avg	Horizontal	153	30	68.2	-14.3	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 274 of 297



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11n HT-20, Test Freq: 5500.00 MHz, Antenna: AP-ANT-48, Power Setting: 17, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5456.07	15.29	3.80	34.30	53.39	Max Avg	Horizontal	162	362	54.0	-0.6	Pass
2	5458.60	28.16	3.79	34.31	66.26	Max Peak	Horizontal	162	362	74.0	-7.7	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5468.96	17.84	3.79	34.32	55.95	Max Avg	Horizontal	153	30	68.2	-12.3	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

*Note 68.2 dBμV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 275 of 297



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11n HT-40, Test Freq: 5510.00 MHz, Antenna: AP-ANT-48, Power Setting: 13, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5457.76	28.29	3.80	34.30	66.39	Max Peak	Horizontal	162	362	74.0	-7.6	Pass
2	5458.32	15.68	3.80	34.30	53.78	Max Avg	Horizontal	162	362	54.0	-0.2	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5469.52	15.09	3.79	34.32	53.20	Max Avg	Horizontal	153	30	68.2	-15.0	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--


*Note 68.2 dBμV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 276 of 297



RESTRICTED
 UPPER
 BAND-EDGE
 EMISSIONS

Variant:
 802.11a, Test
 Freq: 5320.00
 MHz,
 Antenna: AP-
 ANT-48,
 Power
 Setting: 16,
 Duty Cycle
 (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	--
2	5356.77	27.92	3.71	34.49	66.12	Max Peak	Vertical	152	361	74.0	-7.9	Pass
3	5357.66	15.18	3.71	34.49	53.38	Max Avg	Vertical	152	361	54.0	-0.6	Pass

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 277 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5290.00 MHz, Antenna: AP-ANT-48, Power Setting: 9.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	--
2	5350.62	15.56	3.71	34.51	53.78	Max Avg	Horizontal	149	368	54.0	-0.2	Pass
3	5351.66	33.23	3.71	34.51	71.45	Max Peak	Horizontal	149	368	74.0	-2.6	Pass

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 278 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11n HT-20, Test Freq: 5320.00 MHz, Antenna: AP-ANT-48, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	--
2	5356.57	28.48	3.71	34.49	66.68	Max Peak	Vertical	152	361	74.0	-7.3	Pass
3	5356.81	13.78	3.71	34.49	51.98	Max Avg	Vertical	152	361	54.0	-2.0	Pass

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 279 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11n HT-40, Test Freq: 5310.00 MHz, Antenna: AP-ANT-48, Power Setting: 14, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	PoI	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5350.00	15.47	3.70	34.51	53.68	Max Avg	Vertical	152	361	54.0	-0.3	Pass
2	5350.00	28.62	3.70	34.51	66.83	Max Peak	Vertical	152	361	74.0	-7.2	Pass
3	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	--

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 280 of 297



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5250.00 MHz, Antenna: AP-ANT-48, Power Setting: 12, Duty Cycle (%): 95



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5137.22	31.94	3.69	34.12	69.75	Max Peak	Horizontal	180	-6	74.0	-4.3	Pass
2	5138.73	14.92	3.70	34.12	52.74	Max Avg	Horizontal	180	-6	54.0	-1.3	Pass
3	5150.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 281 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5250.00 MHz, Antenna: AP-ANT-48, Power Setting: 13, Duty Cycle (%): 95



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	--
2	5357.47	15.58	3.71	34.49	53.78	Max Avg	Horizontal	180	-6	54.0	-0.2	Pass
3	5357.60	34.23	3.71	34.49	72.43	Max Peak	Horizontal	180	-6	74.0	-1.6	Pass

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-160, Test Freq: 5570.00 MHz, Antenna: AP-ANT-48, Power Setting: 13.5, Duty Cycle (%): 95



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5457.84	33.22	3.80	34.30	71.32	Max Peak	Horizontal	183	-6	74.0	-2.7	Pass
2	5458.38	14.79	3.80	34.30	52.89	Max Avg	Horizontal	183	-6	54.0	-1.1	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5460.62	14.78	3.79	34.31	52.88	Max Avg	Horizontal	153	30	68.2*	-15.4	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.

[back to matrix](#)

*Note 68.2 dBμV/m is band edge average limit for 5470 MHz per FCC 407

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




A.1.2.16. Metal Sheet



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11a, Test Freq: 5500.00 MHz, Antenna: Metal Sheet, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5453.91	23.02	3.79	34.30	61.11	Max Peak	Vertical	179	313	74.0	-12.9	Pass
2	5455.19	9.08	3.79	34.30	47.17	Max Avg	Vertical	179	313	54.0	-6.8	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5466.39	14.36	3.79	34.31	52.46	Max Avg	Horizontal	153	30	68.2	-15.8	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

*Note 68.2 dBμV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 284 of 297



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5530.00 MHz, Antenna: Metal Sheet, Power Setting: 15.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5447.21	15.33	3.76	34.30	53.39	Max Avg	Vertical	173	329	54.0	-0.6	Pass
2	5447.25	31.38	3.76	34.30	69.44	Max Peak	Vertical	173	329	74.0	-4.6	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5466.39	17.22	3.79	34.32	55.33	Max Avg	Horizontal	153	30	68.2	-12.9	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 285 of 297



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11n HT-20, Test Freq: 5500.00 MHz, Antenna: Metal Sheet, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5454.15	9.28	3.79	34.30	47.37	Max Avg	Vertical	179	313	54.0	-6.6	Pass
2	5454.75	23.34	3.79	34.30	61.43	Max Peak	Vertical	179	313	74.0	-12.6	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5465.43	14.46	3.79	34.32	52.57	Max Avg	Horizontal	153	30	68.2	-15.7	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 286 of 297



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 802.11n HT-40, Test Freq: 5510.00 MHz, Antenna: Metal Sheet, Power Setting: 17.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5453.65	15.40	3.79	34.30	53.49	Max Avg	Vertical	179	313	54.0	-0.5	Pass
2	5454.67	31.27	3.79	34.30	69.36	Max Peak	Vertical	179	313	74.0	-4.6	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5465.11	18.68	3.79	34.32	56.79	Max Avg	Horizontal	153	30	68.2	-11.4	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 287 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11a, Test Freq: 5320.00 MHz, Antenna: Metal Sheet, Power Setting: 18.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	--
2	5352.61	30.77	3.71	34.50	68.98	Max Peak	Vertical	179	330	74.0	-5.0	Pass
3	5352.85	15.47	3.71	34.50	53.68	Max Avg	Vertical	179	330	54.0	-0.3	Pass

Test Notes: reduced power setting from 21 to 18.5

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 288 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5290.00 MHz, Antenna: Metal Sheet, Power Setting: 14, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	--
2	5363.35	35.79	3.70	34.48	73.97	Max Peak	Vertical	179	330	74.0	0.0	Pass
3	5364.65	15.71	3.69	34.47	53.87	Max Avg	Vertical	179	330	54.0	-0.1	Pass

Test Notes: reduced power setting from 21 to 14

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 289 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11n HT-20, Test Freq: 5320.00 MHz, Antenna: Metal Sheet, Power Setting: 18.5, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	--
2	5353.05	28.70	3.71	34.50	66.91	Max Peak	Vertical	179	330	74.0	-7.1	Pass
3	5353.57	14.55	3.71	34.50	52.76	Max Avg	Vertical	179	330	54.0	-1.2	Pass

Test Notes: reduced power setting from 21 to 18.5

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 290 of 297



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11n HT-40, Test Freq: 5310.00 MHz, Antenna: Metal Sheet, Power Setting: 17, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	--
2	5363.51	30.37	3.70	34.48	68.55	Max Peak	Vertical	179	330	74.0	-5.5	Pass
3	5364.55	13.93	3.69	34.47	52.09	Max Avg	Vertical	179	330	54.0	-1.9	Pass

Test Notes: reduced power setting from 21 to 17

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 291 of 297

RESTRICTED LOWER BAND-EDGE EMISSIONS



Variant: 802.11ac-160, Test Freq: 5250.00 MHz, Antenna: Aruba Networks Metal Sheet, Power Setting: 15.5, Duty Cycle (%): 95



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5136.92	31.32	3.69	34.12	69.13	Max Peak	Vertical	159	305	74.0	-4.9	Pass
2	5150.00	16.04	3.67	34.11	53.82	Max Avg	Vertical	159	305	54.0	-0.2	Pass
3	5150.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 292 of 297

RESTRICTED UPPER BAND-EDGE EMISSIONS



Variant: 802.11ac-160, Test Freq: 5290.00 MHz, Antenna: Aruba Networks Metal Sheet, Power Setting: 16, Duty Cycle (%): 95



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Band Edge	--	--	--	--	--	--
2	5355.13	33.22	3.71	34.50	71.43	Max Peak	Vertical	159	305	74.0	-2.6	Pass
3	5356.01	15.07	3.71	34.50	53.28	Max Avg	Vertical	159	305	54.0	-0.7	Pass

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. .

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: APIN0334, APIN0335
To: FCC CFR 47 Part 15 Subpart E 15.407 (DFS Bands)
Serial #: ARUB196-U10 Rev A
Issue Date: 17th June 2016
Page: 293 of 297

RESTRICTED LOWER BAND-EDGE EMISSIONS



Variant: 802.11ac-160, Test Freq: 5530.00 MHz, Antenna: Aruba Networks Metal Sheet, Power Setting: 15.5, Duty Cycle (%): 95



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5457.56	14.25	3.80	34.30	52.35	Max Avg	Vertical	160	305	54.0	-1.7	Pass
2	5457.84	32.13	3.80	34.30	70.23	Max Peak	Vertical	160	305	74.0	-3.8	Pass
3	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
4	5460.02	27.72	3.79	34.31	52.00	Max Avg	Horizontal	153	30	68.2	-16.2	Pass
5	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

Test Notes: EUT on 150cm table powered by PDSine 9001GR POE. Power reduced to meet Band Edge Limits.

*Note 68.2 dBμV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




A.1.2.17. AP-ANT-48/20W AC80+80



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5290.00 MHz, Antenna: AP-ANT-48, Power Setting: 16, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBμV	Cable Loss	AF dB	Level dBμV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBμV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
2	5350.11	15.08	3.70	34.51	53.29	Max Avg	Vertical	162	362	54.0	-0.7	Pass
3	5351.28	34.28	3.71	34.51	72.50	Max Peak	Vertical	162	362	74.0	-1.5	Pass
4	5445.75	31.34	3.78	34.30	69.42	Max Peak	Vertical	162	362	74.0	-4.6	Pass
5	5447.35	12.39	3.78	34.30	50.48	Max Avg	Vertical	162	362	54.0	-3.5	Pass
6	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
7	5467.56	14.99	3.79	34.32	53.10	Max Avg	Horizontal	153	30	68.2*	-15.1	Pass
8	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

*Note 68.2 dBμV/m is band edge average limit for 5470 MHz per FCC 407


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED UPPER BAND-EDGE EMISSIONS

Variant: 802.11ac-80, Test Freq: 5290.00 MHz, Antenna: AP-ANT-20W, Power Setting: 18, Duty Cycle (%): 100



Num	Frequency MHz	Raw dBµV	Cable Loss	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5350.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
2	5366.23	9.91	3.71	34.34	47.96	Max Avg	Vertical	160	0	54.0	-6.0	Pass
3	5366.23	23.32	3.69	34.47	61.48	Max Peak	Vertical	160	0	74.0	-12.5	Pass
4	5447.35	4.03	3.77	34.30	42.10	Max Avg	Vertical	160	0	54.0	-11.9	Pass
5	5447.35	16.51	3.77	34.30	54.58	Max Peak	Vertical	160	0	74.0	-19.4	Pass
6	5460.00	--	--	--	--	Restricted Band	--	--	--	--	--	--
7	5465.63	7.54	3.79	34.31	45.64	Max Avg	Horizontal	153	30	68.2*	-22.6	Pass
8	5470.00	--	--	--	--	Band Edge	--	--	--	--	--	--

*Note 68.2 dBµV/m is band edge average limit for 5470 MHz per FCC 407

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

DRAFT



575 Boulder Court
Pleasanton, California 94566, USA
Tel: +1 (925) 462 0304
Fax: +1 (925) 462 0306
www.micomlabs.com

DRAFT