



RF Exposure Evaluation Declaration


FCC ID: Q9DAPIN0504505

APPLICANT: Hewlett Packard Enterprise Company


Application Type: Certification

Product: ACCESS POINT


Model No.: APIN0504, APIN0505

Trademark:  

FCC Classification: Digital Transmission System (DTS)
Unlicensed National Information Infrastructure (UNII)

Reviewed By: 

(Paddy Chen)

Approved By: 

(Chenz Ker)



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.



The test report shall not be reproduced except in full without the written approval of MRT Technology (Taiwan) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
1906TW0102-U5	Rev. 01	Initial report	07-15-2019	Invalid
1906TW0102-U5	Rev. 02	Revise the conducted power refer to OD	10-03-2019	Valid

1. PRODUCT INFORMATION

1.1. Equipment Description

Product Name:	ACCESS POINT
Model No.:	APIN0504, APIN0505
Brand Name:	  a Hewlett Packard Enterprise company
Wi-Fi Specification:	802.11a/b/g/n/ac/ax
Bluetooth Specification:	v4.2 single mode
Zigbee Specification:	802.15.4
Operating Temperature:	0 ~ 50 °C
Power Type:	AC Adapter or POE input
Operating Environment:	Indoor Use

Note: The difference between models is that EUT use different antenna and appearance, APIN0504 use some external antennas, but APIN0505 use internal antenna, other hardware and software are the same. Besides, each model has its own power parameter value.

1.2. Antenna Description

APIN0504

Antenna No.	Directionality	Frequency Band (GHz)	Model No.	Max Peak Gain (dBi)	BF Dir Gain (dBi)	CDD Dir Gain (dBi)	
						For Power	For PSD
Wi-Fi External Antenna List (2.4GHz 2*2 MIMO, 5GHz 2*2 MIMO)							
1	Omni	2.4	AP-ANT-1W	3.8	6.81	3.8	6.81
		5		5.8		8.81	5.8
2	Omni	2.4	AP-ANT-13B	2.3	5.31	2.3	5.31
		5		4.0		7.01	4.0
3	Omni	2.4	AP-ANT-19	3.0	6.01	3.0	6.01
		5		6.0		9.01	6.0
4	Omni	2.4	AP-ANT-20W	2.0	5.01	2.0	5.01
		5		2.0		5.01	2.0
5	Omni	2.4	AP-ANT-40	4.0	7.01	4.0	7.01
		5		5.0		8.01	5.0
6 (Note 3)	Directional	2.4	AP-ANT-25A	5.0	5.0	5.0	8.01
		5		5.0		5.0	5.0
7 (Note 3)	Directional	2.4	AP-ANT-28	7.5	7.5	7.5	10.51
		5		7.5		7.5	7.5
Bluetooth & ZigBee Internal Antenna							
PCB		2.4		3.3			

APIN0505

Directionality	Frequency Band (GHz)	Max Peak Gain (dBi)	BF Dir Gain (dBi)	CDD Dir Gain (dBi)	
				For Power	For PSD
Wi-Fi Internal Antenna List (2.4GHz 2*2 MIMO, 5GHz 4*4 MIMO)					
Omni	2.4	4.29	7.08	4.29	7.08
Omni	5	5.63	8.64	5.63	8.64
Bluetooth & ZigBee Internal Antenna					
PCB	2.4	3.3			

Note:

1. The EUT supports Cyclic Delay Diversity (CDD) mode, and CDD signals are correlated.
For CDD transmissions, directional gain is calculated as follows, $N_{ANT} = 2$, $N_{SS} = 1$.
If all antennas have the same gain, G_{ANT} , Directional gain = $G_{ANT} + \text{Array Gain}$, where Array Gain is as follows.
 - For power spectral density (PSD) measurements on all devices,
Array Gain = $10 \log (N_{ANT}/ N_{SS}) \text{ dB} = 3.01$;
 - For power measurements on IEEE 802.11 devices,
Array Gain = 0 dB for $N_{ANT} \leq 4$;
2. The EUT also supports Beam Forming mode, and the Beam Forming support 802.11n/ac/ax, not include 802.11a/b/g. Directional gain = $G_{ANT} + \text{BF Gain}$, BF Gain was declared by the applicant.
3. Two antennas have Cross-Polarized design, the detail see the antenna specification.

2. RF Exposure Evaluation

2.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	f/1500	6
1500-100,000	--	--	1	30

f= Frequency in MHz

Calculation Formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.2. Test Result of RF Exposure Evaluation

Product	ACCESS POINT
Test Item	RF Exposure Evaluation

Antenna Gain: Refer to clause 1.2.

Maximum EIRP for each model

Test Mode	Frequency Band (MHz)	Max Conducted Power (dBm)	Antenna Gain (dBi)	Max EIRP (dBm)
APIN0504				
BLE	2402 ~ 2480	8.00	3.3	11.30
ZigBee	2405 ~ 2480	8.00	3.3	11.30
802.11b/g/n/ax	2412 ~ 2462	22.00	2.0	24.00
802.11a/n/ac/ax	5180 ~ 5240 5745 ~ 5825	22.00	2.0	24.00
APIN0505				
BLE	2402 ~ 2480	8.00	3.3	11.30
ZigBee	2405 ~ 2480	8.00	3.3	11.30
802.11b/g/n/ax	2412 ~ 2462	22.00	4.29	26.29
802.11a/n/ac/ax	5180 ~ 5240 5745 ~ 5825	22.00	5.63	27.63

Note: Turn-up power from operation description was taken into account for above max conducted power.

APIN0504

Test Mode	Frequency Band (MHz)	Maximum EIRP (dBm)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)
BLE	2402 ~ 2480	11.30	0.0027	1
ZigBee	2405 ~ 2480	11.30	0.0027	1
802.11b/g/n/ax	2412 ~ 2462	24.00	0.0500	1
802.11a/n/ac/ax	5180 ~ 5240 5745 ~ 5825	24.00	0.0500	1

CONCLUSION:

Both of the WLAN 2.4GHz Band, WLAN 5GHz Band, BLE or ZigBee Band can transmit simultaneously.

So the simultaneous combined power density ratio at R (20 cm) = $0.0027 / 1 + 0.0500 / 1 + 0.0500 / 1 = 0.1027 < 1$.

Therefore, the Min Safety Distance is 20cm.

APIN0505

Test Mode	Frequency Band (MHz)	Maximum EIRP (dBm)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)
BLE	2402 ~ 2480	11.30	0.0027	1
ZigBee	2405 ~ 2480	11.30	0.0027	1
802.11b/g/n/ax	2412 ~ 2462	26.29	0.0847	1
802.11a/n/ac/ax	5180 ~ 5240 5745 ~ 5825	27.63	0.1153	1

CONCLUSION:

Both of the WLAN 2.4GHz Band, WLAN 5GHz Band, BLE or ZigBee band can transmit simultaneously.

So the simultaneous combined power density ratio at R (20 cm) = $0.0027 / 1 + 0.0847 / 1 + 0.1153 / 1 = 0.2027 < 1$.

Therefore, the Min Safety Distance is 20cm.

————— The End —————

Appendix A - EUT Photograph

Refer to "1906TW0102-UE" file.