


802.11ac-VHT20 Power Spectral Density – Ant 2

Channel 100 (5500MHz)




Channel 116 (5580MHz)




Channel 140 (5700MHz)




Channel 144 (5720MHz)



Channel 149 (5745MHz)



Channel 157 (5785MHz)




802.11ac-VHT20 Power Spectral Density – Ant 2

Channel 165 (5825MHz)




802.11ax-HE20 Power Spectral Density – Ant 2


Channel 36 (5180MHz)




Channel 44 (5220MHz)




Channel 48 (5240MHz)




Channel 52 (5260MHz)



Channel 60 (5300MHz)




Channel 64 (5320MHz)




802.11ax-HE20 Power Spectral Density – Ant 2


Channel 100 (5500MHz)




Channel 116 (5580MHz)




Channel 140 (5700MHz)




Channel 144 (5720MHz)



Channel 149 (5745MHz)




Channel 157 (5785MHz)




802.11ax-HE20 Power Spectral Density – Ant 2

Channel 165 (5825MHz)




802.11a Power Spectral Density – Ant 3


Channel 36 (5180MHz)




Channel 44 (5220MHz)




Channel 48 (5240MHz)




Channel 52 (5260MHz)




Channel 60 (5300MHz)



Channel 64 (5320MHz)




802.11a Power Spectral Density – Ant 3



802.11a Power Spectral Density – Ant 3

Channel 165 (5825MHz)




802.11ac-VHT20 Power Spectral Density – Ant 3


Channel 36 (5180MHz)



Channel 44 (5220MHz)



Channel 48 (5240MHz)




Channel 52 (5260MHz)



Channel 60 (5300MHz)




Channel 64 (5320MHz)




802.11ac-VHT20 Power Spectral Density – Ant 3


Channel 100 (5500MHz)




Channel 116 (5580MHz)




Channel 140 (5700MHz)




Channel 144 (5720MHz)



Channel 149 (5745MHz)




Channel 157 (5785MHz)



802.11ac-VHT20 Power Spectral Density – Ant 3

Channel 165 (5825MHz)




802.11ax-HE20 Power Spectral Density – Ant 3


Channel 36 (5180MHz)




Channel 44 (5220MHz)




Channel 48 (5240MHz)



Channel 52 (5260MHz)



Channel 60 (5300MHz)




Channel 64 (5320MHz)




802.11ax-HE20 Power Spectral Density – Ant 3


Channel 100 (5500MHz)




Channel 116 (5580MHz)




Channel 140 (5700MHz)




Channel 144 (5720MHz)



Channel 149 (5745MHz)




Channel 157 (5785MHz)



802.11ax-HE20 Power Spectral Density – Ant 3

Channel 165 (5825MHz)



7.6. Frequency Stability Measurement

7.6.1. Test Limit

Manufactures of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

The transmitter center frequency tolerance shall be ± 20 ppm maximum for the 5GHz band (IEEE 802.11 specification).

7.6.2. Test Procedure Used

Frequency Stability Under Temperature Variations:


The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20°C operating frequency as reference frequency. Turn EUT off and set the chamber temperature to highest. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10°C decreased per stage until the lowest temperature reached.

Frequency Stability Under Voltage Variations:

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation ($\pm 15\%$) and endpoint, record the maximum frequency change.

7.6.3. Test Setup



7.6.4.Test Result

Product	ACCESS POINT	Temperature	23°C
Test Engineer	Eric Lin	Relative Humidity	41%
Test Site	SR2	Test Date	2022/06/07
Test Mode	5180MHz (Carrier Mode)		

Voltage (%)	Power (VAC)	Temp (°C)	Frequency Tolerance (ppm)			
			0 minutes	2 minutes	5 minutes	10 minutes
100	120	- 30	9.24	9.23	9.23	9.24
		- 20	10.37	10.36	10.36	10.36
		- 10	9.73	9.72	9.71	9.70
		0	7.52	7.52	7.52	7.51
		+ 10	5.24	5.19	5.15	5.12
		+ 20	1.60	1.61	1.61	1.60
		+ 30	-0.78	-0.79	-0.80	-0.81
		+ 40	-2.96	-2.96	-2.97	-2.98
		+ 50	-3.40	-3.39	-3.40	-3.41
115	138	+ 20	2.19	2.24	2.23	2.21
85	102	+ 20	2.46	2.34	2.31	2.29

Note: Frequency Tolerance (ppm) = $\frac{[Measured\ Frequency\ (Hz) - Declared\ Frequency\ (Hz)]}{Declared\ Frequency\ (Hz)} * 10^6$.

7.7. Radiated Spurious Emission Measurement

7.7.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [uV/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

7.7.2. Test Procedure Used

KDB 789033 D02v02r01 – Section G

7.7.3. Test Setting

Table 1 - RBW as a function of frequency

Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
>1000 MHz	1 MHz

Quasi-Peak Measurements below 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1MHz
3. RBW = as specified in Table 1
4. Detector = CISPR quasi-peak
5. Sweep time = auto couple
6. Trace was allowed to stabilize

Peak Measurements above 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Average Measurements above 1GHz (Method VB)

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW; If the EUT is configured to transmit with duty cycle $\geq 98\%$, set VBW = 10 Hz.

If the EUT duty cycle is $< 98\%$, set $VBW \geq 1/T$. T is the minimum transmission duration.

802.11a	VBW = 510Hz	802.11ax-HE20	VBW = 680Hz
802.11ac-VHT20	VBW = 560Hz	802.11ax-HE40	VBW = 1300Hz
802.11ac-VHT40	VBW = 1100Hz	802.11ax-HE80	VBW = 2700Hz
802.11ac-VHT80	VBW = 2200Hz	802.11ax-HE160	VBW = 4300Hz


4. Detector = Peak
5. Sweep time = auto

6. Trace mode = max hold


7. Trace was allowed to stabilize

7.7.4. Test Setup

Below 1GHz Test Setup:




Above 1GHz Test Setup:



7.7.5.Test Result

Akoustic (Path C _ Partial Path)

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Horizontal	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11a at Channel 5180MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Remark (QP/PK/AV)
1	10358.500	26.74	18.00	44.74	-23.46	68.20	Peak
2	11956.500	26.79	19.02	45.81	-28.19	74.00	Peak
3	* 13537.500	25.47	21.90	47.37	-20.83	68.20	Peak
4	15756.000	27.88	20.72	48.60	-25.40	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Pre-amplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Vertical	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11a at Channel 5180MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	10078.000	28.26	16.87	45.14	-23.06	68.20	Peak
2	11055.500	25.71	19.37	45.08	-28.92	74.00	Peak
3	* 14217.500	25.93	22.44	48.37	-19.83	68.20	Peak
4	15526.500	29.17	21.28	50.45	-23.55	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Horizontal	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11a at Channel 5220MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Remark (QP/PK/AV)
1	10358.500	26.74	18.00	44.74	-23.46	68.20	Peak
2	11956.500	26.79	19.02	45.81	-28.19	74.00	Peak
3	* 13537.500	25.47	21.90	47.37	-20.83	68.20	Peak
4	15756.000	27.88	20.72	48.60	-25.40	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Vertical	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11a at Channel 5220MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	9848.500	27.84	16.31	44.15	-24.05	68.20	Peak
2	10919.500	26.23	19.17	45.40	-28.60	74.00	Peak
3	14064.500	24.89	22.42	47.31	-20.89	68.20	Peak
4	15713.500	30.56	20.82	51.38	-22.62	74.00	Peak
5	* 15713.500	19.84	20.82	40.66	-13.34	54.00	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Horizontal	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11a at Channel 5240MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Remark (QP/PK/AV)
1	9925.000	28.10	16.43	44.54	-23.66	68.20	Peak
2	11404.000	25.31	19.90	45.21	-28.79	74.00	Peak
3	14200.500	24.74	22.43	47.18	-21.02	68.20	Peak
4	15654.000	30.63	20.97	51.60	-22.40	74.00	Peak
5	* 15654.000	20.32	20.97	41.29	-12.71	54.00	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Vertical	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11a at Channel 5240MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Remark (QP/PK/AV)
1	10299.000	26.85	17.76	44.61	-23.59	68.20	Peak
2	11812.000	24.71	19.34	44.05	-29.95	74.00	Peak
3	* 14226.000	24.65	22.44	47.09	-21.11	68.20	Peak
4	15662.500	28.37	20.95	49.32	-24.68	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Horizontal	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11a at Channel 5260MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	10299.000	26.89	17.76	44.65	-23.55	68.20	Peak
2	11149.000	25.33	19.51	44.84	-29.16	74.00	Peak
3	* 13818.000	24.95	22.21	47.16	-21.04	68.20	Peak
4	15781.500	30.17	20.65	50.82	-23.18	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Vertical	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11a at Channel 5260MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Remark (QP/PK/AV)
1	10316.000	26.83	17.83	44.66	-23.54	68.20	Peak
2	11837.500	25.79	19.29	45.08	-28.92	74.00	Peak
3	* 14217.500	24.48	22.44	46.92	-21.28	68.20	Peak
4	15781.500	29.48	20.65	50.13	-23.87	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Horizontal	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11a at Channel 5300MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Remark (QP/PK/AV)
1	10307.500	26.68	17.80	44.48	-23.72	68.20	Peak
2	12007.500	25.77	18.91	44.68	-29.32	74.00	Peak
3	* 14141.000	24.94	22.43	47.37	-20.83	68.20	Peak
4	15900.500	30.48	20.36	50.84	-23.16	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Vertical	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11a at Channel 5300MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Remark (QP/PK/AV)
1	9627.500	29.22	15.93	45.15	-23.05	68.20	Peak
2	10868.500	26.23	19.09	45.32	-28.68	74.00	Peak
3	* 14404.500	24.45	22.45	46.90	-21.30	68.20	Peak
4	15747.500	27.77	20.74	48.51	-25.49	74.00	Peak

Note:

- "*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
- Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Horizontal	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11a at Channel 5320MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Remark (QP/PK/AV)
1	10171.500	26.99	17.25	44.24	-23.96	68.20	Peak
2	11880.000	26.07	19.19	45.26	-28.74	74.00	Peak
3	* 14294.000	24.43	22.44	46.87	-21.33	68.20	Peak
4	15951.500	30.13	20.23	50.36	-23.64	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Vertical	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11a at Channel 5320MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Remark (QP/PK/AV)
1	9984.500	27.89	16.53	44.42	-23.78	68.20	Peak
2	11591.000	24.94	19.84	44.78	-29.22	74.00	Peak
3	* 14132.500	26.04	22.43	48.47	-19.73	68.20	Peak
4	15756.000	28.21	20.72	48.93	-25.07	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Horizontal	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11a at Channel 5500MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	10086.500	27.30	16.91	44.21	-23.99	68.20	Peak
2	12024.500	26.01	18.89	44.90	-29.10	74.00	Peak
3	* 14056.000	24.81	22.42	47.23	-20.97	68.20	Peak
4	15832.500	28.74	20.53	49.27	-24.73	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Vertical	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11a at Channel 5500MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Remark (QP/PK/AV)
1	10180.000	27.32	17.28	44.60	-23.60	68.20	Peak
2	10715.500	26.56	18.88	45.44	-28.56	74.00	Peak
3	* 13903.000	25.17	22.31	47.48	-20.72	68.20	Peak
4	15849.500	27.88	20.48	48.36	-25.64	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Horizontal	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11a at Channel 5580MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Remark (QP/PK/AV)
1	9967.500	27.60	16.51	44.10	-24.10	68.20	Peak
2	11157.500	25.65	19.52	45.17	-28.83	74.00	Peak
3	* 13724.500	25.58	22.11	47.69	-20.51	68.20	Peak
4	15722.000	27.71	20.80	48.51	-25.49	74.00	Peak

Note:

- " *", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
- Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Vertical	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11a at Channel 5580MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Remark (QP/PK/AV)
1	10205.500	27.86	17.39	45.25	-22.95	68.20	Peak
2	12169.000	26.58	18.75	45.33	-28.67	74.00	Peak
3	* 14319.500	25.08	22.44	47.52	-20.68	68.20	Peak
4	15815.500	27.63	20.57	48.20	-25.80	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Horizontal	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11a at Channel 5700MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Remark (QP/PK/AV)
1	9789.000	28.53	16.21	44.73	-23.47	68.20	Peak
2	10894.000	26.02	19.13	45.15	-28.85	74.00	Peak
3	* 13775.500	25.33	22.17	47.50	-20.70	68.20	Peak
4	15832.500	29.06	20.53	49.59	-24.41	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Vertical	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11a at Channel 5700MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	10180.000	26.63	17.28	43.92	-24.28	68.20	Peak
2	10894.000	25.97	19.13	45.10	-28.90	74.00	Peak
3	* 13886.000	24.96	22.29	47.26	-20.94	68.20	Peak
4	15662.500	28.63	20.95	49.58	-24.42	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Horizontal	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11a at Channel 5720MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	10265.000	26.82	17.63	44.45	-23.75	68.20	Peak
2	11914.000	25.61	19.11	44.72	-29.28	74.00	Peak
3	* 13911.500	24.37	22.32	46.69	-21.51	68.20	Peak
4	15739.000	28.32	20.76	49.08	-24.92	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Vertical	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11a at Channel 5720MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Remark (QP/PK/AV)
1	9602.000	28.75	15.89	44.64	-23.56	68.20	Peak
2	10868.500	25.56	19.09	44.65	-29.35	74.00	Peak
3	* 13962.500	25.00	22.38	47.38	-20.82	68.20	Peak
4	15747.500	27.76	20.74	48.50	-25.50	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Horizontal	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11a at Channel 5745MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	10197.000	26.59	17.35	43.94	-24.26	68.20	Peak
2	11684.500	25.18	19.63	44.81	-29.19	74.00	Peak
3	* 14268.500	25.53	22.44	47.97	-20.23	68.20	Peak
4	15832.500	27.99	20.53	48.52	-25.48	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Vertical	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11a at Channel 5745MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Remark (QP/PK/AV)
1	10316.000	25.96	17.83	43.79	-24.41	68.20	Peak
2	11939.500	26.36	19.06	45.42	-28.58	74.00	Peak
3	* 14226.000	25.53	22.44	47.96	-20.24	68.20	Peak
4	15671.000	28.10	20.93	49.03	-24.97	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Horizontal	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11a at Channel 5785MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	9627.500	28.06	15.93	43.99	-24.21	68.20	Peak
2	12075.500	26.35	18.84	45.19	-28.81	74.00	Peak
3	* 14404.500	24.55	22.45	47.00	-21.20	68.20	Peak
4	15858.000	27.34	20.46	47.80	-26.20	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Vertical	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11a at Channel 5785MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	10205.500	26.79	17.39	44.18	-24.02	68.20	Peak
2	11786.500	25.73	19.40	45.13	-28.87	74.00	Peak
3	* 14090.000	24.64	22.43	47.07	-21.13	68.20	Peak
4	15815.500	27.92	20.57	48.49	-25.51	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Horizontal	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11a at Channel 5825MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Remark (QP/PK/AV)
1	9789.000	27.88	16.21	44.09	-24.11	68.20	Peak
2	11701.500	24.14	19.59	43.73	-30.27	74.00	Peak
3	15747.500	27.54	20.74	48.28	-25.72	74.00	Peak
4	* 17473.000	34.45	27.66	62.11	-6.09	68.20	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Vertical	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11a at Channel 5825MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Remark (QP/PK/AV)
1	9950.500	27.53	16.48	44.01	-24.19	68.20	Peak
2	11616.500	24.87	19.79	44.66	-29.34	74.00	Peak
3	15824.000	28.01	20.55	48.56	-25.44	74.00	Peak
4	* 17473.000	30.39	27.66	58.05	-10.15	68.20	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Horizontal	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT20 at Channel 5180MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	9746.500	27.91	16.13	44.04	-24.16	68.20	Peak
2	11038.500	25.39	19.34	44.73	-29.27	74.00	Peak
3	* 14115.500	24.96	22.43	47.38	-20.82	68.20	Peak
4	15543.500	28.66	21.24	49.90	-24.10	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Pre-amplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Vertical	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT20 at Channel 5180MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	10367.000	26.22	18.04	44.25	-23.95	68.20	Peak
2	11616.500	24.31	19.79	44.10	-29.90	74.00	Peak
3	* 14311.000	24.88	22.44	47.32	-20.88	68.20	Peak
4	15824.000	28.34	20.55	48.89	-25.11	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Horizontal	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT20 at Channel 5220MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	10197.000	27.12	17.35	44.47	-23.73	68.20	Peak
2	11599.500	24.01	19.83	43.84	-30.16	74.00	Peak
3	13554.500	25.53	21.92	47.44	-20.76	68.20	Peak
4	15654.000	30.63	20.97	51.60	-22.40	74.00	Peak
5	* 15654.000	20.72	20.97	41.69	-12.31	54.00	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Vertical	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT20 at Channel 5220MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	9976.000	28.05	16.52	44.57	-23.63	68.20	Peak
2	10851.500	25.35	19.07	44.42	-29.58	74.00	Peak
3	14209.000	24.65	22.43	47.08	-21.12	68.20	Peak
4	15662.500	31.30	20.95	52.25	-21.75	74.00	Peak
5	* 15662.500	20.88	20.95	41.83	-12.17	54.00	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Horizontal	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT20 at Channel 5240MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	10290.500	26.65	17.73	44.37	-23.83	68.20	Peak
2	12101.000	26.63	18.82	45.45	-28.55	74.00	Peak
3	* 13741.500	25.00	22.13	47.13	-21.07	68.20	Peak
4	15713.500	30.07	20.82	50.89	-23.11	74.00	Peak

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
- Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Vertical	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT20 at Channel 5240MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	10265.000	26.93	17.63	44.56	-23.64	68.20	Peak
2	10970.500	25.29	19.24	44.53	-29.47	74.00	Peak
3	* 13741.500	25.41	22.13	47.54	-20.66	68.20	Peak
4	15722.000	29.72	20.80	50.52	-23.48	74.00	Peak

Note:

- " *", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
- Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Horizontal	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT20 at Channel 5260MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	10503.000	25.43	18.57	44.00	-24.20	68.20	Peak
2	11914.000	24.92	19.11	44.03	-29.97	74.00	Peak
3	* 14268.500	24.63	22.44	47.07	-21.13	68.20	Peak
4	15773.000	29.61	20.67	50.28	-23.72	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Vertical	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT20 at Channel 5260MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	10486.000	25.76	18.51	44.28	-23.92	68.20	Peak
2	11897.000	25.54	19.15	44.69	-29.31	74.00	Peak
3	* 14302.500	24.49	22.44	46.93	-21.27	68.20	Peak
4	15739.000	27.03	20.76	47.79	-26.21	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Horizontal	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT20 at Channel 5300MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	9636.000	28.98	15.95	44.93	-23.27	68.20	Peak
2	11803.500	25.37	19.36	44.73	-29.27	74.00	Peak
3	* 13877.500	24.62	22.28	46.90	-21.30	68.20	Peak
4	15900.500	29.41	20.36	49.77	-24.23	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Pre-amplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Vertical	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT20 at Channel 5300MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	9636.000	28.98	15.95	44.93	-23.27	68.20	Peak
2	11225.500	25.50	19.63	45.13	-28.87	74.00	Peak
3	* 14294.000	25.28	22.44	47.72	-20.48	68.20	Peak
4	15900.500	29.41	20.36	49.77	-24.23	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Pre-amplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Horizontal	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT20 at Channel 5320MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	10112.000	26.74	17.01	43.75	-24.45	68.20	Peak
2	12279.500	27.44	18.63	46.07	-27.93	74.00	Peak
3	* 14387.500	25.30	22.45	47.75	-20.45	68.20	Peak
4	15951.500	28.76	20.23	48.99	-25.01	74.00	Peak

Note:

- " *", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
- Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Vertical	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT20 at Channel 5320MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	9610.500	28.41	15.91	44.32	-23.88	68.20	Peak
2	10962.000	25.22	19.23	44.45	-29.55	74.00	Peak
3	* 14115.500	24.98	22.43	47.41	-20.79	68.20	Peak
4	15824.000	28.33	20.55	48.88	-25.12	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Pre-amplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Horizontal	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT20 at Channel 5500MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	9772.000	29.02	16.18	45.19	-23.01	68.20	Peak
2	11582.500	25.23	19.86	45.09	-28.91	74.00	Peak
3	* 13639.500	25.46	22.01	47.47	-20.73	68.20	Peak
4	15815.500	27.85	20.57	48.42	-25.58	74.00	Peak

Note:

- " *", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Pre-amplifier(dB).
- Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Vertical	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT20 at Channel 5500MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	10401.000	26.51	18.17	44.68	-23.52	68.20	Peak
2	11387.000	24.75	19.88	44.63	-29.37	74.00	Peak
3	* 14226.000	24.74	22.44	47.18	-21.02	68.20	Peak
4	15552.000	27.34	21.22	48.56	-25.44	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Horizontal	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT20 at Channel 5580MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	10103.500	27.43	16.98	44.41	-23.79	68.20	Peak
2	11489.000	24.63	20.03	44.66	-29.34	74.00	Peak
3	* 14251.500	24.89	22.44	47.33	-20.87	68.20	Peak
4	15858.000	28.47	20.46	48.93	-25.07	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Pre-amplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Vertical	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT20 at Channel 5580MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	8403.500	29.73	13.61	43.34	-30.66	74.00	Peak
2	11404.000	25.08	19.90	44.98	-29.02	74.00	Peak
3	* 15824.000	28.19	20.55	48.74	-25.26	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Pre-amplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Horizontal	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT20 at Channel 5700MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	10120.500	26.92	17.04	43.96	-24.24	68.20	Peak
2	11149.000	24.90	19.51	44.41	-29.59	74.00	Peak
3	* 13835.000	25.03	22.23	47.26	-20.94	68.20	Peak
4	15662.500	28.10	20.95	49.05	-24.95	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Pre-amplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Vertical	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT20 at Channel 5700MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	9942.000	28.30	16.46	44.76	-23.44	68.20	Peak
2	10868.500	26.02	19.09	45.11	-28.89	74.00	Peak
3	* 14039.000	25.23	22.42	47.65	-20.55	68.20	Peak
4	15739.000	27.84	20.76	48.60	-25.40	74.00	Peak

Note:

- " *", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Pre-amplifier(dB).
- Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Horizontal	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT20 at Channel 5720MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	10197.000	27.28	17.35	44.63	-23.57	68.20	Peak
2	11565.500	24.27	19.90	44.17	-29.83	74.00	Peak
3	* 14217.500	25.42	22.44	47.86	-20.34	68.20	Peak
4	15968.500	28.74	20.19	48.93	-25.07	74.00	Peak

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Pre-amplifier(dB).
- Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Vertical	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT20 at Channel 5720MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	9831.500	28.52	16.28	44.80	-23.40	68.20	Peak
2	11650.500	24.81	19.71	44.52	-29.48	74.00	Peak
3	* 14047.500	25.48	22.42	47.91	-20.29	68.20	Peak
4	15917.500	28.81	20.31	49.12	-24.88	74.00	Peak

Note:

- " *", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
- Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Horizontal	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT20 at Channel 5745MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	9661.500	28.77	15.99	44.76	-23.44	68.20	Peak
2	11463.500	24.47	19.99	44.46	-29.54	74.00	Peak
3	* 13869.000	24.95	22.27	47.22	-20.98	68.20	Peak
4	15824.000	28.20	20.55	48.75	-25.25	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Pre-amplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Vertical	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT20 at Channel 5745MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	9763.500	28.45	16.16	44.61	-23.59	68.20	Peak
2	11931.000	25.46	19.08	44.54	-29.46	74.00	Peak
3	* 14132.500	25.05	22.43	47.48	-20.72	68.20	Peak
4	15858.000	27.90	20.46	48.36	-25.64	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Pre-amplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Horizontal	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT20 at Channel 5785MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	10384.000	26.40	18.10	44.50	-23.70	68.20	Peak
2	12143.500	26.47	18.77	45.24	-28.76	74.00	Peak
3	* 13741.500	24.98	22.13	47.11	-21.09	68.20	Peak
4	15756.000	27.37	20.72	48.09	-25.91	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Pre-amplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Vertical	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT20 at Channel 5785MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	10350.000	25.83	17.97	43.80	-24.40	68.20	Peak
2	11710.000	25.88	19.58	45.46	-28.54	74.00	Peak
3	* 14056.000	24.79	22.42	47.21	-20.99	68.20	Peak
4	15824.000	28.02	20.55	48.57	-25.43	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Horizontal	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT20 at Channel 5825MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	10214.000	27.21	17.42	44.63	-23.57	68.20	Peak
2	12024.500	25.46	18.89	44.35	-29.65	74.00	Peak
3	* 14302.500	24.50	22.44	46.95	-21.25	68.20	Peak
4	15628.500	27.22	21.03	48.25	-25.75	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Vertical	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT20 at Channel 5825MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	9950.500	28.20	16.48	44.68	-23.52	68.20	Peak
2	12007.500	25.48	18.91	44.39	-29.61	74.00	Peak
3	* 14311.000	24.94	22.44	47.38	-20.82	68.20	Peak
4	15849.500	27.64	20.48	48.12	-25.88	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Horizontal	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT40 at Channel 5190MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	9687.000	28.52	16.03	44.56	-23.64	68.20	Peak
2	10826.000	25.64	19.03	44.67	-29.33	74.00	Peak
3	* 14243.000	24.70	22.44	47.14	-21.06	68.20	Peak
4	15645.500	27.85	20.99	48.84	-25.16	74.00	Peak

Note:

- " *", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Pre-amplifier(dB).
- Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Vertical	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT40 at Channel 5190MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	9704.000	28.44	16.06	44.50	-23.70	68.20	Peak
2	12262.500	25.64	18.65	44.29	-29.71	74.00	Peak
3	* 14022.000	24.60	22.42	47.02	-21.18	68.20	Peak
4	15764.500	27.45	20.69	48.14	-25.86	74.00	Peak

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Pre-amplifier(dB).
- Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Horizontal	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT40 at Channel 5230MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	9559.500	28.67	15.82	44.49	-23.71	68.20	Peak
2	11480.500	24.24	20.02	44.26	-29.74	74.00	Peak
3	* 14200.500	25.02	22.43	47.46	-20.74	68.20	Peak
4	15696.500	28.85	20.86	49.71	-24.29	74.00	Peak

Note:

- " *", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
- Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Vertical	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT40 at Channel 5230MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	10316.000	26.97	17.83	44.80	-23.40	68.20	Peak
2	11684.500	25.05	19.63	44.68	-29.32	74.00	Peak
3	* 13843.500	26.01	22.24	48.25	-19.95	68.20	Peak
4	15679.500	29.18	20.90	50.08	-23.92	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Horizontal	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT40 at Channel 5270MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	9916.500	27.93	16.42	44.35	-23.85	68.20	Peak
2	12330.500	26.28	18.58	44.86	-29.14	74.00	Peak
3	* 14030.500	24.88	22.42	47.30	-20.90	68.20	Peak
4	15824.000	29.50	20.55	50.05	-23.95	74.00	Peak

Note:

- " *", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Pre-amplifier(dB).
- Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Vertical	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT40 at Channel 5270MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	9568.000	28.09	15.83	43.92	-24.28	68.20	Peak
2	12160.500	26.11	18.75	44.86	-29.14	74.00	Peak
3	* 14294.000	24.71	22.44	47.15	-21.05	68.20	Peak
4	15807.000	29.85	20.59	50.44	-23.56	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Horizontal	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT40 at Channel 5310MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	9908.000	27.64	16.41	44.04	-24.16	68.20	Peak
2	11565.500	24.22	19.90	44.12	-29.88	74.00	Peak
3	* 13996.500	24.55	22.42	46.96	-21.24	68.20	Peak
4	15934.500	29.31	20.27	49.58	-24.42	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Pre-amplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Vertical	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT40 at Channel 5310MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	10290.500	26.26	17.73	43.98	-24.22	68.20	Peak
2	11914.000	24.77	19.11	43.88	-30.12	74.00	Peak
3	* 14302.500	25.27	22.44	47.71	-20.49	68.20	Peak
4	15943.000	28.75	20.25	49.00	-25.00	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Pre-amplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Horizontal	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT40 at Channel 5510MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	10027.000	27.04	16.67	43.71	-24.49	68.20	Peak
2	12101.000	25.64	18.82	44.46	-29.54	74.00	Peak
3	* 13988.000	24.79	22.41	47.20	-21.00	68.20	Peak
4	15917.500	29.68	20.31	49.99	-24.01	74.00	Peak

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Pre-amplifier(dB).
- Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Vertical	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT40 at Channel 5510MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	10537.000	25.27	18.62	43.90	-24.30	68.20	Peak
2	12024.500	26.07	18.89	44.96	-29.04	74.00	Peak
3	* 13945.500	24.69	22.36	47.05	-21.15	68.20	Peak
4	15934.500	27.95	20.27	48.22	-25.78	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Pre-amplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Horizontal	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT40 at Channel 5550MHz	Test Voltage	120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	9780.500	28.16	16.19	44.35	-23.85	68.20	Peak
2	12177.500	26.57	18.74	45.31	-28.69	74.00	Peak
3	* 13631.000	24.97	22.00	46.97	-21.23	68.20	Peak
4	15654.000	27.57	20.97	48.54	-25.46	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Pre-amplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).

EUT	ACCESS POINT	Date of Test	2021-11-11
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	23.2°C/52.7%
Polarity	Vertical	Site / Test Engineer	AC1/Jay Chu
Test Mode	Transmit by 802.11ac-VHT40 at Channel 5550MHz	Test Voltage	120V/60Hz



No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	10205.500	26.48	17.39	43.87	-24.33	68.20	Peak
2	11931.000	25.16	19.08	44.24	-29.76	74.00	Peak
3	* 14098.500	24.78	22.43	47.20	-21.00	68.20	Peak
4	15858.000	27.39	20.46	47.85	-26.15	74.00	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement(dBμV/m) = Reading(dBμV) + C.F (Correction Factor).