

## HPE Aruba Networking AP-ANT-340 Antenna for Indoor Access Points



### Dual-polarized tri-band 4-element low-profile down-tilt-omni antenna (RP-SMA, cabled) for indoor use

The AP-ANT-340 antenna is a tri-band, 4-element, dual-polarized low-profile down-tilt omnidirectional antenna, intended for discrete ceiling mounted applications, providing coverage for access in 2.4GHz, 5GHz and/or 6GHz concurrently.

The AP-ANT-340 mounts directly to the suspended ceiling tile.

## Specifications

### Frequency bands, ranges, and peak gains

- |          |                     |      |
|----------|---------------------|------|
| - 2.4GHz | 2.400GHz – 2.500GHz | 4dBi |
| - 5GHz   | 5.100GHz – 5.900GHz | 5dBi |
| - 6GHz   | 5.900GHz – 7.150GHz | 5dBi |

### Polarization

- Linear, Vertical

### Pattern beamwidth (3dB)

- |          |   |                          |
|----------|---|--------------------------|
| - 2.4GHz | Elevation (V): ~80 degrees (40° downtilt) | Azimuth (H): 360 degrees |
| - 5GHz   | Elevation (V): ~60 degrees (40° downtilt) | Azimuth (H): 360 degrees |
| - 6GHz   | Elevation (V): ~40 degrees (40° downtilt) | Azimuth (H): 360 degrees |

### Input impedance

- 50 Ohms

### Maximum input power

- 2 Watts

### VSWR

- < 2.0:1

### Port isolation

- 2.4GHz            18dB

## Datasheet – HPE Aruba Networking AP-ANT-340 Antenna for Indoor Access Points

- 5GHz 18dB
- 6GHz 18dB

### Dimensions

- 177.8mm (D) x 32mm (H) (antenna itself)
- 214mm (L) x 214mm (W) x 118mm (H) (as it ships)

### Weight

- 0.4kg (antenna itself)
- 0.62kg (as it ships)

### Radome

- Material: PC/ABS, UV resistant
- Color: White

### Fly cable length& type / connector

- 75±1.8cm Plenum Rated RG58LL/ RP-SMA-Male (x4)

### Operating temperature range and relative humidity

- -40°C to +70°C (temp) TBD (humidity)

### Water and dust protection (IP rating)

- IP20

### Wind speed

- Not applicable – indoor use only

### Lightning protection

- DC short circuit

### Installation hardware


- The primary mounting method for drywall or tile flush mount uses the threaded post on the back of the antenna and supplied mounting nut. The post protrudes through the tile or drywall material and feeds the four RF cables. Alternatively, the antenna can be attached directly to a solid wall or ceiling surface using additional hardware supplied with the antenna.

### Shipping content


- Antenna, mounting hardware and instruction manual included in unit carton

## Antenna patterns (typical for all four antenna elements)


Horizontal (azimuth) plane (top view) & Vertical (elevation) planes (front/side view)




2.4GHz antenna patterns (horizontal)



2.4GHz Antenna patterns (40° downtilt horizontal)




2.4GHz antenna patterns (vertical/0)




2.4GHz antennas patterns (vertical/90)


Datasheet – HPE Aruba Networking AP-ANT-340 Antenna for Indoor Access Points




5GHz antenna patterns (horizontal)




5GHz antenna patterns (40° downtilt horizontal)




5GHz antenna patterns (vertical/0)




5GHz antennas patterns (vertical/90)




6GHz antenna patterns (horizontal)



6GHz antenna patterns (40° downtilt horizontal)




6GHz antenna patterns (vertical/0)



6GHz antennas patterns (vertical/90)

## Mechanical drawings



## Ordering information

Part number	Description
<b>HPE Aruba Networking Antennas for Indoor Access Points (RP-SMA)</b>	
<b>S1F82A</b>	HPE Aruba Networking AP-ANT-340 Cabled RP-SMA Tri-Band 4x4 Downtilt Omni Ceiling Antenna