

Company: Hewlett Packard Enterprise

MPE Evaluation of: APINH303

To: FCC CFR 47 Chapter 1 Subpart §1.1310

Report No.: HWPD85-MPE All Bands Rev A

MPE TEST REPORT



MPE TEST REPORT

FROM



MPE Evaluation of: Hewlett Packard Enterprise APINH303

To: FCC CFR 47 Chapter 1 Subpart §1.1310

Test Report Serial No.: HWPD85-MPE All Bands Rev A

This report supersedes: NONE

Applicant: Hewlett Packard Enterprise
8000 Foothills Blvd
Roseville, California 95747
USA

Product Function: 802.11 a/b/g/n/ac Wireless Access
Point

Issue Date: 27th March 2017

This Test Report is Issued Under the Authority of:

MiCOM Labs, Inc.
575 Boulder Court
Pleasanton California 94566
USA
Phone: +1 (925) 462-0304
Fax: +1 (925) 462-0306
www.micomlabs.com



MiCOM Labs is an ISO 17025 Accredited Testing Laboratory



1. MAXIMUM PERMISSIBLE EXPOSURE

Calculations for Maximum Permissible Exposure Levels

Power Density = Pd (mW/cm²) = EIRP/(4*π*d²)

EIRP = P * G

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

Numeric Gain = 10 ^ (G (dBi)/10)

Because the EUT belongs to the General Population/Uncontrolled Exposure the limit of power density is 1.0 mW/cm²

These calculations represent worst case in terms of the exposure levels.

Freq. Band (MHz)	Total Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Power Density @ 20cm	Power Density Limit (mW/cm ²)	Calculated Safe Distance @ 1mW/cm ²	Minimum Separation Distance (cm)
5150.0 - 5250.0	7.6	5.75	16.78	47.64	0.055	1.00	4.67	20.00
5250.0 - 5350.0	7.6	5.75	19.40	87.10	0.100	1.00	6.32	20.00
5725.0 - 5850.0	7.6	5.75	21.38	137.40	0.157	1.00	7.93	20.00
5470.0 - 5725.0	7.6	5.75	20.16	103.75	0.119	1.00	6.89	20.00
2400.0 - 2483.5	6.2	4.17	15.10	32.36	0.027	1.00	3.28	20.00

Total Gain (dBi) = Beamforming Gain + Antenna Gain

Assessment for simultaneous operation:

Freq. Band (MHz)	Total Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Safe Distance @ 1mW/cm ²	Power Density Limit (mW/cm ²) E _{ref}	Power Density (mW/cm ²) @New Distance E _i	Summation E _i /E _{ref}
5725.0 - 5850.0	7.6	5.75	21.38	137.40	20	1.00	0.157	0.157
2400.0 - 2483.5	6.2	4.17	15.10	32.36	20	1.00	0.027	0.027
Total Evaluation:								0.184

The Total Evaluation was calculated using the formula:

$$\sum_{i=1}^n E_i / E_{ref} \leq 1$$

Where

E_i: calculated E-field Strength for transmitter

E_{ref}: E-field strength related limit

Note: for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

Specification

Maximum Permissible Exposure Limits

FCC §1.1310 Limit = 1mW / cm² from 1.310 Table 1

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



575 Boulder Court
Pleasanton, California 94566, USA
Tel: +1 (925) 462 0304
Fax: +1 (925) 462 0306
www.micomlabs.com