



RF Exposure Evaluation Declaration

FCC ID: Q9DAPINR605

Applicant: Hewlett Packard Enterprise Company

Product: ACCESS POINT

Model No.: APINR605

Brand Name:  

FCC Classification: Digital Transmission System (DTS)
Unlicensed National Information Infrastructure (NII)
15E 6GHz Low Power Indoor Access Point (6ID)

FCC Rule Part(s): FCC Part 2.1091

Result: Complies

Reviewed By:

Jame Yuan

Approved By:

Robin Wu



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2209RSU069-U8	V01	Initial Report	2023-05-20	Valid

CONTENTS

Description	Page
1. General Information	4
1.1. Applicant.....	4
1.2. Manufacturer	4
1.3. Testing Facility.....	4
1.4. Product Information	5
1.5. Antenna Details	5
1.6. Applied Standards	6
2. RF Exposure Evaluation.....	7
2.1. Test Limits	7
2.1. MPE Exemptions.....	8
2.2. Calculated Result	11

1. General Information
1.1. Applicant

Hewlett Packard Enterprise Company
 6280 America Center Drive, San Jose CA 95002, United States

1.2. Manufacturer

Hewlett Packard Enterprise Company
 6280 America Center Drive, San Jose CA 95002, United States

1.3. Testing Facility

<input checked="checked" type="checkbox"/>	Test Site – MRT Suzhou Laboratory
	Laboratory Location (Suzhou - Wuzhong) D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China
	Laboratory Location (Suzhou - SIP) 4b Building, Liando U Valley, No.200 Xingpu Rd., Shengpu Town, Suzhou Industrial Park, China
	Laboratory Accreditations
	A2LA: 3628.01 CNAS: L10551 FCC: CN1166 ISED: CN0001 VCCI: <input type="checkbox"/> R-20025 <input type="checkbox"/> G-20034 <input type="checkbox"/> C-20020 <input type="checkbox"/> T-20020 <input type="checkbox"/> R-20141 <input type="checkbox"/> G-20134 <input type="checkbox"/> C-20103 <input type="checkbox"/> T-20104
<input type="checkbox"/>	Test Site – MRT Shenzhen Laboratory
	Laboratory Location (Shenzhen) 1G, Building A, Junxiangda Building, Zhongshanyuan Road West, Nanshan District, Shenzhen, China
	Laboratory Accreditations
	A2LA: 3628.02 CNAS: L10551 FCC: CN1284 ISED: CN0105
<input type="checkbox"/>	Test Site – MRT Taiwan Laboratory
	Laboratory Location (Taiwan) No. 38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)
	Laboratory Accreditations
	TAF: L3261-190725 FCC: 291082, TW3261 ISED: TW3261

1.4. Product Information

Product Name	ACCESS POINT
Model No.	APINR605
Wi-Fi Specification	802.11a/b/g/n/ac/ax
Bluetooth Specification	v5.0 single mode, BLE only
Zigbee Specification	802.15.4
Antenna Information	Refer to section 1.5
Operating Environment	Indoor Use
Operating Temperature	0 ~ 40 °C
Power Type	AC/DC Adapter input
Accessories	
AC/DC Adapter	Model: ADP-50GR BD Input: 100 ~ 240V 1.3A 50 – 60Hz Output: 48V 1.042A 50.016W
Optional Integrated Modular	Modular Name: LTE-A Cat 12 M.2 Module Mode No.: APINCM12 Contain FCC ID: XMR201901EM12G Supported UTRA Band: 2, 4, 5 Supported E-UTRA Band: FDD Band: 2, 4, 5, 7, 12, 13, 14, 17, 25, 26, 30, 66, TDD Band: 38, 41
Note: The information of EUT was provided by the manufacturer, and the accuracy of the information shall be the responsibility of the manufacturer.	

1.5. Antenna Details

Wi-Fi

Antenna Type	Frequency Band (GHz)	Tx Paths	CDD Dir Gain (dBi)		BF Dir Gain (dBi)
			For Power	For PSD	
PIFA	2.4 ~ 2.5	2	4.4	7.4	7.4
	5.15 ~ 5.9	2	4.7	7.6	7.6
	5.9 ~ 7.2	2	4.7	7.7	7.7

Note:

- 1, The EUT supports Cyclic Delay Diversity (CDD) mode, and CDD signals are correlated.
- 2, The EUT also supports Beam Forming mode, and the Beam Forming support 802.11n/ac/ax, not include 802.11a/b/g.
3. For beamforming operation, Aruba OS automatically backs power down based on a $10\log(N)$ factor based on CDD power.
4. The detail calculation method of directional gain refer to antenna specification provided by the applicant.

Bluetooth / ZigBee

Technology	Frequency Range (MHz)	Antenna Type	Max Peak Gain (dBi)
Bluetooth / ZigBee	2400 ~ 2480	PIFA	5.1

WCDMA / LTE

Technology	Frequency Range (MHz)	Antenna Type	Max Peak Gain (dBi)
WCDMA Band 2	1850 ~ 1910	Dipole	2.7
WCDMA Band 4	1710 ~ 1755		2.7
WCDMA Band 5	824 ~ 849		2.7
LTE Band 2	1850 ~ 1910		2.7
LTE Band 4	1710 ~ 1755		2.7
LTE Band 5	824 ~ 849		2.7
LTE Band 7	2500 ~ 2570		2.7
LTE Band 12	699 ~ 716		2.7
LTE Band 13	777 ~ 787		2.7
LTE Band 14	788 ~ 798		2.7
LTE Band 17	704 ~ 716		2.7
LTE Band 25	1850 ~ 1915		2.7
LTE Band 26	814 ~ 849		2.7
LTE Band 30	2305 ~ 2315		2.7
LTE Band 38	2570 ~ 2620		2.7
LTE Band 41	2496 ~ 2690		2.7
LTE Band 66	1710 ~ 1780	2.7	

Note: 2.7dBi is the maximum peak gain from all supported frequency bands.

1.6. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 2.1091 & KDB 447498 D04 Interim General RF Exposure Guidance v01

2. RF Exposure Evaluation

2.1. Test Limits

According to FCC §1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in §1.1307(b)

Limits For Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1,500	--	--	f/300	<6
1,500-100,000	--	--	5	<6
(B) Limits for General Population/ Uncontrolled Exposures				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500	--	--	f/1500	<30
1,500-100,000	--	--	1.0	<30

f= frequency in MHz. * = Plane-wave equivalent power density.

2.1. MPE Exemptions

For single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph §1.1307(b)(2) of this section): A single RF source is exempt if:

(Option A) The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph §1.1307(b)(3)(ii)(A) of this section.

Medical implant devices may only use this exemption and that in paragraph §1.1307(b)(3)(ii)(A);

(Option B) Or the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

(Option C) Or using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical

dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

Table 1 to §1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source Frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1920R^2$
1.34-30	$3450R^2/f^2$
30-300	$3.83R^2$
300-1,500	$0.0128R^{2f}$
1,500-100,000	$19.2R^2$

For multiple RF sources: Multiple RF sources are exempt if:

(A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those in paragraph §1.1307(b)(3)(i)(A) of this section. Medical implant devices may only use this exemption and that in paragraph §1.1307(b)(3)(i)(A).

(B) in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(B) of this section for P_{th} , including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum

distance including existing evaluated transmitters.

P_i = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

$P_{th,i}$ = the exemption threshold power (P_{th}) according to paragraph §1.1307(b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i .

ERP_j = the ERP of fixed, mobile, or portable RF source j .

$ERP_{th,j}$ = exemption threshold ERP for fixed, mobile, or portable RF source j , at a distance of at least $\lambda/2\pi$ according to the applicable formula of paragraph §1.1307(b)(3)(i)(C) of this section.

Evaluated $_k$ = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

Exposure Limit $_k$ = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k , as applicable from §1.1310 of this chapter.

2.2. Calculated Result

Product	ACCESS POINT
Test Item	RF Exposure Evaluation

Test Mode	Frequency Band (MHz)	Turn-up Conducted Power (dBm)	Antenna Gain (dBi)	Max ERP (dBm)
BLE	2402 ~ 2480	7.0	5.1	9.95
ZigBee	2405 ~ 2480	7.0	5.1	9.95
802.11b/g/n/ax	2412 ~ 2462	23.0	4.4	25.25
802.11a/n/ac/ax	5180 ~ 5885	23.0	4.7	25.55
802.11ax	5955 ~ 7095	23.0	4.7	25.55
WCDMA Band 2	1850 ~ 1910	24	2.7	24.55
WCDMA Band 4	1710 ~ 1755	24	2.7	24.55
WCDMA Band 5	824 ~ 849	24	2.7	24.55
LTE Band 2	1850 ~ 1910	24.5	2.7	25.05
LTE Band 4	1710 ~ 1755	24.5	2.7	25.05
LTE Band 5	824 ~ 849	24.5	2.7	25.05
LTE Band 7	2500 ~ 2570	24.5	2.7	25.05
LTE Band 12	699 ~ 716	24.5	2.7	25.05
LTE Band 13	777 ~ 787	24.5	2.7	25.05
LTE Band 14	788 ~ 798	24.5	2.7	25.05
LTE Band 17	704 ~ 716	24.5	2.7	25.05
LTE Band 25	1850 ~ 1915	24.5	2.7	25.05
LTE Band 26	814 ~ 849	24.5	2.7	25.05
LTE Band 30	2305 ~ 2315	20.5	2.7	21.05
LTE Band 38	2570 ~ 2620	24.5	2.7	25.05
LTE Band 41	2496 ~ 2690	24.5	2.7	25.05
LTE Band 66	1710 ~ 1780	24.5	2.7	25.05

Remark:

1. The Max Conducted power was extracted from the Modular tune-up power.
2. The Max ERP (dBm) = Max Conducted Total Power (dBm) + Antenna Gain (dBi) - 2.15.
3. Tune-up power was declared by manufacturer.

For single RF source, Option B

Test Mode	Frequency Band (MHz)	R (m)	Max ERP (mW)	Threshold ERP (mW)
BLE	2402 ~ 2480	0.20	9.9	3060.0
ZigBee	2405 ~ 2480	0.20	9.9	3060.0
802.11b/g/n/ax	2412 ~ 2462	0.20	335.0	3060.0
802.11a/n/ac/ax	5180 ~ 5885	0.20	358.9	3060.0
802.11ax	5955~7095	0.20	358.9	3060.0
WCDMA Band 2	1850 ~ 1910	0.20	285.1	3060.0
WCDMA Band 4	1710 ~ 1755	0.20	285.1	3060.0
WCDMA Band 5	824 ~ 849	0.20	285.1	1681.0
LTE Band 2	1850 ~ 1910	0.20	319.9	3060.0
LTE Band 4	1710 ~ 1755	0.20	319.9	3060.0
LTE Band 5	824 ~ 849	0.20	319.9	1681.0
LTE Band 7	2500 ~ 2570	0.20	319.9	3060.0
LTE Band 12	699 ~ 716	0.20	319.9	1426.0
LTE Band 13	777 ~ 787	0.20	319.9	1585.1
LTE Band 14	788 ~ 798	0.20	319.9	1607.5
LTE Band 17	704 ~ 716	0.20	319.9	1436.2
LTE Band 25	1850 ~ 1915	0.20	319.9	3060.0
LTE Band 26	814 ~ 849	0.20	319.9	1660.6
LTE Band 30	2305 ~ 2315	0.20	127.4	3060.0
LTE Band 38	2570 ~ 2620	0.20	319.9	3060.0
LTE Band 41	2496 ~ 2690	0.20	319.9	3060.0
LTE Band 66	1710 ~ 1780	0.20	319.9	3060.0

Note: R is from user manual.

For multiple RF sources

The EUT supports Wi-Fi 2.4GHz + Wi-Fi 6GHz + IOT (BLE or Zigbee) + LTE, or Wi-Fi 2.4GHz + Wi-Fi 5GHz + IOT + LTE, or Wi-Fi 5GHz + Wi-Fi 6GHz + IOT + LTE simultaneous transmissions. The worst-case combination is Wi-Fi 5GHz + Wi-Fi 6GHz + IOT + LTE.

So the Max Simultaneous Transmission = $9.9/3060$ (IOT) + $358.9/3060$ (NII) + $358.9/3060$ (6ID) + $319.9/1426$ (PCB) = $0.4622 < 1$

Therefore, the device qualifies for RF exposure test exemption.

_____ The End _____