



## **MPE/RF EXPOSURE EVALUATION**

**FCC CFR 47 Part 1.1310**

**Report No.: HPEN155-U5\_FCC\_MPE Rev A**

**Company:** Hewlett Packard Enterprise Company

**Evaluation of:** ASIN0304

## MPE/RF EXPOSURE EVALUATION

FROM



**Company:** Hewlett Packard Enterprise Company

**Evaluation of:** ASIN0304

**To:** FCC CFR 47 Part 1.1310

**Report Serial No.:** HPEN155-U5 Draft FCC MPE

This report supersedes: NONE

**Applicant:** Hewlett Packard Enterprise Company  
3333 Scott Blvd  
Santa Clara, California 95054  
USA

**Issue Date:** 30<sup>th</sup> June 2021

### **This Report is Issued Under the Authority of:**

**MiCOM Labs, Inc.**  
575 Boulder Court  
Pleasanton California 94566  
USA  
Phone: +1 (925) 462-0304  
Fax: +1 (925) 462-0306  
[www.micomlabs.com](http://www.micomlabs.com)



**MiCOM Labs is an ISO 17025 Accredited Testing Laboratory**

### Calculations for RF Exposure Evaluation

$$\text{Power Density} = P_d (\text{W/m}^2) = \text{EIRP}/(4 \cdot \pi \cdot d^2)$$

$$\text{EIRP} = P \cdot G$$

P = Peak output power (W)

G = Antenna numeric gain (numeric)

d = Separation distance (m)

Numeric Gain =  $10^{(G \text{ (dBi)}/10)}$

Because the EUT belongs to the General Population/Uncontrolled Exposure the limit of power density is 1.0 mW/cm<sup>2</sup>

The calculations in the table below use the highest conducted power values together with the antenna gain specified for the EUT. These calculations represent worst case in terms of the exposure levels.

Antenna gains used in this assessment include Beam Forming Gain ( where applicable).

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Power Density (mW/cm <sup>2</sup> ) @ 20cm	Power Density Limit (mW/cm <sup>2</sup> )	Min Calculated safe distance for Limit (cm)
2400.0 - 2483.5 (BLE)	1.9	1.55	6.98	4.99	0.002	1.00	0.78
2400.0 - 2483.5 (Wi-Fi)	5.00	3.16	21.42	138.68	0.087	1.00	5.9
5150.0 - 5250.0	7.30	5.37	21.86	153.46	0.164	1.00	8.1
5250.0 - 5350.0	7.30	5.37	21.92	155.60	0.166	1.00	8.2
5470.0 - 5725.0	7.30	5.37	22.31	170.22	0.182	1.00	8.6
5725.0 - 5850.0	7.30	5.37	21.61	144.88	0.155	1.00	7.9

The ASIN0304 model contains a pre certified LTE radio module FCC ID XMR201906EG21G

### Licensed Frequency Bands

MPE measurement results for licensed bands was provided through 3<sup>rd</sup> Party

Test Report: SGS-CSTC HR/2019/10016E-0102 Date: 7<sup>th</sup> May 2019

### Simultaneous Operation LTE + BLE + Wi-Fi Assessment

Assessment of worst case exposure conditions with the 3 radios transmitting simultaneously.

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density Limit (mW/cm <sup>2</sup> ) E <sub>ref</sub>	Power Density (mW/cm <sup>2</sup> )	E <sub>i</sub> /E <sub>ref</sub>
2400.0 - 2483.5 (BLE)	1.9	1.55	6.98	4.99	1.00	0.002	0.002
5470.0 - 5725.0	7.30	5.37	22.31	170.22	1.00	0.182	0.182
LTE B13 779.5	4.45	2.79	27.30	537.03	0.520	0.298	0.573
<b>Summation of Ratio:</b>							<b>0.757</b>

The Total Evaluation was calculated using the formula:

$$\sum_{i=1}^n E_i / E_{ref} \leq 1$$

Where

E<sub>i</sub>: calculated E-field Strength for transmitter

E<sub>ref</sub>: E-field strength related limit

**Minimum Safe Distance = 0.20 m**

Note: for mobile or fixed location transmitters the minimum separation distance is 0.20m, even if calculations indicate the MPE distance to be less.

**Specification - RF Exposure Evaluation Limits**

The Limit is defined in Table 1 of FCC §1.1310.

**Specification - Maximum Permissible Exposure Limits**

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500	--	--	f/300	6
1,500-100,000	--	--	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500	--	--	f/1500	30
1,500-100,000	--	--	1.0	30

f = frequency in MHz \* = Plane-wave equivalent power density



575 Boulder Court  
Pleasanton, California 94566, USA  
Tel: +1 (925) 462 0304  
Fax: +1 (925) 462 0306  
[www.micomlabs.com](http://www.micomlabs.com)