



RF Exposure Evaluation Declaration

FCC ID: Q9DASIN0305

Applicant: Hewlett Packard Enterprise

Product: HPE Aruba User Experience Sensor

Model No.: ASIN0305

Trademark:  , 

FCC Classification: Digital Transmission System (DTS)
Unlicensed National Information Infrastructure (NII)
15E 6GHz Low Power Dual Client (6CD)

FCC Rule Part(s): FCC Part 2.1091

Result: Complies

Evaluation Date: 2023-08-30

Reviewed By:

Jame Yuan

Approved By:

Robin Wu



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

| Report No. | Version | Description | Issue Date | Note |
|----------------|---------|----------------|------------|-------|
| 2306RSU027-U19 | V01 | Initial Report | 2023-09-22 | Valid |
| | | | | |

CONTENTS

| Description | Page |
|--|----------|
| 1. General Information | 4 |
| 1.1. Applicant | 4 |
| 1.2. Manufacturer | 4 |
| 1.3. Testing Facility | 4 |
| 1.4. Product Information | 5 |
| 1.5. Antenna Details | 6 |
| 1.6. Applied Standards | 6 |
| 2. RF Exposure Evaluation | 7 |
| 2.1. Test Limits | 7 |
| 2.1. MPE Exemptions | 8 |
| 2.2. Calculation Result | 11 |

1. General Information

1.1. Applicant

Hewlett Packard Enterprise
 6280 America Center Drive, San Jose CA 95002, United States

1.2. Manufacturer

Hewlett Packard Enterprise
 6280 America Center Drive, San Jose CA 95002, United States

1.3. Testing Facility

| | |
|-------------------------------------|--|
| <input checked="" type="checkbox"/> | Test Site – MRT Suzhou Laboratory |
| | Laboratory Location (Suzhou - Wuzhong) D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China |
| | Laboratory Location (Suzhou - SIP) 4b Building, Liando U Valley, No.200 Xingpu Rd., Shengpu Town, Suzhou Industrial Park, China |
| | Laboratory Accreditations |
| | A2LA: 3628.01 CNAS: L10551 FCC: CN1166 ISED: CN0001 VCCI: <input type="checkbox"/> R-20025 <input type="checkbox"/> G-20034 <input type="checkbox"/> C-20020 <input type="checkbox"/> T-20020 <input type="checkbox"/> R-20141 <input type="checkbox"/> G-20134 <input type="checkbox"/> C-20103 <input type="checkbox"/> T-20104 |
| <input type="checkbox"/> | Test Site – MRT Shenzhen Laboratory |
| | Laboratory Location (Shenzhen) 1G, Building A, Junxiangda Building, Zhongshanyuan Road West, Nanshan District, Shenzhen, China |
| | Laboratory Accreditations |
| | A2LA: 3628.02 CNAS: L10551 FCC: CN1284 ISED: CN0105 |
| <input type="checkbox"/> | Test Site – MRT Taiwan Laboratory |
| | Laboratory Location (Taiwan) No. 38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) |
| | Laboratory Accreditations |
| | TAF: 3261 FCC: 291082, TW3261 ISED: TW3261 |

1.4. Product Information

| | |
|---|--|
| Product Name | HPE Aruba User Experience Sensor |
| Model No. | ASIN0305 |
| Wi-Fi Specification | 802.11a/b/g/n/ac/ax |
| Bluetooth Specification | BLE only |
| ZigBee Specification | 802.15.4 |
| Power Type | AC/DC Adapter Input |
| Operating Temperature | 0 ~ 40 °C |
| Operating Environment | Indoor Use |
| Accessories | |
| AC/DC Adapter | Model No.: WB-12G12R Input: 100-240V, 50/60Hz, 0.3A Max Output: 12.0V=1.0A 12.0W |
| Note: The information of EUT was provided by the manufacturer, and the accuracy of the information shall be the responsibility of the manufacturer. | |

1.5. Antenna Details

Wi-Fi and IoT Antenna

| Antenna Type | Frequency Band (MHz) | Tx Paths | Directional Gain (dBi) | | Beamforming Gain (dBi) |
|---|----------------------|----------|------------------------|------------|------------------------|
| | | | Uncorrelated | Correlated | |
| Wi-Fi Antennas (Radio 0) | | | | | |
| PIFA Antenna | 2400 ~ 2483.5 | 2 | 2.1 | 5.0 | 5.0 |
| | 5150 ~ 5250 | 2 | 3.5 | 6.5 | 6.5 |
| | 5250 ~ 5350 | 2 | 3.5 | 6.5 | 6.5 |
| | 5470 ~ 5725 | 2 | 3.5 | 6.3 | 6.3 |
| | 5725 ~ 5850 | 2 | 3.5 | 6.0 | 6.0 |
| | 5850 ~ 5895 | 2 | 3.6 | 6.2 | 6.2 |
| Wi-Fi Antennas (Radio 1) | | | | | |
| PIFA Antenna | 2400 ~ 2483.5 | 2 | 2.0 | 4.8 | 4.8 |
| | 5925 ~ 6425 | 2 | 2.7 | 5.5 | 5.5 |
| | 6425 ~ 6525 | 2 | 3.1 | 6.0 | 6.0 |
| | 6525 ~ 6875 | 2 | 3.1 | 6.0 | 6.0 |
| | 6875 ~ 7125 | 2 | 3.2 | 6.1 | 6.1 |
| Bluetooth / ZigBee Antenna | | | | | |
| PIFA Antenna | 2400 ~ 2483.5 | 1 | 2.3 | -- | -- |
| Note: 1, The EUT supports Cyclic Delay Diversity (CDD) mode, and CDD signals are correlated. 2, The EUT also supports Beam Forming mode, and the Beam Forming support 802.11n/ac/ax, not include 802.11a/b/g. 3, The antenna gain is from antenna report that was provided by the applicant. | | | | | |

1.6. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 2.1091 & KDB 447498 D04 Interim General RF Exposure Guidance v01

2. RF Exposure Evaluation

2.1. Test Limits

According to FCC §1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in §1.1307(b)

Limits For Maximum Permissible Exposure (MPE)

| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Average Time (Minutes) |
|---|-------------------------------|-------------------------------|-------------------------------------|------------------------|
| (A) Limits for Occupational/ Control Exposures | | | | |
| 0.3-3.0 | 614 | 1.63 | *(100) | ≤6 |
| 3.0-30 | 1842/f | 4.89/f | *(900/f ²) | <6 |
| 30-300 | 61.4 | 0.163 | 1.0 | <6 |
| 300-1,500 | -- | -- | f/300 | <6 |
| 1,500-100,000 | -- | -- | 5 | <6 |
| (B) Limits for General Population/ Uncontrolled Exposures | | | | |
| 0.3-1.34 | 614 | 1.63 | *(100) | <30 |
| 1.34-30 | 824/f | 2.19/f | *(180/f ²) | <30 |
| 30-300 | 27.5 | 0.073 | 0.2 | <30 |
| 300-1,500 | -- | -- | f/1500 | <30 |
| 1,500-100,000 | -- | -- | 1.0 | <30 |

f= frequency in MHz. * = Plane-wave equivalent power density.

2.1. MPE Exemptions

For single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph §1.1307(b)(2) of this section): A single RF source is exempt if:

(Option A) The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph §1.1307(b)(3)(ii)(A) of this section.

Medical implant devices may only use this exemption and that in paragraph §1.1307(b)(3)(ii)(A);

(Option B) Or the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

(Option C) Or using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical

dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

Table 1 to §1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

| RF Source Frequency (MHz) | Threshold ERP (watts) |
|---------------------------|-----------------------|
| 0.3-1.34 | $1920R^2$ |
| 1.34-30 | $3450R^2/f^2$ |
| 30-300 | $3.83R^2$ |
| 300-1,500 | $0.0128R^{2f}$ |
| 1,500-100,000 | $19.2R^2$ |

For multiple RF sources: Multiple RF sources are exempt if:

(A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those in paragraph §1.1307(b)(3)(i)(A) of this section. Medical implant devices may only use this exemption and that in paragraph §1.1307(b)(3)(i)(A).

(B) in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(B) of this section for P_{th} , including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum

distance including existing evaluated transmitters.

P_i = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

$P_{th,i}$ = the exemption threshold power (P_{th}) according to paragraph §1.1307(b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i .

ERP_j = the ERP of fixed, mobile, or portable RF source j .

$ERP_{th,j}$ = exemption threshold ERP for fixed, mobile, or portable RF source j , at a distance of at least $\lambda/2\pi$ according to the applicable formula of paragraph §1.1307(b)(3)(i)(C) of this section.

***Evaluated* $_k$** = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

***Exposure Limit* $_k$** = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k , as applicable from §1.1310 of this chapter.

2.2. Calculation Result

| | |
|-----------|----------------------------------|
| Product | HPE Aruba User Experience Sensor |
| Test Item | RF Exposure Evaluation |

| Test Mode | Frequency Band (MHz) | Turn-up Conducted Power (dBm) | Antenna Gain (dBi) | Max ERP (dBm) |
|-----------------|----------------------|-------------------------------|--------------------|---------------|
| BLE | 2402 ~ 2480 | 10.0 | 2.3 | 10.15 |
| ZigBee | 2405 ~ 2480 | 10.0 | 2.3 | 10.15 |
| 802.11b/g/n/ax | 2412 ~ 2462 | 23.0 | 2.1 | 22.95 |
| 802.11a/n/ac/ax | 5180 ~ 5885 | 23.0 | 3.6 | 24.45 |
| 802.11ax | 5955 ~ 7095 | 23.0 | 3.2 | 24.05 |

Remark:

1. The Max ERP (dBm) = Max Conducted Total Power (dBm) + Antenna Gain (dBi) - 2.15.
2. Tune-up power was declared by manufacturer.

For single RF source, Option B

| Test Mode | Frequency Band (MHz) | R (m) | Max ERP (mW) | Threshold ERP (mW) |
|-----------------|----------------------|-------|--------------|--------------------|
| BLE | 2402 ~ 2480 | 0.20 | 10.35 | 3060.0 |
| ZigBee | 2405 ~ 2480 | 0.20 | 10.35 | 3060.0 |
| 802.11b/g/n/ax | 2412 ~ 2462 | 0.20 | 197.24 | 3060.0 |
| 802.11a/n/ac/ax | 5180 ~ 5885 | 0.20 | 278.61 | 3060.0 |
| 802.11ax | 5955 ~ 7095 | 0.20 | 254.10 | 3060.0 |

Note: R is from user manual.

For multiple RF sources

The EUT supports Wi-Fi 2.4GHz + Wi-Fi 6GHz + IOT (BLE or Zigbee), or Wi-Fi 2.4GHz + Wi-Fi 5GHz + IOT, or Wi-Fi 5GHz + Wi-Fi 6GHz + IOT simultaneous transmissions. The worst-case combination is Wi-Fi 5GHz + Wi-Fi 6GHz + IOT.

So the Max Simultaneous Transmission = $10.35/3060$ (IOT) + $278.61/3060$ (NII) + $254.10/3060$ (6CD) = $0.1775 < 1$.

Therefore, the device qualifies for RF exposure test exemption.

_____ The End _____