

FCC §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to 1.1307 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for Maximum Permissible Exposure (MPE)

Limits for Occupational/Controlled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E , H or S (minutes)
0.3- 3.0	614	1.63	(100)*	6
3.0 - 30	1842/f	4.89/f	(900/f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6

f = frequency in MHz;

* = Plane-wave equivalent power density;

MPE Calculation

Predication of MPE limit at a given distance

$$S = PG/4\pi R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Frequency	Max Target Output Power	Duty Cycle	Antenna Cable Loss	Typical Antenna Gain		Distance	Power Density	Limit
				dB	dBi			
MHz	mW		dB	dBi	numeric	cm	mW/cm ²	mW/cm ²
450.0125	4100	50%	0	5	3.16	20	1.3	1.5

Note: The manufacturer does not specify an antenna to be used with this device, but a typical installation has a gain up to 5 dBi.

Radio Exposure Statement:

Using the parameters given in the above calculation, a minimum antenna to person distance of 20cm is required to meet the limits for occupational/controlled exposure.

Result: Compliant.

