

## Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Maximum peak output power at device output terminal: 5.34 dBm

Cable and Jumper loss: 0.0 dB

Maximum peak output power at antenna input terminal: 5.34 dBm

3.419794425 mW

Single Antenna gain (typical): 0 dBi

Number of Antennae: 1

Total Antenna gain (typical): 0 dBi  
1 (numeric)

Prediction distance: 20 cm

Prediction frequency: 2426 MHz

MPE limit for uncontrolled exposure at prediction frequency: 1 mW/cm<sup>2</sup>

**Power density at prediction frequency:** 0.000680 mW/cm<sup>2</sup>

0.006803 W/m<sup>2</sup>

Tx On time: 1.000000 ms

Tx period time: 1.000000 ms

Average Factor: 100.000000 %

Average Power density at prediction frequency: 0.006803 W/m<sup>2</sup>

Maximum allowable antenna gain: 31.67269855 dBi

**Margin of Compliance:** 31.67269855 dB