ONE WORLD OUR APPROVAL



Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density

- P = power input to the antenna
- G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Maximum peak output power at device output terminal:	<u>26.70</u> dBm
Cable and Jumper loss:	<u>0.0</u> dB
Maximum peak output power at antenna input terminal:	<u>26.70</u> dBm
	<u>467.7351413</u> mW
Single Antenna gain (typical):	<u> </u>
Number of Antennae:	<u> </u>
Total Antenna gain (typical):	<u> </u>
<u>-</u>	<u>501.1872336</u> (numeric)
Prediction distance:	<u>140</u> cm
Prediction frequency:	<u>2688.75</u> MHz
MPE limit for uncontrolled exposure at prediction frequency:	1 mW/cm ²
	<u> </u>
Power density at prediction frequency:	0.951774 mW/cm ²
Power density at prediction frequency:	0.951774 mW/cm² 9.517745 W/m ²
Power density at prediction frequency: Tx On time:	0.951774 mW/cm² 9.517745 W/m ² 1.000000 ms
Power density at prediction frequency: Tx On time: Tx period time:	0.951774 mW/cm ² 9.517745 W/m ² 1.000000 ms 1.000000 ms
Power density at prediction frequency: Tx On time: Tx period time: Average Factor:	0.951774 mW/cm ² 9.517745 W/m ² 1.000000 ms 1.000000 ms 100.000000 %
Power density at prediction frequency: Tx On time: Tx period time: Average Power density at prediction frequency:	0.951774 mW/cm ² 9.517745 W/m ² 1.000000 ms 1.000000 ms 100.000000 % 9.517745 W/m ²
Power density at prediction frequency: Tx On time: Tx period time: Average Factor: Average Power density at prediction frequency: Maximum allowable antenna gain:	0.951774 mW/cm ² 9.517745 W/m ² 1.000000 ms 1.000000 ms 100.000000 % 9.517745 W/m ² 27.21465935 dBi