



# TEST REPORT

<b>KCTL Inc.</b> 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 <a href="http://www.kctl.co.kr">www.kctl.co.kr</a>		Report No.: <b>KR20-SRF0107</b> Page (1) of (27)	
<b>1. Client</b> ◦ Name : DREAMUS COMPANY ◦ Address : 5, Bangbae-ro 18gil, Seocho-gu, Seoul, Republic of Korea ◦ Date of Receipt : 2020-04-03			
<b>2. Use of Report</b> : Class II Permissive change			
<b>3. Name of Product and Model</b> : SP2000 / PPF33			
<b>4. Manufacturer and Country of Origin</b> : DREAMUS COMPANY / Korea			
<b>5. FCC ID</b> : QDMPPF33			
<b>6. Date of Test</b> : 2020-04-10 to 2020-04-13			
<b>7. Test Standards</b> : FCC Part 15 Subpart C, 15.247			
<b>8. Test Results</b> : Refer to the test result in the test report			
Affirmation	Tested by Name : Hosung Lee		Technical Manager Name : Heesu Ahn
			2020-04-29
<b>KCTL Inc.</b>			
As a test result of the sample which was submitted from the client, this report does not guarantee the whole product quality. This test report should not be used and copied without a written agreement by KCTL Inc.			



## CONTENTS

1.	General information .....	4
2.	Device information .....	4
2.1.	Accessory information .....	5
2.2.	Frequency/channel operations.....	5
2.3.	Duty Cycle Factor .....	6
3.	Antenna requirement .....	7
4.	Summary of tests .....	7
5.	Measurement uncertainty .....	8
6.	Measurement results explanation example .....	9
7.	Test results .....	10
7.1.	Maximum peak output power.....	10
7.2.	Spurious Emission, Band Edge and Restricted bands.....	13
7.3.	AC Conducted emission .....	25
8.	Measurement equipment .....	27

## 1. General information

Client : DREAMUS COMPANY  
Address : 5, Bangbae-ro 18gil, Seocho-gu, Seoul, Republic of Korea  
Manufacturer : DREAMUS COMPANY  
Address : 5, Bangbae-ro 18gil, Seocho-gu, Seoul, Republic of Korea  
Laboratory : KCTL Inc.  
Address : 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea  
Accreditations : FCC Site Designation No: KR0040, FCC Site Registration No: 687132  
VCCI Registration No. : R-20080, G-20078, C-20059, T-20056  
Industry Canada Registration No. : 8035A  
KOLAS No.: KT231

## 2. Device information

Equipment under test : SP2000  
Model : PPF33  
Frequency range : 2 402 MHz ~ 2 480 MHz (Bluetooth(BDR/EDR))  
2 412 MHz ~ 2 462 MHz (802.11b/g/n HT20)  
2 422 MHz ~ 2 452 MHz (802.11n HT40)  
5 180 MHz ~ 5 240 MHz (802.11a/n HT20)  
5 190 MHz ~ 5 230 MHz (802.11n HT40)  
5 210 MHz (802.11ac VHT80)  
5 745 MHz ~ 5 825 MHz (802.11a/n HT20)  
5 755 MHz ~ 5 795 MHz (802.11n HT40)  
5 775 MHz (802.11ac VHT80)  
Modulation technique : GFSK,  $\pi/4$ DQPSK, 8DPSK (Bluetooth(BDR/EDR))  
DSSS, OFDM (802.11a/b/g/n(HT20/40)/ac(VHT80))  
Number of channels : 2.4 GHz: 11 ch (802.11b/g/n HT20), 7 ch (802.11n HT40)  
79 ch (Bluetooth(BDR/EDR))  
5 GHz (UNII 1): 4 ch (802.11a/n HT20)  
2 ch (802.11n HT40)  
1 ch (802.11ac VHT80)  
5.8 GHz (UNII 3): 5 ch (802.11a/n HT20)  
2 ch (802.11n HT40)  
1 ch (802.11ac VHT80)  
Power source : DC 3.8 V  
Antenna specification : Carrier LPS Antenna  
Antenna gain : -2.059 dBi (Bluetooth, WIFI 2.4 GHz), 2.054 dBi (WIFI 5 GHz)  
0.004 dBi (WIFI 5.8 GHz)  
Software version : 1.0

Hardware version : Mp  
 Test device serial No. : N/A  
 Operation temperature : 23 °C

## 2.1. Accessory information

Equipment	Manufacturer	Model	Serial No.	Power source
Battery	HYPERPOWER BATTERIES INC.	PR-596073G	-	DC 3.8 V, 3 700 mA /24 MHz

## 2.2. Frequency/channel operations

This device contains the following capabilities:

WIFI(802.11a/b/g/n(HT20/HT40)/ac(VHT80) , Bluetooth(BDR, EDR)

Ch.	Frequency (MHz)
01	2 412
⋮	⋮
07	2 437
⋮	⋮
11	2 462

Table 2.2.1. 802.11b/g/n HT20 mode

Ch.	Frequency (MHz)
03	2 422
⋮	⋮
07	2 437
⋮	⋮
09	2 452


Table 2.2.2. 802.11n HT40 mode

## 2.3. Duty Cycle Factor

Test mode	On time (ms)	Period (ms)	Duty cycle		Duty Cycle Factor (dB)
			(Linear)	(%)	
802.11 b	8.605	8.699	0.989	98.900	0.047
802.11 g	1.422	1.523	0.934	93.400	0.297
802.11 n_HT 20	1.333	1.433	0.930	93.000	0.317
802.11 n_HT 40	0.664	0.764	0.769	76.900	0.612

### Notes.

1. Duty cycle (Linear) = Ton time / Period
2. DCF(Duty cycle factor) =  $10\log(1/\text{duty cycle})$



### 3. Antenna requirement

Requirement of FCC part section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

- The transmitter has permanently attached Carrier LPS Antenna(internal antenna) on board.

### 4. Summary of tests

FCC Part section(s)	Parameter	Test results
15.247(b)(3)	Maximum peak output power	Pass
15.247(e)	Peak power spectral density	N/T <sup>(Note1)</sup>
15.247(a)(2)	6 dB channel bandwidth	N/T <sup>(Note1)</sup>
15.247(d), 15.205(a), 15.209(a)	Spurious emission	Pass
	Band-edge, restricted band	Pass
15.207(a)	Conducted emissions	Pass

**Notes:** (N/T: Not Tested, N/A: Not Applicable)

- These test item was performed. (FCC ID: QDMPPF33)  
Test Report No. KR19-SRF0069 issued on 30, May, 2019 by KCTL Inc.)
- The data from that application has been verified through appropriate spot checks to demonstrate compliance for this device as shown in the test result of section 7.
- Output power was verified to be within the expected tune up tolerances prior to performing the spot checks for radiated spurious emissions and band edge to confirm that the proposed changes to the digital circuitry had not adversely affected the previously reported values in the original filing.
- The test scenario for spot check is based on the worst-case of original report results.

## 5. Measurement uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of  $k=2$  to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded uncertainty	
Conducted RF power	1.76 dB	
Conducted spurious emissions	4.03 dB	
Radiated spurious emissions	9 kHz ~ 30 MHz:	2.28 dB
	30 MHz ~ 300 MHz	4.98 dB
	300 MHz ~ 1 000 MHz	5.14 dB
	1 GHz ~ 6 GHz	6.70 dB
	Above 6 GHz	6.60 dB
Conducted emissions	9 kHz ~ 150 kHz	3.66 dB
	150 kHz ~ 30 MHz	3.26 dB

KCTL



## 6. Measurement results explanation example

The offset level is set in the spectrum analyzer to compensate the RF cable loss factor between EUT conducted output port and spectrum analyzer.

With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Frequency (MHz)	Factor(dB)	Frequency (MHz)	Factor(dB)
30	10.05	9 000	12.01
50	10.09	10 000	12.13
100	10.15	11 000	12.10
200	10.26	12 000	12.32
300	10.32	13 000	12.43
400	10.39	14 000	12.55
500	10.43	15 000	12.72
600	10.47	16 000	12.39
700	10.54	17 000	12.77
800	10.59	18 000	12.88
900	10.60	19 000	12.96
1 000	10.64	20 000	13.11
2 000	10.92	21 000	13.08
3 000	11.12	22 000	13.17
4 000	11.34	23 000	13.17
5 000	11.51	24 000	13.33
6 000	11.65	25 000	13.40
7 000	11.71	26 000	13.48
8 000	11.92	26 500	13.59


**Note.**

Offset(dB) = RF cable loss(dB) + Attenuator(dB) + EUT cable loss(dB)

## 7. Test results

### 7.1. Maximum peak output power

#### Test setup



#### Limit

According to §15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2 400-2 483.5 MHz, and 5 725-5 850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

According to §15.247(b)(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### Test procedure

558074 D01 DTS Meas Guidance - Section 8.3, ANSI C63.10 - Section 11.9

#### Test settings

##### **General**

Section 15.247 permits the maximum conducted (average) output power to be measured as an alternative to the maximum peak conducted output power for demonstrating compliance to the limit. When this option is exercised, the measured power is to be referenced to the OBW rather than the DTS bandwidth (see ANSI C63.10 for measurement guidance).

When using a spectrum analyzer or EMI receiver to perform these measurements, it shall be capable of utilizing a number of measurement points in each sweep that is greater than or equal to twice the span/RBW to set a bin-to-bin spacing of  $\leq \text{RBW}/2$  so that narrowband signals are not lost between frequency bins.

If possible, configure or modify the operation of the EUT so that it transmits continuously at its maximum power control level. The intent is to test at 100 % duty cycle; however a small reduction in duty cycle (to no lower than 98 %) is permitted, if required by the EUT for amplitude control purposes. Manufacturers are expected to provide software to the test lab to permit such continuous operation.

If continuous transmission (or at least 98 % duty cycle) cannot be achieved due to hardware limitations (e.g., overheating), the EUT shall be operated at its maximum power control level, with

the transmit duration as long as possible, and the duty cycle as high as possible during which sweep triggering/signal gating techniques may be used to perform the measurement over the transmission duration.

### Maximum peak conducted output power

One of the following procedures may be used to determine the maximum peak conducted output power of a DTS EUT.

#### RBW $\geq$ DTS bandwidth

The following procedure shall be used when an instrument with a resolution bandwidth that is greater than the DTS bandwidth is available to perform the measurement:

- Set the RBW  $\geq$  DTS bandwidth.
- Set VBW  $\geq [3 \times \text{RBW}]$ .
- Set span  $\geq [3 \times \text{RBW}]$ .
- Sweep time = auto couple.
- Detector = peak.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use peak marker function to determine the peak amplitude level.

#### Integrated band power method

The following procedure can be used when the maximum available RBW of the instrument is less than the DTS bandwidth:

- Set the RBW = 1 MHz.
- Set the VBW  $\geq [3 \times \text{RBW}]$ .
- Set the span  $\geq [1.5 \times \text{DTS bandwidth}]$ .
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges (for some instruments, this may require a manual override to select the peak detector). If the instrument does not have a band power function, then sum the spectrum levels (in linear power units) at intervals equal to the RBW extending across the DTS channel bandwidth.

### PKPM1 Peak power meter method

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

#### Notes:

A peak responding power sensor is used, where the power sensor system video bandwidth is greater than the occupied bandwidth of the EUT.


#### Test results

Test mode	Frequency(MHz)	Measured output power(dBm)		Limit(dBm)
		Peak	Average	
802.11b	2 412	16.13	12.81	30.00
	2 437	16.38	13.00	
	2 462	16.49	13.07	
802.11g	2 412	19.3	12.49	30.00
	2 437	19.33	12.67	
	2 462	19.22	12.76	
802.11n HT20	2 412	19.66	12.55	30.00
	2 437	19.6	12.48	
	2 462	19.68	12.70	
802.11n HT40	2 422	19.21	12.13	30.00
	2 437	19.49	12.18	
	2 452	19.47	12.13	


## 7.2. Spurious Emission, Band Edge and Restricted bands

### Test setup


The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz Emissions



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 1 GHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz emissions, whichever is lower.



### Limit

According to section 15.209(a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field strength ( $\mu\text{V/m}$ )	Measurement distance (m)
0.009 - 0.490	2 400/F(kHz)	300
0.490 - 1.705	24 000/F(kHz)	30
1.705 - 30	30	30
30 - 88	100**	3
88 - 216	150**	3
216 - 960	200**	3
Above 960	500	3

\*\*Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54–72 MHz, 76–88 MHz, 174–216 MHz or 470–806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., Section 15.231 and 15.241.

According to section 15.205(a) and (b), only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.009 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
0.495 - 0.505	16.694 75 - 16.695 25	608 - 614	5.35 - 5.46
2.173 5 - 2.190 5	16.804 25 - 16.804 75	960 - 1 240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1 300 - 1 427	8.025 - 8.5
4.177 25 - 4.177 75	37.5 - 38.25	1 435 - 1 626.5	9.0 - 9.2
4.207 25 - 4.207 75	73 - 74.6	1 645.5 - 1 646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1 660 - 1 710	10.6 - 12.7
6.267 75 - 6.268 25	108 - 121.94	1 718.8 - 1 722.2	13.25 - 13.4
6.311 75 - 6.312 25	123 - 138	2 200 - 2 300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2 310 - 2 390	15.35 - 16.2
8.362 - 8.366	156.524 75 - 156.525	2 483.5 - 2 500	17.7 - 21.4
8.376 25 - 8.386 75	25	2 690 - 2 900	22.01 - 23.12
8.414 25 - 8.414 75	156.7 - 156.9	3 260 - 3 267	23.6 - 24.0
12.29 - 12.293	162.012 5 - 167.17	3 332 - 3 339	31.2 - 31.8
12.519 75 - 12.520 25	167.72 - 173.2	3 345.8 - 3 358	36.43 - 36.5
12.576 75 - 12.577 25	240 - 285	3 600 - 4 400	Above 38.6
13.36 - 13.41	322 - 335.4		

The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in section 15.209. At frequencies equal to or less than 1 000 MHz, compliance with the limits in section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1 000 MHz, compliance with the emission limits in section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in section 15.35 apply to these measurements.

**Test procedure**

ANSI C63.10-2013

KDB 558074 D01 V05r01

**Test settings****Peak field strength measurements**

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = as specified in table
3. VBW  $\geq$  (3 $\times$ RBW)
4. Detector = peak
5. Sweep time = auto
6. Trace mode = max hold
7. Allow sweeps to continue until the trace stabilizes

**Table. RBW as a function of frequency**

Frequency	RBW
9 kHz to 150 kHz	200 Hz to 300 Hz
0.15 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1 000 MHz	100 kHz to 120 kHz
> 1 000 MHz	1 MHz

**Average field strength measurements****Trace averaging with continuous EUT transmission at full power**

If the EUT can be configured or modified to transmit continuously ( $D \geq 98\%$ ), then the average emission levels shall be measured using the following method (with EUT transmitting continuously):

1. RBW = 1 MHz (unless otherwise specified).
2. VBW  $\geq$  (3 $\times$ RBW).
3. Detector = RMS (power averaging), if  $[\text{span} / (\# \text{ of points in sweep})] \leq (\text{RBW} / 2)$ . Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
4. Averaging type = power (i.e., rms):
  - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
  - 2) Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.
5. Sweep time = auto.
6. Perform a trace average of at least 100 traces.

**Trace averaging across ON and OFF times of the EUT transmissions followed by duty cycle correction**

If continuous transmission of the EUT ( $D \geq 98\%$ ) cannot be achieved and the duty cycle is constant (duty cycle variations are less than  $\pm 2\%$ ), then the following procedure shall be used:

1. The EUT shall be configured to operate at the maximum achievable duty cycle.
2. Measure the duty cycle D of the transmitter output signal as described in 11.6.
3. RBW = 1 MHz (unless otherwise specified).
4. VBW  $\geq$  [3  $\times$  RBW].
5. Detector = RMS (power averaging), if  $[\text{span} / (\# \text{ of points in sweep})] \leq (\text{RBW} / 2)$ . Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this

condition cannot be satisfied, then the detector mode shall be set to peak.

6. Averaging type = power (i.e., rms):
  - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
  - 2) Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.
7. Sweep time = auto.
8. Perform a trace average of at least 100 traces.
9. A correction factor shall be added to the measurement results prior to comparing with the emission limit to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:
  - 1) If power averaging (rms) mode was used in step f), then the applicable correction factor is  $[10 \log (1 / D)]$ , where D is the duty cycle.
  - 2) If linear voltage averaging mode was used in step f), then the applicable correction factor is  $[20 \log (1 / D)]$ , where D is the duty cycle.
  - 3) If a specific emission is demonstrated to be continuous ( $D \geq 98\%$ ) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that emission.

**Notes:**


1. Factors(dB) = Antenna factor(dB/m) + Cable loss(dB) + or Amp. gain(dB) + or  $F_d$ (dB)
2. The worst-case emissions are reported however emissions whose levels were not within 20 dB of respective limits were not reported.
3. Average test would be performed if the peak result were greater than the average limit.
4. <sup>1)</sup> means restricted band.

KCTL




**Test Plot****802.11b / Band-edge****Highest Channel**

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB( $\mu$ V))	(dB)	(dB)	(dB)	(dB( $\mu$ V/m))	(dB( $\mu$ V/m))	(dB)
<b>Peak data</b>								
2 489.56 <sup>1)</sup>	H	46.78	32.08	-29.23	-	49.63	74.00	24.37
<b>Average Data</b>								
No spurious emissions were detected within 20 dB of the limit.								

**Horizontal/Vertical for Band-edge**

**802.11b / RSE****Middle Channel**

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB( $\mu$ V))	(dB)	(dB)	(dB)	(dB( $\mu$ V/m))	(dB( $\mu$ V/m))	(dB)
<b>Peak data</b>								
4 874.33 <sup>1)</sup>	H	65.24	33.95	-55.01	-	44.18	74.00	29.82
7 311.23 <sup>1)</sup>	H	61.31	35.40	-52.69	-	44.02	74.00	29.98
<b>Average Data</b>								
No spurious emissions were detected within 20 dB of the limit.								

**Horizontal/Vertical for 3.5 GHz ~ 18 GHz**

**KCTL Inc.**


65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR20-SRF0107

Page (19) of (27)


**KCTL****802.11g / Band-edge****Highest Channel**

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB( $\mu$ V))	(dB)	(dB)	(dB)	(dB( $\mu$ V/m))	(dB( $\mu$ V/m))	(dB)
Peak data								
2 486.27 <sup>1)</sup>	H	43.89	32.07	-29.22	-	46.74	74.00	27.26
Average Data								
No spurious emissions were detected within 20 dB of the limit.								

**Horizontal/Vertical for Band-edge**


**802.11g / RSE****Middle Channel**

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
<b>Peak data</b>								
4 874.78 <sup>1)</sup>	H	63.15	33.95	-55.02	-	42.08	74.00	31.92
7 310.78 <sup>1)</sup>	V	60.29	35.40	-52.69	-	43.00	74.00	31.00
<b>Average Data</b>								
No spurious emissions were detected within 20 dB of the limit.								

**Horizontal/Vertical for 3.5 GHz ~ 18 GHz**


**802.11n HT20 / Band-edge****Highest Channel**

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB( $\mu$ V))	(dB)	(dB)	(dB)	(dB( $\mu$ V/m))	(dB( $\mu$ V/m))	(dB)
<b>Peak data</b>								
2 483.68 <sup>1)</sup>	H	44.80	32.07	-29.21	-	47.66	74.00	26.34
<b>Average Data</b>								
No spurious emissions were detected within 20 dB of the limit.								

**Horizontal/Vertical for Band-edge**

**802.11n HT20 / RSE****Highest Channel**

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB( $\mu$ V))	(dB)	(dB)	(dB)	(dB( $\mu$ V/m))	(dB( $\mu$ V/m))	(dB)
<b>Peak data</b>								
4 923.27 <sup>1)</sup>	H	61.49	33.97	-55.32	-	40.14	74.00	33.86
7 386.91 <sup>1)</sup>	H	60.97	35.40	-52.40	-	43.97	74.00	30.03
<b>Average Data</b>								
No spurious emissions were detected within 20 dB of the limit.								

**Horizontal/Vertical for 3.5 GHz ~ 18 GHz**

**KCTL Inc.**


65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR20-SRF0107

Page (23) of (27)


**802.11n HT40 / Band-edge****Highest Channel**

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
<b>Peak data</b>								
2 483.77 <sup>1)</sup>	H	46.42	32.07	-29.21	-	49.28	74.00	24.72
<b>Average Data</b>								
No spurious emissions were detected within 20 dB of the limit.								

**Horizontal/Vertical for Band-edge**

**802.11n HT40 / RSE****Middle Channel**


Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
<b>Peak data</b>								
4 873.88 <sup>1)</sup>	V	61.31	33.95	-54.99	-	40.27	74.00	33.73
7 310.78 <sup>1)</sup>	V	59.93	35.40	-52.69	-	42.64	74.00	31.36
<b>Average Data</b>								
No spurious emissions were detected within 20 dB of the limit.								

**Horizontal/Vertical for 3.5 GHz ~ 18 GHz**



### 7.3. AC Conducted emission

#### Test setup



#### Limit

According to 15.207(a), for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 $\mu$ H/50 ohm line impedance stabilization network (LISN). Compliance with the provision of this paragraph shall on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequencies ranges.

Frequency of Emission (MHz)	Conducted limit (dB $\mu$ V/m)	
	Quasi-peak	Average
0.15 – 0.50	66 - 56*	56 - 46*
0.50 – 5.00	56	46
5.00 – 30.0	60	50

#### Measurement procedure

1. The EUT was placed on a wooden table of size, 1 m by 1.5 m, raised 80 cm in which is located 40 cm away from the vertical wall and 1.5m away from the side wall of the shielded room.
2. Each current-carrying conductor of the EUT power cord was individually connected through a 50 $\Omega$ /50 $\mu$ H LISN, which is an input transducer to a spectrum analyzer or an EMI/Field Intensity Meter, to the input power source.
3. Exploratory measurements were made to identify the frequency of the emission that had the highest amplitude relative to the limit by operating the EUT in a range of typical modes of operation, cable position, and with a typical system equipment configuration and arrangement. Based on the exploratory tests of the EUT, the one EUT cable configuration and arrangement and mode of operation that had produced the emission with the highest amplitude relative to the limit was selected for the final measurement.
4. The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment is the system) was then performed over the frequency range of 0.15 MHz to 30 MHz.
5. The measurements were made with the detector set to peak amplitude within a bandwidth of 10 kHz or to quasi-peak and average within a bandwidth of 9 kHz. The EUT was in transmitting mode during the measurements.

# KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)


Report No.:  
KR20-SRF0107

Page (26) of (27)

# KCTL

## Test results

Worst case: 802.11n HT20 / Highest channel



### Final Result

#### --- L2 Phase ---

No.	Frequency	Reading QP	Reading CAV	c.f	Result QP	Result CAV	Limit QP	Limit AV	Margin QP	Margin CAV
	[MHz]	[dB(uV)]	[dB(uV)]	[dB]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB]	[dB]
1	0.17587	28.1	15.7	10.2	38.3	25.9	64.7	54.7	26.4	28.8
2	0.37549	24.6	18.8	10.1	34.7	28.9	58.4	48.4	23.7	19.5
3	0.41262	33.5	29.8	10.1	43.6	39.9	57.6	47.6	14.0	7.7
4	0.43045	29.0	24.8	10.2	39.2	35.0	57.2	47.2	18.0	12.2
5	1.10104	23.9	17.7	10.1	34.0	27.8	56.0	46.0	22.0	18.2
6	1.76383	21.9	16.4	10.0	31.9	26.4	56.0	46.0	24.1	19.6

#### --- L3 Phase ---

No.	Frequency	Reading QP	Reading CAV	c.f	Result QP	Result CAV	Limit QP	Limit AV	Margin QP	Margin CAV
	[MHz]	[dB(uV)]	[dB(uV)]	[dB]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB]	[dB]
1	0.15092	26.3	11.5	9.8	36.1	21.3	65.9	55.9	29.8	34.6
2	0.20413	23.6	10.6	9.9	33.5	20.5	63.4	53.4	29.9	32.9
3	0.2554	21.4	10.1	9.7	31.1	19.8	61.6	51.6	30.5	31.8
4	0.41125	32.4	26.8	9.9	42.3	36.7	57.6	47.6	15.3	10.9
5	1.77002	23.6	17.9	9.9	33.5	27.8	56.0	46.0	22.5	18.2
6	3.69485	24.1	13.8	9.9	34.0	23.7	56.0	46.0	22.0	22.3

## 8. Measurement equipment

Equipment Name	Manufacturer	Model No.	Serial No.	Next Cal. Date
Spectrum Analyzer	R&S	FSV40	100988	21.01.03
Horn antenna	ETS.lindgren	3117	155787	20.10.24
Horn antenna	ETS.lindgren	3116	00086632	21.02.17
Attenuator	API Inmet	40AH2W-10	12	20.05.15
Broadband PreAmplifier	SCHWARZBECK	BBV9718	216	20.07.30
AMPLIFIER	L-3 Narda-MITEQ	AMF-7D-01001800 -22-10P	2031196	21.02.12
AMPLIFIER	L-3 Narda-MITEQ	JS44-18004000-33-8P	2000996	21.01.22
LOOP Antenna	R&S	HFH2-Z2	100355	20.08.24
Antenna Mast	Innco Systems	MA4640-XP-ET	-	-
Turn Table	Innco Systems	DT2000	79	-
Highpass Filter	WT	WT-A1698-HS	WT160411001	20.05.14
TWO-LINE V - NETWORK	R&S	ENV216	101358	20.10.02
EMI TEST RECEIVER	R&S	ESCI	100001	20.08.22
Vector Signal Generator	R&S	SMBV100A	257566	20.07.16
Signal Generator	R&S	SMR40	100007	20.05.13
Cable Assembly	RadiAll	2301761768000PJ	1724.659	-
Cable Assembly	gigalane	RG-400	-	-
Cable Assembly	HUER+SUHNER	SUCOFLEX 104	MY4342/4	-

**End of test report**