

Date / Time:	6/18/2003 11:49:27 AM	Position:	bystander
Filename:	*.txt	Phantom:	HeadBox_spout.csv
Device Tested:	Broadcom	Head Rotation:	0
Antenna:	right	Test Frequency:	2437
Shape File:	dellant0.csv	Power Level:	maximum

Probe:	0123																
Cal File:	123_2450_BODY																
Cal Factors:	<table border="1"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td>Air</td> <td>346</td> <td>318</td> <td>386</td> </tr> <tr> <td>DCP</td> <td>20</td> <td>20</td> <td>20</td> </tr> <tr> <td>Lin</td> <td>.816</td> <td>.816</td> <td>.816</td> </tr> </tbody> </table>		X	Y	Z	Air	346	318	386	DCP	20	20	20	Lin	.816	.816	.816
		X	Y	Z													
	Air	346	318	386													
	DCP	20	20	20													
Lin	.816	.816	.816														
Amp Gain:	2																
Averaging:	1																
Batteries Replaced:	06/12/03																

Liquid:	2450 MHz
Type:	body
Conductivity:	1.921
Relative Permittivity:	50.96
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420

ZOOM SCAN RESULTS:

Spot SAR (W/kg):	Start Scan	End Scan
	0.067	0.064
Change during Scan (%):	-3.34	
Max E-field (V/m):	13.73	
Max SAR (W/kg)	1g	10g
	0.273	0.139

Location of Max (mm):	X	Y	Z
	77.1	25.0	-159.3

AREA SCAN:

Scan Extent:	Min	Max	Steps	
	Y	-50.0	50.0	10.0
	Z	-190.0	-110.0	10.0

Date / Time:	6/18/2003 12:29:39 PM	Position:	lap
Filename:	*.txt	Phantom:	HeadBox_spout.csv
Device Tested:	Broadcom	Head Rotation:	0
Antenna:	right	Test Frequency:	2437
Shape File:	PP02xright_bystander.csv	Power Level:	maximum

Probe:	0123																
Cal File:	123_2450_BODY																
Cal Factors:	<table border="1"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td>Air</td> <td>346</td> <td>318</td> <td>386</td> </tr> <tr> <td>DCP</td> <td>20</td> <td>20</td> <td>20</td> </tr> <tr> <td>Lin</td> <td>.816</td> <td>.816</td> <td>.816</td> </tr> </tbody> </table>		X	Y	Z	Air	346	318	386	DCP	20	20	20	Lin	.816	.816	.816
		X	Y	Z													
	Air	346	318	386													
	DCP	20	20	20													
Lin	.816	.816	.816														
Amp Gain:	2																
Averaging:	1																
Batteries Replaced:	06/12/03																

Liquid:	2450 MHz
Type:	body
Conductivity:	1.911
Relative Permittivity:	50.96
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420

ZOOM SCAN RESULTS:

Spot SAR (W/kg):	Start Scan	End Scan
	0.040	0.044
Change during Scan (%):	10.11	
Max E-field (V/m):	9.38	
Max SAR (W/kg)	1g	10g
	0.137	0.077

Location of Max (mm):	X	Y	Z
	77.1	-31.0	-180.7

AREA SCAN:

Scan Extent:	Min	Max	Steps	
	Y	-50.0	50.0	10.0
	Z	-190.0	-110.0	10.0

Date / Time:	6/18/2003 10:44:04 AM	Position:	bystander 5mm
Filename:	*.txt	Phantom:	HeadBox_spout.csv
Device Tested:	Broadcom	Head Rotation:	0
Antenna:	left	Test Frequency:	1784.8
Shape File:	PP02xright_bystander.csv	Power Level:	maximum

Probe:	0123																
Cal File:	123_2450_BODY																
Cal Factors:	<table border="1"> <tr> <td></td> <td>X</td> <td>Y</td> <td>Z</td> </tr> <tr> <td>Air</td> <td>346</td> <td>318</td> <td>386</td> </tr> <tr> <td>DCP</td> <td>20</td> <td>20</td> <td>20</td> </tr> <tr> <td>Lin</td> <td>.816</td> <td>.816</td> <td>.816</td> </tr> </table>		X	Y	Z	Air	346	318	386	DCP	20	20	20	Lin	.816	.816	.816
		X	Y	Z													
	Air	346	318	386													
	DCP	20	20	20													
Lin	.816	.816	.816														
Amp Gain:	2																
Averaging:	1																
Batteries Replaced:	06/12/03																

Liquid:	2450 MHz
Type:	body
Conductivity:	1.921
Relative Permittivity:	50.96
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420

ZOOM SCAN RESULTS:

Spot SAR (W/kg):	Start Scan	End Scan
	0.049	0.051
Change during Scan (%):	4.54	
Max E-field (V/m):	12.10	
Max SAR (W/kg)	1g	10g
	0.211	0.103

Location of Max (mm):	X	Y	Z
	77.1	-34.0	-158.0

AREA SCAN:

Scan Extent:		Min	Max	Steps
	Y	-50.0	50.0	10.0
	Z	-190.0	-110.0	10.0

Date / Time:	6/18/2003 11:18:05 AM	Position:	lap
Filename:	*.txt	Phantom:	HeadBox_spout.csv
Device Tested:	Broadcom	Head Rotation:	0
Antenna:	left	Test Frequency:	2437
Shape File:	dellant0.csv	Power Level:	maximum

Probe:	0123																
Cal File:	123_2450_BODY																
Cal Factors:	<table border="1"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td>Air</td> <td>346</td> <td>318</td> <td>386</td> </tr> <tr> <td>DCP</td> <td>20</td> <td>20</td> <td>20</td> </tr> <tr> <td>Lin</td> <td>.816</td> <td>.816</td> <td>.816</td> </tr> </tbody> </table>		X	Y	Z	Air	346	318	386	DCP	20	20	20	Lin	.816	.816	.816
		X	Y	Z													
	Air	346	318	386													
	DCP	20	20	20													
Lin	.816	.816	.816														
Amp Gain:	2																
Averaging:	1																
Batteries Replaced:	06/12/03																

Liquid:	2450 MHz
Type:	body
Conductivity:	1.921
Relative Permittivity:	50.96
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420

ZOOM SCAN RESULTS:

Spot SAR (W/kg):	Start Scan	End Scan
	0.020	0.020
Change during Scan (%):	0.00	
Max E-field (V/m):	6.28	
Max SAR (W/kg)	1g	10g
	0.062	0.037

Location of Max (mm):	X	Y	Z
	77.1	-31.0	-183.9

AREA SCAN:

Scan Extent:		Min	Max	Steps
	Y	-50.0	50.0	10.0
	Z	-190.0	-110.0	10.0

Date / Time:	6/18/2003 1:30:43 PM	Position:	bystander
Filename:	*.txt	Phantom:	HeadBox_spout.csv
Device Tested:	Broadcom	Head Rotation:	0
Antenna:	right	Test Frequency:	2412
Shape File:	PP02xright_bystander.csv	Power Level:	maximum

Probe:	0123																
Cal File:	123_2450_BODY																
Cal Factors:	<table border="1"> <tr> <td></td> <td>X</td> <td>Y</td> <td>Z</td> </tr> <tr> <td>Air</td> <td>346</td> <td>318</td> <td>386</td> </tr> <tr> <td>DCP</td> <td>20</td> <td>20</td> <td>20</td> </tr> <tr> <td>Lin</td> <td>.816</td> <td>.816</td> <td>.816</td> </tr> </table>		X	Y	Z	Air	346	318	386	DCP	20	20	20	Lin	.816	.816	.816
		X	Y	Z													
	Air	346	318	386													
	DCP	20	20	20													
Lin	.816	.816	.816														
Amp Gain:	2																
Averaging:	1																
Batteries Replaced:	06/12/03																

Liquid:	2450 MHz
Type:	body
Conductivity:	1.872
Relative Permittivity:	50.93
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420

ZOOM SCAN RESULTS:

Spot SAR (W/kg):	Start Scan	End Scan
	0.065	0.065
Change during Scan (%):	0.00	
Max E-field (V/m):	13.40	
Max SAR (W/kg)	1g	10g
	0.261	0.132

Location of Max (mm):	X	Y	Z
	77.1	-46.0	-161.2

AREA SCAN:

Scan Extent:		Min	Max	Steps
	Y	-50.0	50.0	10.0
	Z	-190.0	-110.0	10.0

Date / Time:	6/18/2003 2:15:06 PM	Position:	bystander
Filename:	*.txt	Phantom:	HeadBox_spout.csv
Device Tested:	Broadcom	Head Rotation:	0
Antenna:	right	Test Frequency:	2462
Shape File:	PP02xright_bystander.csv	Power Level:	maximum

Probe:	0123																
Cal File:	123_2450_BODY																
Cal Factors:	<table border="1"> <tr> <td></td> <td>X</td> <td>Y</td> <td>Z</td> </tr> <tr> <td>Air</td> <td>346</td> <td>318</td> <td>386</td> </tr> <tr> <td>DCP</td> <td>20</td> <td>20</td> <td>20</td> </tr> <tr> <td>Lin</td> <td>.816</td> <td>.816</td> <td>.816</td> </tr> </table>		X	Y	Z	Air	346	318	386	DCP	20	20	20	Lin	.816	.816	.816
		X	Y	Z													
	Air	346	318	386													
	DCP	20	20	20													
Lin	.816	.816	.816														
Amp Gain:	2																
Averaging:	1																
Batteries Replaced:	06/12/03																

Liquid:	2450 MHz
Type:	body
Conductivity:	1.953
Relative Permittivity:	50.79
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420

ZOOM SCAN RESULTS:

Spot SAR (W/kg):	Start Scan	End Scan
	0.066	0.066
Change during Scan (%)	0.00	
Max E-field (V/m):	13.59	
Max SAR (W/kg)	1g	10g
	0.272	0.137

Location of Max (mm):	X	Y	Z
	77.0	-27.0	-159.3

AREA SCAN:

Scan Extent:	Min	Max	Steps	
	Y	-50.0	50.0	10.0
	Z	-190.0	-110.0	10.0

Date / Time:	6/18/2003 2:48:13 PM	Position:	bystander
Filename:	bystander6_right_ant_BT_3d.txt	Phantom:	HeadBox_spout.csv
Device Tested:	Broadcom	Head Rotation:	0
Antenna:	right and Bluetooth	Test Frequency:	802.11: 2437, BT: 2402
Shape File:	PP02xright_bystander.csv	Power Level:	maximum

Probe:	0123																
Cal File:	123_2450_BODY																
Cal Factors:	<table border="1"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td>Air</td> <td>346</td> <td>318</td> <td>386</td> </tr> <tr> <td>DCP</td> <td>20</td> <td>20</td> <td>20</td> </tr> <tr> <td>Lin</td> <td>.816</td> <td>.816</td> <td>.816</td> </tr> </tbody> </table>		X	Y	Z	Air	346	318	386	DCP	20	20	20	Lin	.816	.816	.816
		X	Y	Z													
	Air	346	318	386													
	DCP	20	20	20													
Lin	.816	.816	.816														
Amp Gain:	2																
Averaging:	1																
Batteries Replaced:	06/12/03																

Liquid:	2450 MHz
Type:	body
Conductivity:	1.911
Relative Permittivity:	50.96
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420

ZOOM SCAN RESULTS:

Spot SAR (W/kg):	Start Scan	End Scan
	0.072	0.072
Change during Scan (%):	0.00	
Max E-field (V/m):	14.73	
Max SAR (W/kg)	1g	10g
	0.314	0.134

Location of Max (mm):	X	Y	Z
	77.1	-2.0	-179.6

AREA SCAN:

Scan Extent:		Min	Max	Steps
	Y	-50.0	50.0	10.0
	Z	-190.0	-110.0	10.0

Date / Time:	6/18/2003 3:39:58 PM	Position:	lap
Filename:	lap6_right_ant_BT_3d_3d.txt	Phantom:	HeadBox_spout.csv
Device Tested:	Broadcom	Head Rotation:	0
Antenna:	right and Bluetooth	Test Frequency:	802.11: 2437, BT: 2402
Shape File:	dellant0.csv	Power Level:	maximum

Probe:	0123																
Cal File:	123_2450_BODY																
Cal Factors:	<table border="1"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td>Air</td> <td>346</td> <td>318</td> <td>386</td> </tr> <tr> <td>DCP</td> <td>20</td> <td>20</td> <td>20</td> </tr> <tr> <td>Lin</td> <td>.816</td> <td>.816</td> <td>.816</td> </tr> </tbody> </table>		X	Y	Z	Air	346	318	386	DCP	20	20	20	Lin	.816	.816	.816
		X	Y	Z													
	Air	346	318	386													
	DCP	20	20	20													
Lin	.816	.816	.816														
Amp Gain:	2																
Averaging:	1																
Batteries Replaced:	06/12/03																

Liquid:	2450 MHz
Type:	body
Conductivity:	1.911
Relative Permittivity:	50.96
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420

ZOOM SCAN RESULTS:

Spot SAR (W/kg):	Start Scan	End Scan
	0.035	0.035
Change during Scan (%):	0.00	
Max E-field (V/m):	5.02	
Max SAR (W/kg)	1g	10g
	0.036	0.018

Location of Max (mm):	X	Y	Z
	77.1	-2.0	-179.6

AREA SCAN:

Scan Extent:		Min	Max	Steps
	Y	-50.0	50.0	10.0
	Z	-190.0	-110.0	10.0