

Date / Time:	6/13/2003 10:24:53 AM	Position:	bystander 5mm
Plot #:	1	Phantom:	HeadBox_spout.csv
Device Tested:	BCM94306MPSG	Head Rotation:	0
Antenna:	Right	Test Frequency:	2437
Shape File:	PP02xright_bystander.csv	Power Level:	maximum

Probe:	0123																
Cal File:	123_2450_BODY																
Cal Factors:	<table border="1"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td>Air</td> <td>346</td> <td>318</td> <td>386</td> </tr> <tr> <td>DCP</td> <td>20</td> <td>20</td> <td>20</td> </tr> <tr> <td>Lin</td> <td>.816</td> <td>.816</td> <td>.816</td> </tr> </tbody> </table>		X	Y	Z	Air	346	318	386	DCP	20	20	20	Lin	.816	.816	.816
		X	Y	Z													
	Air	346	318	386													
	DCP	20	20	20													
Lin	.816	.816	.816														
Amp Gain:	2																
Averaging:	1																
Batteries Replaced:	06/12/03																

Liquid:	2450
Type:	body
Conductivity:	1.921
Relative Permittivity:	50.96
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420

ZOOM SCAN RESULTS:

Spot SAR (W/kg):	Start Scan	End Scan
	0.074	0.072
Change during Scan (%):	-2.67	
Max E-field (V/m):	14.54	
Max SAR (W/kg)	1g	10g
	0.309	0.154

Location of Max (mm):	X	Y	Z
	77.1	-31.0	-162.8

AREA SCAN:

Scan Extent:		Min	Max	Steps
	Y	-50.0	50.0	10.0
	Z	-190.0	-110.0	10.0

Date / Time:	6/13/2003 8:57:16 AM	Position:	Lap
Plot #:	2	Phantom:	HeadBox_spout.csv
Device Tested:	BCM94306MPSG	Head Rotation:	0
Antenna:	Right	Test Frequency:	2437
Shape File:	dellant0.csv	Power Level:	maximum

Probe:	0123																
Cal File:	123_2450_BODY																
Cal Factors:	<table border="1"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td>Air</td> <td>346</td> <td>318</td> <td>386</td> </tr> <tr> <td>DCP</td> <td>20</td> <td>20</td> <td>20</td> </tr> <tr> <td>Lin</td> <td>.816</td> <td>.816</td> <td>.816</td> </tr> </tbody> </table>		X	Y	Z	Air	346	318	386	DCP	20	20	20	Lin	.816	.816	.816
		X	Y	Z													
	Air	346	318	386													
	DCP	20	20	20													
Lin	.816	.816	.816														
Amp Gain:	2																
Averaging:	1																
Batteries Replaced:	06/12/03																

Liquid:	2450
Type:	body
Conductivity:	1.921
Relative Permittivity:	50.96
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420

ZOOM SCAN RESULTS:

Spot SAR (W/kg):	Start Scan	End Scan
	0.013	0.013
Change during Scan (%):	0.00	
Max E-field (V/m):	5.77	
Max SAR (W/kg)	1g	10g
	0.049	0.024

Location of Max (mm):	X	Y	Z
	77.0	-64.0	-174.8

AREA SCAN:

Scan Extent:	Min	Max	Steps
Y	-60.0	40.0	10.0
Z	-190.0	-110.0	10.0

Date / Time:	6/13/2003 11:15:25 AM	Position:	bystander 5mm
Plot #:	3	Phantom:	HeadBox_spout.csv
Device Tested:	BCM94306MPSG	Head Rotation:	0
Antenna:	Left	Test Frequency:	2437
Shape File:	PP02xright_bystander.csv	Power Level:	maximum

Probe:	0123																
Cal File:	123_2450_BODY																
Cal Factors:	<table border="1"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td>Air</td> <td>346</td> <td>318</td> <td>386</td> </tr> <tr> <td>DCP</td> <td>20</td> <td>20</td> <td>20</td> </tr> <tr> <td>Lin</td> <td>.816</td> <td>.816</td> <td>.816</td> </tr> </tbody> </table>		X	Y	Z	Air	346	318	386	DCP	20	20	20	Lin	.816	.816	.816
		X	Y	Z													
	Air	346	318	386													
	DCP	20	20	20													
Lin	.816	.816	.816														
Amp Gain:	2																
Averaging:	1																
Batteries Replaced:	06/12/03																

Liquid:	2450
Type:	body
Conductivity:	1.921
Relative Permittivity:	50.96
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420

ZOOM SCAN RESULTS:

Spot SAR (W/kg):	Start Scan	End Scan
	0.074	0.072

Change during Scan (%): -2.70

Max E-field (V/m): 15.05

Max SAR (W/kg)	1g	10g
	0.325	0.156

Location of Max (mm):	X	Y	Z
	77.0	-20.0	-158.0

AREA SCAN:

Scan Extent:	Min	Max	Steps
Y	-50.0	50.0	10.0
Z	-190.0	-110.0	10.0

Date / Time:	6/13/2003 11:40:31 AM	Position:	lap
Plot #:	4	Phantom:	HeadBox_spout.csv
Device Tested:	BCM94306MPSG	Head Rotation:	0
Antenna:	Left	Test Frequency:	2437
Shape File:	dellant0.csv	Power Level:	maximum

Probe:	0123																
Cal File:	123_2450_BODY																
Cal Factors:	<table border="1"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td>Air</td> <td>320</td> <td>280</td> <td>285</td> </tr> <tr> <td>DCP</td> <td>20</td> <td>20</td> <td>20</td> </tr> <tr> <td>Lin</td> <td>.425</td> <td>.418</td> <td>.390</td> </tr> </tbody> </table>		X	Y	Z	Air	320	280	285	DCP	20	20	20	Lin	.425	.418	.390
		X	Y	Z													
	Air	320	280	285													
	DCP	20	20	20													
Lin	.425	.418	.390														
Amp Gain:	2																
Averaging:	1																
Batteries Replaced:	06/12/03																

Liquid:	2450
Type:	body
Conductivity:	1.921
Relative Permittivity:	50.96
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420

ZOOM SCAN RESULTS:

Spot SAR (W/kg):	Start Scan	End Scan
	0.011	0.011
Change during Scan (%):	0.00	
Max E-field (V/m):	4.63	
Max SAR (W/kg)	1g	10g
	0.034	0.022

Location of Max (mm):	X	Y	Z
	77.0	-14.0	-174.0

AREA SCAN:

Scan Extent:		Min	Max	Steps
	Y	-50.0	50.0	10.0
	Z	-190.0	-110.0	10.0

Date / Time:	6/13/2003 12:15:17 PM	Position:	bystander
Plot #:	5	Phantom:	HeadBox_spout.csv
Device Tested:	BCM94306MPSG	Head Rotation:	0
Antenna:	Left	Test Frequency:	2412
Shape File:	PP02xright_bystander.csv	Power Level:	maximum

Probe:	0123																
Cal File:	123_2450_BODY																
Cal Factors:	<table border="1"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td>Air</td> <td>346</td> <td>318</td> <td>386</td> </tr> <tr> <td>DCP</td> <td>20</td> <td>20</td> <td>20</td> </tr> <tr> <td>Lin</td> <td>.816</td> <td>.816</td> <td>.816</td> </tr> </tbody> </table>		X	Y	Z	Air	346	318	386	DCP	20	20	20	Lin	.816	.816	.816
		X	Y	Z													
	Air	346	318	386													
	DCP	20	20	20													
Lin	.816	.816	.816														
Amp Gain:	2																
Averaging:	1																
Batteries Replaced:	06/12/03																

Liquid:	2450
Type:	body
Conductivity:	1.855
Relative Permittivity:	50.95
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420

ZOOM SCAN RESULTS:

Spot SAR (W/kg):	Start Scan	End Scan
	0.069	0.066
Change during Scan (%):	-3.26	
Max E-field (V/m):	14.76	
Max SAR (W/kg)	1g	10g
	0.309	0.163

Location of Max (mm):	X	Y	Z
	77.0	-37.0	-159.3

AREA SCAN:

Scan Extent:		Min	Max	Steps
	Y	-50.0	50.0	10.0
	Z	-190.0	-110.0	10.0

Date / Time:	6/13/2003 1:19:57 PM	Position:	bystander
Plot #:	6	Phantom:	HeadBox_spout.csv
Device Tested:	BCM94306MPSG	Head Rotation:	0
Antenna:	Left	Test Frequency:	2462
Shape File:	PP02xright_bystander.csv	Power Level:	maximum

Probe:	0123																
Cal File:	123_2450_BODY																
Cal Factors:	<table border="1"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td>Air</td> <td>346</td> <td>318</td> <td>386</td> </tr> <tr> <td>DCP</td> <td>20</td> <td>20</td> <td>20</td> </tr> <tr> <td>Lin</td> <td>.816</td> <td>.816</td> <td>.816</td> </tr> </tbody> </table>		X	Y	Z	Air	346	318	386	DCP	20	20	20	Lin	.816	.816	.816
		X	Y	Z													
	Air	346	318	386													
	DCP	20	20	20													
Lin	.816	.816	.816														
Amp Gain:	2																
Averaging:	1																
Batteries Replaced:	06/12/03																

Liquid:	2450
Type:	body
Conductivity:	1.962
Relative Permittivity:	50.8
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420

ZOOM SCAN RESULTS:

Spot SAR (W/kg):	Start Scan	End Scan
	0.077	0.077
Change during Scan (%):	0.00	
Max E-field (V/m):	15.22	
Max SAR (W/kg)	1g	10g
	0.320	0.158

Location of Max (mm):	X	Y	Z
	77.1	-41.0	-157.5

AREA SCAN:

Scan Extent:		Min	Max	Steps
	Y	-50.0	50.0	10.0
	Z	-190.0	-110.0	10.0

Date / Time:	6/16/2003 12:54:40 PM	Position:	bystander
Plot #:	7	Phantom:	HeadBox_spout.csv
Device Tested:	BCM94306MPSG	Head Rotation:	0
Antenna:	Right	Test Frequency:	802.11: 2437, BT: 2402
Shape File:	PP02xright_bystander.csv	Power Level:	maximum

Probe:	0123																
Cal File:	123_2450_BODY																
Cal Factors:	<table border="1"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td>Air</td> <td>346</td> <td>318</td> <td>386</td> </tr> <tr> <td>DCP</td> <td>20</td> <td>20</td> <td>20</td> </tr> <tr> <td>Lin</td> <td>.816</td> <td>.816</td> <td>.816</td> </tr> </tbody> </table>		X	Y	Z	Air	346	318	386	DCP	20	20	20	Lin	.816	.816	.816
		X	Y	Z													
	Air	346	318	386													
	DCP	20	20	20													
Lin	.816	.816	.816														
Amp Gain:	2																
Averaging:	1																
Batteries Replaced:	06/12/03																

Liquid:	2450
Type:	body
Conductivity:	1.921
Relative Permittivity:	50.96
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420

ZOOM SCAN RESULTS:

Spot SAR (W/kg):	Start Scan	End Scan
	0.068	0.066
Change during Scan (%):	-3.05	
Max E-field (V/m):	14.01	
Max SAR (W/kg)	1g	10g
	0.290	0.142

Location of Max (mm):	X	Y	Z
	77.1	-30.0	-161.2

AREA SCAN:

Scan Extent:		Min	Max	Steps
	Y	-50.0	50.0	10.0
	Z	-190.0	-110.0	10.0

Date / Time:	6/16/2003 1:32:11 PM	Position:	lap
Plot #:	8	Phantom:	HeadBox_spout.csv
Device Tested:	BCM94306MPSG	Head Rotation:	0
Antenna:	Right	Test Frequency:	802.11: 2437, BT: 2402
Shape File:	dellant0.csv	Power Level:	maximum

Probe:	0123																
Cal File:	123_2450_BODY																
Cal Factors:	<table border="1"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td>Air</td> <td>346</td> <td>318</td> <td>386</td> </tr> <tr> <td>DCP</td> <td>20</td> <td>20</td> <td>20</td> </tr> <tr> <td>Lin</td> <td>.816</td> <td>.816</td> <td>.816</td> </tr> </tbody> </table>		X	Y	Z	Air	346	318	386	DCP	20	20	20	Lin	.816	.816	.816
		X	Y	Z													
	Air	346	318	386													
	DCP	20	20	20													
Lin	.816	.816	.816														
Amp Gain:	2																
Averaging:	1																
Batteries Replaced:	06/12/03																

Liquid:	2450
Type:	body
Conductivity:	1.921
Relative Permittivity:	50.96
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420

ZOOM SCAN RESULTS:

Spot SAR (W/kg):	Start Scan	End Scan
	0.027	0.027
Change during Scan (%):	0.00	
Max E-field (V/m):	8.49	
Max SAR (W/kg)	1g	10g
	0.109	0.057

Location of Max (mm):	X	Y	Z
	77.1	-11.0	-179.1

AREA SCAN:

Scan Extent:	Min	Max	Steps
Y	-50.0	50.0	10.0
Z	-200.0	-110.0	10.0