

System / software:	SARA2 / 2.3 VPM	Input Power Drift:	
Date / Time:	8/30/2005 8:48:02 AM	DUT Battery Model/No:	
Filename:	tab_side_3d.txt	Probe Serial Number:	0123
Ambient Temperature:	22.0°C	Liquid Simulant:	2450
Device Under Test:	Broadcom	Relative Permittivity:	51.10
Relative Humidity:	50%	Conductivity:	1.912
Phantom S/No:	HeadBox_new_spout.c sv	Liquid Temperature:	22.0°C
Phantom Rotation:	0°	Max SAR Y-axis Location:	-34.00 mm
DUT Position:	side	Max SAR Z-axis Location:	-139.77 mm
Antenna Configuration:	Auxillary	Max E Field:	6.91 V/m
Test Frequency:	2437MHz	SAR 1g:	0.073 W/kg
Air Factors:	405 / 461 / 396	SAR 10g:	0.044 W/kg
Conversion Factors:	.399 / .399 / .399	SAR Start:	0.042 W/kg
Type of Modulation:		SAR End:	0.042 W/kg
Modn. Duty Cycle:		SAR Drift during Scan:	0.00 dB
Diode Compression Factors (V*200):	8 / 6.4 / 8	Probe battery last changed:	7/25/05
Input Power Level:	max	Extrapolation:	poly4

