

System / software:	SARA2 / 2.40 VPM	Input Power Drift:	
Date / Time:	4/19/2006 1:20:07 PM	DUT Battery Model/No:	
Filename:	128pos3_3d.txt	Probe Serial Number:	M0016
Ambient Temperature:	22.8°C	Liquid Simulant:	2450
Device Under Test:	Broadcom BCM94311MCAG	Relative Permittivity:	50.72
Relative Humidity:	30%	Conductivity:	1.911
Phantom S/No:	HeadBox1.csv	Liquid Temperature:	22.0°C
Phantom Rotation:	0°	Max SAR X-axis Location:	-4.80 mm
DUT Position:	side contact	Max SAR Y-axis Location:	-24.00 mm
Antenna Configuration:	main	Max E Field:	9.26 V/m
Test Frequency:	2442MHz	SAR 1g:	0.186 W/kg
Air Factors:	2390 / 2143 / 2668	SAR 10g:	0.921 W/kg
Conversion Factors:	.490 / .490 / .490	SAR Start:	0.004 W/kg
Type of Modulation:		SAR End:	0.004 W/kg
Modn. Duty Cycle:		SAR Drift during Scan:	0.01 %
Diode Compression Factors (V*200):	20 / 20 / 20	Probe battery last changed:	4/19/2006
Input Power Level:	max	Extrapolation:	poly4

