

System / software:	SARA2 / 2.40 VPM	Input Power Drift:	
Date / Time:	4/19/2006 3:36:15 PM	DUT Battery Model/No:	
Filename:	temp.txt	Probe Serial Number:	M0016
Ambient Temperature:	22.8°C	Liquid Simulant:	5800
Device Under Test:	Broadcom BCM94311MCAG	Relative Permittivity:	47.11
Relative Humidity:	30%	Conductivity:	6.456
Phantom S/No:	HeadBox1.csv	Liquid Temperature:	22.0°C
Phantom Rotation:	0°	Max SAR X-axis Location:	23.40 mm
DUT Position:	side contact	Max SAR Y-axis Location:	-13.20 mm
Antenna Configuration:	main	Max E Field:	7.04 V/m
Test Frequency:	5765MHz	SAR 1g:	0.786 W/kg
Air Factors:	2390 / 2143 / 2668	SAR 10g:	0.341 W/kg
Conversion Factors:	.459 / .459 / .459	SAR Start:	0.006 W/kg
Type of Modulation:		SAR End:	0.006 W/kg
Modn. Duty Cycle:		SAR Drift during Scan:	0.00 %
Diode Compression Factors (V*200):	20 / 20 / 20	Probe battery last changed:	4/19/2006
Input Power Level:	max	Extrapolation:	poly4

