



SAR Test Report

FOR:

**Manufacturer: Broadcom Corp.
Model Name: BCM943224HMS
FCC ID: QDS-BRCM1041
IC ID: 4324A-BRCM1041**

Test Report #: SAR_BROAD_094_11001_HMS

Date of Report: 2011-03-10



**FCC Listed #:
A2LA Accredited**

**IC Recognized #
3462B-1**

CETECOM Inc.

411 Dixon Landing Road ♦ Milpitas, CA 95035 ♦ U.S.A.

Phone: + 1 (408) 586 6200 ♦ Fax: + 1 (408) 586 6299 ♦ E-mail: info@cetecomusa.com ♦ <http://www.cetecom.com>

CETECOM Inc. is a Delaware Corporation with Corporation number: 2113686

Board of Directors: Dr. Harald Ansorge, Hans Peter May.



TABLE OF CONTENTS

1. Assessment 4

2. Administrative Data 5

2.1. Identification of the Testing Laboratory Issuing the EMC Test Report5

2.2. Identification of the Client5

2.3. Identification of the Manufacturer5

3. Equipment under Test (EUT) 6

3.1. Specification of the Equipment under Test6

3.2. Identification of the Equipment Under Test (EUT).....6

3.3. Identification of Accessory equipment.....6

4. Subject of Investigation 7

4.1. The IEEE Standard C95.1, the FCC Exposure Criteria, and Radiation Protection Standard Exposure Criteria 7

4.2. Distinction Between Exposed Population, Duration of Exposure and Frequencies 7

4.3. Distinction between Maximum Permissible Exposure and SAR Limits.....8

4.4. SAR Limit.....8

5. The Measurement Procedure 9

5.1. General Requirements.....9

5.2. Body-worn and Other Configurations.....9

5.3. Procedure for assessing the peak spatial-average SAR.....10

5.4. Determination of the largest peak spatial-average SAR12

6. The Measurement System 13

6.1. Robot system specification13

6.2. Isotropic E-Field Probe for Dosimetric Measurements14

6.3. Data Acquisition Electronics.....14

6.4. Phantoms14

6.5. Interpolation and Extrapolation schemes.....14



7. Uncertainty Assessment 15

7.1. Measurement Uncertainty Budget 15

8. Test results summary 16

8.1. Conducted Average Output Power 16

8.2. Test Positions and Configurations..... 17

8.3. SAR results 18

8.4. Dipole verification..... 20

9. References 21

10. Report History 22



1. Assessment

The following device was tested against the limits for general population uncontrolled exposure specified in FCC 2.1093 and RSS-102 Issue 4. The device was tested according to measurement standards and procedures specified in FCC OET Bulletin 65, Supplement C (Edition 01-01), IEEE P1528/D1.2, April 21, 2003, and Radiation Protection Standard Maximum Exposure Levels to Radiofrequency Fields – 3 kHz to 300 GHz and no deviations were ascertained during the course of the tests performed.

Company	Description	Model #
Broadcom Corp.	802.11ag/Draft 802.11n WLAN PCI-E Minicard (Tested inside of HP HSTNN-W82C)	BCM943224HMS

Responsible for Testing Laboratory:

2011-03-10	Compliance	Heiko Strehlow (Director of Compliance)	
Date	Section	Name	Signature

Responsible for the Report:

2011-03-10	Compliance	Josie Sabado (Project Engineer)	
Date	Section	Name	Signature

The test results of this test report relate exclusively to the test item specified in Section 3. CETECOM Inc. USA does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CETECOM Inc. USA.

2. Administrative Data

2.1. Identification of the Testing Laboratory Issuing the EMC Test Report

Company Name:	CETECOM Inc.
Department:	Compliance
Address:	411 Dixon Landing Road Milpitas, CA 95035 U.S.A.
Telephone:	+1 (408) 586 6200
Fax:	+1 (408) 586 6299
Test Lab Director:	Heiko Strehlow
Responsible Project Leader:	Josie Sabado

2.2. Identification of the Client

Applicant's Name:	Broadcom Corp.
Street Address:	190 Mathilda Place
City/Zip Code	Sunnyvale, CA 94086
Country	USA
Contact Person:	Anne Liang
Phone No.	408-922-5890
e-mail:	aliang@broadcom.com

2.3. Identification of the Manufacturer

Same as above client

3. Equipment under Test (EUT)

3.1. Specification of the Equipment under Test

Product Type:	Portable
RF Exposure Environment:	General/Uncontrolled
Marketing Name:	BCM943224HMS
Model No:	BCM943224HMS
Supported Radios:	802.11a/b/g/n
Hardware Revision :	Laptop/Tablet: 55.4KM01.D07G (Main Board) PCI-E Minicard: P202
Software Revision :	Laptop/Tablet: Windows 7 Professional PCI-E Minicard: 5.100.82.34
FCC-ID:	QDS-BRCM1041
IC-ID :	4324A-BRCM1041
Frequency Range:	802.11b/g/n: 2400-2483.5MHz 802.11a/n: 5150-5825MHz
Number of Channels:	802.11b/g/n: 11 802.11a/n: 20
Type(s) of Modulation:	802.11a/b/g/n: BPSK, QPSK, 16-QAM, 64-QAM
Modes of Operation:	802.11a/b/g/n
Antenna Type:	Internal
Maximum Condcuted Output Power:	802.11a: 21.9dBm 802.11b: 18.5dBm 802.11g: 18.2dBm 802.11n HT20: 17.9dBm 802.11n HT40: 19.0dBm

3.2. Identification of the Equipment Under Test (EUT)

EUT #	Serial Number	HW Version	SW Version	Comment
1	ABC04100G1	Laptop/Tablet: 55.4KM01.D07G PCI-E Minicard: P202	Laptop/Tablet: Windows 7 Professional PCI-E Minicard: 5.100.82.34	Radiated and Conducted Unit
2	ABC04900M6	Laptop/Tablet: 55.4KM01.D12G PCI-E Minicard: P202	Laptop/Tablet: Windows 7 Professional PCI-E Minicard: 5.100.82.34	Radiated Unit

3.3. Identification of Accessory equipment

No accessory equipment

4. Subject of Investigation

The objective of the measurements done by Cetecom Inc. was the dosimetric assessment of one device. The tests were performed in configurations for devices operated next to a person's body. The examinations were carried out with the dosimetric assessment system DASY52 described in Section 6.

4.1. The IEEE Standard C95.1, the FCC Exposure Criteria, and Radiation Protection Standard Exposure Criteria

In the USA the recent FCC exposure criteria [FCC 2001] are based upon the IEEE Standard C95.1 [IEEE 1999]. The IEEE standard C95.1 sets limits for human exposure to radio frequency electromagnetic fields in the frequency range 3 kHz to 300 GHz.

The exposure criteria are specified in Radiation Protection Standard Maximum Exposure Levels to Radiofrequency Fields – 3 kHz to 300 GHz. The Radiation Protection Standard sets limits for general public exposure to radio frequency electromagnetic fields in the frequency range 3 kHz to 300 GHz.

4.2. Distinction Between Exposed Population, Duration of Exposure and Frequencies

The American Standard [IEEE 1999] distinguishes between controlled and uncontrolled environment. Controlled environments are locations where there is exposure that may be incurred by persons who are aware of the potential for exposure as a concomitant of employment or by other cognizant persons. Uncontrolled environments are locations where there is the exposure of individuals who have no knowledge or control of their exposure. The exposures may occur in living quarters or workplaces. For exposure in controlled environments higher field strengths are admissible. In addition the duration of exposure is considered. Due to the influence of frequency on important parameters, as the penetration depth of the electromagnetic fields into the human body and the absorption capability of different tissues, the limits in general vary with frequency.

4.3. Distinction between Maximum Permissible Exposure and SAR Limits

The biological relevant parameter describing the effects of electromagnetic fields in the frequency range of interest is the specific absorption rate SAR (dimension: power/mass). It is a measure of the power absorbed per unit mass. The SAR may be spatially averaged over the total mass of an exposed body or its parts. The SAR is calculated from the r.m.s. electric field strength E inside the human body, the conductivity σ and the mass density ρ of the biological tissue:

$$SAR = \sigma \frac{E^2}{\rho} = c \frac{\partial T}{\partial t} \Big|_{t \rightarrow 0^+}$$

The specific absorption rate describes the initial rate of temperature rise $\partial T / \partial t$ as a function of the specific heat capacity c of the tissue. A limitation of the specific absorption rate prevents an excessive heating of the human body by electromagnetic energy.

As it is sometimes difficult to determine the SAR directly by measurement (e.g. whole body averaged SAR), the standard specifies more readily measurable maximum permissible exposures in terms of external electric E and magnetic field strength H and power density S , derived from the SAR limits. The limits for E , H and S have been fixed so that even under worst case conditions, the limits for the specific absorption rate SAR are not exceeded.

For the relevant frequency range the maximum permissible exposure may be exceeded if the exposure can be shown by appropriate techniques to produce SAR values below the corresponding limits.

4.4. SAR Limit

In this report the comparison between the American exposure limits and the measured data is made using the spatial peak SAR; the power level of the device under test guarantees that the whole body averaged SAR is not exceeded.

Having in mind a worst case consideration, the SAR limit is valid for uncontrolled environment and mobile respectively portable transmitters. According to Table 1 the SAR values have to be averaged over a mass of 1g (SAR_{1g}) and 10g (SAR_{10g}) with the shape of a cube.

Standard	Status	Averaged Mass	SAR limit (W/kg)
IEEE C95.1	In force	1g	1.6
Radiation Protection Standard Maximum Exposure Levels to Radio frequency Fields – 3 kHz to 300 GHz	In force	10g	2.0

Table 1: Relevant spatial peak SAR limit averaged over a mass of 1 g

5. The Measurement Procedure

The Federal Communications Commission (FCC) has published a report and order on the 1st of August 1996 [FCC 1996], which requires routine dosimetric assessment of mobile telecommunications devices, either by laboratory measurement techniques or by computational modeling, prior to equipment authorization or use. In 2001 the Commission's Office of Engineering and Technology has released Edition 01-01 of Supplement C to OET Bulletin 65. This revised edition, which replaces Edition 97-01, provides additional guidance and information for evaluating compliance of mobile and portable devices with FCC limits for human exposure to radiofrequency emissions [FCC 2001]. The following KDB Publications have also been used:

447498 – Mobile and portable device RF Exposure Procedures
616217 – SAR Evaluation Considerations for Laptops with Antennas on Display Screens
248227 – SAR Measurement Procedures for 802.11 a/b/g Transmitters
RSS-102 Supplementary Procedures (SPR)-001

In addition, the measurement of SAR shall be performed according to Radiocommunications (Electromagnetic Radiation – Human Exposure) Standard 2003.

5.1. General Requirements

The test shall be performed in a laboratory with an environment which avoids influence on SAR measurements by ambient EM sources and any reflection from the environment itself. The ambient temperature shall be in the range of 20°C to 26°C and 30-70% humidity.

5.2. Body-worn and Other Configurations

Phantom Requirements

For body-worn and other configurations a flat phantom shall be used which is comprised of material with electrical properties similar to the corresponding tissues.

Test Position

The body-worn configurations shall be tested with the supplied accessories (belt-clips, holsters, etc.) attached to the device in normal use configuration. Devices with a headset output shall be tested with a connected headset.

Test to be Performed

For purpose of determining test requirements, accessories may be divided into two categories: those that do not contain metallic components and those that do. For multiple accessories that do not contain metallic components, the device may be tested only with that accessory which provides the closest spacing to the body. For multiple accessories that contain metallic components, the device must be tested with each accessory that contains a unique metallic component. If multiple accessories share an identical metallic component, only the accessory that provides the closest spacing to the body must be tested. If the manufacturer provides none body-

worn accessories a separation distance of 1.5 cm between the back of the device and the flat phantom is recommended. Other separation distances may be used, but they shall not exceed 2.5 cm. In these cases, the device may use body-worn accessories that provide a separation distance greater than that tested for the device provided however that the accessory contains no metallic components.

For devices with retractable antenna the SAR test shall be performed with the antenna fully extended and fully retracted. Other factors that may affect the exposure shall also be tested. For example, optional antennas or optional battery packs which may significantly change the volume, lengths, flip open/closed, etc. of the device, or any other accessories which might have the potential to considerably increase the peak spatial-average SAR value.

5.3. Procedure for assessing the peak spatial-average SAR

Step 1: Power reference measurement:

Prior to the SAR test, a local SAR measurement should be taken at a user-selected spatial reference point to monitor power variations during testing. For example, this power reference point can be spaced 10 mm or less in the normal direction from the liquid-shell interface and within ± 10 mm transverse to the normal line at the ear reference point.

Step 2: Area scan

The measurement procedures for evaluating SAR associated with wireless handsets typically start with a coarse measurement grid in order to determine the approximate location of the local peak SAR values. This is referred to as the "area scan" procedure. The SAR distribution is scanned along the inside surface of typically half of the head of the phantom but at least larger than the areas projected (normal to the phantom's surface) by the handset and antenna. An example grid is given in Figure 4. The distance between the measured points and phantom surface should be less than 8 mm, and should remain constant (variation less than ± 1 mm) during the entire scan in order to determine the locations of the local peak SAR with sufficient precision. The distance between the measurement points should enable the detection of the location of local maximum with an accuracy of better than half the linear dimension of the tissue cube after interpolation. The resolution can also be tested using the functions in Annex E (see E.5.2). The approximate locations of the peak SARs should be determined from area scan. Since a given amplitude local peak with steep gradients may produce lower spatial-average SAR than slightly lower amplitude peaks with less steep gradients, it is necessary to evaluate the other peaks as well. However, since the spatial gradients of local SAR peaks are a function of wavelength inside the tissue simulating liquid and incident magnetic field strength, it is not necessary to evaluate peaks that are less than -2 dB of the local maximum. Two-dimensional spline algorithms [Press, et al, 1996], [Brishoual, 2001] are typically used to determine the peaks and gradients within the scanned area. If the peak is closer than one-half of the linear dimension of the 1 g or 10 g tissue cube to the scan border, the measurement area should be enlarged if possible, e.g., by tilting the probe or the phantom (see Figure 5).




Figure 4 – Example of an area scan including the position of the handset. The scanned area (white dots) should be larger than the area projected by the handset and antenna.

Step 3: Zoom scan

In order to assess the peak spatial SAR values averaged over a 1 g and 10 g cube, fine resolution volume scans, called "zoom scans", are performed at the peak SAR locations determined during the "area scan." The zoom scan volume should have at least 1.5 times the linear dimension of either a 1 g or a 10 g tissue cube for whichever peak spatial-average SAR is being evaluated. The peak local SAR locations that were determined in the area scan (interpolated value) should be on the centerline of the zoom scans. The centerline is the line that is normal to the surface and in the center of the volume scan. If this is not possible, the zoom scan can be shifted but not by more than half the dimension of the 1 g or a 10 g tissue cube.

The maximum spatial-average SAR is determined by a numerical analysis of the SAR values obtained in the volume of the zoom scan, whereby interpolation (between measured points) and extrapolation (between surface and closest measured points) routines should be applied. A 3-D-spline algorithm [Press, et al, 1996], [Kreyszig, 1983], [Brishoual, 2001] can be used for interpolation and a trapezoidal algorithm for the integration (averaging). Scan resolutions of larger than 2 mm can be used provided the uncertainty is evaluated according to E (see E.5).

In some areas of the phantom, such as the jaw and upper head region, the angle of the probe with respect to the line normal to the surface might become large, e.g., at angles larger than $\pm 30^\circ$ (see Figure 5), which may increase the boundary effect to an unacceptable level. In these cases, a change in the orientation of the probe and/or the phantom is recommended during the zoom scan so that the angle between the probe housing tube and the line normal to the surface is significantly reduced ($<30^\circ$).

Step 4: Power reference measurement

The local SAR should be measured at exactly the same location as in Step 1. The absolute value of the measurement drift (the difference between the SAR measured in Step 4 and Step 1) should be recorded in the uncertainty budget. It is recommended that the drift be kept within $\pm 5\%$. If this is not possible, even with repeat testing, additional information may be used to demonstrate the power stability during the test. Power reference measurements can be taken after each zoom scan, if more than one zoom scan is needed. However, the drift should always be referred to the initial state with fully charged battery.

5.4. Determination of the largest peak spatial-average SAR

In order to determine the largest value of the peak spatial-average SAR of a handset, all device positions, configurations and operational modes should be tested for each frequency band according to steps 1 to 3 below.

Step 1: The tests of 6.4 should be conducted at the channel that is closest to the center of the transmit frequency band (f_c) for:

- a) all device positions (cheek and tilt, for both left and right sides of the SAM phantom,
- b) all configurations for each device position in (a), e.g. antenna extended and retracted, and
- c) all operational modes for each device position in (a) and configuration in (b) in each frequency band, e.g. analog and digital.

If more than three frequencies need to be tested, (i.e., $N_c > 3$), then all frequencies, configurations and modes must be tested for all of the above positions.

Step 2: For the condition providing highest spatial peak SAR determined in Step 1 conduct all tests of 6.4 at all other test frequencies, e.g. lowest and highest frequencies. In addition, for all other conditions (device position, configuration and operational mode) where the spatial peak SAR value determined in Step 1 is within 3dB of the applicable SAR limit, it is recommended that all other test frequencies should be tested as well¹.

Step 3: Examine all data to determine the largest value of the peak spatial-average SAR found in Steps 1 to 2.

6. The Measurement System

6.1. Robot system specification

The SAR measurement system being used is the SPEAG DASY52 system, which consists of a Stäubli TX90XL 6-axis robot arm and CS8c controller, SPEAG SAR Probe, Data Acquisition Electronics, and SAM Twin Phantom. The robot is used to articulate the probe to programmed positions inside the phantom to obtain the SAR readings from the EUT.

The system is controlled remotely from a PC, which contains the software to control the robot and data acquisition equipment. The software also displays the data obtained from test scans.




Figure 5: Schematic diagram of the SAR measurement system

In operation, the system first does an area (2D) scan at a fixed depth within the liquid from the inside wall of the phantom. When the maximum SAR point has been found, the system will then carry out a 3D scan centered at that point to determine volume averaged SAR level.

6.2. Isotropic E-Field Probe for Dosimetric Measurements

The probes are constructed using three orthogonal dipole sensors arranged on an interlocking, triangular prism core. The probes have built-in shielding against static charges and are contained within a PEEK cylindrical enclosure material at the tip. Probe calibration is described in the probe's calibration certificate (see appendix C).

6.3. Data Acquisition Electronics

The DAE contains a signal amplifier, multiplexer, 16bit A/D converter and control logic. It uses an optical link for communication with the DASY5 system. The DAE has a dynamic range of -100 to 300 mV. It also contains a two step probe touch detector for mechanical surface detection and emergency robot stop.

6.4. Phantoms

The Twin SAM V4.0 Phantom is designed to specifications defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region.

6.5. Interpolation and Extrapolation schemes

The interpolation, extrapolation and maximum search routines are all based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation. The routines construct a once-continuously differentiable function that interpolates the measurement values.



7. Uncertainty Assessment

Measurement uncertainty values were evaluated for SAR measurements performed by Cetecom Inc. The uncertainty values for components specified in *FCC Supplement C (01-01) to OET Bulletin 65 (97-01)* were evaluated according to the procedures of *IEEE 1528-200X December 29, 2002, NIST 1297 1994 edition and ISO Guide to the Expression of Uncertainty in Measurements (GUM)*.

7.1. Measurement Uncertainty Budget

<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e = f(d,k)</i>	<i>f</i>	<i>g = c x f / e</i>	<i>k</i>
Uncertainty Component	Sec.	Tol. (± %)	Prob. Dist.	Div.	<i>c_i</i> (1-g)	1-g <i>u_i</i> (±%)	<i>v_i</i>
Measurement System							
Probe Calibration	E2.1	5.5	N	1	1	5.5	∞
Axial Isotropy	E2.2	4.7	R	√3	0.7	1.9	∞
Hemispherical Isotropy	E2.2	9.6	R	√3	0.7	3.9	∞
Boundary Effect	E2.3	1.0	R	√3	1	0.6	∞
Linearity	E2.4	4.7	R	√3	1	2.7	∞
System Detection Limits	E2.5	1.0	R	√3	1	0.6	∞
Readout Electronics	E2.6	0.3	N	1	1	0.3	∞
Response Time	E2.7	0.8	R	√3	1	0.5	∞
Integration Time	E2.8	2.6	R	√3	1	1.5	∞
RF Ambient Noise	E6.1	3.0	R	√3	1	1.7	∞
RF Ambient Reflections	E6.1	3.0	R	√3	1	1.7	∞
Probe Positioner Mechanical Tolerance	E6.2	0.4	R	√3	1	0.2	∞
Probe Positioning with respect to Phantom Shell	E6.3	2.9	R	√3	1	1.7	∞
Extrapolation, interpolation and Integration Algorithms for Max. SAR Evaluation	E5.2	1.0	R	√3	1	0.6	∞
Test sample Related							
Test Sample Positioning	E4.2	2.9	N	1	1	2.9	145
Device Holder Uncertainty	E4.1	3.6	N	1	1	3.6	5
Output Power Variation - SAR drift measurement	6.6.2	5.0	R	√3	1	2.9	∞
Phantom and Tissue Parameters							
Phantom Uncertainty (shape and thickness tolerances)	E3.1	4.0	R	√3	1	2.3	∞
Liquid Conductivity Target - tolerance	E3.2	5.0	R	√3	0.7	1.8	∞
Liquid Conductivity - measurement uncertainty	E3.3	2.5	N	1	0.7	1.6	∞
Liquid Permittivity Target tolerance	E3.2	5.0	R	√3	0.6	1.7	∞
Liquid Permittivity - measurement uncertainty	E3.3	2.5	N	1	0.6	1.5	∞
Combined Standard Uncertainty			RSS			± 10.7%	
Expanded Uncertainty (95% CONFIDENCE INTERVAL)			$k=2.00705$			± 21.4%	

8. Test results summary

8.1. Conducted Average Output Power

802.11b/g/n

Channel	Frequency [MHz]	Average Power [dBm]					
		802.11b (Main Antenna)	802.11g (Auxiliary Antenna)	HT20 (Main Antenna)	HT20 (Auxiliary Antenna)	HT40 (Main Antenna)	HT40 (Auxiliary Antenna)
1	2412	18.0	17.6	12.7	12.1		
3	2422					10.5	10.6
6	2437	18.5	18.2	17.9	17.3		
9	2450					10.4	10.5
11	2462	18.0	14.3	12.5	12.0		

802.11a/n

Channel	Frequency [MHz]	Average Power [dBm]					
		802.11a (Main Antenna)	802.11a (Auxiliary Antenna)	HT20 (Main Antenna)	HT20 (Auxiliary Antenna)	HT40 (Main Antenna)	HT40 (Auxiliary Antenna)
36	5180	13.9	14.0	9.4	9.8		
38	5190					11.3	11.4
40	5200	13.9	14.0				
48	5240	14.6	14.3				
52	5260	17.1	17.8	12.6	12.3		
60	5300	17.3	18.1				
62	5310					11.8	11.5
64	5320	17.3	16.8	13.1	12.6		
100	5500	17.5	17.1	14.0	14.3		
102	5510					15.0	15.1
116	5580			13.7	13.7		
118	5590					17.7	18.6
120	5600	17.6	18.1				
124	5620			13.7	13.9		
134	5670					15.4	16.2
140	5700	16.5	17.2	14.6	15.1		
149	5745	17.8	21.9				
151	5755					17.4	19.0
157	5785	17.6	21.9				
159	5795					17.6	19.1

8.2. Test Positions and Configurations

The area scan is over the transmitting antenna. Secondary landscape position was tested with the EUT in tablet mode and the top edge of the EUT against the flat phantom with 0mm air gap. Bystander evaluation was tested with the EUT in laptop mode and the outside face of the screen against the flat phantom with a 2.5cm air gap. See Appendix B for test setup photos.

WLAN is tested on the channel with the highest measured conducted average power.

If the SAR value on the middle channel was more than 3dB below the limit, high and low channels were not evaluated.

SAR evaluation for 802.11g channels is not required when the maximum average output power is less than ¼ dB higher than that measured on the corresponding 802.11b channels.

SAR evaluation for 802.11n HT20 channels is not required when the maximum average output power is less than ¼ dB higher than that measured on the corresponding 802.11a, 802.11b, or 802.11g channels for the corresponding antenna.

802.11b only transmits on the main antenna. 802.11g only transmits on the auxiliary antenna.

The highest average output power for 2.4GHz 802.11n HT40 is 11.48mW (10.6dBm), less than 12mW. SAR evaluation for 2.4GHz 802.11n HT40 is not required.

8.3. SAR results

Position	Operation Mode	EUT	Antenna	Channel	Frequency (MHz)	SAR 1g (W/kg)	SAR 10g (W/kg)	Area Scan (Appendix A)	Positioning Photo (Appendix B)
Secondary Landscape	802.11b	1	Main	6	2437	0.523	0.228	Plot 1	Photo 1
	802.11g	1	Auxiliary	6	2437	0.239	0.122	Plot 2	Photo 1
	802.11a	2	Main	36	5180	0.333	0.107	Plot 3	Photo 1
	802.11a	2	Auxiliary	36	5180	0.910	0.231	Plot 4	Photo 1
	802.11a	2	Auxiliary	48	5240	0.886	0.208	Plot 5	Photo 1
	802.11a	2	Auxiliary	52	5260	1.39	0.369	Plot 6	Photo 1
	802.11a	2	Main	64	5320	0.539	0.173	Plot 7	Photo 1
	802.11a	2	Auxiliary	64	5320	1.34	0.320	Plot 8	Photo 1
	802.11a	1	Main	100	5500	1.27	0.328	Plot 9	Photo 1
	802.11a	2	Auxiliary	100	5500	1.42	0.365	Plot 10	Photo 1
	802.11a	2	Main	120	5600	0.973	0.242	Plot 11	Photo 1
	802.11a	2	Auxiliary	120	5600	1.45	0.397	Plot 12	Photo 1
	802.11a	1	Main	140	5700	1.56	0.346	Plot 13	Photo 1
	802.11a	2	Auxiliary	140	5700	1.02	0.282	Plot 14	Photo 1
	802.11a	2	Main	149	5745	1.54	0.454	Plot 15	Photo 1
	802.11a	2	Auxiliary	149	5745	1.22	0.355	Plot 16	Photo 1
	802.11a	2	Main	157	5785	1.09	0.304	Plot 17	Photo 1
	802.11a	2	Auxiliary	157	5785	1.2	0.351	Plot 18	Photo 1
	802.11n HT40	1	Main/Auxiliary	38	5190	0.818	0.170	Plot 19	Photo 1
		1.07				0.221			
	802.11n HT40	1	Main/Auxiliary	62	5310	1.42	0.293	Plot 20	Photo 1
	802.11n HT40	2	Main/Auxiliary	102	5510	0.821	0.247	Plot 21	Photo 1
		0.716				0.195			
	802.11n HT40	2	Main/Auxiliary	118	5590	1.23	0.343	Plot 22	Photo 1
802.11n HT40	2	Main/Auxiliary	134	5670	0.844	0.240	Plot 23	Photo 1	
	0.871				0.272				
802.11n HT40	2	Main/Auxiliary	159	5795	1.3	0.361	Plot 24	Photo 1	
	1.01				0.313				



Position	Operation Mode	EUT	Antenna	Channel	Frequency (MHz)	SAR 1g (W/kg)	SAR 10g (W/kg)	Area Scan (Appendix A)	Positioning Photo (Appendix B)
Bystander, Laptop mode, Screen Front	802.11b	1	Main	6	2437	0.073	0.037	Plot 25	Photo 2
	802.11g	1	Auxiliary	6	2437	0.049	0.028	Plot 26	Photo 2
	802.11a	1	Main	36	5180	0.028	0.014	Plot 27	Photo 2
	802.11a	2	Auxiliary	36	5180	0.096	0.043	Plot 28	Photo 2
	802.11a	1	Main	64	5320	0.077	0.031	Plot 29	Photo 2
	802.11a	2	Auxiliary	64	5320	0.147	0.057	Plot 30	Photo 2
	802.11a	2	Main	120	5600	0.226	0.098	Plot 31	Photo 2
	802.11a	2	Auxiliary	120	5600	0.276	0.122	Plot 32	Photo 2
	802.11a	2	Main	149	5745	0.405	0.164	Plot 33	Photo 2
	802.11a	2	Auxiliary	149	5745	0.385	0.165	Plot 34	Photo 2
	802.11n HT40	2	Main/Auxiliary	38	5190	0.064	0.032	Plot 35	Photo 2
						0.051	0.024		
	802.11n HT40	2	Main/Auxiliary	62	5310	0.052	0.022	Plot 36	Photo 2
						0.052	0.024		
	802.11n HT40	2	Main/Auxiliary	118	5590	0.268	0.108	Plot 37	Photo 2
						0.250	0.104		
802.11n HT40	2	Main/Auxiliary	159	5795	0.248	0.103	Plot 38	Photo 2	
					0.239	0.095			

8.4. Dipole verification

Prior to formal testing at each frequency a system verification was performed in accordance with IEEE 1528 and the 1 Watt reference SAR value is taken from the Speag dipole calibration report. All of the testing described in this report was performed within 24 hours of the system verification. The following results were obtained:

SAR1g

Date	Frequency (MHz)	CW input at dipole feed (Watts)	1g SAR (W/kg)	1 Watt reference SAR value (W/kg)	Difference reference SAR value to normalized SAR	Area scan (See Appendix A)
2011/01/26	2450	1	53.4	50.8	5.12%	Plot 39
2011/02/01	5200	1	77.5	78.5	-1.27%	Plot 40
2011/03/06	5200	1	78.9	78.5	0.5%	Plot 41
2011/03/07	5200	1	76.9	78.5	-2.04%	Plot 42
2011/03/08	5200	1	82.9	78.5	5.61%	Plot 43
2011/01/31	5800	1	81.8	75.5	8.3%	Plot 44
2011/03/01	5800	1	70.3	75.5	-6.9%	Plot 45
2011/03/08	5800	1	72.3	75.5	-4.24%	Plot 46
2011/03/09	5800	1	71.8	75.5	-4.9%	Plot 47

SAR 10g

Date	Frequency (MHz)	CW input at dipole feed (Watts)	10g SAR (W/kg)	1 Watt reference SAR value (W/kg)	Difference reference SAR value to normalized SAR	Area scan (See Appendix A)
2011/01/26	2450	1	23.8	23.4	-1.71%	Plot 39
2011/02/01	5200	1	22.2	21.8	1.86%	Plot 40
2011/03/06	5200	1	22.9	21.8	5.05%	Plot 41
2011/03/07	5200	1	22.4	21.8	2.75%	Plot 42
2011/03/08	5200	1	23.6	21.8	8.26%	Plot 43
2011/01/31	5800	1	21.4	20.6	3.9%	Plot 44
2011/03/01	5800	1	19.7	20.6	-4.3%	Plot 45
2011/03/08	5800	1	20.8	20.6	0.97%	Plot 46
2011/03/09	5800	1	20.8	20.6	0.97%	Plot 47

9. References

1. [FCC 2001] Federal Communications Commission: Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields, Supplement C (Edition 01-01) to OET Bulletin 65 (Edition 97-01), FCC, 2001.
2. [IEEE 1999] IEEE Std C95.1-1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz, Inst. of Electrical and Electronics Engineers, Inc., 1999.
3. [IEEE 200x] IEEE Std 1528-200x: DRAFT Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques. Draft 6.2, Inst. of Electrical and Electronics Engineers, Inc., 2000.
4. [NIST 1994] NIST: Guidelines for Evaluating and Expressing the Uncertainty of NIST Measurement Results, Technical Note 1297 (TN1297), United States Department of Commerce Technology Administration, National Institute of Standards and Technology, 1994.
5. [IC 2010] Industry Canada, Spectrum Management and Telecommunications: RSS-102 – Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands), March 2010.
6. [ARPANSA 2002] Radiation Protection Standard Maximum Exposure Levels to Radiofrequency Fields – 3 kHz to 300 GHz, Radiation Protection Series No. 3
7. Radiocommunications (Electromagnetic radiation – human Exposure) Standard, April 2007.



10. Report History

2011-03-10: Original Report