



## **ANSI/IEEE Std. C95.1-1992**

in accordance with the requirements of  
FCC Report and Order: ET Docket 93-62, and OET Bulletin 65 Supplement C



## **FCC TEST REPORT**

**For**

**NB**

**Trade Name: Broadcom**

**Model: BCM943228HMB**

Issued to

**Broadcom Corporation**  
190 Mathilda Place Sunnyvale,  
CA 94086, USA

Issued by

**Compliance Certification Services Inc.**  
No.11, Wugong 6th Rd., Wugu Dist.,  
New Taipei City 24891,  
Taiwan. (R.O.C.)  
<http://www.ccsrf.com>  
[service@ccsrf.com](mailto:service@ccsrf.com)  
Issued Date: 2013/03/11



---

**Note:** This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document.



### Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	2013 <del>03</del> /11	Initial Issue	ALL	Anson Lu
01	2013 <del>3</del> /22	Antenna Location	32	Anson Lu



## Table of contents

<b>1</b>	<b>Certificate of Compliance (SAR Evaluation)</b> .....	<b>4</b>
<b>2</b>	<b>EUT Description</b> .....	<b>5</b>
<b>3</b>	<b>Requirements for Compliance Testing Defined</b> .....	<b>6</b>
3.1	Requirements for Compliance Testing Defined by the FCC.....	6
<b>4</b>	<b>Dosimetric Assessment System</b> .....	<b>7</b>
4.1	Measurement System Diagram .....	8
4.2	System Components.....	9
<b>5</b>	<b>Evaluation Procedures</b> .....	<b>12</b>
<b>6</b>	<b>Measurement Uncertainty</b> .....	<b>16</b>
<b>7</b>	<b>Exposure Limit</b> .....	<b>17</b>
<b>8</b>	<b>Tissue Dielectric Properties</b> .....	<b>18</b>
8.1	Test Liquid Confirmation.....	18
8.2	Typical Composition of Ingredients for Liquid Tissue Phantoms.....	19
8.3	Simulating Liquids Parameter Check Results .....	20
<b>9</b>	<b>System Performance Check</b> .....	<b>21</b>
9.1	System Performance Check Results .....	22
<b>10</b>	<b>Device Under Test</b> .....	<b>23</b>
10.1	Simultaneous Transmission .....	23
<b>11</b>	<b>RF Output Power Measurement</b> .....	<b>24</b>
11.1	WiFi (2.4 GHz Band) .....	24
11.2	WiFi (5 GHz Band).....	25
11.3	Bluetooth .....	27
<b>12</b>	<b>SAR Measurements Results</b> .....	<b>28</b>
12.1	Summary of Highest SAR Values.....	30
<b>13</b>	<b>Simultaneous Transmission SAR Analysis</b> .....	<b>31</b>
13.1	Sum of the 1g SAR for Body Exposure Condition.....	31
<b>14</b>	<b>Antenna Locations &amp; Separation Distances</b> .....	<b>32</b>
<b>15</b>	<b>Equipment List &amp; Calibration Status</b> .....	<b>33</b>
<b>16</b>	<b>Facilities</b> .....	<b>34</b>
<b>17</b>	<b>Reference</b> .....	<b>34</b>
<b>18</b>	<b>Attachments</b> .....	<b>35</b>



# 1 Certificate of Compliance (SAR Evaluation)

**Applicant** Broadcom Corporation  
 190 Mathilda Place Sunnyvale,  
 CA 94086, USA

**Equipment Under Test:** NB

**Trade Name:** Broadcom

**Model Number:** BCM943228HMB

**Date of Test:** March 1~ March 6, 2013

**Device Category:** PORTABLE DEVICES

**Exposure Category:** GENERAL POPULATION/UNCONTROLLED EXPOSURE

Applicable Standards	
FCC	<ul style="list-style-type: none"> <li>● FCC OET 65 Supplement C</li> <li>● IEEE 1528 2003</li> <li>● KDB 447498 D01 General RF Exposure Guidance v05</li> <li>● KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01</li> <li>● KDB 248227 D01 SAR measurement for 802 11 a b g v01r02</li> <li>● KDB 616217 D01 SAR for Laptop with Screen Ant v01r01</li> </ul>
<b>Limit</b>	
1.6 W/kg	
<b>Test Result</b>	
Pass	

The device was tested by Compliance Certification Services Inc. in accordance with the measurement methods and procedures specified in OET Bulletin 65 Supplement C (Edition 01-01). The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Approved by:

Tested by:

Alex Wu  
 Section Manager  
 Compliance Certification Services Inc.

Anson Lu  
 SAR Engineer  
 Compliance Certification Services Inc.



## 2 EUT Description

Product	NB		
Trade Name	Broadcom		
Model Number	BCM943228HMB		
Transmitters	Wi-Fi & BT		
Broradcom WiFi+BT combo card	BCM943228HMB		
Modulation Technique	802.11a: Orthogonal Frequency Division Multiplexing (OFDM)		
	802.11b: Direct Sequence Spread Spectrum(DSSS)		
	802.11g: Orthogonal Frequency Division Multiplexing (OFDM)		
	802.11n: Orthogonal Frequency Division Multiplexing (OFDM)		
Antenna Specification	WLAN	Brand name	HIGH-TEK ELECTRONICS CO., LTD
		Parts Number	Main Antenna : DC33001AC00
		Parts Number	Aux Antenna : DC33001AC00
		WLAN antenna: PIFA antenna	
Maximum Output Power	Band		Avg. Pwr(dBm)
	802.11b		18.7 dBm
	802.11g		19.9 dBm
	802.11n HT20		20.4 dBm
	802.11n HT40		16.6 dBm
	802.11a 5.2GHz		13.7 dBm
	802.11a 5.3GHz		17.4 dBm
	802.11a 5.5GHz		17.3 dBm
	802.11a 5.8GHz		17.9 dBm
	802.11n HT20		21.8 dBm
	802.11n HT40		20.6 dBm
	Bluetooth		1.6 dBm
FCC Rule Parts	Frequency Range		Highest Reported 1-g SAR
15.247	2412 - 2462 MHz		0.649 W/kg (Bottom)
	5725 - 5850 MHz		0.565 W/kg (Bottom)
15.407	5150 - 5250 MHz		0.890 W/kg (Bottom)
	5250 - 5350 MHz		1.304 W/kg (Bottom)
	5500 - 5700 MHz		0.807 W/kg (Bottom)
Rechargeable Li-polymer Battery–alternate	Brand: Simplo		
	Model: ASM45N1138		
	Rating: 3.1Ah/46Wh 14.8V		
	Brand: Sony		
Model: ASM45N1140			
Rating: 3.1Ah/46Wh 14.8V			

**Remark:** The sample selected for test was prototype that approximated to production product and was provided by manufacturer.



### **3 Requirements for Compliance Testing Defined**

#### **3.1 Requirements for Compliance Testing Defined by the FCC**


The US Federal Communications Commission has released the report and order "Guidelines for Evaluating the Environmental Effects of RF Radiation", ET Docket No. 93-62 in August 1996 [1]. The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 W/kg for an uncontrolled environment and 8.0 mW/g for an occupational/controlled environment as recommended by the ANSI/IEEE standard C95.1-1992 [6]. According to the Supplement C of OET Bulletin 65 "Evaluating Compliance with FCC Guide-lines for Human Exposure to Radio frequency Electromagnetic Fields", released on Jun 29, 2001 by the FCC, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.



## 4 Dosimetric Assessment System

These measurements were performed with the automated near-field scanning system DASY4/DASY5 from Schmid & Partner Engineering AG (SPEAG). The system is based on a high precision robot (working range greater than 0.9 m) which positions the probes with a positional repeatability of better than  $\pm 0.02$  mm. Special E- and H-field probes have been developed for measurements close to material discontinuity, the sensors of which are directly loaded with a Schottky diode and connected via highly resistive lines to the data acquisition unit. The SAR measurements were conducted with the dosimetric probe EX3DV4-SN: 3554 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe has been calibrated according to the procedure with accuracy of better than  $\pm 10\%$ . The spherical isotropy was evaluated with the procedure and found to be better than  $\pm 0.25$  dB. The phantom used was the SAM Twin Phantom as described in FCC supplement C, IEEE 1528 2003.

#### 4.1 Measurement System Diagram



**The DASY4/DASY5 system for performing compliance tests consists of the following items:**

- A standard high precision 6-axis robot (Stäubli RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to the DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- A computer operating Windows 2000 or Windows XP.
- DASY4/DASY5 software.
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom enabling testing left-hand and right-hand usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- Validation dipole kits allowing validating the proper functioning of the system.





## 4.2 System Components

### DASY4/DASY5 Measurement Server



The DASY4/DASY5 measurement server is based on a PC/104 CPU board with a 166MHz low-power Pentium, 32MB chip disk and 64MB RAM. The necessary circuits for communication with either the DAE3 electronic box as well as the 16-bit AD-converter system for optical detection and digital I/O interface are contained on the DASY4/DASY5 I/O-board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation.



The PC-operating system cannot interfere with these time critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with two expansion slots which are reserved for future applications. Please note that the expansion slots do not have a standardized pinout and therefore only the expansion cards provided by SPEAG can be inserted. Expansion cards from any other supplier could seriously damage the measurement server. Calibration: No calibration required.

### Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE4) consists of a highly sensitive electrometer grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock. The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection. The input impedance of the DAE4 box is 200M $\Omega$ ; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



### EX3DV4 Isotropic E-Field Probe for Dosimetric Measurements

- Construction:** Symmetrical design with triangular core  
Built-in shielding against static charges  
PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
- Calibration:** Basic Broad Band Calibration in air: 10-3000 MHz.  
Conversion Factors (CF) for HSL 900 and HSL 1800  
CF-Calibration for other liquids and frequencies upon request.
- Frequency:** 10 MHz to > 6 GHz; Linearity:  $\pm 0.2$  dB (30 MHz to 3 GHz)
- Directivity:**  $\pm 0.3$  dB in HSL (rotation around probe axis)  
 $\pm 0.5$  dB in HSL (rotation normal to probe axis)
- Dynamic Range:** 10  $\mu$ W/g to > 100 mW/g; Linearity:  $\pm 0.2$  dB  
(noise: typically < 1  $\mu$ W/g)





**Dimensions:** Overall length: 330 mm (Tip: 20 mm)  
Tip diameter: 2.5 mm (Body: 12 mm)  
Distance from probe tip to dipole centers: 1 mm

**Application:** High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%.



Interior of probe


#### SAM Phantom (V4.0)

**Construction:** The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528-2003, CENELEC 50361 and IEC 62209. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points with the robot.

**Shell Thickness:**  $2 \pm 0.2$  mm

**Filling Volume:** Approx. 25 liters

**Dimensions:** Height: 810mm; Length: 1000mm; Width: 500mm



#### SAM Phantom (ELI4)

**Construction:** Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with the latest draft of the standard IEC 62209 Part II and all known tissue simulating liquids. ELI4 has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is supported by software version DASY4/DASY5 and higher and is compatible with all SPEAG dosimetric probes and dipoles

**Shell Thickness:**  $2.0 \pm 0.2$  mm (sagging: <1%)

**Filling Volume:** Approx. 25 liters

**Dimensions:** Major ellipse axis: 600 mm

Minor axis: 400 mm 500mm





### Device Holder for SAM Twin Phantom

**Construction:** In combination with the Twin SAM Phantom V4.0 or Twin SAM, the Mounting Device (made from POM) enables the rotation of the mounted transmitter in spherical coordinates, whereby the rotation point is the ear opening. The devices can be easily and accurately positioned according to IEC, IEEE, CENELEC, FCC or other specifications. The device holder can be locked at different phantom locations (left head, right head, and flat phantom).



### System Validation Kits for SAM Phantom (V4.0)

**Construction:** Symmetrical dipole with 1/4 balun Enables measurement of feedpoint impedance with NWA Matched for use near flat phantoms filled with brain simulating solutions Includes distance holder and tripod adaptor.

**Frequency:** 2450, 5200, 5300, 5600, 5800 MHz

**Return loss:** > 20 dB at specified validation position

**Power capability:** > 100 W ( $f < 1\text{GHz}$ ); > 40 W ( $f > 1\text{GHz}$ )

**Dimensions**  
D2450V2: dipole length: 51.5 mm; overall height: 290 mm  
D5GHzV2: dipole length: 20.6 mm; overall height: 300 mm



### System Validation Kits for ELI4 phantom

**Construction:** Symmetrical dipole with 1/4 balun Enables measurement of feedpoint impedance with NWA Matched for use near flat phantoms filled with brain simulating solutions Includes distance holder and tripod adaptor.

**Frequency:** 2450, 5200, 5300, 5600, 5800 MHz

**Return loss:** > 20 dB at specified validation position

**Power capability:** > 100 W ( $f < 1\text{GHz}$ ); > 40 W ( $f > 1\text{GHz}$ )

**Dimensions:**  
D2450V2: dipole length: 51.5 mm; overall height: 290 mm  
D5GHzV2: dipole length: 20.6 mm; overall height: 300 mm





## 5 Evaluation Procedures

### Data Evaluation

The DASY4/DASY5 post processing software (SEMCAD) automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	- Sensitivity	$Norm_i, a_{i0}, a_{i1}, a_{i2}$
	- Conversion factor	$ConvF_i$
	- Diode compression point	$dcp_i$
Device parameters:	- Frequency	$f$
	- Crest factor	$cf$
Media parameters:	- Conductivity	$\sigma$
	- Density	$\rho$

These parameters must be set correctly in the software. They can be found in the component documents or be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multi-meter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

with	$V_i$	= Compensated signal of channel i	(i = x, y, z)
	$U_i$	= Input signal of channel i	(i = x, y, z)
	$cf$	= Crest factor of exciting field	(DASY parameter)
	$dcp_i$	= Diode compression point	(DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

E-field probes: 
$$E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$$

H-field probes: 
$$H_i = \sqrt{V_i} \cdot \frac{a_{i10} + a_{i11}f + a_{i12}f^2}{f}$$

with	$V_i$	= Compensated signal of channel i	(i = x, y, z)
	$Norm_i$	= Sensor sensitivity of channel i	(i = x, y, z)
		$\mu V/(V/m)^2$ for E0field Probes	
	$ConvF$	= Sensitivity enhancement in solution	
	$aij$	= Sensor sensitivity factors for H-field probes	
	$f$	= Carrier frequency (GHz)	
	$E_i$	= Electric field strength of channel i in V/m	
	$H_i$	= Magnetic field strength of channel i in A/m	



The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

- with  $SAR$  = local specific absorption rate in W/kg  
 $E_{tot}$  = total field strength in V/m  
 $\sigma$  = conductivity in [mho/m] or [Siemens/m]  
 $\rho$  = equivalent tissue density in g/cm<sup>3</sup>

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid.

The power flow density is calculated assuming the excitation field as a free space field.

$$P_{pwe} = \frac{E_{tot}^2}{3770} \quad \text{or} \quad P_{pwe} = H_{tot}^2 \cdot 37.7$$

- with  $P_{pwe}$  = Equivalent power density of a plane wave in mW/cm<sup>2</sup>  
 $E_{tot}$  = total electric field strength in V/m  
 $H_{tot}$  = total magnetic field strength in A/m



## SAR Measurement Procedures

The procedure for assessing the peak spatial-average SAR value consists of the following steps:

- **Power Reference Measurement**

The reference and drift jobs are useful jobs for monitoring the power drift of the device under test in the batch process. Both jobs measure the field at a specified reference position, at a selectable distance from the phantom surface. The reference position can be either the selected section's grid reference point or a user point in this section. The reference job projects the selected point onto the phantom surface, orients the probe perpendicularly to the surface, and approaches the surface using the selected detection method.

- **Area Scan**

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a finer measurement around the hot spot. The sophisticated interpolation routines implemented in DASY4/DASY5 software can find the maximum locations even in relatively coarse grids. The scan area is defined by an editable grid. This grid is anchored at the grid reference point of the selected section in the phantom. When the area scan's property sheet is brought-up, the grid resolution has to less than 15 mm by 15 mm at frequency  $\leq 2$ GHz; the grid resolution has to less than 12mm by 12 mm at frequency between 2GHz to 4GHz; grid resolution has to less than 10 mm by 10 mm at frequency between 4GHz to 6GHz. according to KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01)

- **Zoom Scan**

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The default zoom scan measures points in accordance with the frequency can be divided into three parts. (1)The zoom scan volume was set to 5x5x7 points at frequency  $\leq 2$ GHz. (2) The zoom scan volume was set to 7x7x7 points at frequency between 2GHz to 4GHz (3) The zoom scan volume was set to 7x7x12 points at frequency between 4GHz to 6GHz. The measures points within a cube whose base faces are centered around the maximum found in a preceding area scan job within the same procedure. If the preceding Area Scan job indicates more then one maximum, the number of Zoom Scans has to be enlarged accordingly

- **Power Drift Measurement**

The drift job measures the field at the same location as the most recent reference job within the same procedure, and with the same settings. The drift measurement gives the field difference in dB from the reading conducted within the last reference measurement. Several drift measurements are possible for one reference measurement. This allows a user to monitor the power drift of the device under test within a batch process. In the properties of the Drift job, the user can specify a limit for the drift and have DASY4/DASY5 software stop the measurements if this limit is exceeded.

- **Z-Scan**

The Z Scan job measures points along a vertical straight line. The line runs along the Z-axis of a one-dimensional grid. A user can anchor the grid to the current probe location. As with any other grids, the local Z-axis of the anchor location establishes the Z-axis of the grid.



### Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the IEEE1528 2003 standard. It can be conducted for 1 g and 10 g.

The DASY4/DASY5 system allows evaluations that combine measured data and robot positions, such as:

- maximum search
- extrapolation
- boundary correction
- peak search for averaged SAR

During a maximum search, global and local maximum searches are automatically performed in 2-D after each Area Scan measurement with at least 6 measurement points. It is based on the evaluation of the local SAR gradient calculated by the Quadratic Shepard's method. The algorithm will find the global maximum and all local maxima within -2 dB of the global maxima for all SAR distributions.

### Extrapolation

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. Several measurements at different distances are necessary for the extrapolation.

Extrapolation routines require at least 10 measurement points in 3-D space. They are used in the Cube Scan to obtain SAR values between the lowest measurement points and the inner phantom surface. The routine uses the modified Quadratic Shepard's method for extrapolation.

### Boundary Effect

For measurements in the immediate vicinity of a phantom surface, the field coupling effects between the probe and the boundary influence the probe characteristics. Boundary effect errors of different dosimetric probe types have been analyzed by measurements and using a numerical probe model. As expected, both methods showed an enhanced sensitivity in the immediate vicinity of the boundary. The effect strongly depends on the probe dimensions and disappears with increasing distance from the boundary. The sensitivity can be approximately given as:

$$S \approx S_o + S_b \exp\left(-\frac{z}{a}\right) \cos\left(\pi \frac{z}{\lambda}\right)$$

Since the decay of the boundary effect dominates for small probes ( $a \ll \lambda$ ), the cos-term can be omitted. Factors  $S_b$  (parameter Alpha in the DASY4/DASY5 software) and  $a$  (parameter Delta in the DASY4/DASY5 software) are assessed during probe calibration and used for numerical compensation of the boundary effect. Several simulations and measurements have confirmed that the compensation is valid for different field and boundary configurations.

This simple compensation procedure can largely reduce the probe uncertainty near boundaries. It works well as long as:

- the boundary curvature is small
- the probe axis is angled less than 30° to the boundary normal
- the distance between probe and boundary is larger than 25% of the probe diameter
- the probe is symmetric (all sensors have the same offset from the probe tip)

Since all of these requirements are fulfilled in a DASY4/DASY5 system, the correction of the probe boundary effect in the vicinity of the phantom surface is performed in a fully automated manner via the measurement data extraction during post processing.





## 6 Measurement Uncertainty

Measurement uncertainty for 300 MHz to 3 GHz averaged over 1 gram

Uncertainty Component	Uncertainty	Prob.	Div.	$C_i$ (10g)	Std. Unc.(1-g)	$V_i$ or $V_{eff}$
<b>Measurement System</b>						
Probe Calibration ( $k=1$ )	6.00	Normal	1	1	6.00	$\infty$
Probe Isotropy	7.60	Rectangular	$\sqrt{3}$	0.7	3.07	$\infty$
Boundary Effect	0.65	Rectangular	$\sqrt{3}$	1	0.38	$\infty$
Linearity	4.70	Rectangular	$\sqrt{3}$	1	2.71	$\infty$
System Detection Limit	1.00	Rectangular	$\sqrt{3}$	1	0.58	$\infty$
Readout Electronics	0.30	Normal	1	1	0.30	$\infty$
Response Time	0.80	Rectangular	$\sqrt{3}$	1	0.46	$\infty$
Integration Time	2.60	Rectangular	$\sqrt{3}$	1	1.50	$\infty$
RF Ambient Conditions	3.00	Rectangular	$\sqrt{3}$	1	1.73	$\infty$
RF Ambient Reflections	3.00	Rectangular	$\sqrt{3}$	1	1.73	$\infty$
Probe Positioner Mechanical Tolerance	0.40	Rectangular	$\sqrt{3}$	1	0.23	$\infty$
Probe Positioning with respect to Phantom Shell	2.90	Rectangular	$\sqrt{3}$	1	1.67	$\infty$
Extrapolation, interpolation and integration Algorithms for Max. SAR Evaluation	2.00	Rectangular	$\sqrt{3}$	1	1.15	$\infty$
<b>Test sample Related</b>						
Test sample Positioning	3.70	Normal	1	1	3.7	89
Device Holder Uncertainty	3.40	Normal	1	1	3.4	5
Output Power Variation - SAR drift measurement	5.00	Rectangular	$\sqrt{3}$	1	2.89	$\infty$
<b>Phantom and Tissue Parameters</b>						
Phantom Uncertainty (shape and thickness tolerances)	7.50	Rectangular	$\sqrt{3}$	1	4.33	$\infty$
Liquid Conductivity - deviation from target values	4.14	Rectangular	$\sqrt{3}$	0.64	1.53	$\infty$
Liquid Conductivity - measurement uncertainty	-3.13	Normal	1	0.64	-2.00	39
Liquid Permittivity - deviation from target values	3.92	Rectangular	$\sqrt{3}$	0.6	1.36	$\infty$
Liquid Permittivity - measurement uncertainty	-3.71	Normal	1	0.6	-2.23	39
		RSS			11.47	611
Expanded Uncertainty U, Coverage Factor = 2, > 95 % Confidence =		$k=2$				22.94%
Expanded Uncertainty U, Coverage Factor = 2, > 95 % Confidence =		$k=2$				1.79dB

Measurement uncertainty for 3 to 6 GHz averaged over 1 gram

Uncertainty Component	Uncertainty	Prob.	Div.	$C_i$ (10g)	Std. Unc.(1-g)	$V_i$ or $V_{eff}$
<b>Measurement System</b>						
Probe Calibration ( $k=1$ )	6.55	Normal	1	1	6.55	$\infty$
Probe Isotropy	7.60	Rectangular	$\sqrt{3}$	0.7	3.07	$\infty$
Boundary Effect	2.00	Rectangular	$\sqrt{3}$	1	1.15	$\infty$
Linearity	4.70	Rectangular	$\sqrt{3}$	1	2.71	$\infty$
System Detection Limit	1.00	Rectangular	$\sqrt{3}$	1	0.58	$\infty$
Readout Electronics	0.30	Normal	1	1	0.30	$\infty$
Response Time	0.80	Rectangular	$\sqrt{3}$	1	0.46	$\infty$
Integration Time	2.60	Rectangular	$\sqrt{3}$	1	1.50	$\infty$
RF Ambient Conditions	3.00	Rectangular	$\sqrt{3}$	1	1.73	$\infty$
RF Ambient Reflections	3.00	Rectangular	$\sqrt{3}$	1	1.73	$\infty$
Probe Positioner Mechanical Tolerance	0.80	Rectangular	$\sqrt{3}$	1	0.46	$\infty$
Probe Positioning with respect to Phantom Shell	6.70	Rectangular	$\sqrt{3}$	1	3.87	$\infty$
Extrapolation, interpolation and integration Algorithms for Max. SAR Evaluation	4.00	Rectangular	$\sqrt{3}$	1	2.31	$\infty$
<b>Test sample Related</b>						
Test sample Positioning	3.70	Normal	1	1	3.7	89
Device Holder Uncertainty	3.40	Normal	1	1	3.4	5
Output Power Variation - SAR drift measurement	5.00	Rectangular	$\sqrt{3}$	1	2.89	$\infty$
<b>Phantom and Tissue Parameters</b>						
Phantom Uncertainty (shape and thickness tolerances)	7.90	Rectangular	$\sqrt{3}$	1	4.56	$\infty$
Liquid Conductivity - deviation from target values	5.00	Rectangular	$\sqrt{3}$	0.64	1.85	$\infty$
Liquid Conductivity - measurement uncertainty	-3.90	Normal	1	0.64	-2.50	39
Liquid Permittivity - deviation from target values	5.00	Rectangular	$\sqrt{3}$	0.6	1.73	$\infty$
Liquid Permittivity - measurement uncertainty	0.95	Normal	1	0.6	0.57	39
		RSS			12.56	611
Expanded Uncertainty U, Coverage Factor = 2, > 95 % Confidence =		$k=2$				25.12%
Expanded Uncertainty U, Coverage Factor = 2, > 95 % Confidence =		$k=2$				1.95dB





## 7 Exposure Limit

(A). Limits for Occupational/Controlled Exposure (W/kg)

<u>Whole-Body</u>	<u>Partial-Body</u>	<u>Hands, Wrists, Feet and Ankles</u>
0.4	8.0	2.0

(B). Limits for General Population/Uncontrolled Exposure (W/kg)

<u>Whole-Body</u>	<u>Partial-Body</u>	<u>Hands, Wrists, Feet and Ankles</u>
0.08	1.6	4.0

NOTE: **Whole-Body SAR** is averaged over the entire body, **partial-body SAR** is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. **SAR for hands, wrists, feet and ankles** is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

**Population/Uncontrolled Environments:**

are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

**Occupational/Controlled Environments:**

are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

<p><b>NOTE</b> <b>GENERAL POPULATION/UNCONTROLLED EXPOSURE</b> <b>PARTIAL BODY LIMIT</b> <b>1.6 W/kg</b></p>
--



## 8 Tissue Dielectric Properties

### 8.1 Test Liquid Confirmation

#### Simulating Liquids Parameter Check

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values

The relative permittivity and conductivity of the tissue material should be within  $\pm 5\%$  of the values given in the table below.  $\pm 5\%$  may not be easily achieved at certain frequencies.

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in IEEE 1528 2003 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in IEEE 1528 2003 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations and extrapolated according to the head parameters specified in IEEE 1528 2003

Target Frequency (MHz)	Head		Body	
	$\epsilon_r$	$\sigma$ (S/m)	$\epsilon_r$	$\sigma$ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800 – 2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5000	36.2	4.45	49.3	5.07
5100	36.1	4.55	49.1	5.18
5200	36.0	4.66	49.0	5.30
5300	35.9	4.76	48.9	5.42
5400	35.8	4.86	48.7	5.53
5500	35.6	4.96	48.6	5.65
5600	35.5	5.07	48.5	5.77
5700	35.4	5.17	48.3	5.88
5800	35.3	5.27	48.2	6.00



## 8.2 Typical Composition of Ingredients for Liquid Tissue Phantoms

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Ingredients (% by weight)	Frequency (MHz)									
	450		835		915		1900		2450	
Tissue Type	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body
Water	38.56	51.16	41.45	52.4	41.05	56.0	54.9	40.4	62.7	73.2
Salt (NaCl)	3.95	1.49	1.45	1.4	1.35	0.76	0.18	0.5	0.5	0.04
Sugar	56.32	46.78	56.0	45.0	56.5	41.76	0.0	58.0	0.0	0.0
HEC	0.98	0.52	1.0	1.0	1.0	1.21	0.0	1.0	0.0	0.0
Bactericide	0.19	0.05	0.1	0.1	0.1	0.27	0.0	0.1	0.0	0.0
Triton X-100	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	36.8	0.0
DGBE	0.0	0.0	0.0	0.0	0.0	0.0	44.92	0.0	0.0	26.7
Dielectric Constant	43.42	58.0	42.54	56.1	42.0	56.8	39.9	54.0	39.8	52.5
Conductivity (S/m)	0.85	0.83	0.91	0.95	1.0	1.07	1.42	1.45	1.88	1.78

alt: 99% Pure Sodium Chloride

Sugar: 98% Pure Sucrose

Water: De-ionized, 16 MΩ<sup>+</sup> resistivity

HEC: Hydroxy thyl Cellulose

DGBE: 99% Di(ethylene glycol) butyl ether, [2-(2-butoxyethoxy)ethanol]

Triton X-100 (ultra-pure): Polyethylene glycol mono [4-(1, 1, 3, 3-tetramethylbutyl)phenyl]ether

Simulating Liquids for 5 GHz, Manufactured by SPEAG:

Ingredients	(% by weight)
Water	50-65
Mineral oil	10-30
Emulsifiers	8-25
Sodium and Salt	0-1.5



### 8.3 Simulating Liquids Parameter Check Results

Date	Band	Freq (MHz)	Measured			Standard		Δ		Limit
			e' (εr)	e''	σ	e' (εr)	σ	e' (εr)	σ	±5
2013/3/1	Body 5000	5180	49.16	17.61	5.07	49.07	5.25	0.18%	-3.55%	±5
		5200	49.12	17.66	5.10	49.04	5.28	0.16%	-3.30%	±5
		5500	48.64	17.82	5.45	48.64	5.62	0.01%	-3.17%	±5
		5800	48.21	18.14	5.84	48.23	5.97	-0.05%	-2.13%	±5
		5825	48.21	18.12	5.86	48.20	6.00	0.02%	-2.27%	±5
2013/3/4	Body 5000	5180	49.32	17.54	5.05	49.07	5.25	0.51%	-3.90%	±5
		5200	49.25	17.58	5.08	49.04	5.28	0.44%	-3.75%	±5
		5500	48.84	17.83	5.45	48.64	5.62	0.42%	-3.13%	±5
		5800	48.36	18.08	5.82	48.23	5.97	0.27%	-2.46%	±5
		5825	48.35	18.10	5.86	48.20	6.00	0.31%	-2.39%	±5
2013/3/5	Body 5000	5180	49.27	17.55	5.05	49.07	5.25	0.41%	-3.88%	±5
		5200	49.14	17.57	5.08	49.04	5.28	0.20%	-3.78%	±5
		5500	48.94	18.02	5.51	48.64	5.62	0.61%	-2.08%	±5
		5800	48.35	18.30	5.90	48.23	5.97	0.25%	-1.25%	±5
		5825	48.39	18.40	5.96	48.20	6.00	0.40%	-0.74%	±5
2013/3/6	Body 5000	5180	49.43	17.62	5.07	49.07	5.25	0.73%	-3.50%	±5
		5200	49.25	17.66	5.10	49.04	5.28	0.43%	-3.31%	±5
		5500	49.10	18.11	5.53	48.64	5.62	0.95%	-1.61%	±5
		5800	48.50	18.38	5.92	48.23	5.97	0.55%	-0.81%	±5
		5825	48.52	18.46	5.97	48.20	6.00	0.67%	-0.42%	±5
2013/3/6	Body 2450	2412	50.95	13.88	1.86	52.75	1.91	-3.41%	-2.81%	±5
		2437	51.00	13.87	1.88	52.72	1.94	-3.25%	-3.10%	±5
		2442	50.99	13.87	1.88	52.71	1.94	-3.27%	-3.13%	±5
		2462	50.83	13.95	1.91	52.68	1.97	-3.53%	-3.01%	±5
		2472	50.72	14.02	1.92	52.67	1.98	-3.71%	-2.84%	±5



## 9 System Performance Check

The system performance check is performed prior to any usage of the system in order to guarantee reproducible results. The system performance check verifies that the system operates within its specifications. The system performance check results are tabulated below. And also the corresponding SAR plot is attached as well in the SAR plots files.

### System Performance Check Measurement Conditions

- The measurements were performed in the flat section of the SAM twin phantom filled with Body simulating liquid of the following parameters.
- The DASY4/DASY5 system with an E-field probe EX3DV4 SN: 3554 was used for the measurements.
- The dipole was mounted on the small tripod so that the dipole feed point was positioned below the center marking of the flat phantom section and the dipole was oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 15 mm (below 1 GHz) and 10 mm (above 1 GHz) from dipole center to the simulating liquid surface.
- The coarse grid with a grid spacing of 10mm was aligned with the dipole.
- Special 7x7x7 fine cube was chosen for cube integration (dx=dy= 5 mm, dz= 5 mm).
- Distance between probe sensors and phantom surface was set to 3.0 mm.
- The dipole input power (forward power) was 100 mW±3%.
- The results are normalized to 1 W input power.

### Reference SAR Values for System Performance Check

The reference SAR values can be obtained from the calibration certificate of system validation dipoles

System Dipole	Serial No.	Cal. Date	Freq. (MHz)	Target SAR Values (W/kg)		
				1g/10g	Head	Body
D2450V2	728	11/20/2012	2450	1g	53.1	51.3
				10g	24.9	24.0
D5GHzV2	1004	11/16/2012	5200	1g	77.8	71.8
				10g	22.1	20.1
D5GHzV2	1004	11/16/2012	5300	1g	83.9	75.4
				10g	24.0	21.2
D5GHzV2	1004	11/16/2012	5600	1g	83.3	78.8
				10g	23.6	21.8
D5GHzV2	1004	11/16/2012	5800	1g	79.8	73.5
				10g	22.7	20.4



### 9.1 System Performance Check Results

Date	System Dipole			Parameters	Target	Measured	Deviation[%]	Limited[%]
	Type	Serial No.	Liquid					
2013/3/1	D5GHzV2 (5.2GHz)	1004	Body	1g SAR:	71.80	70.40	-1.95	± 5
				10g SAR:	20.10	20.00	-0.50	± 5
2013/3/1	D5GHzV2 (5.3GHz)	1004	Body	1g SAR:	75.40	75.30	-0.13	± 5
				10g SAR:	21.20	21.40	0.94	± 5
2013/3/4	D5GHzV2 (5.6GHz)	1004	Body	1g SAR:	78.80	77.90	-1.14	± 5
				10g SAR:	21.80	21.80	0.00	± 5
2013/3/5	D5GHzV2 (5.8GHz)	1004	Body	1g SAR:	73.50	74.80	1.77	± 5
				10g SAR:	20.40	21.10	3.43	± 5
2013/3/5	D5GHzV2 (5.3GHz)	1004	Body	1g SAR:	75.40	76.90	1.99	± 5
				10g SAR:	21.20	21.80	2.83	± 5
2013/3/6	D5GHzV2 (5.2GHz)	1004	Body	1g SAR:	71.80	71.80	0.00	± 5
				10g SAR:	20.10	20.40	1.49	± 5
2013/3/6	D2450V2	728	Body	1g SAR:	51.30	52.90	3.12	± 5
				10g SAR:	24.00	25.00	4.17	± 5



## 10 Device Under Test

### 10.1 Simultaneous Transmission

No.	Conditions	Head	Body	Hotspot
1	WiFi + BT	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>

#### Note(s):

1. As the tablet has been assessed in accordance with KDB 447498, which has more conservative measurement distances than KDB 941225, further assessment in accordance with KDB 941225 is judged unnecessary. This is also in accordance with FCC training provided in October 2012 (TCBC Workshop) which indicates that hotspot mode KDB procedures are not intended for larger tablets.



## 11 RF Output Power Measurement

### 11.1 WiFi (2.4 GHz Band)

Required Test Channels per KDB 248227 D01

Mode	Band (GHz)	Freq. (MHz)	Ch #	Default Test Channels	
				802.11b	802.11g
802.11 b/g	2.4	2412	1 <sup>#</sup>	✓	▽
		2437	6	✓	▽
		2462	11 <sup>#</sup>	✓	▽

**Notes**

✓ = "default test channels"

▽ = possible 802.11g channels with maximum average output ¼ dB the "default test channels"

<sup>#</sup> = when output power is reduced for channel 1 and /or 11 to meet restricted band requirements the highest output channels closest to each of these channels should be tested.

The indicated Wi-Fi target powers in the following table are absolute maximums.

**Output power table**

Band (GHz)	Mode	Data rate (Mbps)	Ch #	Freq. (MHz)	Target Pwr (dBm)			Tune-up Tolerance (dBm)	Maximum Tune-up Pwr (dBm)	Avg. Pwr (dBm)		
					Main	Aux	Total			Main	Aux	Total
2.4	802.11b	1	1	2412	18.0			±1.5	19.5	18.7		
			6	2437	16.5			±1.5	18.0	16.8		
			11	2462	16.5			±1.5	18.0	16.7		
	802.11g	6	1	2412	15.0			±1.5	16.5	15.7		
			6	2437	19.0			±1.5	20.5	19.9		
			11	2462	14.5			±1.5	16.0	15.0		
	802.11n HT20	MCS8	1	2412	13.0	13.0	16.0	±1.5	17.5	13.4	13.7	16.6
			6	2437	17.5	17.5	20.5	±1.5	22.0	17.2	17.5	20.4
			11	2462	12.0	12.0	15.0	±1.5	16.5	12.6	12.8	15.7
	802.11n HT40	MCS8	3	2412	11.5	11.5	14.5	±1.5	16.0	12.5	12.7	15.6
			6	2437	12.5	12.5	15.5	±1.5	17.0	13.4	13.8	16.6
			9	2462	10.5	10.5	13.5	±1.5	15.0	11.0	11.5	14.3





**11.2 WiFi (5 GHz Band)**

Required Test Channels per KDB 248227 D01

Mode	Band (GHz)	Freq. (MHz)	Ch #	Default Test Channels			
				§15.247		UNII	
802.11a	UNII	5180	36			✓	
		5200	40				*
		5220	44				*
		5240	48			✓	
		5260	52			✓	
		5280	56				*
		5300	60				*
		5320	64			✓	
		5500	100				*
		5520	104			✓	
		5540	108				*
		5560	112				*
		5580	116			✓	
		5600	120				*
		5620	124			✓	
		5640	128				*
		5660	132				*
		5680	136			✓	
	5700	140				*	
		UNII or §15.247	5745	149	✓		✓
	5765		153		*		*
	5785		157	✓			*
	5805		161		*	✓	
	§15.247	5825	165	✓			

**Notes**  
 ✓ = "default test channels"  
 \* = possible 802.11a channels with maximum average output > the "default test channels"

The indicated Wi-Fi target powers in the following table are absolute maximums.



**WiFi 5.2GHz Band:**

Band (GHz)	Mode	Data rate (Mbps)	Ch #	Freq. (MHz)	Target Pwr (dBm)			Tune-up Tolerance (dBm)	Maximum Tune-up Pwr (dBm)	Avg. Pwr (dBm)		
					Main	Aux	Total			Main	Aux	Total
5.2	802.11a	6	36	5180	13.0			± 1.5	14.5	13.4		
			40	5200	13.0			± 1.5	14.5	13.6		
			44	5220	13.0			± 1.5	14.5	13.7		
			48	5240	13.0			± 1.5	14.5	13.5		
	802.11n (HT20)	MCS8	36	5180	9.0	9.0	12.0	± 1.5	13.5	9.6	8.4	12.1
			40	5200	9.0	9.0	12.0	± 1.5	13.5	9.0	7.5	11.3
			44	5220	9.0	9.0	12.0	± 1.5	13.5	9.3	8.0	11.7
			48	5240	8.5	8.5	11.5	± 1.5	13.0	9.0	8.2	11.6
	802.11n (HT40)	MCS8	38	5190	9.0	9.0	12.0	± 1.5	13.5	10.0	8.6	12.4
			46	5230	10.0	10.0	13.0	± 1.5	14.5	10.1	9.0	12.6

**WiFi 5.3GHz Band:**

Band (GHz)	Mode	Data rate (Mbps)	Ch #	Freq. (MHz)	Target Pwr (dBm)			Tune-up Tolerance (dBm)	Maximum Tune-up Pwr (dBm)	Avg. Pwr (dBm)		
					Main	Aux	Total			Main	Aux	Total
5.3	802.11a	6	52	5260	17.5			± 1.5	19.0	17.4		
			56	5280	16.0			± 1.5	17.5	16.5		
			60	5300	15.5			± 1.5	17.0	16.1		
			64	5320	14.0			± 1.5	15.5	14.5		
	802.11n (HT20)	MCS8	52	5260	13.0	13.0	16.0	± 1.5	17.5	13.2	13.2	16.2
			56	5280	16.0	16.0	19.0	± 1.5	20.5	16.6	16.8	19.7
			60	5300	16.0	16.0	19.0	± 1.5	20.5	16.5	16.2	19.4
			64	5320	14.0	14.0	17.0	± 1.5	18.5	14.5	14.4	17.5
	802.11n (HT40)	MCS8	54	5270	16.5	16.5	19.5	± 1.5	21.0	16.4	16.5	19.5
			62	5310	11.0	11.0	14.0	± 1.5	15.5	11.6	11.6	14.6

**WiFi 5.5GHz Band:**

Band (GHz)	Mode	Data rate (Mbps)	Ch #	Freq. (MHz)	Target Pwr (dBm)			Tune-up Tolerance (dBm)	Maximum Tune-up Pwr (dBm)	Avg. Pwr (dBm)			
					Main	Aux	Total			Main	Aux	Total	
5.5	802.11a	6	100	5500	16.5			± 1.5	18.0	17.0			
			104	5520	17.0			± 1.5	18.5	17.1			
			108	5540	17.0			± 1.5	18.5	17.2			
			112	5560	17.0			± 1.5	18.5	17.3			
			116	5580	17.0			± 1.5	18.5	17.2			
			132	5660	17.0			± 1.5	18.5	17.3			
			136	5680	17.0			± 1.5	18.5	17.2			
			140	5700	17.0			± 1.5	18.5	17.2			
	802.11n (HT20)	MCS8	100	5500	16.0	16.0	19.0	± 1.5	20.5	16.5	16.0	19.3	
			104	5520	16.0	16.0	19.0	± 1.5	20.5	16.5	15.9	19.2	
			108	5540	16.0	16.0	19.0	± 1.5	20.5	16.5	16.2	19.4	
			112	5560	16.0	16.0	19.0	± 1.5	20.5	16.7	16.8	19.8	
			116	5580	16.0	16.0	19.0	± 1.5	20.5	16.6	16.7	19.7	
			132	5660	16.0	16.0	19.0	± 1.5	20.5	16.6	16.6	19.6	
			136	5680	16.0	16.0	19.0	± 1.5	20.5	16.5	16.3	19.4	
			140	5700	12.0	12.0	15.0	± 1.5	16.5	12.7	13.3	16.0	
	802.11n (HT40)	MCS8	102	5510	13.0	13.0	16.0	± 1.5	17.5	13.7	12.6	16.2	
			118	5550	17.0	17.0	20.0	± 1.5	21.5	17.7	17.5	20.6	
				134	5670	17.0	17.0	20.0	± 1.5	21.5	17.1	17.9	20.5



**WiFi 5.8GHz Band:**

Band (GHz)	Mode	Data rate (Mbps)	Ch #	Freq. (MHz)	Target Pwr (dBm)			Tune-up Tolerance (dBm)	Maximum Tune-up Pwr (dBm)	Avg. Pwr (dBm)					
					Main	Aux	Total			Main	Aux	Total			
5.8	802.11a	6	149	5745	17.0			± 1.5	18.5	17.8					
			153	5765	17.0			± 1.5	18.5	17.7					
			157	5785	17.0			± 1.5	18.5	17.8					
			161	5805	17.0			± 1.5	18.5	17.9					
	802.11n (HT20)	MCS8	6	149	5745	17.0	17.0	20.0	± 1.5	21.5	18.2	18.4	21.3		
				153	5765	17.5	17.5	20.5	± 1.5	22.0	18.0	18.4	21.2		
				157	5785	17.5	17.5	20.5	± 1.5	22.0	18.0	18.4	21.2		
				161	5805	17.5	17.5	20.5	± 1.5	22.0	18.3	18.5	21.4		
			802.11n (HT40)	MCS8	6	151	5755	16.0	16.0	19.0	± 1.5	20.5	16.5	17.0	19.8
						159	5795	16.0	16.0	19.0	± 1.5	20.5	16.5	17.4	20.0

**11.3 Bluetooth**

Target Power: 0.5 dBm

Tune-up Tolerance: -1.5dBm / +1.5dBm

**Output power table**

Band	Mode	Ch #	Freq. (MHz)	Avg pwr (dBm)
Bluetooth	BLE	0	2402	1.5
		19	2440	1.6
		38	2480	1.4



## 12 SAR Measurements Results

### Wi-Fi (2.4GHz Band):

Band	Mode	Test Position	Channel	Dist. (mm)	Power (dBm)		Measured 1g SAR	Reported SAR(W/kg)	Note
					Tune up limit	Measured			
2.4GHz	802.11b	Bottom	1	0	19.5	18.7	0.360	0.433	
			6	0					1
			11	0					1
	802.11g	Bottom	1	0					1
			6	0	20.5	19.9	0.565	0.649	
			11	0					1
	802.11n HT20	Bottom	1	0					1
			6	0	22.0	20.4	0.308	0.445	
			11	0					1

#### Note(s):

1. Testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g SAR for the mid-band or highest output power channel.  $\leq 0.8$  W/kg and transmission band  $\leq 100$  MHz (Per KDB 447498 D01 v05 section 4.3.3)

### Wi-Fi (5.2GHz Band):

Band	mode	Test Position	Channel	Dist. (mm)	Power (dBm)		Measured 1g SAR (W/kg)	Reported SAR(W/kg)	Note
					Tune up limit	Measured			
5.2GHz	802.11a	Bottom	40	0	14.5	13.6	0.656	0.807	
			44	0	14.5	13.7	0.740	0.890	

### Wi-Fi (5.3GHz Band):

Band	mode	Test Position	Channel	Dist. (mm)	Power (dBm)		Measured 1g SAR	Reported SAR(W/kg)	Note
					Tune up limit	Measured			
5.3GHz	802.11a	Bottom	52	0	19.0	17.4	0.902	1.304	
			60	0	17.0	16.1	0.860	1.058	
	802.11n HT20	Bottom	56	0	20.5	19.7	1.040	1.250	
			60	0	20.5	19.4	1.010	1.301	
	802.11n HT20	Bottom	56	0	20.5	19.7	0.966	1.161	1

#### Note(s):

1. Repeated measurements are required only when the measured SAR is  $\geq 0.80$  W/kg. If the measured SAR values are  $< 1.45$  W/kg with  $\leq 20\%$  variation, only one repeated measurement is required to reaffirm that the results are not expected to have substantial variations, which may introduce significant compliance concerns. (Per KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01)

- 1.1 Original SAR = 1.040 W/kg, therefore two times repeat SAR is required.
- 1.2 Repeat SAR = 0.966 W/kg  $< 1.45$ W/kg
- 1.3 SAR variation= 7.6%  $< 20\%$



**Wi-Fi (5.5GHz Band):**

Band	mode	Test Position	Channel	Dist. (mm)	Power (dBm)		Measured 1g SAR	Reported SAR(W/kg)	Note
					Tune up limit	Measured			
5.5GHz	802.11a	Bottom	108	0	18.5	17.2	0.463	0.625	
			112	0	18.5	17.3	0.481	0.634	
			132	0	18.5	17.3	0.523	0.689	
	802.11n HT40	Bottom	118	0	21.5	20.6	0.656	0.807	

**Wi-Fi (5.8GHz Band):**

Band	mode	Test Position	Channel	Dist. (mm)	Power (dBm)		Measured 1g SAR	Reported SAR(W/kg)	Note
					Tune up limit	Measured			
5.8GHz	802.11a	Bottom	149	0	18.5	17.8	0.462	0.543	
			161	0	18.5	17.9	0.456	0.524	
			165	0	18.5	17.8	0.452	0.531	
	802.11n HT20	Bottom	149	0	21.5	21.3	0.540	0.565	
			161	0	22.0	21.4	0.438	0.503	
			165	0	22.0	21.8	0.493	0.516	

**Bluetooth:**

Band	Mode	Freq. (MHz)	Power (dBm)		Estimated 1g SAR (W/kg)	Note
			Tune up limit	Measured		
Bluetooth	BLE	2402				
		2440	2.0	1.6	0.026	
		2480				

**Note(s):**

1. When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following KDB 447498 D01 v05 section 4.3.2

- Maximum power of channel, including tune-up tolerance (mW)=1.58mW
- Minimum test separation distance (mm) = 12.83 mm

Estimated SAR= (1.58mW/12.83mm)[(2.440GHz^0.5)/7.5]=0.026mW/g



### 12.1 Summary of Highest SAR Values

Results for highest reported SAR values for each frequency band and mode

Technology/Band	Test configuration	Mode	Highest Reported 1g-SAR (W/kg)
WiFi 2.4 GHz	Bottom	802.11g 6Mbps	0.649
WiFi 5.2 GHz	Bottom	802.11a 6Mbps	0.890
WiFi 5.3 GHz	Bottom	802.11a 6Mbps	1.304
WiFi 5.5 GHz	Bottom	802.11n HT20	0.807
WiFi 5.8 GHz	Bottom	802.11a 6Mbps	0.565



## 13 Simultaneous Transmission SAR Analysis

### 13.1 Sum of the 1g SAR for Body Exposure Condition

#### Sum of the SAR with Reported Values

Band	Test Position	Mode	Channel	Reported SAR (W/Kg)	Bluetooth	$\Sigma$ 1-g SAR (W/kg)
2.4GHz	Bottom	802.11b	1	0.433	0.026	0.459
		802.11g	6	0.649	0.026	0.675
		802.11n HT20	6	0.445	0.026	0.471

Band	Test Position	Mode	Channel	Reported SAR (W/Kg)	Bluetooth	$\Sigma$ 1-g SAR (W/kg)
5.2GHz	Bottom	802.11a	40	0.807	0.026	0.833
			44	0.890	0.026	0.916

Band	Test Position	Mode	Channel	Reported SAR (W/Kg)	Bluetooth	$\Sigma$ 1-g SAR (W/kg)
5.3GHz	Bottom	802.11a	52	1.304	0.026	1.330
			60	1.058	0.026	1.084
		802.11n HT20	56	1.250	0.026	1.276
			60	1.301	0.026	1.327

Band	Test Position	Mode	Channel	Reported SAR (W/Kg)	Bluetooth	$\Sigma$ 1-g SAR (W/kg)
5.5GHz	Bottom	802.11a	108	0.625	0.026	0.651
			112	0.634	0.026	0.660
			132	0.689	0.026	0.715
		802.11n HT40	118	0.807	0.026	0.833


Band	Test Position	Mode	Channel	Reported SAR (W/Kg)	Bluetooth	$\Sigma$ 1-g SAR (W/kg)
5.8GHz	Bottom	802.11a	149	0.543	0.026	0.569
			161	0.524	0.026	0.550
			165	0.531	0.026	0.557
		802.11n HT20	149	0.565	0.026	0.591
			161	0.503	0.026	0.529
			165	0.516	0.026	0.542

#### Note(s):

Simultaneous transmission SAR measurement (Volume Scan) is not required when the  $\Sigma$  1-g SAR is < 1.6 mW/g



## 14 Antenna Locations & Separation Distances







## 15 Equipment List & Calibration Status

Name of Equipment	Manufacturer	Type/Model	Serial Number	Calibration Cycle(year)	Calibration Due
S-Parameter Network Analyzer	Agilent	E8358A	US40260243	1	07/03/2013
Electronic Probe kit	Hewlett Packard	85070D	N/A	N/A	N/A
Power Meter	Agilent	E4416A	GB41291611	1	09/18/2013
Power Sensor	Agilent	8481H	MY41091956	1	09/18/2013
Spectrum Analyzer	Agilent	E4446A	US42510252	1	12/09/2013
Signal Generatot	Agilent	83630B	3844A01022	1	08/26/2013
Data Acquisition Electronics (DAE)	SPEAG	DAE4	558	1	07/18/2013
Dosimetric E-Field Probe	SPEAG	EX3DV4	3554	1	09/26/2013
2450 MHz System Validation Dipole	SPEAG	D2450V2	728	1	11/19/2013
5GHz System Validation Dipole	SPEAG	D5GHzV2	1004	1	11/15/2013
Robot	Staubli	RX90L	02/5T69A1/A/01	N/A	N/A
Amplifier	Mini-Circuit	ZVE-8G	665500309	N/A	N/A
DC Power generator	ABM	8301HD	N/A	N/A	N/A
Probe Alignment Unit	SPEAG	LB (V2)	348	N/A	N/A
SAM Twin Phantom V4.0	SPEAG	N/A	N/A	N/A	N/A
Devices Holder	SPEAG	N/A	N/A	N/A	N/A



## 16 Facilities

All measurement facilities used to collect the measurement data are located at

- No. 81-1, Lane 210, Bade Rd. 2, Luchu Hsiang, Taoyuan Hsien, Taiwan, R.O.C.
- No.11, Wugong 6th Rd., Wugu Dist., New Taipei City 24891, Taiwan. (R.O.C.)
- No. 199, Chunghsen Road, Hsintien City, Taipei Hsien, Taiwan, R.O.C.

## 17 Reference

- [1] Federal Communications Commission, \Report and order: Guidelines for evaluating the environmental effects of radiofrequency radiation", Tech. Rep. FCC 96-326, FCC, Washington, D.C. 20554, 1996.
- [2] David L. Means Kwok Chan, Robert F. Cleveland, \Evaluating compliance with FCC guidelines for human exposure to radiofrequency electromagnetic fields", Tech. Rep., Federal Communication Commission, Office of Engineering & Technology, Washington, DC, 1997.
- [3] Thomas Schmid, Oliver Egger, and Niels Kuster, \Automated E-field scanning system for dosimetric assessments", IEEE Transactions on Microwave Theory and Techniques, vol. 44, pp. 105{113, Jan. 1996.
- [4] Niels Kuster, Ralph Kastle, and Thomas Schmid, \Dosimetric evaluation of mobile communications equipment with known precision", IEEE Transactions on Communications, vol. E80-B, no. 5, pp. 645{652, May 1997.
- [5] CENELEC, \Considerations for evaluating of human exposure to electromagnetic fields (EMFs) from mobile telecommunication equipment (MTE) in the frequency range 30MHz - 6GHz", Tech. Rep., CENELEC, European Committee for Electrotechnical Standardization, Brussels, 1997.
- [6] ANSI, ANSI/IEEE C95.1-1992: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz, The Institute of Electrical and Electronics Engineers, Inc., New York, NY 10017, 1992.
- [7] Katja Pokovic, Thomas Schmid, and Niels Kuster, \Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies", in ICECOM '97, Dubrovnik, October 15{17, 1997, pp. 120{124.
- [8] Katja Pokovic, Thomas Schmid, and Niels Kuster, \E-field probe with improved isotropy in brain simulating liquids", in Proceedings of the ELMAR, Zadar, Croatia, 23{25 June, 1996, pp. 172{175.
- [9] Volker Hombach, Klaus Meier, Michael Burkhardt, Eberhard K. uhn, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 900 MHz", IEEE Transactions on Microwave Theory and Techniques, vol. 44, no. 10, pp. 1865{1873, Oct. 1996.
- [10] Klaus Meier, Ralf Kastle, Volker Hombach, Roger Tay, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 1800 MHz", IEEE Transactions on Microwave Theory and Techniques, Oct. 1997, in press.
- [11] W. Gander, Computermathematik, Birkhaeuser, Basel, 1992.
- [12] W. H. Press, S. A. Teukolsky, W. T. Vetterling, and B. P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second Edition, Cambridge University Press, 1992..Dosimetric Evaluation of Sample device, month 1998 9
- [13] NIS81 NAMAS, \The treatment of uncertainty in EMC measurement", Tech. Rep., NAMAS Executive, National Physical Laboratory, Teddington, Middlesex, England, 1994.
- [14] Barry N. Taylor and Christ E. Kuyatt, \Guidelines for evaluating and expressing the uncertainty of NIST measurement results", Tech. Rep., National Institute of Standards and Technology, 1994. Dosimetric Evaluation of Sample device, month 1998 10



## 18 Attachments

Exhibit	Content
1	System performance check Plots
2	SAR test plots for 2.4GHz Band
3	SAR test plots for 5.2GHz Band
4	SAR test plots for 5.3GHz Band
5	SAR test plots for 5.5GHz Band
6	SAR test plots for 5.8GHz Band
7	SAR_Probe_EX3DV4_sn3554_20120927
8	SAR_DAE4_sn558_20120719
9	SAR_Dipole_D2450V2_sn728_20121120
10	SAR_Dipole_D5GHzV2_sn1004_20121116
11	T130222W02-SF PHOTOS

**End of Report**