

TEST REPORT

Report No. :	AF	007452-001	Date : 2005 April 25
Application No. :	LF205014(1)		
Client :	On Sui	l Galaxy Inc. e Sundial Ave, te 310 Manchester, I 03103, U.S.A.	
Sample Description	:	One(1) submitted sample stated to be <u>MLS RC Soccer Gam</u> Rating : 1 x 9V size battery No. of submitted sample : Two (2) piece (s)***	<u>e</u> of Model No. <u>E019</u>
Date Received	:	2005 April 11	
Test Period	:	2005 April 11 – 2005 April 22	
Test Requested	:	FCC Part 15 Certification	
Test Method	:	FCC Rules and Regulations Part 15 – July 2004 ANSI C63.4 – 2003	
Test Result	:	See attached sheet(s) from page 2 to 11.	
Conclusion	:	The submitted sample was found to comply with requireme Subpart C.	nt of FCC Part 15

For and on behalf of CMA Testing and Certification Laboratories

Danny Chui

Page 1 of 11

Authorized Signature :

FCC ID : QEA-MLSRC27T

EMC Engineer - EL. Division

This document shall not be reproduced either in full or in part except with written approval by the Authorized Representative of CMA Testing. Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St.., Fo Tan, Shatin, Hong Kong. Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: <u>info@cmatcl.com</u> Web Site: <u>http://www.cmatcl.com</u>



TEST REPORT

Report No. : AF007452-001

Date : 2005 April 25

Table of Contents

1	General Information	. 3			
1.1	General Description	. 3			
1.2	2 Location of the test site	. 4			
1.3	3 List of measuring equipment	. 5			
2	Description of the radiated emission test	. 6			
2.1	Test Procedure	. 6			
2.2					
2.3	8 Radiated Emission Measurement Data	. 7			
3	Description of the Line-conducted Test	. 8			
3.1	Test Procedure	. 8			
3.2	2 Test Result	. 8			
3.3	Graph and Table of Conducted Emission Measurement Data	. 8			
4	4 Photograph				
4.1	Photographs of the Test Setup for Radiated Emission and Conduction Emission	. 9			
4.2	2 Photographs of the External and Internal Configurations of the EUT	. 9			
5	Supplementary document	10			
5.1	Bandwidth	10			
5.2	2 Duty cycle	10			
6	5 Appendices 11				

Page 2 of 11



TEST REPORT

Report No. : AF007452-001

Date : 2005 April 25

1 General Information

1.1 General Description

The equipment under test (EUT) is a transmitter for MLS RC Soccer Game. Operating at 27.145 MHz which is controlled by a crystal. The EUT is powered by 9V size battery. It has two control stick in the EUT. When the forward, backward, turn left and turn right stick is pushed once, it will transmit a radio signal for receiver go difference direction.

The brief circuit description is listed as follows :

- X1, Q1 and associated circuit act as oscillator.
- Q2 and associated circuit act as RF amplify.
- U1 and associated circuit act as encoder.



TEST REPORT

Report No. : AF007452-001

Date : 2005 April 25

1.2 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 - 2003. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at :

Ground Floor, Yan Hing Centre, 9 – 13 Wong Chuk Yeung Street, Fo Tan, Shatin, New Territories, Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 - 2003. A shielded room is located at :

Ground Floor, Yan Hing Centre, 9 – 13 Wong Chuk Yeung Street, Fo Tan, Shatin, New Territories, Hong Kong.

FCC ID : QEA-MLSRC27T

Page 4 of 11



TEST REPORT

Report No. : AF007452-001

Date : 2005 April 25

1.3 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.	Calibration Certification No.
EMI Test Receiver	R&S	ESCS30	100001	S43284
Broadband Antenna	Schaffner	CBL6112B	2692	CA3025
Signal Generator	IFR	2023B	202302/938	S43098
LISN	R&S	ESH3-Z5	100010	S43101
Pulse Limiter	R&S	ESH3-Z2	100001	\$43325



TEST REPORT

Report No. : AF007452-001

Date : 2005 April 25

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 - 2001.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

The device was rotated through three orthogonal axes to determine which attitude and configuration produce the highest emission during measurement.

2.2 Test Result

Peak Detector data was measured unless otherwise stated.

* Emissions appearing within the restricted bands shall follow the requirement of section 15.205.

It was found that the EUT meet the FCC requirement.



TEST REPORT

Report No. : AF007452-001

Date : 2005 April 25

2.3 Radiated Emission Measurement Data

Radiated emission

pursuant to

the requirement of FCC Part 15 subpart C

Frequency	Polarity	Reading at	Antenna and	Average	Field	Limit at 3m	Margin
(MHz)	(H/V)	3m	Cable factor	Factor	Strength	$(dB\mu V/m)$	(dB)
		(dBµV/m)	(dB)	(dB)	(dBµV/m)		
27.145	V	58.3	18.4	-5.7	71.0	80.0	-9.0
54.296	V	28.7	8.1	-	36.8	40.0	-3.2
81.440	Н	20.9	7.2	-	28.1	40.0	-11.9
* 108.585	Н	18.7	11.0	-	29.7	43.5	-13.8
* 135.708	Н	17.2	12.4	-	29.6	43.5	-13.9
* 162.871	Н	15.9	10.4	-	26.3	43.5	-17.2
190.016	Н	14.6	9.2	-	23.8	43.5	-19.7
217.159	Н	15.7	9.7	-	25.4	46.0	-20.6
* 244.304	Н	18.8	9.7	-	28.5	46.0	-17.5
* 271.449	Н	16.8	13.9	-	30.7	46.0	-15.3





TEST REPORT

Report No. : AF007452-001

Date : 2005 April 25

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 - 2001. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

No measurement is required as the EUT is a battery-operated product.

3.3 Graph and Table of Conducted Emission Measurement Data

Not Applicable





TEST REPORT

Report No. : AF007452-001

Date : 2005 April 25

4 Photograph

4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission

For electronic filing, the photos are saved with filename TSup1.jpg to TSup2.jpg

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho2.jpg.

Page 9 of 11



TEST REPORT

Report No. : AF007452-001

Date : 2005 April 25

5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmp.jpg
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf

5.1 Bandwidth

The plot on saved in TestRpt 2.pdf shows the fundamental emission is confined in the specified band. It also shows that the band edge met the 15.209 requirement at 26.9599 and 27.2801 MHz.

5.2 The duty cycle is simply the on-time divided by the period :

The duration of one cycle	=	79.1ms
Effective period of the cycle	=	(58 x 580µs) + (4 x 1.79ms)
	=	40.8ms
Duty Cycle	=	40.8ms / 79.1ms
	=	0.516

Therefore, the average factor is found by $20 \log_{10} 0.516 = -5.7 dB$

FCC ID : QEA-MLSRC27T

Page 10 of 11



TEST REPORT

Report No. : AF007452-001

Date : 2005 April 25

6 Appendices

A1	Photos of the set-up of Radiated Emissions	1 page
A2	Photos of External Configurations	1 page
A3	Photos of Internal Configurations	1 page
A4	ID Label/Location	1 page
A5	Bandwidth Plot	1 page
A6	Duty Cycle	2 pages
A7	Block Diagram	1 page
A8	Schematics	1 page
A9	User Manual	1 page
A10	Operation Description	1 page

***** End of Report *****

FCC ID : QEA-MLSRC27T

Page 11 of 11