Applicant: Kid Galaxy Inc

Product Description: Car of 2.4G High Speed 20V RC F150

Model No.: 10314

FCC ID: QEA-U282-2G4R

Frequency range: 2413MHz – 2473MHz

Maximum Antenna Gain: 4.4 dBi

Maximum EIRP Output Power: 0.0000708W

Following KDB 447498 D01, clause 4.3.1:

4.3.1 Exemption from Routine Evaluation Limits – RF Exposure Evaluation

RF Exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is less than 20 cm, except when the device operates as follows

For 100 MHz to 6 GHz and test separation distances \leq 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] $\cdot [\sqrt{f_{\text{(GHz)}}}] \le 3.0$ for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz

 $0.0708/(5)*\sqrt{2.473} = 0.0223 < 3$

Thus for <20cm portable usage, the SAR exclusion condition is fulfilled and SAR evaluation is not required for a separation distance of 5mm or more.