



TEST REPORT

Report No. : AE017412-001 Date : 2004 September 23

Application No.: LE210212(8)

Applicant : Kid Galaxy Inc.
One Sundial Ave,
Suite 310 Manchester,
NH 03103, U.S.A.

Sample Description : One(1) submitted sample stated to be RC Buggies
of Model No. 10405
Rating : 3 x 1.5V "AA" size battery
No. of sample(s) : Three (3) piece(s) ***

Date Received : 2004 September 07

Test Period : 2004 September 07 – 2004 September 21

Test Requested : FCC Part 15 Certification

Test Method : FCC Rules and Regulations Part 15 – Dec 2003
ANSI C63.4 – 2001

Test Result : See attached sheet(s) from page 2 to 11.

Conclusion : The submitted sample was found to comply with requirement of FCC
Part 15 Subpart B.

For and on behalf of
CMA Testing and Certification Laboratories

Authorized Signature : _____


Danny Chui

EMC Engineer - EL. Division

Page 1 of 11

FCC ID : QEABUGGIES49R



TEST REPORT

Report No. : AE017412-001

Date : 2004 September 23

Table of Contents

1	General Information	3
1.1	General Description.....	3
1.2	Related Submittal Grants	3
1.3	Location of the test site	4
1.4	List of measuring equipment	5
2	Description of the radiated emission test.....	6
2.1	Test Procedure	6
2.2	Test Result.....	6
2.3	Radiated Emission Measurement Data	7
3	Description of the Line-conducted Test	8
3.1	Test Procedure	8
3.2	Test Result.....	8
3.3	Graph and Table of Conducted Emission Measurement Data.....	8
4	Photograph	9
4.1	Photographs of the Test Setup for Radiated Emission and Conduction Emission.....	9
4.2	Photographs of the External and Internal Configurations of the EUT	9
5	Supplementary document	10
5.1	Bandwidth	10
6	Appendices	11



TEST REPORT

Report No. : AE017412-001

Date : 2004 September 23

1 General Information

1.1 General Description

The equipment under test (EUT) is a super regenerative receiver for RC Buggies Series. Operating at 49.860 MHz which is controlled by a LRC Circuit. The EUT is powered by 3 x 1.5V "AA" size battery. When the EUT is switched "on", it will spin moving. When it received a forward signal, it will stop spin moving and going forward.

The brief circuit description is listed as follows :

- Q4~Q9 and associated circuit act as control drive motor circuit.
- Q2~Q3 and associated circuit act as transistor amplifier.
- Q1 and associated circuit act as RF oscillation.

1.2 Related Submittal Grants

This is a single application for certification of a receiver. The transmitter for this receiver is authorized by Certification procedure.



TEST REPORT

Report No. : AE017412-001

Date : 2004 September 23

1.3 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2001. An Open Area Testing Site is set up for investigation and located at :

Top of the Roof, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2001. A double shielded room is located at :

Roof Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.



TEST REPORT

Report No. : AE017412-001

Date : 2004 September 23

1.4 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.	Calibration Certification No.
EMI Test Receiver	R&S	ESCS30	100001	S21141
Broadband Antenna	Schaffner	CBL6113B	2718	AC1753
Signal Generator	IFR	2023B	202302/938	Nil
LISN	R&S	ESH3-Z5	100038	S21142
Pulse Limiter	R&S	ESH3-Z2	100001	20-73194
Biconical Antenna	R&S	HK116	837414/004	4000.7752.02

FCC ID : QEABUGGIES49R

Page 5 of 11



TEST REPORT

Report No. : AE017412-001

Date : 2004 September 23

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2001.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

A signal generator was used to radiate an unmodulated continuous wave (CW) signal to the EUT (super regenerative receiver) at its operating frequency in order to “cohere” the characteristic broadband emissions from the receiver.

2.2 Test Result

The emissions meeting the requirement of section 15.109 are based on measurements employing the CISPR quasai-peak detector.

It was found that the EUT meet the FCC requirement.



TEST REPORT

Report No. : AE017412-001

Date : 2004 September 23

2.3 Radiated Emission Measurement Data

**Radiated emission
pursuant to
the requirement of FCC Part 15 subpart B**

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dB μ V/m)	Antenna and Cable factor (dB)	Field Strength (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
49.535	V	16.5	11.1	27.6	40.0	-12.4
50.180	V	21.4	8.7	30.1	40.0	-9.9
50.505	V	21.5	8.7	30.2	40.0	-9.8
53.095	V	15.8	8.7	24.5	40.0	-15.5
53.420	V	15.1	8.7	23.8	40.0	-16.2
98.790	V	13.9	10.0	23.9	43.5	-19.6
99.580	V	14.1	10.0	24.1	43.5	-19.4
147.621	V	11.9	12.4	24.3	43.5	-19.2
149.185	V	12.1	12.4	24.5	43.5	-19.0
197.012	V	14.6	10.5	25.1	43.5	-18.4



TEST REPORT

Report No. : AE017412-001

Date : 2004 September 23

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2001. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

No measurement is required as the EUT is a battery-operated product.

3.3 Graph and Table of Conducted Emission Measurement Data

Not Applicable



TEST REPORT

Report No. : AE017412-001

Date : 2004 September 23

4 Photograph

4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission

For electronic filing, the photos are saved with filename TSup1.jpg to TSup2.jpg

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho2.jpg.



TEST REPORT

Report No. : AE017412-001

Date : 2004 September 23

5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmp.jpg
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf

5.1 Bandwidth

NA

5.2 The duty cycle is simply the on-time divided by the period :

NA



TEST REPORT

Report No. : AE017412-001

Date : 2004 September 23

6 Appendices

A1.	Photos of the set-up of Radiated Emissions	1 page
A2.	Photos of External Configurations	1 page
A3.	Photos of Internal Configurations	1 page
A4.	ID Label/Location	1 page
A5.	Block Diagram	1 page
A6.	Schematics	1 page
A7.	User Manual	1 page
A8.	Operation Description	1 page

***** End of Report *****