MRE report

Applicant: Kid Galaxy Inc

Product Description: Cycle of R/C Motercycle Model No.: 10198, 10197, 10180, 10181

FCC ID: QEACYCLE2G4R

Frequency range: 2418MHz – 2472MHz

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for General Population/Uncontrolled Exposure

Frequency Range	Electric Field	Magnetic Field	Power Density	Averaging Time
(MHz)	Strength (V/m)	Strength (A/m)	(mW/cm^2)	(minutes)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100000	/	/	1.0	30

f = frequency in MHz

MPE Calculation Method

The MPE was calculated at 20cm to show compliance with the power density limit. The following formula was used to calculate the Power Density:

$$E\left(\frac{V}{m}\right) = \frac{\sqrt{(30*P*G)}}{d}$$
 Power Density: $Pd\left(\frac{W}{m^2}\right) = \frac{E^2}{377}$

E = Electric field (V/m)

P = Peak RF output power (W)

G = EUT Antenna numeric gain

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 * P * G}{377 * d^2}$$

Calculated Result and Limit

Maximum peak output power (dBm): -13.418 Maximum peak output power (mW): 0.0455

Distance (cm): 20

Frequency (MHz): 2472 Antenna Gain (dBi): -0.382

^{* =} Plane-wave equivalent power density

Antenna Gain (numeric): 0.916 Power density of prediction frequency at 20 cm (mW/cm²): 0.0000083 MPE limit for uncontrolled exposure at prediction frequency (mW/cm²): 1.0

The device is compliant with the requirement MPE limit for uncontrolled exposure. The maximum power density at the distance of 20 cm is $0.0000083~\text{mW/cm}^2$, limit is $1.0~\text{mW/cm}^2$.