

FCC Part 15B Compliance Test Report

Test Report no.:	Tre_FCC_0619_03.doc	Date of Report:	15.5.2006
Number of pages:	14	Customer's Contact person:	Alison Kingston
Testing laboratory:	TCC Nokia Tampere Laboratory P.O. Box 68 Sinitaival 5 FIN-33720 TAMPERE, FINLAND Tel. +358 (0) 7180 46800 Fax. +358 (0) 7180 46880	Client:	Nokia Corporation Nokia House Summit Avenue, Southwood FARNBOROUGH HAMPSHIRE GU14 0NG UK Tel. +44 1252 866000 Fax. +44 1252 866001
FCC listing no.:	94436		
IC recognition no.:	3608		
Tested devices/ accessories:	GSM phone RM-132 / Battery BP-6M, AC charger AC-4, Data cable CA-53, Laptop IBM Thinkpad T22, AC adapter 02K6543, Printer HP deskjet 1600CC3540A, Digital camera FUJI DS-7, Serial cable for camera, Parallel cable for printer		
FCC ID:	QFXRM-132	IC:	661Z-RM132
Supplement reports:	-		
Testing has been carried out in accordance with:	CFR 47, FCC rules Part 15 Subpart B, ANSI C63.4 (2003), ICES-003, CISPR 22 and IC standards RSS-132, RSS-133 and RSS-210. Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method and limit".		
Documentation:	The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.		
Test Results:	The EUT complies with the requirements in respect of all parameters subject to the test. The test results relate only to devices specified in this document.		
Date and signature for the contents:			

Jari Jantunen, System Manager

1. Summary for FCC Part 15B Compliance Test Report

Date of receipt	2.5.2006
Testing completed	9.5.2006
The customer's contact person	Alison Kingston
Test Plan referred to	\\EMC\\TESTPLAN\\
Notes	-
Document name	T:\\Projects\\RM-132\\EMC\\Results\\FCC\\Tre_FCC_0619_03.doc

1.1. EUT and Accessory Information

The EUT is a quadri band (GSM850/900/1800/1900) mobile phone with GPRS, EGPRS and Bluetooth. GSM bands are tested in idle mode. Bluetooth is tested with maximum rated TX power.

Product	Type	SN	HW	MV	SW	DUT
GSM phone	RM-132	004400711716512	5120	-	1.0613.0.4	40653
Battery	BP-6M	-	-	-	-	40599
AC-Charger	AC-4	-	1.1	1.0	-	40656
Data cable	CA-53	-	-	-	-	40658
Laptop	IBM Thinkpad T22	555V2PT	-	-	-	40201
AC Adapter	02K6543	-	-	-	-	40202
Printer	HP deskjet 1600CC3540A	USB8302546	-	-	-	40077
Digital camera	FUJI DS-7	7102516	-	-	-	40076
Serial cable for camera	-	-	-	-	-	40088
Parallel cable for printer	-	-	-	-	-	40087

1.2. Summary of Test Results

GSM 850:

Section in CFR 47	Section in ICES-003 (RSS-132)	Name of the test	Result
15.107, a	5.3	AC powerline conducted emissions	PASSED
15.109, a	5.5 (6.6)	Radiated emissions	PASSED

GSM 1900:

Section in CFR 47	Section in ICES-003 (RSS-133)	Name of the test	Result
15.107, a	5.3	AC powerline conducted emissions	PASSED
15.109, a	5.5 (9)	Radiated emissions	PASSED

Bluetooth:

Section in CFR 47	Section in ICES-003	Name of the test	Result
15.107, a	5.3	AC powerline conducted emissions	PASSED
15.109, a	5.5	Radiated emissions	PASSED

PASSED The EUT complies with the essential requirements in the standard.
 FAILED The EUT does not comply with the essential requirements in the standard.
 NP The test was not performed by the TCC Nokia Tampere Laboratory.


CONTENTS

1. Summary for FCC Part 15B Compliance Test Report.....	2
1.1. EUT and Accessory Information	2
1.2. Summary of Test Results.....	2
2. AC powerline conducted emissions (FCC §15.107, ICES-003 section 5.3).....	4
2.1. Test setup	4
2.2. Test method and limit.....	4
2.3. GSM 850 Test results	5
2.4. GSM 1900 Test results	6
2.5. Bluetooth Test results	7
3. Radiated emissions (FCC §15.109, ICES-003 section 5.5, RSS-132 6.6, RSS-133 9) 8	
3.1. Test setup	8
3.2. Test method and limit.....	8
3.3. GSM 850 Test results	9
3.4. GSM 1900 Test results	10
3.5. Bluetooth Test results	12
4. Test Equipment.....	14
4.1. Conducted measurements	14
4.2. Radiated measurements	14

2. AC powerline conducted emissions (FCC §15.107, ICES-003 section 5.3)

EUT with DUT number	RM-132 DUT 40653
Accessories with DUT numbers	BP-6M DUT 40599, HS-23 DUT 40655, AC-4 DUT 40656, CA-53 DUT 40658, IBM Thinkpad T22 DUT 40201, 02K6543 DUT 40202, HP deskjet 1600CC3540A DUT 40077, FUJI DS-7 DUT 40076, Serial cable for camera DUT 40088, Parallel cable for printer DUT 40087
Operation Voltage [V] / [Hz]	115 / 60
Result	PASSED
Remarks	Continuous data transfer was active between the phone and the computer during the test.
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	20 / 47 / 102.3
Date of measurements	9.5.2006
Measured by	Jari Jantunen

2.1. Test setup



2.2. Test method and limit

The measurement is made according to ANSI C63.4-2003 as follows:

The EUT is placed on a wooden table 80 cm above the reference groundplane.

The EUT is connected via LISN to a test power supply.

The measurement results are obtained as described below:

$$U [dB\mu V] = U_{RX} + A_{TOT}$$


Where U_{RX} is receiver reading and A_{TOT} is total correction factor including cable and pulse limiter attenuations.

CISPR 22 Class B limits

Frequency range [MHz]	Quasi peak limit [dBμV]	Average limit [dBμV]
0.15 - 0.5	66 - 56	56 - 46
0.5 - 5	56	46
5 - 30	60	50

2.3. GSM 850 Test results

RX mode, channel 190 / 881.6 MHz



Quasi peak (RBW: 9 kHz)


Frequency [MHz]	U [dBμV]	Line	Result
0.255000	31.40	L1	PASSED
0.400000	27.80	L1	PASSED
0.415000	27.30	N	PASSED
0.630000	25.00	L1	PASSED
2.565000	22.00	L1	PASSED
2.715000	24.50	L1	PASSED
2.735000	24.80	L1	PASSED
2.780000	24.10	L1	PASSED
2.850000	23.60	L1	PASSED
3.680000	21.60	L1	PASSED

Average (RBW: 9 kHz)

Frequency [MHz]	U [dBμV]	Line	Result
0.190000	29.20	L1	PASSED
0.485000	21.10	L1	PASSED
4.240000	26.00	L1	PASSED
22.500000	28.50	L1	PASSED

2.4. GSM 1900 Test results

RX mode, channel 661 / 1960.0 MHz



Quasi peak (RBW: 9 kHz)


Frequency [MHz]	U [dBμV]	Line	Result
0.155000	35.60	L1	PASSED
0.195000	33.60	N	PASSED
0.490000	26.20	N	PASSED
0.530000	25.70	L1	PASSED
2.425000	20.10	L1	PASSED
2.515000	20.80	L1	PASSED
2.650000	23.30	L1	PASSED
2.760000	24.30	L1	PASSED
2.780000	24.10	L1	PASSED
4.240000	26.60	L1	PASSED

Average (RBW: 9 kHz)

Frequency [MHz]	U [dBμV]	Line	Result
0.185000	29.30	L1	PASSED
0.300000	25.50	N	PASSED
0.455000	21.70	N	PASSED
4.240000	26.00	N	PASSED
22.500000	28.40	L1	PASSED

2.5. Bluetooth Test results

TX mode, channel 40 / 2442 MHz



Quasi peak (RBW: 9 kHz)

Frequency [MHz]	U [dBμV]	Line	Result
0.190000	34.20	L1	PASSED
0.340000	28.90	N	PASSED
0.460000	26.70	L1	PASSED
0.725000	25.00	L1	PASSED
2.695000	21.70	N	PASSED
2.720000	24.10	L1	PASSED
2.735000	24.10	L1	PASSED
2.875000	23.20	L1	PASSED
2.930000	20.70	L1	PASSED
2.960000	20.30	L1	PASSED

Average (RBW: 9 kHz)


Frequency [MHz]	U [dBμV]	Line	Result
0.190000	29.10	L1	PASSED
4.240000	26.00	L1	PASSED
22.500000	28.50	L1	PASSED

3. Radiated emissions

(FCC §15.109, ICES-003 section 5.5, RSS-132 6.6, RSS-133 9)

EUT with DUT number	RM-132 DUT 40653
Accessories with DUT numbers	BP-6M DUT 40599, HS-23 DUT 40655, AC-4 DUT 40656, CA-53 DUT 40658, IBM Thinkpad T22 DUT 40201, 02K6543 DUT 40202, HP deskjet 1600CC3540A DUT 40077, FUJI DS-7 DUT 40076, Serial cable for camera DUT 40088, Parallel cable for printer DUT 40087
Operation Voltage [V] / [Hz]	115 / 60
Result	PASSED
Remarks	Continuous data transfer was active between the phone and the computer during the test.
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	22 / 47 / 103.0
Date of measurements	8.5.2006
Measured by	Jari Jantunen

3.1. Test setup



3.2. Test method and limit

The measurement is made according to ANSI C63.4-2003as follows:

The measurement is performed in the Semi-Anechoic Chamber with conducting metal floor.

The measurement distance is 3 m.

The EUT is placed on a nonconductive plate at 80 cm height.

For each suspected frequency, the turntable is rotated 360 degrees and antenna is scanned from 1 to 4 m. This is repeated for both horizontal and vertical receive antenna polarizations.

The emissions less than 20 dB below the permissible value are reported.

The measurement results are obtained as described below:

$$E [\mu\text{V/m}] = U_{RX} + A_{TOT}$$

Where U_{RX} is receiver reading and A_{TOT} is total correction factor including cable loss, antenna factor and preamplifier gain ($A_{TOT} = L_{CABLES} + AF - G_{PREAMP}$).

CISPR 22 and FCC Part 15 Class B limits (3 m measurement distance)

Frequency range [MHz]	Quasi peak limit [dBμV/m]	Average limit [dBμV/m]	Peak limit [dBμV/m]
30 – 230	40	-	-
230 – 1000	47	-	-
Above 1000	-	54	74

3.3. GSM 850 Test results

RX mode, channel 128 / 869.2 MHz

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
3476.800000	38.80	87.10	43.70	-4.90	HORIZONTAL	PASSED
6953.600000	43.70	153.11	42.70	1.00	VERTICAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
3476.800000	26.40	20.89	31.30	-4.90	HORIZONTAL	PASSED
6953.600000	31.00	35.48	30.00	1.00	VERTICAL	PASSED

RX mode, channel 190 / 881.6 MHz

Quasi peak (RBW: 120 kHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
675.150701	21.00	11.22	46.40	-25.40	VERTICAL	PASSED
823.547295	20.30	10.35	43.10	-22.80	VERTICAL	PASSED
835.069339	24.40	16.60	47.60	-23.20	VERTICAL	PASSED
840.279359	24.60	16.98	48.00	-23.40	VERTICAL	PASSED
896.493587	32.80	43.65	55.30	-22.50	VERTICAL	PASSED

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
3526.400000	39.60	95.50	44.40	-4.80	HORIZONTAL	PASSED
7052.800000	42.90	139.64	41.60	1.30	VERTICAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
1296.089178	31.20	36.31	49.80	-18.60	VERTICAL	PASSED
2451.897796	28.40	26.30	37.50	-9.10	HORIZONTAL	PASSED
2462.419840	28.50	26.61	37.30	-8.80	VERTICAL	PASSED
3526.400000	26.30	20.65	31.10	-4.80	VERTICAL	PASSED
7052.800000	29.00	28.18	27.70	1.30	VERTICAL	PASSED

RX mode, channel 251 / 893.8 MHz

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
3575.200000	39.00	89.13	43.80	-4.80	HORIZONTAL	PASSED
7150.400000	42.70	136.46	40.70	2.00	HORIZONTAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
3575.200000	26.00	19.95	30.80	-4.80	HORIZONTAL	PASSED
7150.400000	29.20	28.84	27.20	2.00	HORIZONTAL	PASSED

3.4. GSM 1900 Test results

RX mode, channel 512 / 1930.2 MHz

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
3860.000000	40.00	100.00	42.70	-2.70	HORIZONTAL	PASSED
7720.000000	43.80	154.88	40.60	3.20	HORIZONTAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
3860.000000	27.40	23.44	30.10	-2.70	VERTICAL	PASSED
7720.000000	30.20	32.36	27.00	3.20	HORIZONTAL	PASSED

RX mode, channel 661 / 1960.0 MHz

Quasi peak (RBW: 120 kHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
501.402004	34.00	50.12	62.50	-28.50	VERTICAL	PASSED
646.192585	19.60	9.55	45.30	-25.70	HORIZONTAL	PASSED
697.896794	30.70	34.28	55.40	-24.70	VERTICAL	PASSED
838.175351	21.90	12.45	45.20	-23.30	VERTICAL	PASSED
862.925451	26.30	20.65	49.40	-23.10	VERTICAL	PASSED
896.091583	34.40	52.48	56.90	-22.50	VERTICAL	PASSED

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
3920.000000	41.00	112.20	43.30	-2.30	VERTICAL	PASSED
7840.000000	46.10	201.84	42.80	3.30	VERTICAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
1259.519038	34.70	54.33	54.00	-19.30	VERTICAL	PASSED
1293.589178	29.90	31.26	48.50	-18.60	VERTICAL	PASSED
1326.651303	29.80	30.90	48.40	-18.60	VERTICAL	PASSED
2445.889780	28.30	26.00	37.40	-9.10	VERTICAL	PASSED
3920.000000	27.90	24.83	30.20	-2.30	VERTICAL	PASSED
7840.000000	32.00	39.81	28.70	3.30	VERTICAL	PASSED

RX mode, channel 810 / 1989.8 MHz

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
3980.000000	42.30	130.32	44.30	-2.00	HORIZONTAL	PASSED
7960.000000	43.20	144.54	39.50	3.70	HORIZONTAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
3980.000000	28.50	26.61	30.50	-2.00	VERTICAL	PASSED
7960.000000	30.60	33.88	26.90	3.70	VERTICAL	PASSED

3.5. Bluetooth Test results

RX mode, channel 0 / 2402 MHz

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4804.000000	40.00	100.00	41.30	-1.30	VERTICAL	PASSED
7206.000000	42.40	131.83	40.40	2.00	HORIZONTAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4804.000000	27.90	24.83	29.20	-1.30	VERTICAL	PASSED
7206.000000	29.10	28.51	27.10	2.00	VERTICAL	PASSED

RX mode, channel 40 / 2442 MHz

Quasi peak (RBW: 120 kHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
38.195391	26.80	21.88	39.60	-12.80	VERTICAL	PASSED
245.791784	26.40	20.89	50.10	-23.70	HORIZONTAL	PASSED
270.040481	29.20	28.84	51.70	-22.50	VERTICAL	PASSED

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4884.000000	40.40	104.71	42.00	-1.60	VERTICAL	PASSED
7279.061122	43.80	154.88	41.10	2.70	VERTICAL	PASSED
7437.877756	43.60	151.36	40.40	3.20	VERTICAL	PASSED
17490.975952	52.50	421.70	34.50	18.00	VERTICAL	PASSED
17942.893788	55.40	588.84	34.10	21.30	VERTICAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4884.000000	27.90	24.83	29.50	-1.60	HORIZONTAL	PASSED
7415.327655	30.50	33.50	27.20	3.30	VERTICAL	PASSED
7438.877756	30.40	33.11	27.20	3.20	VERTICAL	PASSED
17486.475952	38.90	88.10	20.90	18.00	VERTICAL	PASSED
17949.393788	42.60	134.90	21.20	21.40	VERTICAL	PASSED

RX mode, channel 78 / 2480 MHz

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dB μ V/m]	E [μ V/m]	U _{RX} [dB μ V]	A _{TOT} [dB]	Polarisation	Result
4960.000000	40.90	110.92	41.90	-1.00	VERTICAL	PASSED
7440.000000	43.20	144.54	40.00	3.20	HORIZONTAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dB μ V/m]	E [μ V/m]	U _{RX} [dB μ V]	A _{TOT} [dB]	Polarisation	Result
4960.000000	28.30	26.00	29.30	-1.00	HORIZONTAL	PASSED
7440.000000	30.30	32.73	27.10	3.20	HORIZONTAL	PASSED

4. Test Equipment

4.1. Conducted measurements

Eq. No	Equipment	Type	Manufacturer	Used in
TM37610	Spectrum analyzer	FSU	R&S	15C,22/24
TM37678	Radio communication tester	CMU-200	R&S	15C,22/24
	Attenuator 10 dB	6251.17.A	Huber+Suhner AG	15C,22/24
TM22901	Step attenuator 110dB	8496A	Agilent	15C,22/24
TM37499	Power splitter	11667A	Agilent	15C,22/24
	Temperature chamber	VT4002	Vötsch	15C,22/24
TM38112	DC power supply	6632A	Agilent	15C,22/24
TM38111	Multimeter	34401A	Agilent	15C,22/24
TM38845	EMI receiver	ESI 40	R&S	15B,15C
TM37773	Radio communication tester	CMU-200	R&S	15B,15C
TM38631	Signal generator	83640L	Agilent	15B,15C
TM38114	DC power supply	6632A	Agilent	15B,15C
TM22835	Multimeter	87	Fluke	15B,15C
TM30600	Pulse Limiter	ESH3-Z2	R&S	15B,15C
TM26490	LISN 50 µH	ESH3-Z5/	R&S	15B,15C
TM30636	LISN 50 µH	L2-16/	PMM	15B,15C

4.2. Radiated measurements

Eq. No	Equipment	Type	Manufacturer	Used in
TM30599	3m semi-anechoic chamber		TDK	15B,15C, 22/24
TM38845	EMI receiver	ESI 40	R&S	15B,15C, 22/24
TM37498	Preamplifier	AMF-5D-020180-26-10P	MITEQ	15B,15C, 22/24
TM37523	Preamplifier	AMF-4D-10M-3G-25-20P	MITEQ	15B,15C, 22/24
TM37516	Biconilog antenna	HL562	R&S	15B,15C, 22/24
TM26496	Double ridged waveguide antenna	3115	EMCO	15B,15C, 22/24
TM39158	Horn antenna	3116	EMCO	15B,15C, 22/24
TM26492	Reference dipole set	UHAP/VHAP	Schwarzbeck	15B,15C, 22/24
TM37501	Dipole antenna	3125-870	EMCO	22/24
TM37502	Dipole antenna	3125-1880	EMCO	22/24
TM37773	Radio communication tester	CMU-200	R&S	15B,15C, 22/24
TM38631	Signal generator	83640L	Agilent	15B,15C, 22/24
TM38066	High pass filter	4HC3000/18000-3-KK	Trilithic	15B,15C, 22/24
	High pass filter	WHK2010-10SS	Trilithic	15B,15C, 22/24
	Low pass filter	WLK1750-10SS	Trilithic	15B,15C, 22/24
TM26511	Tunable notch filter	WRCA870	Wainwright	22/24
TM38215	Tunable notch filter	WRCD1850/1910-0.2/40	Wainwright	22/24
TM38214	Band reject filter	WRCT 2402/2480-2400/2483.5-30	Wainwright	15C
TM30642	Turntable controller	HD-100	Deisel	15B,15C, 22/24
TM26500	Turntable	DS412	Deisel	15B,15C, 22/24
TM38842	Antenna mast controller	2090	EMCO	15B,15C, 22/24
TM38843	Antenna mast	2075	EMCO	15B,15C, 22/24
TM38114	DC power supply	6632A	Agilent	15B,15C, 22/24
TM22835	Multimeter	87	Fluke	15B,15C, 22/24