

SAR Compliance Test Report

Test report no.:	Cph_SAR_0831_03	Date of report:	2008-07-29
Template version:	9.0	Number of pages:	95
Testing laboratory:	TCC Nokia Copenhagen Laboratory Frederikskaj 1790 COPENHAGEN V DENMARK Tel. +45 33 292929 Fax. +45 33 292934	Client:	Nokia Corporation Nokia House Summit Avenue, Southwood FARNBOROUGH HAMPSHIRE GU14 ONG UK Tel. +44 1252 866000 Fax. +44 1252 866001
Responsible test engineer:	Jesper Nielsen	Product contact person:	Markku Porttila
Measurements made by:	Lars Osterman & Jesper Nielsen		
Tested device:	RM-350		
FCC ID:	QFXRM-350	IC:	661Z-RM350
Supplement reports:	Cph_SAR_0831_04, Salo_SAR_0827_12 for RM-348 / QFXRM-348 / IC ID: 661Z-RM348		
Testing has been carried out in accordance with:	47CFR §2.1093 Radiofrequency Radiation Exposure Evaluation: Portable Devices FCC OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01) Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields RSS-102 Evaluation Procedure for Mobile and Portable Radio Transmitters with Respect to Health Canada's Safety Code 6 for Exposure of Humans to Radio Frequency Fields IEEE 1528 - 2003 IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Technique		
Documentation:	The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.		
Test results:	The tested device complies with the requirements in respect of all parameters subject to the test. The test results and statements relate only to the items tested. The test report shall not be reproduced except in full, without written approval of the laboratory.		
Date and signatures:			
For the contents:			

CONTENTS

1. SUMMARY OF SAR TEST REPORT.....	3
1.1 TEST DETAILS.....	3
1.2 MAXIMUM RESULTS.....	3
1.2.1 Head Configuration.....	3
1.2.2 Body Worn Configuration	4
1.2.3 Maximum Drift	4
1.2.4 Measurement Uncertainty	4
2. DESCRIPTION OF THE DEVICE UNDER TEST	5
2.1 DESCRIPTION OF THE ANTENNA	5
3. TEST CONDITIONS	6
3.1 TEMPERATURE AND HUMIDITY	6
3.2 TEST SIGNAL, FREQUENCIES AND OUTPUT POWER	6
4. DESCRIPTION OF THE TEST EQUIPMENT	7
4.1 MEASUREMENT SYSTEM AND COMPONENTS	7
4.1.1 Isotropic E-field Probe Type ES3DV3	9
4.2 PHANTOMS	9
4.3 TISSUE SIMULANTS	10
4.3.1 Tissue Simulant Recipes	10
4.3.2 System Checking	11
4.3.3 Tissue Simulants used in the Measurements.....	14
5. DESCRIPTION OF THE TEST PROCEDURE	16
5.1 DEVICE HOLDER.....	16
5.2 TEST POSITIONS.....	16
5.2.1 Against Phantom Head.....	16
5.2.2 Body Worn Configuration	17
5.3 SCAN PROCEDURES.....	17
5.4 SAR AVERAGING METHODS.....	17
6. MEASUREMENT UNCERTAINTY	18
7. RESULTS	19
APPENDIX A: SYSTEM CHECKING SCANS.....	26
APPENDIX B: MEASUREMENT SCANS.....	40
APPENDIX C: RELEVANT PAGES FROM PROBE CALIBRATION REPORT(S)	94
APPENDIX D: RELEVANT PAGES FROM DIPOLE VALIDATION KIT REPORT(S)	95

1. SUMMARY OF SAR TEST REPORT

1.1 Test Details

Period of test	2008-07-08 to 2008-08-04
SN, HW and SW numbers of tested device	SN: 004401/10/210598/4, HW: 4220, SW: 0.75, DUT: 25442 SN: 004401/10/096280/8, HW: 4000, SW: 0.70, DUT: 13032
Batteries used in testing	BL-6F, DUT: 25440, 13033, 13034, 13035
Headsets used in testing	HS-45, DUT: 25444, 13036
Other accessories used in testing	-
State of sample	Prototype unit
Notes	-

1.2 Maximum Results

The maximum measured SAR values for Head configuration and Body Worn configuration are given in section 1.2.1 and 1.2.2 respectively. The device conforms to the requirements of the standard(s) when the maximum measured SAR value is less than or equal to the limit.

1.2.1 Head Configuration

Mode	Ch / f (MHz)	Radiated power	Position	Measured SAR value (1g avg)	Scaled* SAR value (1g avg)	SAR limit (1g avg)	Result
**GSM850	251 / 848.8	29.2 dBm ERP	Right, Cheek	0.753 W/kg	0.84 W/kg	1.6 W/kg	PASSED
WCDMA850	4175 / 835.0	18.7 dBm ERP	Right, Cheek	0.541 W/kg	0.61 W/kg	1.6 W/kg	PASSED
**3-slot GPRS1900	810 / 1909.8	25.5 dBm EIRP	Left, Cheek	0.820 W/kg	0.92 W/kg	1.6 W/kg	PASSED
WCDMA1900	9538 / 1907.6	15.6 dBm EIRP	Left, Cheek	0.845 W/kg	0.95 W/kg	1.6 W/kg	PASSED
**WLAN2450	11 / 2562.0	23.9 dBm EIRP	Left, Cheek	0.427 W/kg	0.48 W/kg	1.6 W/kg	PASSED
**GSM850 + WLAN2450	-	-	Left, Cheek	1.114 W/kg	1.25 W/kg	1.6 W/kg	PASSED
WCDMA850 + WLAN2450	-	-	Left, Cheek	0.966 W/kg	1.08 W/kg	1.6 W/kg	PASSED
**3-slot GPRS1900 + WLAN2450	-	-	Left, Cheek	1.247 W/kg	1.40 W/kg	1.6 W/kg	PASSED
WCDMA1900 + WLAN2450	-	-	Left, Cheek	1.272 W/kg	1.42 W/kg	1.6 W/kg	PASSED

1.2.2 Body Worn Configuration

Mode	Ch / f (MHz)	Radiated power	Separation distance	Measured SAR value (1g avg)	Scaled* SAR value (1g avg)	SAR limit (1g avg)	Result
**GSM850	251 / 848.8	29.2 dBm ERP	1.5 cm	0.594 W/kg	0.67 W/kg	1.6 W/kg	PASSED
WCDMA850	4175 / 835.0	18.7 dBm ERP	1.5 cm	0.431 W/kg	0.48 W/kg	1.6 W/kg	PASSED
**3-slot GPRS1900	810 / 1909.8	25.5 dBm EIRP	1.5 cm	0.337 W/kg	0.38 W/kg	1.6 W/kg	PASSED
WCDMA1900	9262 / 1852.4	15.2 dBm EIRP	1.5 cm	0.443 W/kg	0.50 W/kg	1.6 W/kg	PASSED
**WLAN2450	11 / 2562.0	23.9 dBm EIRP	1.5 cm	0.417 W/kg	0.47 W/kg	1.6 W/kg	PASSED
**GSM850 + WLAN2450	-	-	1.5 cm	0.983 W/kg	1.10 W/kg	1.6 W/kg	PASSED
WCDMA850 + WLAN2450	-	-	1.5 cm	0.820 W/kg	0.92 W/kg	1.6 W/kg	PASSED
**3-slot GPRS1900 + WLAN2450	-	-	1.5 cm	0.726 W/kg	0.81 W/kg	1.6 W/kg	PASSED
WCDMA1900 + WLAN2450	-	-	1.5 cm	0.832 W/kg	0.93 W/kg	1.6 W/kg	PASSED

*SAR values are scaled up by 12% to cover measurement drift.

**SAR values taken from Salo_SAR_0827_12 for RM-348 / QFXRM-348 / IC ID: 661Z-RM348.

1.2.3 Maximum Drift

Maximum drift covered by 12% scaling up of the SAR values	Maximum drift during measurements
0.5dB	0.48 dB

1.2.4 Measurement Uncertainty

Expanded Uncertainty (k=2) 95%	± 25.8%
--------------------------------	---------

2. DESCRIPTION OF THE DEVICE UNDER TEST

Device category	Portable
Exposure environment	General population / uncontrolled

Modes of Operation	Bands	Modulation Mode	Duty Cycle	Transmitter Frequency Range (MHz)
GSM	850 1900	GMSK	1/8	824 – 849 1850 – 1910
GPRS	850 1900	GMSK	1/8 to 3/8	824 – 849 1850 – 1910
EGPRS	850 1900	GMSK / 8PSK	1/8 to 3/8	824 – 849 1850 – 1910
WCDMA	850 (Band V) 1900 (Band II)	-	1	826 – 847 1852 – 1908
BT	2450	GFSK	1	2402 – 2480
WLAN	2450	11Mbps QPSK	1	2412 – 2462

Outside of USA and Canada, the transmitter of the device is capable of operating also in GSM/GPRS/EGPRS900 and GSM/GPRS/EGPRS1800 bands which are not part of this filing.

This device has Voice-over-IP/Dual Transfer Mode capability for use at the ear. Therefore, SAR for multi slot GPRS mode was evaluated against the head profile of the phantom.

2.1 Description of the Antenna

The device has an internal antenna.

3. TEST CONDITIONS

3.1 Temperature and Humidity

Ambient temperature (°C):	20.5 to 22.5
Ambient humidity (RH %):	35 to 55

3.2 Test Signal, Frequencies and Output Power

The device was put into operation by using a call tester. Communication between the device and the call tester was established by air link.

The device output power was set to maximum power level for all tests; a fully charged battery was used for every test sequence.

The transmission mode of the device in all WCDMA tests was configured to 12.2kbps RMC with all TPC bits set as “1”.

In all operating bands the measurements were performed on lowest, middle and highest channels.

The radiated output power of the device was measured by a separate test laboratory on the same unit(s) as used for SAR testing.

Some of the SAR results, SAR plots and test details given in this report are duplicated from the earlier report Salo_SAR_0827_12 for RM-348 / FCC ID: QFXRM-348 / IC ID: 661Z-RM348. The difference between RM-350 and RM-348 is that RM-350 has had WCDMA900 and WCDMA2100 components replaced by WCDMA850 and WCDMA1900 components.

4. DESCRIPTION OF THE TEST EQUIPMENT

4.1 Measurement System and Components

The measurements were performed using an automated near-field scanning system, DASY4, manufactured by Schmid & Partner Engineering AG (SPEAG) in Switzerland. The SAR extrapolation algorithm used in all measurements was the 'advanced extrapolation' algorithm.

The following table lists calibration dates of SPEAG components:

Test Equipment	Serial Number	Calibration interval	Calibration expiry
DAE3	501	12 months	2009-03
DAE4	728	12 months	2009-04
DAE4	793	12 months	2009-04
E-field Probe ES3DV3	3118	12 months	2008-10
E-field Probe ES3DV3	3131	12 months	2009-04
E-field Probe ES3DV3	3165	12 months	2009-04
Dipole Validation Kit, D835V2	480	24 months	2009-05
Dipole Validation Kit, D835V2	4d042	24 months	2008-09
Dipole Validation Kit, D1900V2	5d013	24 months	2008-07
Dipole Validation Kit, D1900V2	5d026	24 months	2010-03
Dipole Validation Kit, D2450V2	729	24 months	2010-01
DASY4 software	Version 4.7	-	-

Additional test equipment used in testing:

Test Equipment	Model	Serial Number	Calibration interval	Calibration expiry
Signal Generator	SML03	101265	12 months	2009-07
Amplifier	ZHL-42 (SMA)	N072095-5	12 months	2009-07
Power Meter	NRVS	849305/028	12 months	2009-07
Power Sensor	NRV-Z32	839176/020	12 months	2009-07
Call Tester	CMU 200	101111	-	-
Call Tester	CMU 200	103293	-	-
Call Tester	CMU 200	100084	-	-
Vector Network Analyzer	8753E	US38432928	12 months	2009-07
Dielectric Probe Kit	85070B	US33020420	-	-
Signal Generator	SME06	848650/011	36 months	2009-03
Amplifier	2100-BBS3Q8CCJ	1003	-	-
Power Meter	NRP	100293	24 months	2009-07
Power Sensor	NRP-Z51	100830	24 months	2009-07
Call Tester	CMU200	105900	-	-
Call Tester	CMU200	110735	-	-
BT Tester	CBT	100263	-	-
Vector Network Analyzer	AT8753ES	MY40001091	12 months	2008-08
Dielectric Probe Kit	HP85070B	US33020403	-	-

4.1.1 Isotropic E-field Probe Type ES3DV3

Construction	Symmetrical design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., butyl diglycol)
Calibration	Calibration certificate in Appendix C
Frequency	10 MHz to 4 GHz (dosimetry); Linearity: ± 0.2 dB (30 MHz to 4 GHz)
Directivity	± 0.2 dB in HSL (rotation around probe axis) ± 0.3 dB in HSL (rotation normal to probe axis)
Dynamic Range	5 μ W/g to > 100 mW/g; Linearity: ± 0.2 dB
Dimensions	Overall length: 330 mm Tip length: 20 mm Body diameter: 12 mm Tip diameter: 3.9 mm Distance from probe tip to dipole centers: 2.0 mm
Application	General dosimetry up to 4 GHz Compliance tests of mobile phones Fast automatic scanning in arbitrary phantoms

4.2 Phantoms

The phantom used for all tests i.e. for both system checks and device testing, was the twin-headed "SAM Phantom", manufactured by SPEAG. The phantom conforms to the requirements of IEEE 1528 - 2003.

System checking was performed using the flat section, whilst Head SAR tests used the left and right head profile sections. Body SAR testing also used the flat section between the head profiles.

The SPEAG device holder (see Section 5.1) was used to position the device in all tests whilst a tripod was used to position the validation dipoles against the flat section of phantom.

4.3 Tissue Simulants

Recommended values for the dielectric parameters of the tissue simulants are given in IEEE 1528 - 2003 and FCC Supplement C to OET Bulletin 65. All tests were carried out using simulants whose dielectric parameters were within $\pm 5\%$ of the recommended values. All tests were carried out within 24 hours of measuring the dielectric parameters.

The depth of the tissue simulant was 15.0 ± 0.5 cm measured from the ear reference point during system checking and device measurements.

4.3.1 Tissue Simulant Recipes

The following recipe(s) were used for Head and Body tissue simulant(s):

800MHz band		
Ingredient	Head (% by weight)	Body (% by weight)
Deionised Water	39.74	55.97
HEC	0.25	1.21
Sugar	58.31	41.76
Preservative	0.15	0.27
Salt	1.55	0.79

800MHz band		
Ingredient	Head (% by weight)	Body (% by weight)
Deionised Water	51.50	69.25
Tween 20	47.35	30.00
Salt	1.15	0.75

1900MHz band

Ingredient	Head (% by weight)	Body (% by weight)
Deionised Water	54.88	69.02
Butyl Diglycol	44.91	30.76
Salt	0.21	0.22

1900MHz band

Ingredient	Head (% by weight)	Body (% by weight)
Deionised Water	54.50	70.25
Tween 20	45.23	29.41
Salt	0.27	0.34

2450MHz band

Ingredient	Head (% by weight)	Body (% by weight)
Deionised Water	56.0	70.20
Tween 20	44.0	29.62
Salt	-	0.18

4.3.2 System Checking

The manufacturer calibrates the probes annually. Dielectric parameters of the tissue simulants were measured every day using the dielectric probe kit and the network analyser. A system check measurement was made following the determination of the dielectric parameters of the simulant, using the dipole validation kit. A power level of 250 mW was supplied to the dipole antenna, which was placed under the flat section of the twin SAM phantom. The system checking results (dielectric parameters and SAR values) are given in the table below.

System checking, head tissue simulant

f [MHz]	Description	SAR [W/kg], 1g	Dielectric Parameters		Temp [°C]
			ϵ_r	σ [S/m]	
835	Reference result	2.33	42.2	0.90	
	± 10% window	2.10 - 2.56			
	2008-07-18	2.31	41.2	0.90	21.9
	2008-07-30	2.33	40.5	0.89	21.0
835	Reference result	2.29	41.6	0.90	
	± 10% window	2.06 - 2.52			
	2008-08-01	2.33	41.0	0.90	21.0
1900	Reference result	9.69	39.3	1.44	
	± 10% window	8.72 - 10.66			
	2008-07-08	10.3	38.8	1.40	21.0
	2008-07-30	10.6	38.4	1.42	21.0
1900	Reference result	10.3	40.2	1.47	
	± 10% window	9.3 - 11.3			
	2008-07-21	10.3	40.0	1.46	22.1
	2008-07-31	10.0	38.8	1.42	20.9
2450	Reference result	14.3	37.8	1.82	
	± 10% window	12.9 - 15.7			
	2008-07-09	13.9	39.1	1.82	21.0
	2008-07-31	14.3	38.8	1.86	21.0

System checking, body tissue simulant

f [MHz]	Description	SAR [W/kg], 1g	Dielectric Parameters		Temp [°C]
			ϵ_r	σ [S/m]	
835	Reference result	2.45	53.8	0.98	
	$\pm 10\%$ window	2.20 - 2.70			
	2008-07-21	2.49	54.0	0.96	21.8
835	Reference result	2.48	53.0	0.98	
	$\pm 10\%$ window	2.23 - 2.73			
	2008-08-04	2.60	54.5	0.99	21.0
1900	Reference result	10.1	52.3	1.57	
	$\pm 10\%$ window	9.1 - 11.1			
	2008-07-09	9.51	51.3	1.52	21.0
1900	Reference result	10.5	51.7	1.57	
	$\pm 10\%$ window	9.5 - 11.5			
	2008-07-22	10.2	53.4	1.62	22.4

Plots of the system checking scans are given in Appendix A.

4.3.3 Tissue Simulants used in the Measurements

Head tissue simulant measurements

f [MHz]	Description	Dielectric Parameters		Temp [°C]
		ϵ_r	σ [S/m]	
836	Recommended value	41.5	0.90	
	$\pm 5\%$ window	39.4 – 43.6	0.86 – 0.95	
	2008-07-18	41.2	0.90	21.9
	2008-07-30	40.5	0.89	21.0
	2008-08-01	41.0	0.90	21.0
1880	Recommended value	40.0	1.40	
	$\pm 5\%$ window	38.0 – 42.0	1.33 – 1.47	
	2008-07-08	38.8	1.38	21.0
	2008-07-21	40.0	1.44	22.1
	2008-07-30	38.5	1.40	21.0
	2008-07-31	38.9	1.39	20.9
2442	Recommended value	39.2	1.79	
	$\pm 5\%$ window	37.3 – 41.2	1.70 – 1.88	
	2008-07-09	39.1	1.81	21.0
	2008-07-31	38.8	1.85	21.0

Body tissue simulant measurements

f [MHz]	Description	Dielectric Parameters		Temp [°C]
		ϵ_r	σ [S/m]	
836	Recommended value	55.2	0.97	
	$\pm 5\%$ window	52.4 – 58.0	0.92 – 1.02	
	2008-07-21	54.0	0.97	21.8
	2008-08-04	54.5	0.99	21.0
1880	Recommended value	53.3	1.52	
	$\pm 5\%$ window	50.6 – 56.0	1.44 – 1.60	
	2008-07-08	51.3	1.49	21.0
	2008-07-09	51.4	1.50	21.0
	2008-07-22	53.4	1.60	22.4
2442	Recommended value	52.7	1.94	
	$\pm 5\%$ window	50.1 – 55.3	1.85 – 2.04	
	2008-07-09	50.8	1.98	21.0

5. DESCRIPTION OF THE TEST PROCEDURE

5.1 Device Holder

The device was placed in the device holder (illustrated below) that is supplied by SPEAG as an integral part of the Dasy system.



Device holder supplied by SPEAG

A Nokia designed spacer (illustrated below) was used to position the device within the SPEAG holder. The spacer positions the device so that the holder has minimal effect on the test results but still holds the device securely. The spacer was removed before the tests.



Nokia spacer

5.2 Test Positions

5.2.1 Against Phantom Head

Measurements were made in “cheek” and “tilt” positions on both the left hand and right hand sides of the phantom.

The positions used in the measurements were according to IEEE 1528 - 2003 "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques".

5.2.2 Body Worn Configuration

The device was placed in the SPEAG holder using the Nokia spacer and placed below the flat section of the phantom. The distance between the device and the phantom was kept at the separation distance indicated in Section 1.2.2 using a separate flat spacer that was removed before the start of the measurements. The device was oriented with both sides facing the phantom to find the highest results.

5.3 Scan Procedures

First, area scans were used for determination of the field distribution. Next, a zoom scan, a minimum of 5x5x7 points covering a volume of at least 30x30x30mm, was performed around the highest E-field value to determine the averaged SAR value. Drift was determined by measuring the same point at the start of the area scan and again at the end of the zoom scan.

5.4 SAR Averaging Methods

The maximum SAR value was averaged over a cube of tissue using interpolation and extrapolation.

The interpolation, extrapolation and maximum search routines within Dasy4 are all based on the modified Quadratic Shepard's method (Robert J. Renka, "Multivariate Interpolation Of Large Sets Of Scattered Data", University of North Texas ACM Transactions on Mathematical Software, vol. 14, no. 2, June 1988, pp. 139-148).

The interpolation scheme combines a least-square fitted function method with a weighted average method. A trivariate 3-D / bivariate 2-D quadratic function is computed for each measurement point and fitted to neighbouring points by a least-square method. For the zoom scan, inverse distance weighting is incorporated to fit distant points more accurately. The interpolating function is finally calculated as a weighted average of the quadratics.

In the zoom scan, the interpolation function is used to extrapolate the Peak SAR from the deepest measurement points to the inner surface of the phantom.

6. MEASUREMENT UNCERTAINTY

Table 6.1 – Measurement uncertainty evaluation

Uncertainty Component	Section in IEEE 1528	Tol. (%)	Prob Dist	Div	C_i	$C_i \cdot U_i$ (%)	V_i
Measurement System							
Probe Calibration	E2.1	±5.9	N	1	1	±5.9	∞
Axial Isotropy	E2.2	±4.7	R	√3	$(1-c_p)^{1/2}$	±1.9	∞
Hemispherical Isotropy	E2.2	±9.6	R	√3	$(c_p)^{1/2}$	±3.9	∞
Boundary Effect	E2.3	±1.0	R	√3	1	±0.6	∞
Linearity	E2.4	±4.7	R	√3	1	±2.7	∞
System Detection Limits	E2.5	±1.0	R	√3	1	±0.6	∞
Readout Electronics	E2.6	±1.0	N	1	1	±1.0	∞
Response Time	E2.7	±0.8	R	√3	1	±0.5	∞
Integration Time	E2.8	±2.6	R	√3	1	±1.5	∞
RF Ambient Conditions - Noise	E6.1	±3.0	R	√3	1	±1.7	∞
RF Ambient Conditions - Reflections	E6.1	±3.0	R	√3	1	±1.7	∞
Probe Positioner Mechanical Tolerance	E6.2	±0.4	R	√3	1	±0.2	∞
Probe Positioning with respect to Phantom Shell	E6.3	±2.9	R	√3	1	±1.7	∞
Extrapolation, interpolation and Integration Algorithms for Max. SAR Evaluation	E5	±3.9	R	√3	1	±2.3	∞
Test sample Related							
Test Sample Positioning	E4.2	±6.0	N	1	1	±6.0	11
Device Holder Uncertainty	E4.1	±5.0	N	1	1	±5.0	7
Output Power Variation - SAR drift measurement	6.6.3	±0.0	R	√3	1	±0.0	∞
Phantom and Tissue Parameters							
Phantom Uncertainty (shape and thickness tolerances)	E3.1	±4.0	R	√3	1	±2.3	∞
Conductivity Target - tolerance	E3.2	±5.0	R	√3	0.64	±1.8	∞
Conductivity - measurement uncertainty	E3.3	±5.5	N	1	0.64	±3.5	5
Permittivity Target - tolerance	E3.2	±5.0	R	√3	0.6	±1.7	∞
Permittivity - measurement uncertainty	E3.3	±2.9	N	1	0.6	±1.7	5
Combined Standard Uncertainty			RSS			±12.9	116
Coverage Factor for 95%			k=2				
Expanded Uncertainty						±25.8	

7. RESULTS

The measured Head SAR values for the test device are tabulated below:

850 MHz Head SAR results

Option used	Test configuration		SAR, averaged over 1g (W/kg)		
			Ch 128 824.2 MHz	Ch 190 836.6 MHz	Ch 251 848.8 MHz
GSM	Power		27.8 dBm	29.2 dBm	29.2 dBm
Camera slide closed	Left	Cheek	-	0.687	-
		Tilt	-	0.344	-
	Right	Cheek	0.629	0.711	0.739
		Tilt	-	0.354	-
2-slot GPRS	Power		24.8 dBm	26.1 dBm	25.9 dBm
Camera slide closed	Left	Cheek	-	0.597	-
		Tilt	-	-	-
	Right	Cheek	-	-	-
		Tilt	-	-	-
3-slot GPRS	Power		23.1 dBm	24.2 dBm	24.0 dBm
Camera slide closed	Left	Cheek	-	0.564	-
		Tilt	-	-	-
	Right	Cheek	-	-	-
		Tilt	-	-	-
1-slot 8PSK EGPRS	Power		17.5 dBm	20.1 dBm	18.2 dBm
Camera slide closed	Left	Cheek	-	-	-
		Tilt	-	-	-
	Right	Cheek	-	-	0.105
		Tilt	-	-	-
GSM Camera slide open	Right cheek		0.667	0.745	0.753

850 MHz Head SAR results - continued

Option used	Test configuration		SAR, averaged over 1g (W/kg)		
			Ch 4132 826.4 MHz	Ch 4175 835.0 MHz	Ch 4233 846.6 MHz
WCDMA	Power		24.4 dBm	18.7 dBm	19.0 dBm
Camera slide closed	Left	Cheek	-	0.539	-
		Tilt	-	0.244	-
	Right	Cheek	0.418	0.541	0.495
		Tilt	-	0.310	-
WCDMA Camera slide open	Right Cheek		0.409	0.536	0.481
GSM Camera slide open	Right cheek, BT active		-	-	0.724

1900 MHz Head SAR results

Mode	Test configuration		SAR, averaged over 1g (W/kg)		
			Ch 512 1850.2 MHz	Ch 661 1880.0 MHz	Ch 810 1909.8 MHz
GSM	Power		29.1 dBm	30.0 dBm	29.6 dBm
Camera slide closed	Left	Cheek	-	0.603	-
		Tilt	-	-	-
	Right	Cheek	-	-	-
		Tilt	-	-	-
2-slot GPRS	Power		26.8 dBm	27.7 dBm	27.3 dBm
Camera slide closed	Left	Cheek	-	0.652	-
		Tilt	-	-	-
	Right	Cheek	-	-	-
		Tilt	-	-	-
3-slot GPRS	Power		25.2 dBm	26.0 dBm	25.5 dBm
Camera slide closed	Left	Cheek	0.484	0.668	0.688
		Tilt	-	0.210	-
	Right	Cheek	-	0.489	-
		Tilt	-	0.222	-
3-slot 8PSK EGPRS	Power		25.3 dBm	25.8 dBm	25.1 dBm
Camera slide closed	Left	Cheek	-	-	0.461
		Tilt	-	-	-
	Right	Cheek	-	-	-
		Tilt	-	-	-
3-slot GPRS Camera slide open	Left Cheek		0.571	0.700	0.820

1900 MHz Head SAR results - continued

Option used	Test configuration		SAR, averaged over 1g (W/kg)		
			Ch 9262 1852.4 MHz	Ch 9400 1880.0 MHz	Ch 9538 1907.6 MHz
WCDMA	Power		15.2 dBm	16.7 dBm	15.6 dBm
Camera slide closed	Left	Cheek	0.784	0.789	0.845
		Tilt	-	0.219	-
	Right	Cheek	-	0.601	-
		Tilt	-	0.303	-
WCDMA Camera slide open	Left Cheek		0.633	0.644	0.689
WCDMA Camera slide closed	Left Cheek, BT active		-	-	0.796

2450 MHz Head SAR results

Mode	Test configuration		SAR, averaged over 1g (W/kg)		
			Ch 1 2412.0 MHz	Ch 7 2442.0 MHz	Ch 11 2462.0 MHz
WLAN	Power		22.4 dBm	24.6 dBm	23.9 dBm
Camera slide closed	Left	Cheek	0.306	0.330	0.362
		Tilt	-	0.278	-
	Right	Cheek	-	0.204	-
		Tilt	-	0.229	-
Camera slide open	Left Cheek		0.362	0.386	0.427

The measured Body SAR values for the test device are tabulated below:

850 MHz Body SAR results

Option used	Device orientation	Test configuration	SAR, averaged over 1g (W/kg)		
			Ch 128 824.2 MHz	Ch 190 836.6 MHz	Ch 251 848.8 MHz
GSM		Power	27.8 dBm	29.2 dBm	29.2 dBm
Camera slide closed	Display facing phantom	Without headset	-	0.490	-
		Headset HS-45	-	0.281	-
	Back facing phantom	Without headset	0.481	0.552	0.594
		Headset HS-45	-	0.292	-
Option used	Device orientation	Test configuration	Ch 4132 826.4 MHz	Ch 4175 835.0 MHz	Ch 4233 846.6 MHz
WCDMA		Power	24.4 dBm	18.7 dBm	19.0 dBm
Camera slide closed	Display facing phantom	Without headset	-	0.405	-
		Headset AD-54+HS-45	-	0.245	-
	Back facing phantom	Without headset	0.311	0.431	0.403
		Headset AD-54+HS-45	-	0.250	-
GSM Camera slide closed	Back facing phantom	Without headset, BT active	-	-	0.593

1900 MHz Body SAR results

Option used	Device orientation	Test configuration	SAR, averaged over 1g (W/kg)		
			Ch 512 1850.2 MHz	Ch 661 1880.0 MHz	Ch 810 1909.8 MHz
3-slot GPRS		Power	25.2 dBm	26.0 dBm	25.5 dBm
Camera slide closed	Display facing phantom	Without headset	-	0.203	-
		Headset HS-45	-	0.176	-
	Back facing phantom	Without headset	0.236	0.292	0.337
		Headset HS-45	-	0.245	-
Option used	Device orientation	Test configuration	Ch 9262 1852.4 MHz	Ch 9400 1880.0 MHz	Ch 9538 1907.6 MHz
WCDMA		Power	15.2 dBm	16.7 dBm	15.6 dBm
Camera slide closed	Display facing phantom	Without headset	-	0.266	-
		Headset AD-54+HS-45	-	0.243	-
	Back facing phantom	Without headset	0.443	0.409	0.416
		Headset AD-54+HS-45	-	0.379	-
WCDMA Camera slide closed	Back facing phantom	Without headset BT active	0.441	-	-

2450MHz Body SAR results

Option used	Device orientation	Test configuration	SAR, averaged over 1g (W/kg)		
			Ch 1 2412.0 MHz	Ch 7 2442.0 MHz	Ch 11 2462.0 MHz
WLAN		Power	22.4 dBm	24.6 dBm	23.9 dBm
Camera slide closed	Display facing phantom	Without headset	-	-	-
		Headset HS-45	-	-	-
	Back facing phantom	Without headset	-	0.389	-
		Headset HS-45	0.323	0.392	0.414

Simultaneous transmissions: Combined SAR results

Test configuration	Max. 1g SAR results				
	WLAN2450	GSM850	WCDMA850	3-slot GPRS1900	WCDMA1900
Head: Left, Cheek	0.427	0.687	0.539	0.820	0.845
Head: Left, Tilt	0.278	0.344	0.244	0.210	0.219
Head: Right, Cheek	0.204	0.753	0.541	0.489	0.601
Head: Right, Tilt	0.229	0.354	0.310	0.222	0.303
Body: Without Headset	0.389	0.594	0.431	0.337	0.443
Body: Headset HS-45	0.414	0.292	0.250	0.245	0.335

Simultaneous transmissions: Combined SAR results

Test configuration	Combined 1g SAR values			
	WLAN2450 + GSM850	WLAN2450 + WCDMA850	WLAN2450 + 3-slot GPRS1900	WLAN2450 + WCDMA1900
Head: Left, Cheek	1.114	0.966	1.247	1.272
Head: Left, Tilt	0.622	0.522	0.488	0.497
Head: Right, Cheek	0.957	0.745	0.693	0.805
Head: Right, Tilt	0.583	0.539	0.451	0.532
Body: Without Headset	0.983	0.820	0.726	0.832
Body: Headset HS-45	0.706	0.664	0.659	0.749

Combining the maximum SAR values of WLAN2450 and the cellular bands tends to overestimate the SAR value since their maxima do not necessarily occur in the same location.

Plots of the Measurement scans are given in Appendix B.

APPENDIX A: SYSTEM CHECKING SCANS

See the following pages

Date/Time: 2008-07-18 11:20:13

Test Laboratory: TCC Nokia
Type: D835V2; Serial: 4d042

Communication System: CW835

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: Head 850; Medium Notes: Medium Temperature: 21.9 C

Medium parameters used: $f = 835$ MHz; $\sigma = 0.898$ mho/m; $\epsilon_r = 41.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3118; Probe Notes:
- ConvF(5.99, 5.99, 5.99); Calibrated: 2007-10-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn501; Calibrated: 2008-03-17
- Phantom: SAM 4; Type: Twin Phantom; Serial: TP-1410
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

d=15mm, Pin=250mW/Area Scan (61x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 2.46 mW/g

d=15mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 51.8 V/m


Peak SAR (extrapolated) = 3.38 W/kg

SAR(1 g) = 2.31 mW/g

SAR(10 g) = 1.51 mW/g

Power Drift = 0.022 dB

Maximum value of SAR (measured) = 2.50 mW/g



Date/Time: 2008-07-30 15:41:15

Test Laboratory: TCC Nokia
Type: D835V2; Serial: 4d042

Communication System: CW835

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: Head 850; Medium Notes: Medium Temperature: 21.0 C

Medium parameters used: $f = 835$ MHz; $\sigma = 0.89$ mho/m; $\epsilon_r = 40.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3118; Probe Notes:
- ConvF(5.99, 5.99, 5.99); Calibrated: 2007-10-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn501; Calibrated: 2008-03-17
- Phantom: SAM 4; Type: Twin Phantom; Serial: TP-1410
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

d=15mm, Pin=250mW/Area Scan (61x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 2.50 mW/g

d=15mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 51.8 V/m


Peak SAR (extrapolated) = 3.42 W/kg

SAR(1 g) = 2.33 mW/g

SAR(10 g) = 1.53 mW/g

Power Drift = -0.004 dB

Maximum value of SAR (measured) = 2.53 mW/g



Date/Time: 2008-08-01 08:42:53

Test Laboratory: TCC Nokia
Type: D835V2; Serial: D835V2 - SN:480

Communication System: CW835

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: HSL850; Medium Notes: 20.8C

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.903 \text{ mho/m}$; $\epsilon_r = 41$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3131
- ConvF(6.14, 6.14, 6.14); Calibrated: 2008-04-22
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2008-04-23
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

d=15mm, Pin=250mW/Area Scan (61x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 2.50 mW/g

d=15mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 53.5 V/m


Peak SAR (extrapolated) = 3.49 W/kg

SAR(1 g) = 2.33 mW/g

SAR(10 g) = 1.52 mW/g

Power Drift = -0.015 dB

Maximum value of SAR (measured) = 2.53 mW/g



Date/Time: 2008-07-08 09:18:03

Test Laboratory: TCC Nokia
Type: D1900V2; Serial: D1900V2 - SN:5d013

Communication System: CW1900

Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: HSL1900; Medium Notes: 21.2C

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.4$ mho/m; $\epsilon_r = 38.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3131
- ConvF(5.02, 5.02, 5.02); Calibrated: 2008-04-22
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2008-04-23
- Phantom: SAM 3; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

d=15mm, Pin=250mW/Area Scan (61x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 12.1 mW/g

d=15mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 94.6 V/m


Peak SAR (extrapolated) = 18.7 W/kg

SAR(1 g) = 10.3 mW/g

SAR(10 g) = 5.38 mW/g

Power Drift = -0.028 dB

Maximum value of SAR (measured) = 11.6 mW/g



Date/Time: 2008-07-30 12:42:42

Test Laboratory: TCC Nokia
Type: D1900V2; Serial: D1900V2 - SN:5d013

Communication System: CW1900

Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: HSL1900; Medium Notes: 20.7C

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.42$ mho/m; $\epsilon_r = 38.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3131
- ConvF(5.02, 5.02, 5.02); Calibrated: 2008-04-22
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2008-04-23
- Phantom: SAM 3; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

d=15mm, Pin=250mW/Area Scan (61x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 12.5 mW/g

d=15mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 93.9 V/m


Peak SAR (extrapolated) = 19.3 W/kg

SAR(1 g) = 10.6 mW/g

SAR(10 g) = 5.51 mW/g

Power Drift = -0.030 dB

Maximum value of SAR (measured) = 12.0 mW/g



Date/Time: 2008-07-21 14:23:49

Test Laboratory: TCC Nokia
Type: D1900V2; Serial: 5d026

Communication System: CW1900

Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: Head 1900; Medium Notes: Medium Temperature: 22.1 C

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 40$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3118; Probe Notes:
- ConvF(5.26, 5.26, 5.26); Calibrated: 2007-10-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn501; Calibrated: 2008-03-17
- Phantom: SAM 2; Type: Twin Phantom; Serial: TP-1037
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

d=10mm, Pin=250mW/Area Scan (71x71x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 11.7 mW/g

d=10mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 90.4 V/m


Peak SAR (extrapolated) = 19.5 W/kg

SAR(1 g) = 10.3 mW/g

SAR(10 g) = 5.32 mW/g

Power Drift = 0.042 dB

Maximum value of SAR (measured) = 11.7 mW/g



Date/Time: 2008-07-31 16:33:25

Test Laboratory: TCC Nokia
Type: D1900V2; Serial: 5d026

Communication System: CW1900

Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: Head 1900; Medium Notes: Medium Temperature: 20.9 C

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.42$ mho/m; $\epsilon_r = 38.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3118; Probe Notes:
- ConvF(5.26, 5.26, 5.26); Calibrated: 2007-10-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn501; Calibrated: 2008-03-17
- Phantom: SAM 6; Type: SAM Twin Phantom; Serial: TP-1301
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

d=15mm, Pin=250mW/Area Scan (61x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 11.6 mW/g

d=15mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 88.4 V/m


Peak SAR (extrapolated) = 18.6 W/kg

SAR(1 g) = 10 mW/g

SAR(10 g) = 5.16 mW/g

Power Drift = 0.042 dB

Maximum value of SAR (measured) = 11.2 mW/g



Date/Time: 2008-07-09 11:34:54

Test Laboratory: TCC Nokia

Type: D2450V2; Serial: D2450V2 - SN:729

Communication System: CW2450

Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: HSL2450; Medium Notes: 21.6C

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.82$ mho/m; $\epsilon_r = 39.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3165
- ConvF(4.57, 4.57, 4.57); Calibrated: 2008-04-23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn793; Calibrated: 2008-04-30
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1449
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

d=15mm, Pin=250mW/Area Scan (61x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 16.8 mW/g

d=15mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 94.3 V/m


Peak SAR (extrapolated) = 29.2 W/kg

SAR(1 g) = 13.9 mW/g

SAR(10 g) = 6.47 mW/g

Power Drift = -0.033 dB

Maximum value of SAR (measured) = 15.8 mW/g



Date/Time: 2008-07-31 12:24:40

Test Laboratory: TCC Nokia

Type: D2450V2; Serial: D2450V2 - SN:729

Communication System: CW2450

Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: HSL2450; Medium Notes: 21.5 C

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.86$ mho/m; $\epsilon_r = 38.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3165
- ConvF(4.57, 4.57, 4.57); Calibrated: 2008-04-23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn793; Calibrated: 2008-04-30
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1449
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

d=15mm, Pin=250mW/Area Scan (61x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 17.1 mW/g

d=15mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 93.8 V/m


Peak SAR (extrapolated) = 30.4 W/kg

SAR(1 g) = 14.3 mW/g

SAR(10 g) = 6.6 mW/g

Power Drift = 0.025 dB

Maximum value of SAR (measured) = 16.4 mW/g



Date/Time: 2008-07-21 09:58:42

Test Laboratory: TCC Nokia
Type: D835V2; Serial: 4d042

Communication System: CW835

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: Body 850; Medium Notes: Medium Temperature: 21.8 C

Medium parameters used: $f = 835$ MHz; $\sigma = 0.965$ mho/m; $\epsilon_r = 54$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3118; Probe Notes:
- ConvF(5.59, 5.59, 5.59); Calibrated: 2007-10-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn501; Calibrated: 2008-03-17
- Phantom: SAM 5; Type: Twin Phantom; Serial: TP-1412
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

d=15mm, Pin=250mW/Area Scan (61x121x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 2.67 mW/g

d=15mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 52.6 V/m


Peak SAR (extrapolated) = 3.56 W/kg

SAR(1 g) = 2.49 mW/g

SAR(10 g) = 1.65 mW/g

Power Drift = 0.094 dB

Maximum value of SAR (measured) = 2.69 mW/g



Date/Time: 2008-08-04 14:42:51

Test Laboratory: TCC Nokia
Type: D835V2; Serial: D835V2 - SN:480

Communication System: CW850

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: BSL850; Medium Notes: 21.0C

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.992 \text{ mho/m}$; $\epsilon_r = 54.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3131
- ConvF(5.68, 5.68, 5.68); Calibrated: 2008-04-22
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2008-04-23
- Phantom: SAM 3; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

d=15mm, Pin=250mW/Area Scan (61x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 2.79 mW/g

d=15mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 53.8 V/m


Peak SAR (extrapolated) = 3.80 W/kg

SAR(1 g) = 2.6 mW/g

SAR(10 g) = 1.71 mW/g

Power Drift = -0.014 dB

Maximum value of SAR (measured) = 2.81 mW/g



Date/Time: 2008-07-09 09:02:12

Test Laboratory: TCC Nokia
Type: D1900V2; Serial: D1900V2 - SN:5d013

Communication System: CW1900

Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: BSL1900; Medium Notes: 20.6C

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.52$ mho/m; $\epsilon_r = 51.3$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3131
- ConvF(5.15, 5.15, 5.15); Calibrated: 2008-04-22
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2008-04-23
- Phantom: SAM 2; Type: Twin SAM 040 CA; Serial: TP - 1177
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

d=15mm, Pin=250mW/Area Scan (61x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 11.5 mW/g

d=15mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 86.2 V/m


Peak SAR (extrapolated) = 16.9 W/kg

SAR(1 g) = 9.51 mW/g

SAR(10 g) = 4.98 mW/g

Power Drift = -0.016 dB

Maximum value of SAR (measured) = 10.8 mW/g



Date/Time: 2008-07-22 09:59:26

Test Laboratory: TCC Nokia
Type: D1900V2; Serial: 5d026

Communication System: CW1900

Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: Body 1900; Medium Notes: Medium Temperature: 22.4 C

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.62$ mho/m; $\epsilon_r = 53.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3118; Probe Notes:
- ConvF(4.92, 4.92, 4.92); Calibrated: 2007-10-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn501; Calibrated: 2008-03-17
- Phantom: SAM 3; Type: Twin Phantom; Serial: TP-1302
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

d=10mm, Pin=250mW/Area Scan (71x71x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 11.8 mW/g

d=10mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 85.7 V/m


Peak SAR (extrapolated) = 18.7 W/kg

SAR(1 g) = 10.2 mW/g

SAR(10 g) = 5.29 mW/g

Power Drift = -0.050 dB

Maximum value of SAR (measured) = 11.6 mW/g



APPENDIX B: MEASUREMENT SCANS

See the following pages

Date/Time: 2008-08-01 10:34:19

Test Laboratory: TCC Nokia

Type: RM-348; Serial: 004401/10/096280/8

Communication System: GSM850

Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: HSL850; Medium Notes: 20.6C

Medium parameters used: $f = 837$ MHz; $\sigma = 0.904$ mho/m; $\epsilon_r = 41$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3131; Probe Notes:
- ConvF(6.14, 6.14, 6.14); Calibrated: 2008-04-22
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2008-04-23
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position – Middle - Camera slide closed/Area Scan (51x91x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.737 mW/g

Cheek position - Middle - Camera slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 8.98 V/m

Peak SAR (extrapolated) = 0.886 W/kg


SAR(1 g) = 0.687 mW/g

SAR(10 g) = 0.499 mW/g

Power Drift = -0.071 dB

Warning: Maximum averaged SAR over 10 g is located on the boundary of the measurement cube. This cube might not incorporate the absolute averaged SAR. Please consider a refinement of the Area Scan measurement.

Maximum value of SAR (measured) = 0.723 mW/g



Date/Time: 2008-08-01 11:59:09

Test Laboratory: TCC Nokia

Type: RM-348; Serial: 004401/10/096280/8

Communication System: GSM850

Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: HSL850; Medium Notes: 20.6C

Medium parameters used: $f = 837$ MHz; $\sigma = 0.904$ mho/m; $\epsilon_r = 41$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3131; Probe Notes:
- ConvF(6.14, 6.14, 6.14); Calibrated: 2008-04-22
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2008-04-23
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Tilt position – Middle - Camera slide closed/Area Scan (51x91x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.363 mW/g

Tilt position - Middle - Camera slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 12.5 V/m

Peak SAR (extrapolated) = 0.439 W/kg

SAR(1 g) = 0.344 mW/g

SAR(10 g) = 0.254 mW/g

Power Drift = -0.039 dB

Maximum value of SAR (measured) = 0.362 mW/g



Date/Time: 2008-08-01 15:50:26

Test Laboratory: TCC Nokia

Type: RM-348; Serial: 004401/10/096280/8

Communication System: GSM850

Frequency: 848.8 MHz; Duty Cycle: 1:8.3

Medium: HSL850; Medium Notes: 20.3C

Medium parameters used: $f = 849$ MHz; $\sigma = 0.913$ mho/m; $\epsilon_r = 41$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3131; Probe Notes:
- ConvF(6.14, 6.14, 6.14); Calibrated: 2008-04-22
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2008-04-23
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position – High - Camera slide closed/Area Scan (51x91x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.803 mW/g

Cheek position - High - Camera slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 9.58 V/m


Peak SAR (extrapolated) = 0.962 W/kg

SAR(1 g) = 0.739 mW/g

SAR(10 g) = 0.534 mW/g

Power Drift = -0.006 dB

Maximum value of SAR (measured) = 0.790 mW/g



Date/Time: 2008-08-01 15:12:54

Test Laboratory: TCC Nokia
Type: RM-348; Serial: 004401/10/096280/8

Communication System: GSM850

Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: HSL850; Medium Notes: 20.3C

Medium parameters used: $f = 837$ MHz; $\sigma = 0.904$ mho/m; $\epsilon_r = 41$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3131; Probe Notes:
- ConvF(6.14, 6.14, 6.14); Calibrated: 2008-04-22
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2008-04-23
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Tilt position – Middle - Camera slide closed/Area Scan (51x91x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.373 mW/g

Tilt position – Middle - Camera slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 14.4 V/m


Peak SAR (extrapolated) = 0.459 W/kg

SAR(1 g) = 0.354 mW/g

SAR(10 g) = 0.260 mW/g

Power Drift = -0.022 dB

Maximum value of SAR (measured) = 0.374 mW/g



Date/Time: 2008-08-01 10:54:49

Test Laboratory: TCC Nokia

Type: RM-348; Serial: 004401/10/096280/8

Communication System: 2-slot GPRS850

Frequency: 836.6 MHz; Duty Cycle: 1:4.2

Medium: HSL850; Medium Notes: 20.6C

Medium parameters used: $f = 837$ MHz; $\sigma = 0.904$ mho/m; $\epsilon_r = 41$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3131; Probe Notes:
- ConvF(6.14, 6.14, 6.14); Calibrated: 2008-04-22
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2008-04-23
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - Middle - Camera slide closed/Area Scan (51x91x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.625 mW/g

Cheek position - Middle - Camera slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 8.24 V/m

Peak SAR (extrapolated) = 0.764 W/kg


SAR(1 g) = 0.597 mW/g

SAR(10 g) = 0.435 mW/g

Power Drift = 0.242 dB

Warning: Maximum averaged SAR over 10 g is located on the boundary of the measurement cube. This cube might not incorporate the absolute averaged SAR. Please consider a refinement of the Area Scan measurement.

Maximum value of SAR (measured) = 0.628 mW/g



Date/Time: 2008-08-01 11:21:39

Test Laboratory: TCC Nokia

Type: RM-348; Serial: 004401/10/096280/8

Communication System: 3-slot GPRS850

Frequency: 836.6 MHz; Duty Cycle: 1:2.8

Medium: HSL850; Medium Notes: 20.6C

Medium parameters used: $f = 837$ MHz; $\sigma = 0.904$ mho/m; $\epsilon_r = 41$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3131; Probe Notes:
- ConvF(6.14, 6.14, 6.14); Calibrated: 2008-04-22
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2008-04-23
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position, Middle - Camera slide closed/Area Scan (51x91x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.598 mW/g

Cheek position, Middle - Camera slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 8.21 V/m


Peak SAR (extrapolated) = 0.735 W/kg

SAR(1 g) = 0.564 mW/g

SAR(10 g) = 0.412 mW/g

Power Drift = 0.018 dB

Maximum value of SAR (measured) = 0.593 mW/g



Date/Time: 2008-08-01 16:09:35

Test Laboratory: TCC Nokia

Type: RM-348; Serial: 004401/10/096280/8

Communication System: 1-slot 8PSK EGPRS850

Frequency: 849 MHz; Duty Cycle: 1:8.3

Medium: HSL850; Medium Notes: 20.3C

Medium parameters used: $f = 849$ MHz; $\sigma = 0.913$ mho/m; $\epsilon_r = 41$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3131; Probe Notes:
- ConvF(6.14, 6.14, 6.14); Calibrated: 2008-04-22
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2008-04-23
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position – High - Camera slide closed/Area Scan (51x91x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.112 mW/g

Cheek position – High - Camera slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 3.64 V/m


Peak SAR (extrapolated) = 0.137 W/kg

SAR(1 g) = 0.105 mW/g

SAR(10 g) = 0.077 mW/g

Power Drift = 0.143 dB

Maximum value of SAR (measured) = 0.112 mW/g



Date/Time: 2008-08-01 18:38:10

Test Laboratory: TCC Nokia

Type: RM-348; Serial: 004401/10/096280/8

Communication System: GSM850

Frequency: 848.8 MHz; Duty Cycle: 1:8.3

Medium: HSL850; Medium Notes: 20.3C

Medium parameters used: $f = 849$ MHz; $\sigma = 0.913$ mho/m; $\epsilon_r = 41$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3131; Probe Notes:
- ConvF(6.14, 6.14, 6.14); Calibrated: 2008-04-22
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2008-04-23
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position – High - Camera slide open/Area Scan (51x91x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.812 mW/g

Cheek position – High - Camera slide open/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 10.3 V/m


Peak SAR (extrapolated) = 0.978 W/kg

SAR(1 g) = 0.753 mW/g

SAR(10 g) = 0.543 mW/g

Power Drift = 0.009 dB

Maximum value of SAR (measured) = 0.805 mW/g



Date/Time: 2008-07-18 14:49:52

Test Laboratory: TCC Nokia

Type: RM-350; Serial: 004401/10/210598/4

Communication System: WCDMA850

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: Head 850; Medium Notes: Medium Temperature: 21.9 C

Medium parameters used: $f = 835$ MHz; $\sigma = 0.898$ mho/m; $\epsilon_r = 41.2$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3118; Probe Notes:
- ConvF(5.99, 5.99, 5.99); Calibrated: 2007-10-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn501; Calibrated: 2008-03-17
- Phantom: SAM 4; Type: Twin Phantom; Serial: TP-1410
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position – Middle – Camera slide closed/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.570 mW/g

Cheek position - Middle – Camera slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 11.6 V/m


Peak SAR (extrapolated) = 0.680 W/kg

SAR(1 g) = 0.539 mW/g

SAR(10 g) = 0.394 mW/g

Power Drift = -0.283 dB

Maximum value of SAR (measured) = 0.578 mW/g



Date/Time: 2008-07-18 15:05:04

Test Laboratory: TCC Nokia

Type: RM-350; Serial: 004401/10/210598/4

Communication System: WCDMA850

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: Head 850; Medium Notes: Medium Temperature: 21.9 C

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.898 \text{ mho/m}$; $\epsilon_r = 41.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3118; Probe Notes:
- ConvF(5.99, 5.99, 5.99); Calibrated: 2007-10-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn501; Calibrated: 2008-03-17
- Phantom: SAM 4; Type: Twin Phantom; Serial: TP-1410
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Tilt position - Middle – Camera slide closed/Area Scan (51x101x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 0.253 mW/g

Tilt position - Middle – Camera slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 13.7 V/m


Peak SAR (extrapolated) = 0.305 W/kg

SAR(1 g) = 0.244 mW/g

SAR(10 g) = 0.181 mW/g

Power Drift = 0.046 dB

Maximum value of SAR (measured) = 0.255 mW/g



Date/Time: 2008-07-18 17:48:04

Test Laboratory: TCC Nokia

Type: RM-350; Serial: 004401/10/210598/4

Communication System: WCDMA850

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: Head 850; Medium Notes: Medium Temperature: 21.9 C

Medium parameters used: $f = 835$ MHz; $\sigma = 0.898$ mho/m; $\epsilon_r = 41.2$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3118; Probe Notes:
- ConvF(5.99, 5.99, 5.99); Calibrated: 2007-10-26
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn501; Calibrated: 2008-03-17
- Phantom: SAM 4; Type: Twin Phantom; Serial: TP-1410
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - Middle – Camera slide closed/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.573 mW/g

Cheek position - Middle – Camera slide closed/Zoom Scan (7x7x8)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 10.4 V/m

Peak SAR (extrapolated) = 0.679 W/kg


SAR(1 g) = 0.541 mW/g

SAR(10 g) = 0.401 mW/g

Power Drift = 0.043 dB

Warning: Maximum averaged SAR over 10 g is located on the boundary of the measurement cube. This cube might not incorporate the absolute averaged SAR. Please consider a refinement of the Area Scan measurement.

Maximum value of SAR (measured) = 0.570 mW/g



Date/Time: 2008-07-18 16:15:59

Test Laboratory: TCC Nokia

Type: RM-350; Serial: 004401/10/210598/4

Communication System: WCDMA850

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: Head 850; Medium Notes: Medium Temperature: 21.9 C

Medium parameters used: $f = 835$ MHz; $\sigma = 0.898$ mho/m; $\epsilon_r = 41.2$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3118; Probe Notes:
- ConvF(5.99, 5.99, 5.99); Calibrated: 2007-10-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn501; Calibrated: 2008-03-17
- Phantom: SAM 4; Type: Twin Phantom; Serial: TP-1410
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Tilt position - Middle – Camera slide closed/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.322 mW/g

Tilt position - Middle – Camera slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 12.9 V/m


Peak SAR (extrapolated) = 0.384 W/kg

SAR(1 g) = 0.310 mW/g

SAR(10 g) = 0.231 mW/g

Power Drift = 0.001 dB

Maximum value of SAR (measured) = 0.327 mW/g



Date/Time: 2008-07-30 22:36:55

Test Laboratory: TCC Nokia

Type: RM-350; Serial: 004401/10/210598/4

Communication System: WCDMA850

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: Head 850; Medium Notes: Medium Temperature: 21.0 C

Medium parameters used: $f = 835$ MHz; $\sigma = 0.89$ mho/m; $\epsilon_r = 40.5$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3118; Probe Notes:
- ConvF(5.99, 5.99, 5.99); Calibrated: 2007-10-26
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn501; Calibrated: 2008-03-17
- Phantom: SAM 4; Type: Twin Phantom; Serial: TP-1410
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - Middle - Camera slide open/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.565 mW/g

Cheek position - Middle - Camera slide open/Zoom Scan (7x7x8)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 8.23 V/m


Peak SAR (extrapolated) = 0.668 W/kg

SAR(1 g) = 0.536 mW/g

SAR(10 g) = 0.398 mW/g

Power Drift = 0.058 dB

Maximum value of SAR (measured) = 0.566 mW/g



Date/Time: 2008-08-01 18:23:37

Test Laboratory: TCC Nokia

Type: RM-348; Serial: 004401/10/096280/8

Communication System: GSM850

Frequency: 848.8 MHz; Duty Cycle: 1:8.3

Medium: HSL850; Medium Notes: 20.3C

Medium parameters used: $f = 849$ MHz; $\sigma = 0.913$ mho/m; $\epsilon_r = 41$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3131; Probe Notes:
- ConvF(6.14, 6.14, 6.14); Calibrated: 2008-04-22
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2008-04-23
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position – High - Camera slide open – BT Active/Area Scan (51x91x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.790 mW/g

Cheek position - High - Camera slide open – BT Active/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 10.00 V/m


Peak SAR (extrapolated) = 0.947 W/kg

SAR(1 g) = 0.724 mW/g

SAR(10 g) = 0.520 mW/g

Power Drift = -0.041 dB

Maximum value of SAR (measured) = 0.775 mW/g



Date/Time: 2008-07-08 10:02:56

Test Laboratory: TCC Nokia

Type: RM-348; Serial: 004401/10/096280/8

Communication System: GSM1900

Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: HSL1900; Medium Notes: 20.9C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.38$ mho/m; $\epsilon_r = 38.8$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3131; Probe Notes:
- ConvF(5.02, 5.02, 5.02); Calibrated: 2008-04-22
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2008-04-23
- Phantom: SAM 3; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - Middle – Camera slide closed/Area Scan (51x91x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.653 mW/g

Cheek position - Middle – Camera slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 7.48 V/m


Peak SAR (extrapolated) = 0.916 W/kg

SAR(1 g) = 0.603 mW/g

SAR(10 g) = 0.348 mW/g

Power Drift = -0.378 dB

Maximum value of SAR (measured) = 0.659 mW/g



Date/Time: 2008-07-08 10:24:30

Test Laboratory: TCC Nokia

Type: RM-348; Serial: 004401/10/096280/8

Communication System: 2-slot GPRS1900

Frequency: 1880 MHz; Duty Cycle: 1:4.2

Medium: HSL1900; Medium Notes: 20.9C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.38$ mho/m; $\epsilon_r = 38.8$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3131; Probe Notes:
- ConvF(5.02, 5.02, 5.02); Calibrated: 2008-04-22
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2008-04-23
- Phantom: SAM 3; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - Middle – Camera slide closed/Area Scan (51x91x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.706 mW/g

Cheek position - Middle – Camera slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 7.55 V/m


Peak SAR (extrapolated) = 0.985 W/kg

SAR(1 g) = 0.652 mW/g

SAR(10 g) = 0.377 mW/g

Power Drift = -0.172 dB

Maximum value of SAR (measured) = 0.710 mW/g



Date/Time: 2008-07-08 12:27:52

Test Laboratory: TCC Nokia
Type: RM-348; Serial: 004401/10/096280/8

Communication System: 3-slot GPRS1900

Frequency: 1909.8 MHz; Duty Cycle: 1:2.8

Medium: HSL1900; Medium Notes: 20.9C

Medium parameters used: $f = 1910$ MHz; $\sigma = 1.41$ mho/m; $\epsilon_r = 38.7$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3131; Probe Notes:
- ConvF(5.02, 5.02, 5.02); Calibrated: 2008-04-22
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2008-04-23
- Phantom: SAM 3; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - High – Camera slide closed/Area Scan (51x91x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.757 mW/g

Cheek position - High – Camera slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 8.29 V/m


Peak SAR (extrapolated) = 1.04 W/kg

SAR(1 g) = 0.688 mW/g

SAR(10 g) = 0.397 mW/g

Power Drift = 0.077 dB

Maximum value of SAR (measured) = 0.743 mW/g



Date/Time: 2008-07-08 11:09:14

Test Laboratory: TCC Nokia
Type: RM-348; Serial: 004401/10/096280/8

Communication System: 3-slot GPRS1900

Frequency: 1880 MHz; Duty Cycle: 1:2.8

Medium: HSL1900; Medium Notes: 20.9C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.38$ mho/m; $\epsilon_r = 38.8$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3131; Probe Notes:
- ConvF(5.02, 5.02, 5.02); Calibrated: 2008-04-22
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2008-04-23
- Phantom: SAM 3; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Tilt position - Middle – Camera slide closed/Area Scan (51x91x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.240 mW/g

Tilt position - Middle – Camera slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 10.7 V/m


Peak SAR (extrapolated) = 0.299 W/kg

SAR(1 g) = 0.210 mW/g

SAR(10 g) = 0.133 mW/g

Power Drift = 0.005 dB

Maximum value of SAR (measured) = 0.224 mW/g



Date/Time: 2008-07-08 11:30:01

Test Laboratory: TCC Nokia
Type: RM-348; Serial: 004401/10/096280/8

Communication System: 3-slot GPRS1900

Frequency: 1880 MHz; Duty Cycle: 1:2.8

Medium: HSL1900; Medium Notes: 20.8C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.38$ mho/m; $\epsilon_r = 38.8$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3131; Probe Notes:
- ConvF(5.02, 5.02, 5.02); Calibrated: 2008-04-22
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2008-04-23
- Phantom: SAM 3; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - Middle – Camera slide closed/Area Scan (51x91x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.519 mW/g

Cheek position - Middle – Camera slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 6.59 V/m


Peak SAR (extrapolated) = 0.783 W/kg

SAR(1 g) = 0.489 mW/g

SAR(10 g) = 0.279 mW/g

Power Drift = -0.215 dB

Maximum value of SAR (measured) = 0.536 mW/g



Date/Time: 2008-07-08 11:46:40

Test Laboratory: TCC Nokia

Type: RM-348; Serial: 004401/10/096280/8

Communication System: 3-slot GPRS1900

Frequency: 1880 MHz; Duty Cycle: 1:2.8

Medium: HSL1900; Medium Notes: 20.8C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.38$ mho/m; $\epsilon_r = 38.8$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3131; Probe Notes:
- ConvF(5.02, 5.02, 5.02); Calibrated: 2008-04-22
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2008-04-23
- Phantom: SAM 3; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Tilt position - Middle – Camera slide closed/Area Scan (51x91x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.260 mW/g

Tilt position - Middle – Camera slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 9.38 V/m


Peak SAR (extrapolated) = 0.330 W/kg

SAR(1 g) = 0.222 mW/g

SAR(10 g) = 0.138 mW/g

Power Drift = -0.017 dB

Maximum value of SAR (measured) = 0.239 mW/g



Date/Time: 2008-07-08 13:44:14

Test Laboratory: TCC Nokia

Type: RM-348; Serial: 004401/10/096280/8

Communication System: 3-slot 8PSK EGPRS1900

Frequency: 1909.8 MHz; Duty Cycle: 1:2.8

Medium: HSL1900; Medium Notes: 20.9C

Medium parameters used: $f = 1910$ MHz; $\sigma = 1.41$ mho/m; $\epsilon_r = 38.7$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3131; Probe Notes:
- ConvF(5.02, 5.02, 5.02); Calibrated: 2008-04-22
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2008-04-23
- Phantom: SAM 3; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - High – Camera slide closed/Area Scan (51x91x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.505 mW/g

Cheek position - High – Camera slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 5.77 V/m


Peak SAR (extrapolated) = 0.705 W/kg

SAR(1 g) = 0.461 mW/g

SAR(10 g) = 0.265 mW/g

Power Drift = 0.478 dB

Maximum value of SAR (measured) = 0.502 mW/g



Date/Time: 2008-07-30 17:45:31

Test Laboratory: TCC Nokia

Type: RM-348; Serial: 004401/10/096280/8

Communication System: 3-slot GPRS1900

Frequency: 1909.8 MHz; Duty Cycle: 1:2.8

Medium: HSL1900; Medium Notes: 20.8C

Medium parameters used: $f = 1910$ MHz; $\sigma = 1.43$ mho/m; $\epsilon_r = 38.4$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3131; Probe Notes:
- ConvF(5.02, 5.02, 5.02); Calibrated: 2008-04-22
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2008-04-23
- Phantom: SAM 3; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - High – Camera slide open/Area Scan (51x91x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.887 mW/g

Cheek position - High – Camera slide open/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 7.59 V/m


Peak SAR (extrapolated) = 1.24 W/kg

SAR(1 g) = 0.820 mW/g

SAR(10 g) = 0.466 mW/g

Power Drift = 0.019 dB

Maximum value of SAR (measured) = 0.898 mW/g



Date/Time: 2008-07-21 17:16:51

Test Laboratory: TCC Nokia

Type: RM-350; Serial: 004401/10/210598/4

Communication System: WCDMA1900

Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium: Head 1900; Medium Notes: Medium Temperature: 22.1 C

Medium parameters used: $f = 1908$ MHz; $\sigma = 1.47$ mho/m; $\epsilon_r = 39.9$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3118; Probe Notes:
- ConvF(5.26, 5.26, 5.26); Calibrated: 2007-10-26
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn501; Calibrated: 2008-03-17
- Phantom: SAM 2; Type: Twin Phantom; Serial: TP-1037
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - High – Camera slide closed/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.887 mW/g

Cheek position - High – Camera slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 8.69 V/m


Peak SAR (extrapolated) = 1.34 W/kg

SAR(1 g) = 0.845 mW/g

SAR(10 g) = 0.476 mW/g

Power Drift = 0.105 dB

Maximum value of SAR (measured) = 0.892 mW/g



Date/Time: 2008-07-21 15:51:22

Test Laboratory: TCC Nokia

Type: RM-350; Serial: 004401/10/210598/4

Communication System: WCDMA1900

Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: Head 1900; Medium Notes: Medium Temperature: 22.1 C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 40$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3118; Probe Notes:
- ConvF(5.26, 5.26, 5.26); Calibrated: 2007-10-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn501; Calibrated: 2008-03-17
- Phantom: SAM 2; Type: Twin Phantom; Serial: TP-1037
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Tilt position - Middle – Camera slide closed/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.259 mW/g

Tilt position - Middle – Camera slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 11.6 V/m


Peak SAR (extrapolated) = 0.323 W/kg

SAR(1 g) = 0.219 mW/g

SAR(10 g) = 0.140 mW/g

Power Drift = 0.000 dB

Maximum value of SAR (measured) = 0.233 mW/g



Date/Time: 2008-07-21 16:14:49

Test Laboratory: TCC Nokia

Type: RM-350; Serial: 004401/10/210598/4

Communication System: WCDMA1900

Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: Head 1900; Medium Notes: Medium Temperature: 22.1 C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 40$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3118; Probe Notes:
- ConvF(5.26, 5.26, 5.26); Calibrated: 2007-10-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn501; Calibrated: 2008-03-17
- Phantom: SAM 2; Type: Twin Phantom; Serial: TP-1037
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - Middle – Camera slide closed/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.656 mW/g

Cheek position - Middle – Camera slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 8.02 V/m


Peak SAR (extrapolated) = 1.01 W/kg

SAR(1 g) = 0.601 mW/g

SAR(10 g) = 0.341 mW/g

Power Drift = 0.060 dB

Maximum value of SAR (measured) = 0.634 mW/g



Date/Time: 2008-07-21 16:32:29

Test Laboratory: TCC Nokia

Type: RM-350; Serial: 004401/10/210598/4

Communication System: WCDMA1900

Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: Head 1900; Medium Notes: Medium Temperature: 22.1 C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 40$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3118; Probe Notes:
- ConvF(5.26, 5.26, 5.26); Calibrated: 2007-10-26
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn501; Calibrated: 2008-03-17
- Phantom: SAM 2; Type: Twin Phantom; Serial: TP-1037
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Tilt position - Middle – Camera slide closed/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.354 mW/g

Tilt position - Middle – Camera slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 12.2 V/m


Peak SAR (extrapolated) = 0.459 W/kg

SAR(1 g) = 0.303 mW/g

SAR(10 g) = 0.186 mW/g

Power Drift = 0.055 dB

Maximum value of SAR (measured) = 0.329 mW/g



Date/Time: 2008-07-31 19:45:17

Test Laboratory: TCC Nokia

Type: RM-350; Serial: 004401/10/210598/4

Communication System: WCDMA1900

Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium: Head 1900; Medium Notes: Medium Temperature: 20.9 C

Medium parameters used: $f = 1908$ MHz; $\sigma = 1.42$ mho/m; $\epsilon_r = 38.8$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3118; Probe Notes:
- ConvF(5.26, 5.26, 5.26); Calibrated: 2007-10-26
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn501; Calibrated: 2008-03-17
- Phantom: SAM 6; Type: SAM Twin Phantom; Serial: TP-1301
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - High - Camera slide open/Area Scan (51x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.719 mW/g

Cheek position - High - Camera slide open/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 7.06 V/m


Peak SAR (extrapolated) = 1.09 W/kg

SAR(1 g) = 0.689 mW/g

SAR(10 g) = 0.391 mW/g

Power Drift = 0.012 dB

Maximum value of SAR (measured) = 0.762 mW/g



Date/Time: 2008-07-21 17:32:57

Test Laboratory: TCC Nokia

Type: RM-350; Serial: 004401/10/210598/4

Communication System: WCDMA1900

Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium: Head 1900; Medium Notes: Medium Temperature: 22.1 C

Medium parameters used: $f = 1908$ MHz; $\sigma = 1.47$ mho/m; $\epsilon_r = 39.9$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3118; Probe Notes:
- ConvF(5.26, 5.26, 5.26); Calibrated: 2007-10-26
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn501; Calibrated: 2008-03-17
- Phantom: SAM 2; Type: Twin Phantom; Serial: TP-1037
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - High – Camera slide closed - BT Active/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.824 mW/g

Cheek position - High – Camera slide closed - BT Active/Zoom Scan (5x5x7)/Cube 0: Measurement grid:

dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 8.58 V/m


Peak SAR (extrapolated) = 1.26 W/kg

SAR(1 g) = 0.796 mW/g

SAR(10 g) = 0.448 mW/g

Power Drift = 0.080 dB

Maximum value of SAR (measured) = 0.853 mW/g



Date/Time: 2008-07-09 13:58:23

Test Laboratory: TCC Nokia

Type: RM-348; Serial: 004401/10/096280/8

Communication System: WLAN 2450

Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: HSL2450; Medium Notes: 21.2C

Medium parameters used: $f = 2462$ MHz; $\sigma = 1.84$ mho/m; $\epsilon_r = 39$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3165; Probe Notes:
- ConvF(4.57, 4.57, 4.57); Calibrated: 2008-04-23
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn793; Calibrated: 2008-04-30
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1449
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - High – Camera slide closed/Area Scan (51x91x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.352 mW/g

Cheek position - High – Camera slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 10.8 V/m


Peak SAR (extrapolated) = 0.762 W/kg

SAR(1 g) = 0.362 mW/g

SAR(10 g) = 0.174 mW/g

Power Drift = 0.187 dB

Maximum value of SAR (measured) = 0.409 mW/g



Date/Time: 2008-07-09 12:48:45

Test Laboratory: TCC Nokia

Type: RM-348; Serial: 004401/10/096280/8

Communication System: WLAN 2450

Frequency: 2442 MHz; Duty Cycle: 1:1

Medium: HSL2450; Medium Notes: 21.2C

Medium parameters used: $f = 2442$ MHz; $\sigma = 1.81$ mho/m; $\epsilon_r = 39.1$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3165; Probe Notes:
- ConvF(4.57, 4.57, 4.57); Calibrated: 2008-04-23
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn793; Calibrated: 2008-04-30
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1449
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Tilt position - Middle – Camera slide closed/Area Scan (51x91x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.293 mW/g

Tilt position - Middle – Camera slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 12.1 V/m


Peak SAR (extrapolated) = 0.561 W/kg

SAR(1 g) = 0.278 mW/g

SAR(10 g) = 0.143 mW/g

Power Drift = -0.144 dB

Maximum value of SAR (measured) = 0.299 mW/g



Date/Time: 2008-07-09 13:10:11

Test Laboratory: TCC Nokia

Type: RM-348; Serial: 004401/10/096280/8

Communication System: WLAN 2450

Frequency: 2442 MHz; Duty Cycle: 1:1

Medium: HSL2450; Medium Notes: 21.0C

Medium parameters used: $f = 2442$ MHz; $\sigma = 1.81$ mho/m; $\epsilon_r = 39.1$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3165; Probe Notes:
- ConvF(4.57, 4.57, 4.57); Calibrated: 2008-04-23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn793; Calibrated: 2008-04-30
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1449
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - Middle – Camera slide closed/Area Scan (51x91x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.223 mW/g

Cheek position - Middle – Camera slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 10.5 V/m

Peak SAR (extrapolated) = 0.380 W/kg


SAR(1 g) = 0.204 mW/g

SAR(10 g) = 0.113 mW/g

Power Drift = -0.257 dB

Warning: Maximum averaged SAR over 1 g is located on the boundary of the measurement cube. This cube might not incorporate the absolute averaged SAR. Please consider a refinement of the Area Scan measurement.

Maximum value of SAR (measured) = 0.218 mW/g



Date/Time: 2008-07-09 13:26:25

Test Laboratory: TCC Nokia

Type: RM-348; Serial: 004401/10/096280/8

Communication System: WLAN 2450

Frequency: 2442 MHz; Duty Cycle: 1:1

Medium: HSL2450; Medium Notes: 21.0C

Medium parameters used: $f = 2442$ MHz; $\sigma = 1.81$ mho/m; $\epsilon_r = 39.1$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3165; Probe Notes:
- ConvF(4.57, 4.57, 4.57); Calibrated: 2008-04-23
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn793; Calibrated: 2008-04-30
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1449
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Tilt position - Middle – Camera slide closed/Area Scan (51x91x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.250 mW/g

Tilt position - Middle – Camera slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 11.4 V/m


Peak SAR (extrapolated) = 0.427 W/kg

SAR(1 g) = 0.229 mW/g

SAR(10 g) = 0.120 mW/g

Power Drift = -0.093 dB

Maximum value of SAR (measured) = 0.248 mW/g



Date/Time: 2008-07-31 15:26:31

Test Laboratory: TCC Nokia

Type: RM-348; Serial: 004401/10/096280/8

Communication System: WLAN 2450

Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: HSL2450; Medium Notes: 21.0 C

Medium parameters used: $f = 2462$ MHz; $\sigma = 1.87$ mho/m; $\epsilon_r = 38.8$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3165; Probe Notes:
- ConvF(4.57, 4.57, 4.57); Calibrated: 2008-04-23
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn793; Calibrated: 2008-04-30
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1449
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - High – Camera slide closed/Area Scan (51x91x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.410 mW/g

Cheek position - High – Camera slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 11.6 V/m


Peak SAR (extrapolated) = 0.893 W/kg

SAR(1 g) = 0.427 mW/g

SAR(10 g) = 0.206 mW/g

Power Drift = -0.027 dB

Maximum value of SAR (measured) = 0.473 mW/g



Date/Time: 2008-08-04 15:13:09

Test Laboratory: TCC Nokia

Type: RM-348; Serial: 004401/10/096280/8

Communication System: GSM850

Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: BSL850; Medium Notes: 21.0C

Medium parameters used: $f = 837$ MHz; $\sigma = 0.993$ mho/m; $\epsilon_r = 54.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3131; Probe Notes:
- ConvF(5.68, 5.68, 5.68); Calibrated: 2008-04-22
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2008-04-23
- Phantom: SAM 3; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Body Measurement – Middle - No Accessory – Camera slide closed - Display facing phantom/Area Scan

(41x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.526 mW/g

Body Measurement – Middle - No Accessory – Camera slide closed - Display facing phantom/Zoom Scan

(5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 9.38 V/m


Peak SAR (extrapolated) = 0.634 W/kg

SAR(1 g) = 0.490 mW/g

SAR(10 g) = 0.359 mW/g

Power Drift = -0.145 dB

Maximum value of SAR (measured) = 0.517 mW/g



Date/Time: 2008-08-04 15:28:04

Test Laboratory: TCC Nokia

Type: RM-348; Serial: 004401/10/096280/8

Communication System: GSM850

Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: BSL850; Medium Notes: 21.0C

Medium parameters used: $f = 837$ MHz; $\sigma = 0.993$ mho/m; $\epsilon_r = 54.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3131; Probe Notes:
- ConvF(5.68, 5.68, 5.68); Calibrated: 2008-04-22
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2008-04-23
- Phantom: SAM 3; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Body Measurement – Middle - HS-45 – Camera slide closed - Display facing phantom/Area Scan (41x81x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.300 mW/g

Body Measurement – Middle - HS-45 – Camera slide closed - Display facing phantom/Zoom Scan (5x5x7)/Cube

0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 7.80 V/m


Peak SAR (extrapolated) = 0.366 W/kg

SAR(1 g) = 0.281 mW/g

SAR(10 g) = 0.204 mW/g

Power Drift = -0.026 dB

Maximum value of SAR (measured) = 0.297 mW/g



Date/Time: 2008-08-04 16:39:34

Test Laboratory: TCC Nokia

Type: RM-348; Serial: 004401/10/096280/8

Communication System: GSM850

Frequency: 848.8 MHz; Duty Cycle: 1:8.3

Medium: BSL850; Medium Notes: 21.0C

Medium parameters used: $f = 849$ MHz; $\sigma = 1$ mho/m; $\epsilon_r = 54.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3131; Probe Notes:
- ConvF(5.68, 5.68, 5.68); Calibrated: 2008-04-22
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2008-04-23
- Phantom: SAM 3; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Body Measurement – High - No Accessory – Camera slide closed - Back facing phantom/Area Scan (41x81x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.625 mW/g

Body Measurement - High - No Accessory – Camera slide closed - Back facing phantom/Zoom Scan

(5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 9.93 V/m

Peak SAR (extrapolated) = 0.789 W/kg


SAR(1 g) = 0.594 mW/g

SAR(10 g) = 0.424 mW/g

Power Drift = 0.018 dB

Warning: Maximum averaged SAR over 10 g is located on the boundary of the measurement cube. This cube might not incorporate the absolute averaged SAR. Please consider a refinement of the Area Scan measurement.

Maximum value of SAR (measured) = 0.628 mW/g



SAR Report

Cph_SAR_0831_03

Applicant: Nokia Corporation

Type: RM-350

Copyright © 2008 TCC Nokia

Date/Time: 2008-08-04 15:58:01

Test Laboratory: TCC Nokia

Type: RM-348; Serial: 004401/10/096280/8

Communication System: GSM850

Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: BSL850; Medium Notes: 21.0C

Medium parameters used: $f = 837$ MHz; $\sigma = 0.993$ mho/m; $\epsilon_r = 54.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3131; Probe Notes:
- ConvF(5.68, 5.68, 5.68); Calibrated: 2008-04-22
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2008-04-23
- Phantom: SAM 3; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Body Measurement – Middle - HS-45 – Camera slide closed - Back facing phantom/Area Scan (41x81x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.309 mW/g

Body Measurement – Middle - HS-45 – Camera slide closed - Back facing phantom/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 10.4 V/m

Peak SAR (extrapolated) = 0.389 W/kg


SAR(1 g) = 0.292 mW/g

SAR(10 g) = 0.208 mW/g

Power Drift = -0.037 dB

Warning: Maximum averaged SAR over 10 g is located on the boundary of the measurement cube. This cube might not incorporate the absolute averaged SAR. Please consider a refinement of the Area Scan measurement.

Maximum value of SAR (measured) = 0.309 mW/g



Date/Time: 2008-07-21 11:40:32

Test Laboratory: TCC Nokia

Type: RM-350; Serial: 004401/10/210598/4

Communication System: WCDMA850

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: Body 850; Medium Notes: Medium Temperature: 21.8 C

Medium parameters used: $f = 835$ MHz; $\sigma = 0.965$ mho/m; $\epsilon_r = 54$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3118; Probe Notes:
- ConvF(5.59, 5.59, 5.59); Calibrated: 2007-10-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn501; Calibrated: 2008-03-17
- Phantom: SAM 5; Type: Twin Phantom; Serial: TP-1412
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Body - Middle - No Accessory – Camera slide closed - Display facing phantom/Area Scan (51x101x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.434 mW/g

Body - Middle - No Accessory – Camera slide closed - Display facing phantom/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 8.99 V/m


Peak SAR (extrapolated) = 0.504 W/kg

SAR(1 g) = 0.405 mW/g

SAR(10 g) = 0.301 mW/g

Power Drift = -0.043 dB

Maximum value of SAR (measured) = 0.427 mW/g



Date/Time: 2008-07-21 11:55:39

Test Laboratory: TCC Nokia

Type: RM-350; Serial: 004401/10/210598/4

Communication System: WCDMA850

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: Body 850; Medium Notes: Medium Temperature: 21.8 C

Medium parameters used: $f = 835$ MHz; $\sigma = 0.965$ mho/m; $\epsilon_r = 54$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3118; Probe Notes:
- ConvF(5.59, 5.59, 5.59); Calibrated: 2007-10-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn501; Calibrated: 2008-03-17
- Phantom: SAM 5; Type: Twin Phantom; Serial: TP-1412
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Body - Middle - HS-45 – Camera slide closed - Display facing phantom/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.262 mW/g

Body - Middle - HS-45 – Camera slide closed - Display facing phantom/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 7.19 V/m


Peak SAR (extrapolated) = 0.311 W/kg

SAR(1 g) = 0.245 mW/g

SAR(10 g) = 0.179 mW/g

Power Drift = -0.055 dB

Maximum value of SAR (measured) = 0.259 mW/g



Date/Time: 2008-07-21 12:27:04

Test Laboratory: TCC Nokia

Type: RM-350; Serial: 004401/10/210598/4

Communication System: WCDMA850

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: Body 850; Medium Notes: Medium Temperature: 21.8 C

Medium parameters used: $f = 835$ MHz; $\sigma = 0.965$ mho/m; $\epsilon_r = 54$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3118; Probe Notes:
- ConvF(5.59, 5.59, 5.59); Calibrated: 2007-10-26
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn501; Calibrated: 2008-03-17
- Phantom: SAM 5; Type: Twin Phantom; Serial: TP-1412
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Body - Middle - No Accessory – Camera slide closed - Back facing phantom/Area Scan (51x101x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.464 mW/g

Body - Middle - No Accessory – Camera slide closed - Back facing phantom/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 9.98 V/m


Peak SAR (extrapolated) = 0.550 W/kg

SAR(1 g) = 0.431 mW/g

SAR(10 g) = 0.313 mW/g

Power Drift = 0.003 dB

Maximum value of SAR (measured) = 0.457 mW/g



Date/Time: 2008-07-21 12:37:20

Test Laboratory: TCC Nokia

Type: RM-350; Serial: 004401/10/210598/4

Communication System: WCDMA850

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: Body 850; Medium Notes: Medium Temperature: 21.8 C

Medium parameters used: $f = 835$ MHz; $\sigma = 0.965$ mho/m; $\epsilon_r = 54$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3118; Probe Notes:
- ConvF(5.59, 5.59, 5.59); Calibrated: 2007-10-26
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn501; Calibrated: 2008-03-17
- Phantom: SAM 5; Type: Twin Phantom; Serial: TP-1412
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Body - Middle - HS-45 – Camera slide closed - Back facing phantom/Area Scan (51x101x1): Measurement grid:
dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.267 mW/g

Body - Middle - HS-45 – Camera slide closed - Back facing phantom/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 7.85 V/m


Peak SAR (extrapolated) = 0.327 W/kg

SAR(1 g) = 0.250 mW/g

SAR(10 g) = 0.179 mW/g

Power Drift = 0.024 dB

Maximum value of SAR (measured) = 0.266 mW/g



Date/Time: 2008-08-04 17:03:34

Test Laboratory: TCC Nokia
Type: RM-348; Serial: 004401/10/096280/8

Communication System: GSM850

Frequency: 848.8 MHz; Duty Cycle: 1:8.3

Medium: BSL850; Medium Notes: 21.0C

Medium parameters used: $f = 849$ MHz; $\sigma = 1$ mho/m; $\epsilon_r = 54.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3131; Probe Notes:
- ConvF(5.68, 5.68, 5.68); Calibrated: 2008-04-22
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2008-04-23
- Phantom: SAM 3; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Body Measurement – High - No Accessory – Camera slide closed - Back facing phantom – BT Active/Area Scan (41x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.626 mW/g

Body Measurement – High - No Accessory – Camera slide closed - Back facing phantom – BT Active/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 9.96 V/m


Peak SAR (extrapolated) = 0.786 W/kg

SAR(1 g) = 0.593 mW/g

SAR(10 g) = 0.425 mW/g

Power Drift = 0.028 dB

Maximum value of SAR (measured) = 0.629 mW/g



Date/Time: 2008-07-08 14:25:33

Test Laboratory: TCC Nokia
Type: RM-348; Serial: 004401/10/096280/8

Communication System: 3-slot GPRS1900

Frequency: 1880 MHz; Duty Cycle: 1:2.8

Medium: BSL1900; Medium Notes: 20.6C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.49$ mho/m; $\epsilon_r = 51.3$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3131; Probe Notes:
- ConvF(5.15, 5.15, 5.15); Calibrated: 2008-04-22
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2008-04-23
- Phantom: SAM 2; Type: Twin SAM 040 CA; Serial: TP - 1177
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Body Measurement – Middle - No Accessory - Camera slide closed - Display facing phantom/Area Scan

(41x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.220 mW/g

Body Measurement – Middle - No Accessory – Camera slide closed - Display facing phantom/Zoom Scan

(5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 7.44 V/m


Peak SAR (extrapolated) = 0.317 W/kg

SAR(1 g) = 0.203 mW/g

SAR(10 g) = 0.126 mW/g

Power Drift = -0.202 dB

Maximum value of SAR (measured) = 0.216 mW/g



Date/Time: 2008-07-08 14:38:04

Test Laboratory: TCC Nokia

Type: RM-348; Serial: 004401/10/096280/8

Communication System: 3-slot GPRS1900

Frequency: 1880 MHz; Duty Cycle: 1:2.8

Medium: BSL1900; Medium Notes: 20.6C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.49$ mho/m; $\epsilon_r = 51.3$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3131; Probe Notes:
- ConvF(5.15, 5.15, 5.15); Calibrated: 2008-04-22
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2008-04-23
- Phantom: SAM 2; Type: Twin SAM 040 CA; Serial: TP - 1177
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Body Measurement – Middle - HS-45 – Camera slide closed - Display facing phantom/Area Scan (41x81x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.191 mW/g

Body Measurement – Middle - HS-45 – Camera slide closed - Display facing phantom/Zoom Scan (5x5x7)/Cube

0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 6.23 V/m

Peak SAR (extrapolated) = 0.270 W/kg


SAR(1 g) = 0.176 mW/g

SAR(10 g) = 0.109 mW/g

Power Drift = -0.074 dB

Warning: Maximum averaged SAR over 10 g is located on the boundary of the measurement cube. This cube might not incorporate the absolute averaged SAR. Please consider a refinement of the Area Scan measurement.

Maximum value of SAR (measured) = 0.188 mW/g



Date/Time: 2008-07-09 10:22:09

Test Laboratory: TCC Nokia

Type: RM-348; Serial: 004401/10/096280/8

Communication System: 3-slot GPRS1900

Frequency: 1909.8 MHz; Duty Cycle: 1:2.8

Medium: BSL1900; Medium Notes: 20.6C

Medium parameters used: $f = 1910$ MHz; $\sigma = 1.52$ mho/m; $\epsilon_r = 51.3$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3131; Probe Notes:
- ConvF(5.15, 5.15, 5.15); Calibrated: 2008-04-22
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2008-04-23
- Phantom: SAM 2; Type: Twin SAM 040 CA; Serial: TP - 1177
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Body Measurement – High - No Accessory – Camera slide closed - Back facing phantom/Area Scan (41x81x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.363 mW/g

Body Measurement – High - No Accessory – Camera slide closed - Back facing phantom/Zoom Scan

(5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 6.99 V/m


Peak SAR (extrapolated) = 0.562 W/kg

SAR(1 g) = 0.337 mW/g

SAR(10 g) = 0.192 mW/g

Power Drift = -0.048 dB

Maximum value of SAR (measured) = 0.362 mW/g



Date/Time: 2008-07-09 09:57:39

Test Laboratory: TCC Nokia

Type: RM-348; Serial: 004401/10/096280/8

Communication System: 3-slot GPRS1900

Frequency: 1880 MHz; Duty Cycle: 1:2.8

Medium: BSL1900; Medium Notes: 20.6C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.5$ mho/m; $\epsilon_r = 51.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3131; Probe Notes:
- ConvF(5.15, 5.15, 5.15); Calibrated: 2008-04-22
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2008-04-23
- Phantom: SAM 2; Type: Twin SAM 040 CA; Serial: TP - 1177
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Body Measurement – Middle - HS-45 – Camera slide closed - Back facing phantom/Area Scan (41x81x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.259 mW/g

Body Measurement – Middle - HS-45 – Camera slide closed - Back facing phantom/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 5.34 V/m


Peak SAR (extrapolated) = 0.414 W/kg

SAR(1 g) = 0.245 mW/g

SAR(10 g) = 0.139 mW/g

Power Drift = -0.077 dB

Maximum value of SAR (measured) = 0.269 mW/g



Date/Time: 2008-07-22 10:36:43

Test Laboratory: TCC Nokia

Type: RM-350; Serial: 004401/10/210598/4

Communication System: WCDMA1900

Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: Body 1900; Medium Notes: Medium Temperature: 22.4 C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.6$ mho/m; $\epsilon_r = 53.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3118; Probe Notes:
- ConvF(4.92, 4.92, 4.92); Calibrated: 2007-10-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn501; Calibrated: 2008-03-17
- Phantom: SAM 3; Type: Twin Phantom; Serial: TP-1302
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Body - Middle - No Accessory – Camera slide closed - Display facing phantom/Area Scan (51x101x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.284 mW/g

Body - Middle - No Accessory – Camera slide closed - Display facing phantom/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 7.83 V/m

Peak SAR (extrapolated) = 0.424 W/kg


SAR(1 g) = 0.266 mW/g

SAR(10 g) = 0.162 mW/g

Power Drift = 0.008 dB

Warning: Maximum averaged SAR over 10 g is located on the boundary of the measurement cube. This cube might not incorporate the absolute averaged SAR. Please consider a refinement of the Area Scan measurement.

Maximum value of SAR (measured) = 0.286 mW/g



Date/Time: 2008-07-22 10:53:10

Test Laboratory: TCC Nokia

Type: RM-350; Serial: 004401/10/210598/4

Communication System: WCDMA1900

Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: Body 1900; Medium Notes: Medium Temperature: 22.4 C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.6$ mho/m; $\epsilon_r = 53.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3118; Probe Notes:
- ConvF(4.92, 4.92, 4.92); Calibrated: 2007-10-26
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn501; Calibrated: 2008-03-17
- Phantom: SAM 3; Type: Twin Phantom; Serial: TP-1302
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Body - Middle - HS-45 – Camera slide closed - Display facing phantom/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.264 mW/g

Body - Middle - HS-45 – Camera slide closed - Display facing phantom/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 6.12 V/m


Peak SAR (extrapolated) = 0.383 W/kg

SAR(1 g) = 0.243 mW/g

SAR(10 g) = 0.146 mW/g

Power Drift = -0.019 dB

Maximum value of SAR (measured) = 0.264 mW/g



Date/Time: 2008-07-22 12:04:47

Test Laboratory: TCC Nokia

Type: RM-350; Serial: 004401/10/210598/4

Communication System: WCDMA1900

Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: Body 1900; Medium Notes: Medium Temperature: 22.4 C

Medium parameters used (interpolated): $f = 1852.4$ MHz; $\sigma = 1.57$ mho/m; $\epsilon_r = 53.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3118; Probe Notes:
- ConvF(4.92, 4.92, 4.92); Calibrated: 2007-10-26
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn501; Calibrated: 2008-03-17
- Phantom: SAM 3; Type: Twin Phantom; Serial: TP-1302
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Body - Low - No Accessory – Camera slide closed - Back facing phantom/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.467 mW/g

Body - Low - No Accessory – Camera slide closed - Back facing phantom/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 7.62 V/m


Peak SAR (extrapolated) = 0.766 W/kg

SAR(1 g) = 0.443 mW/g

SAR(10 g) = 0.245 mW/g

Power Drift = -0.040 dB

Maximum value of SAR (measured) = 0.490 mW/g



Date/Time: 2008-07-22 12:15:35

Test Laboratory: TCC Nokia

Type: RM-350; Serial: 004401/10/210598/4

Communication System: WCDMA1900

Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: Body 1900; Medium Notes: Medium Temperature: 22.4 C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.6$ mho/m; $\epsilon_r = 53.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3118; Probe Notes:
- ConvF(4.92, 4.92, 4.92); Calibrated: 2007-10-26
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn501; Calibrated: 2008-03-17
- Phantom: SAM 3; Type: Twin Phantom; Serial: TP-1302
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Body - Low - HS-45 – Camera slide closed - Back facing phantom/Area Scan (51x101x1): Measurement grid:
dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.390 mW/g

Body - Low - HS-45 – Camera slide closed - Back facing phantom/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 6.12 V/m


Peak SAR (extrapolated) = 0.663 W/kg

SAR(1 g) = 0.379 mW/g

SAR(10 g) = 0.208 mW/g

Power Drift = -0.029 dB

Maximum value of SAR (measured) = 0.423 mW/g



Date/Time: 2008-07-22 13:01:33

Test Laboratory: TCC Nokia

Type: RM-350; Serial: 004401/10/210598/4

Communication System: WCDMA1900

Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: Body 1900; Medium Notes: Medium Temperature: 22.4 C

Medium parameters used (interpolated): $f = 1852.4$ MHz; $\sigma = 1.57$ mho/m; $\epsilon_r = 53.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3118; Probe Notes:
- ConvF(4.92, 4.92, 4.92); Calibrated: 2007-10-26
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn501; Calibrated: 2008-03-17
- Phantom: SAM 3; Type: Twin Phantom; Serial: TP-1302
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Body - Low - No Accessory – Camera slide closed - Back facing phantom - BT Active/Area Scan (51x101x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.465 mW/g

Body - Low - No Accessory – Camera slide closed - Back facing phantom - BT Active/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 7.60 V/m


Peak SAR (extrapolated) = 0.761 W/kg

SAR(1 g) = 0.441 mW/g

SAR(10 g) = 0.245 mW/g

Power Drift = 0.055 dB

Maximum value of SAR (measured) = 0.488 mW/g



Date/Time: 2008-07-09 14:36:09

Test Laboratory: TCC Nokia

Type: RM-348; Serial: 004401/10/096280/8

Communication System: WLAN 2450

Frequency: 2442 MHz; Duty Cycle: 1:1

Medium: BSL2450; Medium Notes: 20.3C

Medium parameters used: $f = 2442$ MHz; $\sigma = 1.98$ mho/m; $\epsilon_r = 50.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3165; Probe Notes:
- ConvF(4.24, 4.24, 4.24); Calibrated: 2008-04-23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn793; Calibrated: 2008-04-30
- Phantom: SAM 3; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Body Measurement – Middle - No Accessory – Camera slide closed – Back facing phantom/Area Scan (41x81x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.452 mW/g

Body Measurement – Middle - No Accessory – Camera slide closed – Back facing phantom/Zoom Scan

(5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 7.46 V/m


Peak SAR (extrapolated) = 0.669 W/kg

SAR(1 g) = 0.389 mW/g

SAR(10 g) = 0.212 mW/g

Power Drift = -0.156 dB

Maximum value of SAR (measured) = 0.427 mW/g



Date/Time: 2008-07-09 15:12:36

Test Laboratory: TCC Nokia

Type: RM-348; Serial: 004401/10/096280/8

Communication System: WLAN 2450

Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: BSL2450; Medium Notes: 20.3C

Medium parameters used: $f = 2462$ MHz; $\sigma = 2.01$ mho/m; $\epsilon_r = 50.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3165; Probe Notes:
- ConvF(4.24, 4.24, 4.24); Calibrated: 2008-04-23
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn793; Calibrated: 2008-04-30
- Phantom: SAM 3; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Body Measurement – High - HS-45 – Camera slide closed – Back facing phantom/Area Scan (41x81x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.476 mW/g

Body Measurement – High - HS-45 – Camera slide closed – Back facing phantom/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 6.76 V/m

Peak SAR (extrapolated) = 0.721 W/kg

SAR(1 g) = 0.414 mW/g

SAR(10 g) = 0.225 mW/g

Power Drift = -0.032 dB

Maximum value of SAR (measured) = 0.458 mW/g

