

Test Setup photos for RM-609 SAR Compliance Test Report

Test report no.:	SAR_Photo_RM-609_14	Date of report:	2011-02-23
Template version:	17.0	Number of pages:	7
Testing laboratory:	<p>TCC Nokia Copenhagen Laboratory Frederikskaej 1790 COPENHAGEN V DENMARK Tel. +45 33 292929 Fax. +45 33 292934</p> <p>TCC Nokia Salo Laboratory</p>	Client:	<p>Nokia Corporation Nokia House Summit Avenue, Southwood FARNBOROUGH HAMPSHIRE GU14 0NG UK Tel. +44 1252 866000 Fax. +44 1252 866001</p>
Responsible test engineer:	Leif Funch Klysner	Product contact person:	Simon J. Read
Measurements made by:	Jesper Nielsen, Preben Runchel		
Tested device:	RM-609		
FCC ID:	QFXRM-609	IC:	661Z-RM609
Supplement reports:	FCC_RM-609_03, FCC_RM-609_11		
Testing has been carried out in accordance with:	<p>47CFR §2.1093 Radiofrequency Radiation Exposure Evaluation: Portable Devices FCC OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01) Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields</p> <p>RSS-102 Evaluation Procedure for Mobile and Portable Radio Transmitters with Respect to Health Canada's Safety Code 6 for Exposure of Humans to Radio Frequency Fields</p> <p>IEEE 1528 - 2003 IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Technique</p>		
Documentation:	The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.		
Test results:	<p>The tested device complies with the requirements in respect of all parameters subject to the test. The test results and statements relate only to the items tested. The test report shall not be reproduced except in full, without written approval of the laboratory.</p>		

Date and signatures:

For the contents:

CONTENTS

1. SUMMARY OF SAR TEST REPORT	3
1.1 TEST DETAILS.....	3
1.2 PICTURE OF THE DEVICE.....	3
2. TEST POSITIONS	3
2.1 AGAINST PHANTOM HEAD.....	3
2.2 BODY WORN CONFIGURATION	4
2.3 BODY WORN CONFIGURATION FOR ASSESSMENT OF WIRELESS ROUTER MODE	5

1. SUMMARY OF SAR TEST REPORT

1.1 Test Details

Period of test	2011-02-02 to 2011-02-23
SN, HW and SW numbers of tested device	SN: 004402/13/343431/0, HW: 3500, SW: 020.027, DUT: 23784
Batteries used in testing	BP-4L Sony, DUT: 23776, 23777, 23778, 23781, 23782, 23783 BP-4L LG, DUT: 23764, 23768, 23769, 23770, 23771, 23772, 23773, 23774, 23775, 23779
Headsets used in testing	WH-207, DUT: 23765
Other accessories used in testing	
State of sample	Prototype unit
Notes	-

1.2 Picture of the Device



2. TEST POSITIONS

2.1 Against Phantom Head

Measurements were made in "cheek" and "tilt" positions on both the left hand and right hand sides of the phantom.

The positions used in the measurements were according to IEEE 1528 - 2003 "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques".




Photo of the Device in "cheek" position




Photo of the Device in "tilt" position

2.2 Body Worn Configuration

The device was placed in the SPEAG holder using the Nokia spacer and placed below the flat section of the phantom. The distance between the device and the phantom was kept at the separation distance indicated in the photo below using a separate flat spacer that was removed before the start of the measurements.



Photo of the device positioned for Body SAR measurement.
The spacer was removed for the tests.

Nokia body-worn accessories are commonly available for the separation distance used in this testing.

2.3 Body Worn Configuration for assessment of Wireless Router mode

The device was placed in the SPEAG holder using the Nokia spacer and, in sequence, the display side, the back and each of the 4 edges was positioned 10mm away from the flat phantom. The spacer was removed before the start of the measurements.




Photo of the device positioned for WR mode measurement – display facing phantom.
The spacer was removed before the start of the measurements.




Photo of the device positioned for WR mode measurement – back facing phantom.
The spacer was removed before the start of the measurements.



Photo of the device positioned for WR mode measurement – top edge facing phantom.
The spacer was removed before the start of the measurements.



Photo of the device positioned for WR mode measurement – bottom edge facing phantom.
The spacer was removed before the start of the measurements.



Photo of the device positioned for WR mode measurement – left edge facing phantom.
The spacer was removed before the start of the measurements.



Photo of the device positioned for WR mode measurement – right edge facing phantom.
The spacer was removed before the start of the measurements.