



Product Service

---

**Choose certainty.  
Add value.**

# Report On

FCC Testing of the  
ip.access Ltd 243B S16 3G AP (Bands 2 & 5)  
In accordance with FCC CFR 47 Part 15B

COMMERCIAL-IN-CONFIDENCE

FCC ID: QGGIPA243B

Document 75918692 Report 01 Issue 1

September 2012



Product Service

TÜV SÜD Product Service Ltd, Octagon House, Concorde Way, Segensworth North,  
Fareham, Hampshire, United Kingdom, PO15 5RL  
Tel: +44 (0) 1489 558100. Website: [www.tuvps.co.uk](http://www.tuvps.co.uk)

COMMERCIAL-IN-CONFIDENCE

**REPORT ON**

FCC Testing of the  
ip.access Ltd 243B S16 3G AP (Bands 2 & 5)  
In accordance with FCC CFR 47 Part 15B

Document 75918692 Report 01 Issue 1

September 2012

**PREPARED FOR**

ip.access Ltd  
Building 2020  
Cambourne Business Park  
Cambourne  
Cambridge  
CB23 6DW

**PREPARED BY**

**Natalie Bennett**  
Senior Administrator (Technical)

**APPROVED BY**

**Mark Jenkins**  
Authorised Signatory

**DATED**

25 September 2012

---

**ENGINEERING STATEMENT**

The measurements shown in this report were made in accordance with the procedures described on test pages. All reported testing was carried out on a sample equipment to demonstrate limited compliance with FCC CFR 47 Part 15B. The sample tested was found to comply with the requirements defined in the applied rules.

Test Engineer(s);

G Lawler





## CONTENTS

Section	Page No
<b>1</b>	<b>REPORT SUMMARY ..... 3</b>
1.1	Introduction ..... 4
1.2	Brief Summary of Results ..... 5
1.3	Application Form ..... 6
1.4	Product Information ..... 8
1.5	Test Conditions ..... 8
1.6	Deviations from the Standard ..... 8
1.7	Modification Record ..... 8
<b>2</b>	<b>TEST DETAILS ..... 9</b>
2.1	AC Line Conducted Emissions ..... 10
2.2	Radiated Emissions ..... 15
<b>3</b>	<b>TEST EQUIPMENT USED ..... 20</b>
3.1	Test Equipment Used ..... 21
3.2	Measurement Uncertainty ..... 22
<b>4</b>	<b>ACCREDITATION, DISCLAIMERS AND COPYRIGHT ..... 23</b>
4.1	Accreditation, Disclaimers and Copyright ..... 24



Product Service

## **SECTION 1**

### **REPORT SUMMARY**

FCC Testing of the  
ip.access Ltd 243B S16 3G AP (Bands 2 & 5)  
In accordance with FCC CFR 47 Part 15B



Product Service

## 1.1 INTRODUCTION

The information contained in this report is intended to show verification of the FCC Testing of the ip.access Ltd 243B S16 3G AP (Bands 2 & 5) to the requirements of FCC CFR 47 Part 15B.

Objective	To perform FCC Testing to determine the Equipment Under Test's (EUT's) compliance with the Test Specification, for the series of tests carried out.
Manufacturer	ip.access Ltd
Model Number(s)	243B
Serial Number(s)	000295-0000106246
Number of Samples Tested	1
Test Specification/Issue/Date	FCC CFR 47 Part 15B (2011)
Incoming Release Date	Application Form 23 August 2012
Disposal Reference Number Date	Held Pending Disposal Not Applicable Not Applicable
Order Number Date	PO30806 06 July 2012
Start of Test	29 August 2012
Finish of Test	29 August 2012
Name of Engineer(s)	G Lawler



Product Service

## 1.2 BRIEF SUMMARY OF RESULTS

A brief summary of the tests carried out in accordance with FCC CFR 47 Part 15B is shown below.

Section	Spec Clause	Test Description	Result	Comments/Base Standard
Idle with 9V AC/DC Adapter				
2.1	15.107	AC Line Conducted Emissions	Pass	
2.2	15.109	Radiated Emissions	Pass	
Idle with POE				
2.1	15.107	AC Line Conducted Emissions	Pass	
2.2	15.109	Radiated Emissions	Pass	



Product Service

1.3 APPLICATION FORM

APPLICANT'S DETAILS	
COMPANY NAME :	IP Access Ltd
ADDRESS :	Building 2020 Cambourne Business Park Cambourne Cambridge CB23 6DW
NAME FOR CONTACT PURPOSES :	Costa Panayi
TELEPHONE NO: 01954 713721	FAX NO: 01954 713799
	E-MAIL: costa.panayi@ipaccess.com

EQUIPMENT INFORMATION			
Model name/number	nano3G S16 Access Point	Identification/Part number	243B (Bands 2 & 5)
Hardware Version	XA	Software Version	SR2.7.573.0.7749_PL1
Manufacturer	IP Access Ltd	Country of Origin	UK
FCC ID	QGGIPA243B	Industry Canada ID	N/A
Technical description (a brief description of the intended use and operation):			
The S16 Access Point is a 16 user 3G Basestation operating in Bands 2 & 5 for the US market.			
<u>Supply Voltage:</u>			
<input checked="" type="checkbox"/>	AC mains	State AC voltage	110 V and AC frequency 60 Hz
<input checked="" type="checkbox"/>	POE DC (external)	State DC voltage	48 V and DC current 0.25 A
<input type="checkbox"/>	DC (internal)	State DC voltage	..... V and Battery type .....
<u>Frequency characteristics:</u>			
Transmitter Frequency range	869 MHz to 894 MHz	Channel spacing	5 MHz (if channelized)
Receiver Frequency range (if different)	824 MHz to 849 MHz	Channel spacing	5 MHz (if channelized)
Designated test frequencies:	1850 MHz to 1910 MHz		
Bottom: 871.4 MHz	Middle: 881.6 MHz	Top:	891.6 MHz
Bottom: 1932.4 MHz	Middle: 1960.0 MHz	Top:	1987.6 MHz
Intermediate Frequencies :	N/A		
Highest Internally Generated Frequency :	1987.6 MHz		
<u>Power characteristics:</u>			
Maximum transmitter power	0.1 W (Band 2)	Minimum transmitter power (if variable)	N/A
	0.1 W (Band 5)		
<input checked="" type="checkbox"/>	Continuous transmission	State duty cycle	.....
<input type="checkbox"/>	Intermittent transmission		
	If intermittent, can transmitter be set to continuous transmit test mode?		Y/N
<u>Antenna characteristics:</u>			
<input type="checkbox"/>	Antenna connector	State impedance	..... ohm
<input type="checkbox"/>	Temporary antenna connector	State impedance	..... ohm
<input checked="" type="checkbox"/>	Integral antenna	State gain	0 dBi
<u>Modulation characteristics:</u>			
<input checked="" type="checkbox"/>	Amplitude	<input type="checkbox"/>	Other
<input type="checkbox"/>	Frequency	Details:	.....
<input checked="" type="checkbox"/>	Phase		
Can the transmitter operate un-modulated?	No		
ITU Class of emission:	5M00D1W		
<u>Battery/Power Supply</u>			
Model name/number	POE Single Port Midspan	Identification/Part number	PD-3501G
Manufacturer	PowerDsine	Country of Origin	Taiwan
Model name/number	POE Active Splitter	Identification/Part number	MIT-06I-1209-IP
Manufacturer	MSTronic	Country of Origin	China
Model name/number	Switching Adapter	Identification/Part number	PSA15R-090PV
Manufacturer	Phihong	Country of Origin	Taiwan
<u>Extreme conditions:</u>			
Maximum temperature	40 °C	Minimum temperature	0 °C
Maximum supply voltage	..... V	Minimum supply voltage	..... V



Product Service

I hereby declare that I am entitled to sign on behalf of the applicant and that the information supplied is correct and complete.

Signature : Held on file at TÜV SÜD Product Service Ltd

Name : Costa Panayi

Position held : Product Design and Development Engineer

Date : 23<sup>rd</sup> August 2012

TÜV Product Service Ltd formally certifies that the manufacturer's declaration as typed out in this report, is a true and accurate record of the original received from the applicant.





Product Service

## **1.4 PRODUCT INFORMATION**

### **1.4.1 Technical Description**

The Equipment Under Test (EUT) was a ip.access Ltd 243B S16 3G AP (Bands 2 & 5). A full technical description can be found in the manufacturer's documentation.

## **1.5 TEST CONDITIONS**

For all tests the EUT was set up in accordance with the relevant test standard and to represent typical operating conditions. Tests were applied with the EUT situated in a shielded enclosure.

The EUT was powered from a 9 V DC supply.

FCC Accreditation  
90987 Octagon House, Fareham Test Laboratory

## **1.6 DEVIATIONS FROM THE STANDARD**

No deviations from the applicable test standard or test plan were made during testing

## **1.7 MODIFICATION RECORD**

Modification 0 - No modifications were made to the test sample during testing.



Product Service

## **SECTION 2**

### **TEST DETAILS**

FCC Testing of the  
ip.access Ltd 243B S16 3G AP (Bands 2 & 5)  
In accordance with FCC CFR 47 Part 15B



## 2.1 AC LINE CONDUCTED EMISSIONS

### 2.1.1 Specification Reference

FCC CFR 47 Part 15B, Clause 15.107

### 2.1.2 Equipment Under Test and Modification State

243B S/N: 000295-0000106246 - Modification State 0

### 2.1.3 Date of Test

29 August 2012

### 2.1.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

### 2.1.5 Test Procedure

The EUT is set up on a test table 800mm above a horizontal ground plane. A vertical ground plane is also required and is placed 400mm from the EUT. Where a EUT is floor standing it will be stood on but insulated from the ground plane by up to 12mm.

The EUT is powered through a Line Impedance Stabilisation Network (LISN) which is bonded to the ground plane. The EUT is located so that the distance between the EUT and the LISN is no less than 800mm. Where possible the cable between the mains input of the EUT and the LISN is 1m. Where this is not possible the cable is non inductively bundled with the bundle not exceeding 400mm in length.

A preliminary profile of the Conducted Emissions is obtained over the frequency range 150kHz to 30MHz. Any points of interest are noted for formal measurements.

During formal measurements, the measuring receiver is tuned to the emission of interest where Quasi – Peak and Average measurements are performed in a 9kHz Video and Resolution Bandwidth.

### 2.1.6 Environmental Conditions


Ambient Temperature	19.9°C
Relative Humidity	60.0%



2.1.7 Test Results

Idle with 9V AC/DC Adapter


Live Line



Frequency (MHz)	QP Level (dBµV)	QP Limit (dBµV)	QP Margin (dBµV)	AV Level (dBµV)	AV Limit (dBµV)	AV Margin (dBµV)
0.182	42.0	64.4	-22.4	32.0	54.4	-22.3
0.245	43.3	61.9	-18.6	34.5	51.9	-17.4
0.362	40.0	58.7	-18.6	29.3	48.7	-19.4
0.574	36.3	56.0	-19.7	23.0	46.0	-23.0
0.867	36.1	56.0	-19.9	25.0	46.0	-21.0
1.250	35.8	56.0	-20.2	24.8	46.0	-21.2



Neutral Line




Frequency (MHz)	QP Level (dBµV)	QP Limit (dBµV)	QP Margin (dBµV)	AV Level (dBµV)	AV Limit (dBµV)	AV Margin (dBµV)
0.181	45.8	64.4	-18.6	36.3	54.4	-18.1
0.247	45.5	61.9	-16.3	36.4	51.9	-15.5
0.363	44.2	58.7	-14.5	32.7	48.7	-15.9
0.481	35.9	56.3	-20.4	23.8	46.3	-22.6
0.521	40.2	56.0	-15.8	26.7	46.0	-19.3
0.886	39.6	56.0	-16.4	28.6	46.0	-17.4



Product Service

Idle with POE


Live Line



Frequency (MHz)	QP Level (dBµV)	QP Limit (dBµV)	QP Margin (dBµV)	AV Level (dBµV)	AV Limit (dBµV)	AV Margin (dBµV)
0.150	41.0	66.0	-25.0	20.7	56.0	-35.3
0.190	48.7	64.1	-15.3	36.8	54.1	-17.2
21.769	43.2	60.0	-16.8	35.4	50.0	-14.6
21.835	42.4	60.0	-17.6	34.9	50.0	-15.1
22.333	42.2	60.0	-17.8	34.1	50.0	-15.9
22.472	40.5	60.0	-19.5	32.5	50.0	-17.5



Neutral Line



Frequency (MHz)	QP Level (dBµV)	QP Limit (dBµV)	QP Margin (dBµV)	AV Level (dBµV)	AV Limit (dBµV)	AV Margin (dBµV)
0.150	41.1	66.0	-24.9	22.2	56.0	-33.8
0.193	49.1	63.9	-14.8	35.8	53.9	-18.1
0.252	41.9	61.7	-19.8	29.2	51.7	-22.4
21.079	43.7	60.0	-16.3	37.4	50.0	-12.6
22.028	44.5	60.0	-15.5	37.2	50.0	-12.8
22.928	40.7	60.0	-19.3	32.6	50.0	-17.4



## 2.2 RADIATED EMISSIONS

### 2.2.1 Specification Reference

FCC CFR 47 Part 15B, Clause 15.109

### 2.2.2 Equipment Under Test and Modification State

243B S/N: 000295-0000106246 - Modification State 0

### 2.2.3 Date of Test

29 August 2012

### 2.2.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

### 2.2.5 Test Procedure

A preliminary profile of the Spurious Radiated Emissions is obtained up to the 5th harmonic of the EUT's highest internally generated fundamental frequency. For frequencies from 30MHz to 18GHz the EUT is placed on a test table 800mm above the ground plane. For frequencies above 18GHz, the EUT height is increased by 200mm to a height of 1000mm. This is to ensure the beam width of the measuring antenna gives sufficient vertical coverage of the EUT.

During characterisation the turntable azimuth is adjusted from 0 to 360 degrees with the measuring antenna in one polarity. It is then repeated for the other polarity. Any frequencies of interest are noted for formal measuring later. The distance from the measuring antenna to the boundary of the EUT is 3m. Above 18GHz this distance may be reduced to 1m.

During formal measurement the spectrum analyser is tuned to the frequency of the emission. The turntable azimuth is adjusted from 0 to 360 degrees to determine the point at which the maximum emission level occurs. Then the height of the measuring antenna is adjusted from a height of 1m to 4m to determine the height at which the maximum emission level occurs. Once the point of maximum emission has been determined the emission is measured. Emissions in the 30MHz to 1GHz range are measured using a CISPR Quasi – Peak detector function in a 120kHz bandwidth. Emissions in the range 1GHz to 40GHz require Peak and Average measurements. The Peak measurements are made using a peak detector with 1MHz Resolution and Video bandwidths. The average measurements employ a peak detector with a Resolution bandwidth of 1MHz and a Video bandwidth of 10Hz. If measurements are made at a 1m measuring distance, then 10dB is added to the specification limit.

### 2.2.6 Environmental Conditions

Ambient Temperature	19.9°C
Relative Humidity	60.0%






**2.2.7 Test Results**

Idle with 9V AC/DC Adapter

30 MHz to 1 GHz



Frequency (MHz)	QP Level (dBµV/m)	QP Level (µV/m)	QP Limit (dBµV/m)	QP Limit (µV/m)	QP Margin (dBµV/m)	QP Margin (µV/m)	Angle (Deg)	Height (m)	Polarity
30.731	31.1	35.9	40.0	100	-8.9	64.1	315	1.00	Vertical
32.324	30.3	32.7	40.0	100	-9.7	67.3	137	1.88	Vertical
64.174	28.5	26.6	40.0	100	-11.5	73.4	206	1.00	Vertical
69.117	27.7	24.3	40.0	100	-12.3	75.7	1	1.00	Vertical
81.198	29.1	28.5	40.0	100	-10.9	71.5	124	1.00	Vertical
125.023	28.1	25.4	43.5	150	-15.4	124.6	19	1.03	Vertical
800.024	39.2	91.2	46.0	200	-6.8	108.8	359	1.00	Horizontal




Product Service

1 GHz to 13 GHz


Frequency (GHz)	Antenna Polarisation	Antenna Height (cm)	EUT Arc (degrees)	Final Peak (dBµV/m)	Final Average (dBµV/m)
7.520	Vertical	100	004	50.68	46.75

1 GHz to 8 GHz



Date: 29.AUG.2012 20:44:13

8 GHz to 13 GHz




Date: 29.AUG.2012 20:38:14



Idle with POE

30 MHz to 1 GHz




Frequency (MHz)	QP Level (dBµV/m)	QP Level (µV/m)	QP Limit (dBµV/m)	QP Limit (µV/m)	QP Margin (dBµV/m)	QP Margin (µV/m)	Angle (Deg)	Height (m)	Polarity
30.564	31.5	37.6	40.0	100	-8.5	62.4	158	1.00	Vertical
31.984	30.3	32.7	40.0	100	-9.7	67.3	166	1.25	Vertical
50.435	29.8	30.9	40.0	100	-10.2	69.1	227	1.08	Vertical
55.988	30.7	34.3	40.0	100	-9.3	65.7	226	1.24	Vertical
58.680	27.8	24.5	40.0	100	-12.2	75.5	5	1.00	Vertical
110.792	25.2	18.2	43.5	150	-18.3	131.8	18	1.00	Vertical
143.298	26.4	20.9	46.0	200	-17.1	179.1	268	1.15	Vertical



1 GHz to 13 GHz


Frequency (GHz)	Antenna Polarisation	Antenna Height (cm)	EUT Arc (degrees)	Final Peak (dBµV/m)	Final Average (dBµV/m)
7.520	Vertical	100	261	49.26	44.48

1GHz to 8GHz



Date: 29.AUG.2012 20:11:18

8GHz to 13GHz



Date: 29.AUG.2012 20:25:08



Product Service

### **SECTION 3**

#### **TEST EQUIPMENT USED**



### 3.1 TEST EQUIPMENT USED

List of absolute measuring and other principal items of test equipment.

Instrument	Manufacturer	Type No.	TE No.	Calibration Period (months)	Calibration Due
<b>Section 2.1 – AC Line Conducted Emissions</b>					
Transient Limiter	Hewlett Packard	11947A	15	12	1-Dec-2012
3 phase LISN	Rohde & Schwarz	ESH2-Z5	323	12	13-Jan-2013
Screened Room (5)	Rainford	Rainford	1545	36	25-Dec-2013
EMI Test Receiver	Rohde & Schwarz	ESU40	3506	12	29-Sep-2012
7m Armoured RF Cable	SSI Cable Corp.	1501-13-13-7m WA(-)	3600	-	TU
<b>Section 2.2 - Radiated Emissions</b>					
Antenna (Double Ridge Guide, 1GHz-18GHz)	EMCO	3115	235	12	14-Nov-2012
Pre-Amplifier	Phase One	PS04-0086	1533	12	20-Sep-2012
Screened Room (5)	Rainford	Rainford	1545	36	25-Dec-2013
Mast Controller	Inn-Co GmbH	CO 1000	1606	-	TU
Antenna (Bilog)	Chase	CBL6143	2904	24	12-May-2013
High Pass Filter (3GHz)	RLC Electronics	F-100-3000-5-R	3349	12	29-May-2013
EMI Test Receiver	Rohde & Schwarz	ESU40	3506	12	29-Sep-2012
9m RF Cable (N Type)	Rhophase	NPS-2303-9000- NPS	3791	-	TU
Tilt Antenna Mast	matur GmbH	TAM 4.0-P	3916	-	TU
Mast Controller	matur GmbH	NCD	3917	-	TU
Low Noise Amplifier	Wright Technologies	APS04-0085	3969	-	TU

TU – Traceability Unscheduled



Product Service

### 3.2 MEASUREMENT UNCERTAINTY

For a 95% confidence level, the measurement uncertainties for defined systems are:-

Test Discipline	MU
Radiated Emissions	30MHz to 1GHz: $\pm 5.1$ dB 1GHz to 40GHz: $\pm 6.3$ dB
AC Line Conducted Emissions	$\pm 3.2$ dB



Product Service

## **SECTION 4**

### **ACCREDITATION, DISCLAIMERS AND COPYRIGHT**





Product Service

#### 4.1 ACCREDITATION, DISCLAIMERS AND COPYRIGHT



This report relates only to the actual item/items tested.

Our UKAS Accreditation does not cover opinions and interpretations and any expressed are outside the scope of our UKAS Accreditation.

Results of tests not covered by our UKAS Accreditation Schedule are marked NUA  
(Not UKAS Accredited).

This report must not be reproduced, except in its entirety, without the written permission of  
TÜV SÜD Product Service Limited

© 2012 TÜV SÜD Product Service Limited