

**Maximum Permissible Exposure Test Report**

**for**

**Demarc Technologies Group, LLC  
FCC ID: QGK-DT200**

June 26, 2003  
Revised: July 25, 2003

**WLL PROJECT #: 7384RFFCC**

*This report may not be reproduced, except in full, without the prior written consent of Washington Laboratories, Ltd.*

# Maximum Permissible Exposure Test Report

for

**Demarc Technologies Group, LLC**

**FCC ID: QGK-DT200**

## 1.0 Introduction

This report has been prepared on behalf of Demarc Technologies Group, LLC. to show compliance with the RF exposure requirements of FCC Part 15.247 as defined in FCC Part 1.1307(b)(1) for the Demarc Wireless LAN card.

## 3.8 Radio Frequency Radiation Exposure

In accordance with Section 1.1310 of the FCC rules, the Maximum Permissible Exposure (MPE) limit for this frequency range is  $1\text{mW}/\text{cm}^2$  for General Population/Uncontrolled Access.

The EUT is designed for telecommunications transmissions and may use high gain antennas (up to 18 dBi) and the transmitter section is designed for mounting on an antenna mast. A unique connector is used on the card to prevent the use of higher gain antennas. Warnings are in the installation manual which limit the exposure to the direct beam during installation and maintenance. These warnings to the installers insure that the general public is not exposed to RF energy.

The Demarc Wireless LAN card is designed for a transmit power of 23.1dBm (205mW). Assuming the highest allowable gain antenna is used (18 dBi) the following power density is calculated.

$$S = (PG)/(4\pi R^2)$$

Where,

S = Power Density

P = Output Power at the Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna

For this device, the calculation is as follows:

$$S = \text{FCC Limit} = 1\text{mW}/\text{cm}^2$$

$$P = \text{Output Power} = 205\text{mW}$$

$$G = \text{Worst Case Gain} = 18 \text{ dBi} (65 \text{ linear gain})$$

Solving for the minimum safe distance:

$$R = \sqrt{\frac{P \times G}{4 \times \rho \times S}}$$

$$R = \{(205\text{mW})(65)\} / \{(12.566)(1 \text{ mW/cm}^2)\}^{1/2} = 32.6 \text{ cm}$$

The calculated 32.6 cm distance is the minimum distance required for installation to ensure the MPE limit of 1 mW/cm<sup>2</sup> is not exceeded. Warnings are provided in the users manual to limit exposure to the direct beam during the installation and maintenance phase and to ensure that the antenna is installed at distances greater than 33 cm from people. These warnings ensure that the device is installed properly and does not expose the general public to RF energy hazards.