

**RF-EXPOSURE ASSESSMENT REPORT**

**FCC 47 CFR Part 2.1091  
Industry Canada RSS-102**

**RF-Exposure evaluation of mobile equipment**

**Report Reference No.** ..... : G0M-1112-1639-TFC091M-V01

**Testing Laboratory** ..... : Eurofins Product Service GmbH

**Address** ..... : Storkower Str. 38c  
15526 Reichenwalde  
Germany

**Accreditation** ..... :



A2LA Accredited Testing Laboratory, Certificate No.: 1983.01  
FCC Filed Test Laboratory, Reg.-No.: 96970  
IC OATS Filing assigned code: 3470A

**Applicant's name** ..... : Kondo Kagaku Co., Ltd.

**Address** ..... : 4-17-7 Higashi Nippori, Arakawa-Ku  
Tokyo 116-0014  
JAPAN

**Test specification:**



**Standard**..... : 47 CFR 1.1310 / 47 CFR 2.1091 / 47 CFR 2.1093  
OET Bulletin 65:1997  
RSS-102, Issue 4:2010  
Safety Code 6:2009

**Equipment under test (EUT):**

Product description	Radio control transmitter for Model Cars	
Model No.	EX-1	
Hardware version	None	
Firmware / Software version	None	
	FCC-ID: QH9KTSS-703	IC: N/A

**Test result** ..... : **Passed**

<b>Possible test case verdicts:</b>	
- not applicable to test object.....	: N/A
- test object does meet the requirement .....	: P (Pass)
- test object does not meet the requirement .....	: F (Fail)
<b>Testing:</b>	
Date of receipt of test item.....	: 2012-03-21
Date (s) of assessment.....	: 2012-05-24
Compiled by.....	: Christian Weber
Assessed by (+ signature)..... (Testing Manager)	: Christian Weber
Approved by (+ signature)..... (Test Lab Manager)	: Toralf Jahn
Date of issue.....	: 2012-05-24
Total number of pages .....	: 11
<b>General remarks:</b>	
<p><b>The test results presented in this report relate only to the object tested.</b></p> <p><b>The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report.</b></p> <p>This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.</p>	
<b>Additional comments:</b>	

  
.....  
  
.....

**REPORT INDEX**

<b>1</b>	<b>EQUIPMENT (TEST ITEM) DESCRIPTION</b>	<b>4</b>
1.1	Reference Documents	5
1.2	Radiation Sources	6
<b>2</b>	<b>RESULT SUMMARY</b>	<b>7</b>
<b>3</b>	<b>RF-EXPOSURE CLASSIFICATIONS</b>	<b>8</b>
<b>4</b>	<b>ASSESSMENT</b>	<b>9</b>
4.1	MPE Assessment – 47 CFR 2.1091 / RSS-102	9

## 1 Equipment (Test item) Description

<b>Description</b>	Radio control transmitter for Model Cars
<b>Model</b>	EX-1
<b>Serial number</b>	None
<b>Hardware version</b>	None
<b>Software / Firmware version</b>	None
<b>FCC-ID</b>	QH9KTSS-703
<b>IC</b>	N/A
<b>Equipment type</b>	End product

**1.1 Reference Documents**

Document type	Document No.	Issued by	Date
FCC 15.247 Test Report	G0M-1112-1639-TFC247B-V01	Eurofins Product Service GmbH	2012-05-23

**1.2 Radiation Sources**

Mode #	Description	
2.4GHz	Frequency range [MHz]	2404 - 2480
	Channels	29
	Transmission modes	FHSS
	Modulations	Frequency
	Maximum radiated power [dBm]	11.3
	Maximum transmission duty cycle [%]	6
	Antenna 1 gain [dBi]	1.9
	Antenna 1 diameter [cm]	~6

## 2 Result Summary

FCC 47 CFR Part 2.1091, IC RSS-102			
Product Specific Standard Section	Requirement	Result	Remarks
47 CFR 2.1091	Maximum permissible exposure @ 20cm below limit	PASS	
RSS-102 2.5.2	Maximum permissible exposure @ 20cm below limit	N/A	
<b>Remarks:</b>			

### 3 RF-Exposure Classifications

Device Types	
Fixed	A fixed device is defined as a device physically secured at one fixed location and cannot be easily re-located.
Mobile	A mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. (47 CFR 2.1091)
Portable	A portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user. (47 CFR 2.1093)

Exposure Categories	
Occupational / Controlled	Limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.
General population / uncontrolled	Exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.



## 4 Assessment

### 4.1 MPE Assessment – 47 CFR 2.1091 / RSS-102

MPE Assessment acc. to 47 CFR 2.1091 / IC RSS-102				Verdict: PASS
Assessment according to reference		Reference Method		
		FCC OET Bulletin 65 / RSS-102 & Safety Code 6		
Device type		mobile		
Exposure category		General public		
IC Limits – Occupational / Controlled Exposure				
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [W/m <sup>2</sup> ]	Averaging time [min]
0.003 – 1.0	600	4.9	N/A	6
1 – 10	600/f	4.9/f	N/A	6
10 – 30	60	4.9/f	N/A	6
30 – 300	60	0.163	10.0*	6
300 – 1500	3.54·f <sup>0.5</sup>	0.0094·f <sup>0.5</sup>	f/30	6
1500 - 15000	137	0.364	50	6
15000 - 150000	137	0.364	50	616000/f <sup>0.5</sup>
150000 - 300000	0.354·f <sup>0.5</sup>	9.4·10 <sup>-4</sup> ·f <sup>0.5</sup>	3.33·10 <sup>-4</sup> ·f	616000/f <sup>0.5</sup>
IC Limits – General Population / Uncontrolled Exposure				
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [W/m <sup>2</sup> ]	Averaging time [min]
0.003 – 1.0	280	2.19	N/A	6
1 – 10	280/f	2.19/f	N/A	6
10 – 30	28	2.19/f	N/A	6
30 – 300	28	0.073	2.0*	6
300 – 1500	1.585·f <sup>0.5</sup>	0.0042·f <sup>0.5</sup>	f/150	6
1500 - 15000	61.4	0.163	10	6
15000 - 150000	61.4	0.163	10	616000/f <sup>0.5</sup>
150000 - 300000	0.158·f <sup>0.5</sup>	4.21·10 <sup>-4</sup> ·f <sup>0.5</sup>	6.67·10 <sup>-5</sup> ·f	616000/f <sup>0.5</sup>
* = Power density is applicable at frequencies greater than 100 MHz; f in MHz				

FCC Limits – Occupational / Controlled Exposure				
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [mW/cm <sup>2</sup> ]	Averaging time [min]
0.3 – 3.0	614	1.63	(100)*	6
3.0 - 30	1842/f	4.89/f	(900/f <sup>2</sup> )*	6
30 - 300	61.4	0.163	1.0	6
300 - 1500	N/A	N/A	f/300	6
1500 - 100000	N/A	N/A	5.0	6
FCC Limits – General Population / Uncontrolled Exposure				
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [mW/cm <sup>2</sup> ]	Averaging time [min]
0.3 – 1.34	614	1.63	(100)*	30
1.34 - 30	842/f	2.19/f	(180/f <sup>2</sup> )*	30
30 - 300	27.5	0.073	0.2	30
300 - 1500	N/A	N/A	f/1500	30
1500 - 100000	N/A	N/A	1.0	30
* = Plane wave equivalent power density; f in MHz				
Assessment Relations				
$\lambda[m] = \frac{c \left[ \frac{m}{s} \right]}{f[Hz]} ; R_{FF}[m] \geq \frac{2 \cdot D[m]^2}{\lambda[m]}$ $S[mW/cm^2] = \frac{P_{E.I.R.P.}[mW]}{4\pi R[cm]^2} ; R[cm] = \sqrt{\frac{P_{E.I.R.P.}[mW]}{4\pi S[mW/cm^2]}}$ $P_R[mW] = P_C[mW] \cdot G ; P_R[dBm] = P_C[dBm] + G[dBi]$ $DCC [dB] = 10 \cdot \text{Log}_{10} \left( \frac{DC[\%]}{100} \right)$				
Assessment procedure				
<p>For each radio and frequency band the worst case transmission mode with the highest peak conducted or radiated power is evaluated at the frequency that results in the most restrictive rf-exposure limit. From the peak power values, antenna gains and duty cycles taken from the reference documents, the source average radiated power values are calculated. From the average radiated power the power densities at antenna far-field distance, at 20cm separation distance from the radiation source is calculated. Compliance with the RF-Exposure limit is determined at 20cm separation distance.</p>				

<b>Assessment results – Frequency hopping in the 2400 – 2483.5 MHz band</b>		
Transmission mode		
Operating mode frequency range [MHz]	2404 – 2480	
Assessment frequency (f) [MHz]	2404	
Transmission duty cycle (DC) [%]	6	
Peak conducted power (P <sub>C</sub> ) [dBm]	9.4	
Peak radiated power (P <sub>R</sub> ) [dBm e.i.r.p.]	11.3	
Peak Antenna gain (G) [dBi]	1.9	
Maximum Antenna Diameter D [cm]	6.0	
Antenna far-field distance		
Transmission frequency wavelength (λ)	0.125m	12.48cm
Antenna far-field distance (R <sub>FF</sub> )	0.058m	5.77cm
Power evaluation		
Peak conducted power (P <sub>C</sub> )	8.71mW	9.40dBm
Peak Antenna Gain (G)	1.55	1.90dBi
Calculated peak radiated power (P <sub>R-Calc</sub> )	13.49mW	11.30dBm
Measured peak radiated power (P <sub>R</sub> )	13.49mW	11.30dBm
Source average Power		
Maximum transmission duty cycle (DC)	6.0%	
Duty cycle correction (DCC)	0.06	-12.22dB
Measured peak radiated power (P <sub>R</sub> )	13.49mW	11.30dBm
Averaged peak radiated power (P <sub>RAVG</sub> )	0.81mW	-0.92dBm
Power density		
Compliance power density limit	1.000mW/cm <sup>2</sup>	10.00W/m <sup>2</sup>
Power density @ Antenna far-field distance	0.002mW/cm <sup>2</sup>	0.019W/m <sup>2</sup>
Power density @ 20cm	0.000mW/cm <sup>2</sup>	0.002W/m <sup>2</sup>
Distance for compliance power density	0.003m	0.25cm
Verdict		
<b>The power density of the EUT at 20cm is below the FCC/IC MPE limit!</b>		
Comments:		