



EUROFINS PRODUCT SERVICE GMBH



Testing Cert # 1983.01

TEST - REPORT

**FCC RULES PART 15 / SUBPART C §15.249
RSS 210 Issue 7**

FCC ID: QH9T090825

RC transmitter for car model

EX-10EURUS with RF 902S

Test report no.: G0M20909-2577-C-1



Eurofins Product Service GmbH
Storkower Str. 38c, 15526 Reichenwalde,
Germany

Phone +49-33631-888 0
Fax +49-33631-888 660

TABLE OF CONTENTS

1	General Information	3
1.1	Notes	3
1.2	Testing laboratory	4
1.2.1	Location	4
1.2.2	Details of accreditation status	4
1.2.3	Details of approval holder	4
1.4	Application details	5
1.5	Test item	5
1.6	Test standards	6
2	Technical test	6
2.1	Summary of test results	6
2.2	Test environment	6
2.3	Test equipment utilized	7
2.4	General Test Procedure	8
3	Test results (enclosure)	9
3.1	Output Power (Field Strength) FCC § 15.249 (a), RSS 210 A2.9	10
3.1.2	De facto equivalent isotropic radiated power	10
3.1.3	Transmitter	10
3.2	RF Exposure Compliance Requirements	11
3.3	Radiated Emissions; FCC § 15.249 (d); RSS 210 A2.9	11
Annex A	Pictures	13
Annex B	Fundamental Field Strength	19
Annex C	Spurious Emissions radiated - Transmitter operating	22

1 General Information

1.1 Notes

The results of this test report relate exclusively to the item tested as specified in chapter "Description of test item" and are not transferable to any other test items.

Eurofins Product Service GmbH is not responsible for any generalisations and conclusions drawn from this report. Any modification of the test item can lead to invalidity of test results and this test report may therefore be not applicable to the modified test item.

The test report may only be reproduced or published in full. Reproducing or publishing extracts of the report requires the prior written approval of the Eurofins Product Service GmbH.

This document is subject to the General Terms and Conditions and the Testing and Certification System of Eurofins Product Service GmbH, available on request or accessible at www.pt.eurofins.com.

Operator:

13.10.2009

M. Handrik



Date

Eurofins Lab


Name

Signature

Technical responsibility for area of testing:

13.10.2009

T. Jahn



Date

Eurofins

Name

Signature

 Test Report No.: G0M20909-2577-C-1

1.2 Testing laboratory

1.2.1 Location

EUROFINS PRODUCT SERVICE GMBH
Storkower Strasse 38c
D- 15526 Reichenwalde
Germany
Telephone : + 49 33631 888 00
Telefax : + 49 33631 888 660

1.2.2 Details of accreditation status

DAR ACCREDITED TESTING LABORATORY
DAR-REGISTRATION NUMBER: DAT-P-268/08

RECOGNIZED NOTIFIED BODY EMC
REGISTRATION NUMBER: BNetzA-bS EMV-07/61

RECOGNIZED NOTIFIED BODY R&TTE
REGISTRATION NUMBER: BNetzA-bS-02/51-53

FCC FILED TEST LABORATORY
REG.-NO. 96970

A2LA ACCREDITED TESTING LABORATORY
CERTIFICATE NO. 1983.01

BLUETOOTH QUALIFICATION TEST FACILITY (BQTF)
ACCREDITED BY BLUETOOTH QUALIFICATION REVIEW BOARD

INDUSTRY CANADA FILED TEST LABORATORY
REG. No. IC 3470

1.2.3 Details of approval holder

Name : Kondo Kagaku Co. Ltd.
Street : 4-17-7 Higashi Nippori, Arakawa-Ku
Town : Tokyo 116-0014
Country : Japan
Telephone : +81 3 3807-7751
Fax : +81 3 3807-8155

Contact : Mr. Koji Akiyama
Telephone : +81 3 3807-7751

1.4 Application details

Date of receipt of application : 17.09.2009
Date of receipt of test item : 17.09.2009
Date of test : 29.09.2009 - 05.10.2009

1.5 Test item

Description of test item : RC transmitter for car model
Type identification : EX-10EURUS with RF 902S
Serial number : without
Photos : See Annex A

Technical data

Frequency band : 2400 MHz - 2483.5 MHz
Tested frequencies : F₁ 2404MHz
F₂ 2440MHz
F₃ 2480MHz
Antenna : internal
Number of Channels : 39
Power supply : 12.0VDC
Operating mode : simplex

Manufacturer:

Name : Kondo Kagaku Co. Ltd.
Street : 4-17-7 Higashi Nippori, Arakawa-Ku
Town : Tokyo 116-0014
Country : Japan

1.6 Test standards

Technical standard : FCC RULES PART 15 / SUBPART C § 15.249
IC Standards: RSS 210 Issue 7

2 Technical test

2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed.

or

The deviations as specified in 2.5 were ascertained in the course of the tests performed.

2.2 Test environment

Temperature : 23 °C

Relative humidity content : 51 %

Air pressure : 936 hPa

Extrem conditions parameters: : test voltage - extreme nom.: 12.0VDC
min.: 10.4VDC
max: 13.6VDC

Additional information : none

2.3 Test equipment utilized

ID No.	Test equipment	Type	Manufacturer
ETS 0012	Biconical Antenna	HK 116	R & S
ETS 0013	LPD Antenna	HL 223	R & S
ETS 0014	Log Periodical Antenna	HL 025	R & S
ETS 0015	Log Periodical Antenna	HL 025	R & S
ETS 0018	Horn antenna	BBHA 9120D	Schwarzbeck
ETS 0125	Reference dipole	3126-1880	ETS Lindgren
ETS 0228	Climatic chamber	VT 4010	Vötsch
ETS 0253	Spectrum Analyzer	FSIQ26	R & S
ETS 0271	Spectrum Analyzer	FSEK30	R & S
ETS 0288	Artificial mains	ESH2-Z5	R & S
ETS 0311	Anechoic chamber	AC 4	Frankonia
ETS 0474	EMI Test Receiver	ESCS 30	R&S

2.4 General Test Procedure

POWER LINE CONDUCTED INTERFERENCE: The procedure used was ANSI STANDARD C63.4-2003 5.2 using a 50 μ H LISN (if necessary). Both lines were observed. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-2003 6.4 using a spectrum analyzer. The resolution bandwidth of the spectrum analyzer was 100 kHz for measurements below 1 GHz and RBW 1 MHz was used above 1 GHz. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The ambient temperature of the UUT was 23 °C with a humidity of 43 %.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dB μ V) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB.

Example:

Freq (MHz) METER READING + ACF + CABLE LOSS (to the receiver) = FS
33 20 dB μ V + 10.36 dB + 6 dB = 36.36 dB μ V/m @ 3 m

ANSI STANDARD C63.4-2003 6.2.1 MEASUREMENT PROCEDURES: The UUT was placed on a table 80 cm high and with dimensions of 1m by 1.5 m (non metallic table). The UUT was placed in the center of the table. The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to 10th harmonic of the fundamental.

Peak readings were taken in three (3) orthogonal planes and the highest readings.

Measurements were made by EUROFINS PRODUCT SERVICE GMBH

at the registered open field test site located at Storkower Str. 38c, 15526 Reichenwalde, Germany.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1 m to 4 m. The antenna was placed in both the horizontal and vertical planes.

ANTENNA & GROUND:

The unit use internal antenna. There is no provision for an external antenna (see photo).

3 Test results (enclosure)

TEST CASE	FCC 49CFR PART	IC RSS-	Required	Test passed	Test failed
<i>Transmitter parameter</i>					
Output Power (Field Strength)	15.249(a)	RSS 210 A 2.9	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Spurious Emissions radiated - Transmitter operating	15.249 (d)	RSS 210 A 2.9	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Spurious Emissions conducted - Transmitter operating	15.249 (d)	RSS 210 A2.9	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Occupied bandwidth	15.215(c);	RSS GEN 4.6.1	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Out of Band Spurious Emission, Bandedge-Transmitter operating	15.249 (d)	RSS 210 A 2.9	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Conducted Measurement at (AC) Power Line	15.207	Gen 7.2.2	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<i>Receiver Parameter</i>					
Radiated emissions	15.107	Gen 7.2.3	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

3.1 Output Power (Field Strength) FCC § 15.249 (a), RSS 210 A2.9

This measurement applies to equipment with an integral antenna and to equipment with an antenna connector and equipped with an antenna as declared by the applicant.

Limits:

Fundamental Frequency	Field Strength of Fundamental (millivolts/meter)	Field Strength of Harmonics (microvolts/meter)
902 - 928 MHz	50	500
2400 - 2483.5 MHz	50	500
5725 - 5875 MHz	50	500
24.0 - 24.25 GHz	250	2500

The power was measured with modulation (declared by the applicant).

Test conditions	Frequency [dB μ V/m]		
	2404MHz	2440MHz	2480MHz
$T_{nom} = 23^{\circ}\text{C}$ $V_{nom} = 12\text{VDC}$	91.51	88.34	84.95
Measurement uncertainty	< 3 dB		

Test equipment used: ETS 0018, ETS 0271, 0253, ETS 0311

Remark: See attached diagrams Annex.

3.1.2 De facto equivalent isotropic radiated power

Because using an permanent antenna there are no deviations from the radiated test results according 3.1.

3.1.3 Transmitter

At the transmitter the measurement was transacted with the modulation declared by the manufacturer and the maximum available output power of the EUT.

3.2 RF Exposure Compliance Requirements

Not applicable for this kind of device for the low power level.

3.3 Radiated Emissions; FCC § 15.249 (d); RSS 210 A2.9

Out of Band Radiated Emissions

FCC Rule: 15.249(d), 15.35(b); RSS 210 A2.9

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

For frequencies above 1000 MHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

Limits:

Frequency of Emission (MHz)	Field strength (microvolts/meter)	Field Strength (dB microvolts/meter)
30 - 88	100	40.0
88 - 216	150	43.5
216 - 960	200	46.0
Above 960	500	54.0

For frequencies above 1GHz (Peak measurements).

Limit + 20 dB

54.0 dB μ V/m + 20 dB= 74 dB μ V/m

or

46.0 dB μ V/m + 20 dB= 66 dB μ V/m

Must be antenuatted at least 50 dB below the level of fundamental emission

Spurious emission was measured with modulation (declared by manufacturer).

SAMPLE CALCULATION OF LIMIT. All results will be updated by an automatic measuring system in accordance with point 2.3.

The peak and average spurious emission plots was measured with the average limits.
The critical peak value listed in the table agree with the above calculated limits.

Summary table with radiated data of the test plots

Freq.	Used Ch.	Frequency Marker [GHz]	Polarization	Max. Field Strength [dB μ V/m]	Compliance Limit [dB μ V/m]	Detector	BW [MHz]	Margin [dB]
2	L	0.801	V	30.07	66	P	0.1	<u>-35.93</u>
2	M	0.814	V	28.44	66	P	0.1	<u>-37.56</u>
2	H	0.827	V	28.51	66	P	0.1	<u>-37.49</u>
3	L	1.601	V	39.76	74	P	1	<u>-34.24</u>
3	L	2.407	V	44.17	74	P	1	<u>-29.83</u>
3	L	1.601	H	38.84	74	P	1	<u>-35.16</u>
3	L	2.407	H	42.79	74	P	1	<u>-31.21</u>
3	M	1.625	V	38.58	74	P	1	<u>-35.42</u>
3	M	2.437	V	46.32	74	P	1	<u>-27.68</u>
3	M	1.625	H	40.79	74	P	1	<u>-33.21</u>
3	M	2.437	H	41.66	74	P	1	<u>-32.34</u>
3	H	1.649	V	39.89	74	P	1	<u>-34.11</u>
3	H	2.479	V	43.11	74	P	1	<u>-30.89</u>
3	H	1.649	H	39.46	74	P	1	<u>-34.54</u>
3	H	2.479	H	45.14	74	P	1	<u>-28.86</u>
4	L	4.810	V	38.78	74	P	1	<u>-35.22</u>
4	L	4.810	H	44.38	74	P	1	<u>-29.62</u>
4	M	4.882	V	41.13	74	P	1	<u>-32.87</u>
4	M	4.882	H	41.04	74	P	1	<u>-32.96</u>
4	H	4.962	V	42.11	74	P	1	<u>-31.89</u>
4	H	4.962	H	38.33	74	P	1	<u>-35.67</u>

Freq. – Frequency Range:

- 1: 30 – 200 MHz
- 2: 200 – 1000 MHz
- 3: 1 – 4 GHz
- 4: 4 – 8 GHz
- 5: 8 – 12 GHz
- 6: 12 – 17 GHz
- 7: 17 – 26.5 GHz

TEST RESULT (Transmitter): The unit DOES meet the FCC requirements.

Test equipment used: ETS 0012; ETS 0013; ETS 0015; ETS 0018; ETS 0271; ETS 0253; ETS 0311

Remark: See attached diagrams Annex.

 Test Report No.: G0M20909-2577-C-1


Annex B

Fundamental Field Strength

Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: low
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC / mid:88.34dBµV/m;high:84.95dBµV/m
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq: 2.404GHz, Emax: 91.51dBµV/m, RBW: 1MHz



Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C

Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: low
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC / mid:88.66dBµV/m;high:86.18dBµV/m
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq: 2.404GHz, Emax: 92.04dBµV/m, RBW: 1MHz




Annex C

Spurious Emissions radiated - Transmitter operating

Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: low
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249
Comment 1: Dist.: 3m, Ant.: HK 116
Comment 2: Freq: 174.449MHz, Emax: 33.39dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: low
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249
Comment 1: Dist.: 3m, Ant.: HK 116
Comment 2: Freq: 186.713MHz, Emax: 33.45dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: low
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249
Comment 1: Dist.: 3m, Ant.: HL 223, amplif.
Comment 2: Freq: 801.202MHz, Emax: 30.07dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: high
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249
Comment 1: Dist.: 3m, Ant.: HL 223, amplif.
Comment 2: Freq: 826.854MHz, Emax: 28.51dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: low
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, amplif.
Comment 2: Freq: 2.407GHz, Emax: 44.17dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: low
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, amplif.
Comment 2: Freq: 2.407GHz, Emax: 42.79dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: low
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 7.984GHz, Emax: 39.27dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: low
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 4.810GHz, Emax: 44.38dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: low
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 11.439GHz, Emax: 43.57dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: low
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 11.415GHz, Emax: 43.14dBuV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: low
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 14.725GHz, Emax: 44.84dBuV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: low
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 14.806GHz, Emax: 44.75dBuV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: low
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Comment 2: Freq: 24.577GHz, Emax: 49.97dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: low
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Comment 2: Freq: 24.539GHz, Emax: 49.70dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: mid
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249
Comment 1: Dist.: 3m, Ant.: HK 116
Comment 2: Freq: 191.824MHz, Emax: 33.68dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: mid
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249
Comment 1: Dist.: 3m, Ant.: HK 116
Comment 2: Freq: 189.780MHz, Emax: 33.61dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: mid
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249
Comment 1: Dist.: 3m, Ant.: HL 223, amplif.
Comment 2: Freq: 814.028MHz, Emax: 28.44dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: lmid
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249
Comment 1: Dist.: 3m, Ant.: HL 223, amplif.
Comment 2: Freq: 858.918MHz, Emax: 24.23dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: mid
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, amplif.
Comment 2: Freq: 2.437GHz, Emax: 46.32dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: mid
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, amplif.
Comment 2: Freq: 2.437GHz, Emax: 41.66dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: mid
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 4.882GHz, Emax: 41.13dBuV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: mid
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 4.882GHz, Emax: 41.04dBuV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: mid
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 11.383GHz, Emax: 43.30dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: mid
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 11.535GHz, Emax: 42.90dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: mid
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 14.465GHz, Emax: 44.63dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: mid
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 16.990GHz, Emax: 44.84dBuV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: mid
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Comment 2: Freq: 24.653GHz, Emax: 52.23dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: mid
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Comment 2: Freq: 24.634GHz, Emax: 49.97dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: high
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249
Comment 1: Dist.: 3m, Ant.: HK 116
Comment 2: Freq: 198.637MHz, Emax: 33.67dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: high
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249
Comment 1: Dist.: 3m, Ant.: HK 116
Comment 2: Freq: 189.780MHz, Emax: 33.22dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: high
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249
Comment 1: Dist.: 3m, Ant.: HL 223, amplif.
Comment 2: Freq: 826.854MHz, Emax: 28.51dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: high
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249
Comment 1: Dist.: 3m, Ant.: HL 223, amplif.
Comment 2: Freq: 910.220MHz, Emax: 23.89dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: high
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, amplif.
Comment 2: Freq: 2.479GHz, Emax: 43.11dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: high
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, amplif.
Comment 2: Freq: 2.479GHz, Emax: 45.14dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: high
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 4.962GHz, Emax: 42.11dBuV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: high
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 7.800GHz, Emax: 39.11dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: high
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 11.607GHz, Emax: 42.75dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: high
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 11.415GHz, Emax: 43.29dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: high
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 16.960GHz, Emax: 44.78dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: high
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 14.515GHz, Emax: 44.91dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C

Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: high
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Comment 2: Freq: 24.577GHz, Emax: 51.74dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C

Approval Holder: Kondo Kagaku Co., Ltd. / Ord.: G0M20909-2577
EUT: RC transmitter for car model
Model: EX-10EURUS->RF 902S / ch.: high
Test Site / Operator: Eurofins Product Service GmbH / Mr. Handrik
Test Condition: Tnom: 23°C / Unom.: 12VDC
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Comment 2: Freq: 24.215GHz, Emax: 50.00dBµV/m, RBW: 1MHz

