



PCTEST ENGINEERING LABORATORY, INC.

6660-B Dobbin Road, Columbia, MD 21045 USA
Tel. 410.290.6652 / Fax 410.290.6554
<http://www.pctestlab.com>



MEASUREMENT REPORT FCC PART 15.247 WPAN 802.15.4 Zigbee

Applicant Name:

SmartSynch Inc.
4400 Old Canton Road, Suite 300
Jackson, MS 39211
USA

Date of Testing:

December 12-16, 2011

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Test Report Serial No.:

0Y1111282055.QHC

FCC ID: QHC-SGRCWZ

APPLICANT: SmartSynch Inc.

Application Type:

Certification

Model(s):

GridRouter CWZ

EUT Type:

Smart Grid Communications Hub

Max. RF Output Power:

10.57 mW (10.24 dBm) Peak Conducted

Frequency Range:

2405 - 2475 MHz (DSSS)

FCC Classification:

Digital Transmission System (DTS)

FCC Rule Part(s):

Part 15.247

Test Device Serial No.:

N/A

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C-63.4-2003. Test results reported herein relate only to the item(s) tested.



I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Grant Conditions: Power output listed is conducted.

PCTEST certifies that no party to this application has been subject to a denial of Federal benefits that includes FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.




Randy Ortanez
President



FCC ID: QHC-SGRCWZ		FCC Pt. 15.247 802.15.4 ZIGBEE TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1111282055.QHC	Test Dates: December 12-16, 2011	EUT Type: Smart Grid Communications Hub		Page 1 of 32

T A B L E O F C O N T E N T S

FCC PART 15.247 MEASUREMENT REPORT.....	3
1.0 INTRODUCTION.....	4
1.1 SCOPE.....	4
1.2 PCTEST TEST LOCATION.....	4
2.0 PRODUCT INFORMATION.....	5
2.1 EQUIPMENT DESCRIPTION.....	5
2.2 EUT CAPABILITIES.....	5
2.3 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS.....	5
2.4 LABELING REQUIREMENTS.....	5
3.0 DESCRIPTION OF TEST.....	6
3.1 EVALUATION PROCEDURE.....	6
3.2 RADIATED EMISSIONS.....	6
4.0 ANTENNA REQUIREMENTS.....	7
5.0 TEST EQUIPMENT CALIBRATION DATA.....	8
6.0 TEST RESULTS.....	9
6.1 SUMMARY.....	9
6.2 6DB BANDWIDTH MEASUREMENT.....	10
6.3 OUTPUT POWER MEASUREMENT.....	12
6.4 POWER SPECTRAL DENSITY.....	13
6.5 CONDUCTED EMISSIONS AT THE BAND EDGE.....	15
6.6 CONDUCTED SPURIOUS EMISSIONS.....	18
6.7 RADIATED SPURIOUS EMISSION MEASUREMENTS.....	21
6.8 RADIATED RESTRICTED BAND EDGE MEASUREMENTS.....	25
6.9 LINE-CONDUCTED TEST DATA.....	30
7.0 CONCLUSION.....	32

FCC ID: QHC-SGRCWZ		FCC Pt. 15.247 802.15.4 ZIGBEE TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1111282055.QHC	Test Dates: December 12-16, 2011	EUT Type: Smart Grid Communications Hub		Page 2 of 32



MEASUREMENT REPORT

FCC Part 15.247



§ 2.1033 General Information

APPLICANT: SmartSynch Inc.

APPLICANT ADDRESS: 4400 Old Canton Road, Suite 300
Jackson, MS 39211, USA

TEST SITE: PCTEST ENGINEERING LABORATORY, INC.

TEST SITE ADDRESS: 6660-B Dobbin Road, Columbia, MD 21045 USA

FCC RULE PART(S): Part 15.247

MODEL NAME: GridRouter CWZ

FCC ID: QHC-SGRCWZ

Test Device Serial No.: N/A ☐ Production ☒ Pre-Production ☐ Engineering

FCC CLASSIFICATION: Digital Transmission System (DTS)

DATE(S) OF TEST: December 12-16, 2011

TEST REPORT S/N: 0Y1111282055.QHC



Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21045, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 90864) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451A-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451A-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.



FCC ID: QHC-SGRCWZ		FCC Pt. 15.247 802.15.4 ZIGBEE TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1111282055.QHC	Test Dates: December 12-16, 2011	EUT Type: Smart Grid Communications Hub		Page 3 of 32

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.

1.2 PCTEST Test Location

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity area, the Baltimore-Washington Internt'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2003 on January 27, 2006.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: QHC-SGRCWZ	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.15.4 ZIGBEE TEST REPORT (CERTIFICATION)	Smart Synch	Reviewed by: Quality Manager
Test Report S/N: 0Y1111282055.QHC	Test Dates: December 12-16, 2011	EUT Type: Smart Grid Communications Hub		Page 4 of 32

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **SmartSynch Smart Grid Communications Hub** FCC ID: **QHC-SGRCWZ**. The EUT consisted of the following component(s):

Manufacturer / Model	FCC ID	Description
SmartSynch / Model: GridRouter CWZ	QHC-SGRCWZ	Smart Grid Communications Hub

Table 2-1. EUT Equipment Description

2.2 EUT Capabilities

850/1900 GSM/GPRS/EDGE, 850/1900 WCDMA, 802.11b/g WLAN, Zigbee

2.3 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

2.4 Labeling Requirements

Per 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the trade name and FCC ID must be displayed on the device per Section 15.19(b)(2).

Please see attachment for FCC ID label and label location.

FCC ID: QHC-SGRCWZ		FCC Pt. 15.247 802.15.4 ZIGBEE TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1111282055.QHC	Test Dates: December 12-16, 2011	EUT Type: Smart Grid Communications Hub		Page 5 of 32

3.0 DESCRIPTION OF TEST

3.1 Evaluation Procedure

The measurement procedure described in the American National Standard for Methods of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz (ANSI C63.4-2003) and FCC procedure dated March 23, 2005 entitled "Measurements of Digital Transmission Systems Operating Under Section 15.247" were used in the measurement of the **SmartSynch Smart Grid Communications Hub FCC ID: QHC-SGRCWZ**.

Deviation from measurement procedure.....None

3.2 Radiated Emissions




Figure 3-1. 3-Meter Test Site




Figure 3-2. Dimensions of Outdoor Test Site




Figure 3-3. Turntable and System Setup






Figure 3-4. Normalized Site Attenuation Curves (H&V)

Preliminary measurements were made indoors at 1-meter using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequency producing the maximum EME. Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, and turntable azimuth with respect to the antenna was noted for each frequency found. The spectrum was scanned from 30 to 200 MHz using a bi-conical antenna and from 200 to 1000 MHz using a log-spiral antenna. Above 1 GHz, linearly polarized double ridge horn antennas were used.

Final measurements were made outdoors at 3-meter test range using RobertsTM Dipole antennas or horn antennas (see Figure 3-1). The test equipment was placed on a wooden and plastic bench situated on a 1.5m x 2m area adjacent to the measurement area (see Figure 3-2). Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The detector function was set to CISPR quasi-peak mode and the bandwidth of the spectrum analyzer was set to 100kHz for frequencies below 1GHz or 1MHz for frequencies above 1GHz. Above 1GHz the detector function was set to average mode (RBW = 1MHz, VBW = 10Hz).

The half-wave dipole antenna was tuned to the frequency found during preliminary radiated measurements. The EUT, support equipment and interconnecting cables were re-configured to the set-up producing the maximum emission for the frequency and were placed on top of a 0.8-meter high non-metallic 1 x 1.5 meter table (see Figure 3-3). The EUT, support equipment, and interconnecting cables were re-arranged and manipulated to maximize each EME emission. The turntable containing the system was rotated and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by: varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and/or support equipment, and powering the monitor from the floor mounted outlet box and the computer aux AC outlet, if applicable; and changing the polarity of the antenna, whichever determined the worst-case emission. Photographs of the worst-case emission can be seen in the test setup photographs. Each EME reported was calibrated using the Agilent E8257D (250kHz – 20GHz) PSG Signal Generator. The Theoretical Normalized Site Attenuation Curves for both horizontal and vertical polarization are shown in Figure 3-4.

FCC ID: QHC-SGRCWZ		FCC Pt. 15.247 802.15.4 ZIGBEE TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1111282055.QHC	Test Dates: December 12-16, 2011	EUT Type: Smart Grid Communications Hub		Page 6 of 32

4.0 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”



- The antenna(s) of the Smart Grid Communications Hub are **uniquely coupled** to the intentional radiator via a reverse SMA connector.

Conclusion:

The **SmartSynch Smart Grid Communications Hub FCC ID: QHC-SGRCWZ** unit complies with the requirement of §15.203.

Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
11	2405	19	2445
12	2410	20	2450
13	2415	21	2455
14	2420	22	2460
15	2425	23	2465
16	2430	24	2470
17	2435	25	2475
18	2440		

Table 4-1. Frequency / Channel Operations



FCC ID: QHC-SGRCWZ		FCC Pt. 15.247 802.15.4 ZIGBEE TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1111282055.QHC	Test Dates: December 12-16, 2011	EUT Type: Smart Grid Communications Hub		Page 7 of 32

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	No. 165	(30MHz - 1000MHz) RG58 Coax Cable	N/A		N/A	N/A
-	No. 166	(1000-26500MHz) Microwave RF Cable	N/A		N/A	N/A
-	No. 167	(100kHz - 100MHz) RG58 Coax Cable	N/A		N/A	N/A
Agilent	8447D	Broadband Amplifier	3/17/2011	Annual	3/17/2012	1937A03348
Agilent	8447D	Broadband Amplifier	3/17/2011	Annual	3/17/2012	2443A01900
Agilent	8449B	(1-26.5GHz) Pre-Amplifier	2/8/2011	Annual	2/8/2012	3008A00985
Agilent	85650A	Quasi-Peak Adapter	4/7/2011	Annual	4/7/2012	3303A01872
Agilent	85650A	Quasi-Peak Adapter	4/7/2011	Annual	4/7/2012	2043A00301
Agilent	8566B	(100Hz-22GHz) Spectrum Analyzer	4/7/2011	Annual	4/7/2012	2618A02866
Agilent	8566B	(100Hz-22GHz) Spectrum Analyzer	4/7/2011	Annual	4/7/2012	2542A11898
Agilent	8566B	(100Hz-22GHz) Spectrum Analyzer	4/7/2011	Annual	4/7/2012	3638A08713
Agilent	E4407B	ESA Spectrum Analyzer	4/5/2011	Annual	4/5/2012	US39210313
Agilent	E8257D	(250kHz-20GHz) Signal Generator	4/8/2011	Annual	4/8/2012	MY45470194
Agilent	N9020A	MXA Signal Analyzer	10/10/2011	Annual	10/10/2012	US46470561
Agilent	N9038A	MXE EMI Receiver	8/5/2011	Annual	8/5/2012	MY51210133
Anritsu	MA2411B	Pulse Sensor	10/13/2011	Annual	10/13/2012	1027293
Anritsu	ML2495A	Power Meter	10/13/2011	Annual	10/13/2012	1039008
Emco	3115	Horn Antenna (1-18GHz)	4/8/2010	Biennial	4/8/2012	9205-3874
Emco	3816/2	LISN	11/5/2010	Biennial	11/5/2012	9707-1077
Emco	3816/2	LISN	11/3/2010	Biennial	11/3/2012	9707-1079
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	7/22/2011	Annual	7/22/2012	125518
ETS Lindgren	3160-09	18-26.5 GHz Standard Gain Horn	5/31/2011	Annual	5/31/2012	135427
Gigatronics	80701A	(0.05-18GHz) Power Sensor	10/12/2011	Annual	10/12/2012	1833460
Gigatronics	8651A	Universal Power Meter	10/12/2011	Annual	10/12/2012	8650319
MiniCircuits	VHF-3100+	High Pass Filter	N/A		N/A	30721
Rohde & Schwarz	RS-PR18	1-18 GHz Pre-Amplifier	6/9/2011	Annual	6/9/2012	100071
Rohde & Schwarz	RS-PR26	18-26.5 GHz Pre-Amplifier	6/9/2011	Annual	6/9/2012	100040
Schwarzbeck	VULB-9161SE	Trilog Super Broadband Test Antenna	11/8/2011	Biennial	11/8/2013	9161-4075
Sunol	DRH-118	Horn Antenna (1 - 18GHz)	7/5/2011	Biennial	7/5/2013	A050307

Table 5-1. Annual Test Equipment Calibration Schedule

FCC ID: QHC-SGRCWZ		FCC Pt. 15.247 802.15.4 ZIGBEE TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y111282055.QHC	Test Dates: December 12-16, 2011	EUT Type: Smart Grid Communications Hub		Page 8 of 32



6.0 TEST RESULTS

6.1 Summary

Company Name: SmartSynch Inc.
 FCC ID: QHC-SGRCWZ
 FCC Classification: Digital Transmission System (DTS)

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
TRANSMITTER MODE (TX)					
15.247(a)(2)	6dB Bandwidth	> 500kHz	CONDUCTED	PASS	Section 6.2
15.247(b)(3)	Transmitter Output Power	< 1 Watt		PASS	Sections 6.3
15.247(e)	Transmitter Power Spectral Density	< 8dBm / 3kHz Band		PASS	Section 6.4
15.247(d)	Band Edge / Out-of-Band Emissions	Conducted < 30dBc		PASS	Sections 6.5, 6.6
15.205 15.209	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-210 table 3 limits)	RADIATED	PASS	Sections 6.7, 6.8
15.207	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 limits or < RSS-Gen table 2 limits	LINE CONDUCTED	PASS	Section 6.9
RECEIVER MODE (RX) / DIGITAL EMISSIONS					
15.107	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.107 limits or < RSS-Gen table 2 limits	LINE CONDUCTED	PASS	Part 15B Test Report
15.109	General Field Strength Limits (Restricted Bands and Radiated Emissions Limits)	< FCC 15.109 limits or < RSS-210 table 3 limits	RADIATED (30MHz-1GHz) (1-25 GHz)	PASS	Part 15B Test Report

Table 6-1. Summary of Test Results

FCC ID: QHC-SGRCWZ		FCC Pt. 15.247 802.15.4 ZIGBEE TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1111282055.QHC	Test Dates: December 12-16, 2011	EUT Type: Smart Grid Communications Hub		Page 9 of 32

6.2 6dB Bandwidth Measurement

§15.247(a)(2)

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the receive antenna while the EUT is operating in transmission mode at the appropriate frequencies. **The minimum permissible 6dB bandwidth is 500 kHz.**

Frequency [MHz]	Channel No.	Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]	Pass / Fail
2405	11	1.658	0.500	Pass
2440	18	1.633	0.500	Pass
2475	25	1.808	0.500	Pass

Table 6-2. Conducted Bandwidth Measurements






Figure 6-1. Test Instrument & Measurement Setup




Plot 6-1. 6dB Bandwidth Plot (802.15.4 – Ch. 11)

FCC ID: QHC-SGRCWZ	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.15.4 ZIGBEE TEST REPORT (CERTIFICATION)	SmartSynch	Reviewed by: Quality Manager
Test Report S/N: 0Y1111282055.QHC	Test Dates: December 12-16, 2011	EUT Type: Smart Grid Communications Hub		Page 10 of 32



Plot 6-2. 6dB Bandwidth Plot (802.15.4 – Ch. 18)



Plot 6-3. 6dB Bandwidth Plot (802.15.4 – Ch. 25)

FCC ID: QHC-SGRCWZ	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.15.4 ZIGBEE TEST REPORT (CERTIFICATION)	SmartSynch	Reviewed by: Quality Manager
Test Report S/N: 0Y1111282055.QHC	Test Dates: December 12-16, 2011	EUT Type: Smart Grid Communications Hub		Page 11 of 32

6.3 Output Power Measurement

§15.247(b)(3)

A transmitter antenna terminal of EUT is connected to the input of an RF power sensor. Measurement is made using a broadband power meter while the EUT is operating in transmission mode at the appropriate frequencies. ***The maximum permissible conducted output power is 1 Watt.***

Freq [MHz]	Channel	Measured Peak Power [dBm]
2405	11	-13.81
2410	12	-13.88
2415	13	-6.9
2420	14	10.24
2440	18	10.1
2465	23	9.43
2470	24	9.31
2475	25	-15.05

Table 6-3. Conducted Output Power Measurements






Figure 6-2. Test Instrument & Measurement Setup



Plot 6-5. Power Spectral Density Plot (802.15.4 – Ch. 18)




Plot 6-6. Power Spectral Density Plot (802.15.4 – Ch. 25)


FCC ID: QHC-SGRCWZ	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.15.4 ZIGBEE TEST REPORT (CERTIFICATION)	SmartSynch	Reviewed by: Quality Manager
Test Report S/N: 0Y1111282055.QHC	Test Dates: December 12-16, 2011	EUT Type: Smart Grid Communications Hub		Page 14 of 32

6.5 Conducted Emissions at the Band Edge

\$15.247(d)




Plot 6-7. Band Edge Plot (802.15.4 – Ch. 11)




Plot 6-8. Band Edge Plot (802.15.4 – Ch. 12)

FCC ID: QHC-SGRCWZ	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.15.4 ZIGBEE TEST REPORT (CERTIFICATION)	Smart Synch	Reviewed by: Quality Manager
Test Report S/N: 0Y1111282055.QHC	Test Dates: December 12-16, 2011	EUT Type: Smart Grid Communications Hub		Page 15 of 32




Plot 6-9. Band Edge Plot (802.15.4 – Ch. 13)




Plot 6-10. Band Edge Plot (802.15.4 – Ch. 14)

FCC ID: QHC-SGRCWZ	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.15.4 ZIGBEE TEST REPORT (CERTIFICATION)	Smart Synch	Reviewed by: Quality Manager
Test Report S/N: 0Y1111282055.QHC	Test Dates: December 12-16, 2011	EUT Type: Smart Grid Communications Hub		Page 16 of 32



Plot 6-11. Band Edge Plot (802.15.4 – Ch. 24)




Plot 6-12. Band Edge Plot (802.15.4 – Ch. 25)


FCC ID: QHC-SGRCWZ	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.15.4 ZIGBEE TEST REPORT (CERTIFICATION)	SmartSynch	Reviewed by: Quality Manager
Test Report S/N: 0Y1111282055.QHC	Test Dates: December 12-16, 2011	EUT Type: Smart Grid Communications Hub		Page 17 of 32

6.6 Conducted Spurious Emissions

§15.247(d)




Plot 6-13. Conducted Spurious Plot (802.15.4 – Ch. 11)




Plot 6-14. Conducted Spurious Plot (802.15.4 – Ch. 11)

FCC ID: QHC-SGRCWZ	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.15.4 ZIGBEE TEST REPORT (CERTIFICATION)	SmartSynch	Reviewed by: Quality Manager
Test Report S/N: 0Y1111282055.QHC	Test Dates: December 12-16, 2011	EUT Type: Smart Grid Communications Hub		Page 18 of 32




Plot 6-15. Conducted Spurious Plot (802.15.4 – Ch. 18)




Plot 6-16. Conducted Spurious Plot (802.15.4 – Ch. 18)

FCC ID: QHC-SGRCWZ	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.15.4 ZIGBEE TEST REPORT (CERTIFICATION)	SmartSynch	Reviewed by: Quality Manager
Test Report S/N: 0Y1111282055.QHC	Test Dates: December 12-16, 2011	EUT Type: Smart Grid Communications Hub		Page 19 of 32



Plot 6-17. Conducted Spurious Plot (802.15.4 – Ch. 25)



Plot 6-18. Conducted Spurious Plot (802.15.4 – Ch. 25)

FCC ID: QHC-SGRCWZ	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.15.4 ZIGBEE TEST REPORT (CERTIFICATION)	SmartSynch	Reviewed by: Quality Manager
Test Report S/N: 0Y1111282055.QHC	Test Dates: December 12-16, 2011	EUT Type: Smart Grid Communications Hub		Page 20 of 32

6.7 Radiated Spurious Emission Measurements

§15.247(d) / §15.205

The EUT was tested from 9kHz up to the tenth harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average measurements were taken using RBW = 1MHz, VBW = 10Hz, and linearly polarized horn antennas. Peak measurements above 1 GHz utilized RBW=VBW=1MHz. All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table 6-5 per Section 15.209

Frequency	Field Strength [μV/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3



Table 6-5. Radiated Limits

Sample Calculation

- Field Strength Level $_{[dB\mu V/m]} = \text{Analyzer Level}_{[dBm]} + 107 + \text{AFCL}_{[dB]}$

Notes:

- AFCL = Antenna Factor $_{[dB]} + \text{Cable Loss}_{[dB]}$

FCC ID: QHC-SGRCWZ		FCC Pt. 15.247 802.15.4 ZIGBEE TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1111282055.QHC	Test Dates: December 12-16, 2011	EUT Type: Smart Grid Communications Hub		Page 21 of 32

Radiated Spurious Emission Measurements (Cont'd)

§15.247(d) / §15.205

Distance of Measurements: 3 Meters

Operating Frequency: 2405MHz



Channel: 11

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol [H/V]	AFCL [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4810.00	-109.69	Avg	V	41.93	39.23	53.98	-14.75
4810.00	-99.39	Peak	V	41.93	49.53	73.98	-24.45
12025.00	-135.00	Avg	V	53.16	25.16	53.98	-28.82
12025.00	-125.00	Peak	V	53.16	35.16	73.98	-38.82

Table 6-6. Radiated Measurements @ 3 meters

NOTES:

1. All emissions shown lie in the restricted bands specified in §15.205 and RSS-210 section 2.7, Table 1 and are below the limit shown in Table 6-5.
2. Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz. Peak measurements above 1 GHz utilized RBW=VBW=1MHz.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The EUT is supplied with nominal AC voltage.
5. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported. No significant emissions were found beyond the fifth harmonic for this device.
6. Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
7. Above 960MHz the limit is 500 μV/m (54dBμ/m) at 3 meters radiated.

FCC ID: QHC-SGRCWZ		FCC Pt. 15.247 802.15.4 ZIGBEE TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1111282055.QHC	Test Dates: December 12-16, 2011	EUT Type: Smart Grid Communications Hub		Page 22 of 32

Radiated Spurious Emission Measurements (Cont'd)

§15.247(d) / §15.205

Distance of Measurements: 3 Meters

Operating Frequency: 2440MHz

Channel: 18

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol [H/V]	AFCL [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
4880.00	-103.92	Avg	V	42.16	45.25	53.98	-8.73
4880.00	-94.92	Peak	V	42.16	54.25	73.98	-19.73
7320.00	-135.00	Avg	V	47.57	19.57	53.98	-34.41
7320.00	-125.00	Peak	V	47.57	29.57	73.98	-44.41
12200.00	-135.00	Avg	V	53.13	25.13	53.98	-28.85
12200.00	-125.00	Peak	V	53.13	35.13	73.98	-38.85

Table 6-7. Radiated Measurements @ 3 meters

NOTES:

1. All emissions shown lie in the restricted bands specified in §15.205 and RSS-210 section 2.7, Table 1 and are below the limit shown in Table 6-5.
2. Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz. Peak measurements above 1 GHz utilized RBW=VBW=1MHz.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The EUT is supplied with nominal AC voltage.
5. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported. No significant emissions were found beyond the fifth harmonic for this device.
6. Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
7. Above 960MHz the limit is 500 μ V/m (54dB μ /m) at 3 meters radiated.

FCC ID: QHC-SGRCWZ		FCC Pt. 15.247 802.15.4 ZIGBEE TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1111282055.QHC	Test Dates: December 12-16, 2011	EUT Type: Smart Grid Communications Hub		Page 23 of 32

Radiated Spurious Emission Measurements (Cont'd)

§15.247(d) / §15.205

Distance of Measurements: 3 Meters

Operating Frequency: 2475MHz

Channel: 25

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol [H/V]	AFCL [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4950.00	-110.84	Avg	V	42.40	38.56	53.98	-15.42
4950.00	-99.04	Peak	V	42.40	50.36	73.98	-23.62
7425.00	-135.00	Avg	V	47.60	19.60	53.98	-34.38
7425.00	-125.00	Peak	V	47.60	29.60	73.98	-44.38
12375.00	-135.00	Avg	V	53.10	25.10	53.98	-28.88
12375.00	-125.00	Peak	V	53.10	35.10	73.98	-38.88

Table 6-8. Radiated Measurements @ 3 meters

NOTES:

1. All emissions shown lie in the restricted bands specified in §15.205 and RSS-210 section 2.7, Table 1 and are below the limit shown in Table 6-5.
2. Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz. Peak measurements above 1 GHz utilized RBW=VBW=1MHz.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The EUT is supplied with nominal AC voltage.
5. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported. No significant emissions were found beyond the fifth harmonic for this device.
6. Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
7. Above 960MHz the limit is 500 μV/m (54dBμ/m) at 3 meters radiated.

FCC ID: QHC-SGRCWZ		FCC Pt. 15.247 802.15.4 ZIGBEE TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1111282055.QHC	Test Dates: December 12-16, 2011	EUT Type: Smart Grid Communications Hub		Page 24 of 32

6.8 Radiated Restricted Band Edge Measurements

§15.205 / §15.209

Distance of Measurements: 3 Meters

Operating Frequency: 2405 MHz



Channel: 11

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol [H/V]	AFCL [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
2340.80	-97.61	Avg	V	35.53	44.92	53.98	-9.06
2340.80	-88.71	Peak	V	35.53	53.82	73.98	-20.16
2357.90	-102.10	Avg	V	35.67	40.57	53.98	-13.41
2357.90	-91.30	Peak	V	35.67	51.37	73.98	-22.61
2388.30	-102.97	Avg	V	35.92	39.95	53.98	-14.03
2388.30	-93.07	Peak	V	35.92	49.85	73.98	-24.13

Table 6-9. Radiated Restricted Band Edge Measurements (2310 – 2390 MHz)

NOTES:

1. All emissions shown lie in the restricted bands specified in §15.205 and RSS-210 section 2.7, Table 1 and are below the limit shown in Table 6-5.
2. Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz. . Peak measurements above 1 GHz utilized RBW=VBW=1MHz.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The EUT is supplied with nominal AC voltage.
5. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported. No significant emissions were found beyond the fifth harmonic for this device.
6. Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
7. Above 960MHz the limit is 500 μ V/m (54dB μ /m) at 3 meters radiated.

FCC ID: QHC-SGRCWZ		FCC Pt. 15.247 802.15.4 ZIGBEE TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1111282055.QHC	Test Dates: December 12-16, 2011	EUT Type: Smart Grid Communications Hub		Page 25 of 32

Radiated Restricted Band Edge Measurements (Cont'd)

§15.205 / §15.209

Distance of Measurements: 3 Meters

Operating Frequency: 2415 MHz



Channel: 13

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol [H/V]	AFCL [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
2350.80	-94.43	Avg	V	35.06	47.63	53.98	-6.35
2350.80	-87.53	Peak	V	35.06	54.53	73.98	-19.45
2368.20	-106.73	Avg	V	35.25	35.52	53.98	-18.46
2368.20	-91.43	Peak	V	35.25	50.82	73.98	-23.16
2380.80	-103.80	Avg	V	35.38	38.58	53.98	-15.40
2380.80	-90.10	Peak	V	35.38	52.28	73.98	-21.70

Table 6-10. Radiated Restricted Band Edge Measurements (2310 – 2390 MHz)

NOTES:

1. All emissions shown lie in the restricted bands specified in §15.205 and RSS-210 section 2.7, Table 1 and are below the limit shown in Table 6-5.
2. Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz. . Peak measurements above 1 GHz utilized RBW=VBW=1MHz.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The EUT is supplied with nominal AC voltage.
5. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported. No significant emissions were found beyond the fifth harmonic for this device.
6. Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
7. Above 960MHz the limit is 500 μ V/m (54dB μ /m) at 3 meters radiated.

FCC ID: QHC-SGRCWZ		FCC Pt. 15.247 802.15.4 ZIGBEE TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1111282055.QHC	Test Dates: December 12-16, 2011	EUT Type: Smart Grid Communications Hub		Page 26 of 32

Radiated Restricted Band Edge Measurements (Cont'd)

§15.205 / §15.209

Distance of Measurements: 3 Meters

Operating Frequency: 2420 MHz



Channel: 14

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol [H/V]	AFCL [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
2347.60	-96.33	Avg	V	35.02	45.69	53.98	-8.29
2347.60	-85.83	Peak	V	35.02	56.19	73.98	-17.79
2355.70	-92.33	Avg	V	35.11	49.78	53.98	-4.20
2355.70	-82.43	Peak	V	35.11	59.68	73.98	-14.30
2380.80	-94.00	Avg	V	35.38	48.38	53.98	-5.60
2380.80	-70.10	Peak	V	35.38	72.28	73.98	-1.70

Table 6-11. Radiated Restricted Band Edge Measurements (2310 – 2390 MHz)

NOTES:

1. All emissions shown lie in the restricted bands specified in §15.205 and RSS-210 section 2.7, Table 1 and are below the limit shown in Table 6-5.
2. Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz. . Peak measurements above 1 GHz utilized RBW=VBW=1MHz.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The EUT is supplied with nominal AC voltage.
5. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported. No significant emissions were found beyond the fifth harmonic for this device.
6. Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
7. Above 960MHz the limit is 500 μ V/m (54dB μ /m) at 3 meters radiated.

FCC ID: QHC-SGRCWZ		FCC Pt. 15.247 802.15.4 ZIGBEE TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1111282055.QHC	Test Dates: December 12-16, 2011	EUT Type: Smart Grid Communications Hub		Page 27 of 32

Radiated Restricted Band Edge Measurements (Cont'd)

§15.205 / §15.209

Distance of Measurements: 3 Meters

Operating Frequency: 2470 MHz



Channel: 24

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol [H/V]	AFCL [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
2483.50	-91.37	Avg	V	36.34	51.97	53.98	-2.01
2483.50	-83.67	Peak	V	36.34	59.67	73.98	-14.31
2484.30	-91.68	Avg	V	36.35	51.67	53.98	-2.31
2484.30	-78.78	Peak	V	36.35	64.57	73.98	-9.41
2487.60	-93.09	Avg	V	36.36	50.27	53.98	-3.71
2487.60	-84.19	Peak	V	36.36	59.17	73.98	-14.81

Table 6-12. Radiated Restricted Band Edge Measurements (2483.5 – 2500 MHz)

NOTES:

1. All emissions shown lie in the restricted bands specified in §15.205 and RSS-210 section 2.7, Table 1 and are below the limit shown in Table 6-5.
2. Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz. . Peak measurements above 1 GHz utilized RBW=VBW=1MHz.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The EUT is supplied with nominal AC voltage.
5. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported. No significant emissions were found beyond the fifth harmonic for this device.
6. Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
7. Above 960MHz the limit is 500 μV/m (54dBμ/m) at 3 meters radiated.

FCC ID: QHC-SGRCWZ		FCC Pt. 15.247 802.15.4 ZIGBEE TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1111282055.QHC	Test Dates: December 12-16, 2011	EUT Type: Smart Grid Communications Hub		Page 28 of 32

Radiated Restricted Band Edge Measurements (Cont'd)

§15.205 / §15.209

Distance of Measurements: 3 Meters

Operating Frequency: 2475MHz



Channel: 25

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol [H/V]	AFCL [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
2483.50	-109.87	Avg	V	36.36	33.49	53.98	-20.49
2483.50	-98.67	Peak	V	36.36	44.69	73.98	-29.29
2489.30	-109.29	Avg	V	36.39	34.10	53.98	-19.88
2489.30	-95.69	Peak	V	36.39	47.70	73.98	-26.28
2498.40	-109.22	Avg	V	36.42	34.21	53.98	-19.77
2498.40	-95.22	Peak	V	36.42	48.21	73.98	-25.77

Table 6-13. Radiated Restricted Band Edge Measurements (2483.5 – 2500 MHz)

NOTES:

1. All emissions shown lie in the restricted bands specified in §15.205 and RSS-210 section 2.7, Table 1 and are below the limit shown in Table 6-5.
2. Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz. . Peak measurements above 1 GHz utilized RBW=VBW=1MHz.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The EUT is supplied with nominal AC voltage.
5. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported. No significant emissions were found beyond the fifth harmonic for this device.
6. Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
7. Above 960MHz the limit is 500 μV/m (54dBμ/m) at 3 meters radiated.

FCC ID: QHC-SGRCWZ		FCC Pt. 15.247 802.15.4 ZIGBEE TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1111282055.QHC	Test Dates: December 12-16, 2011	EUT Type: Smart Grid Communications Hub		Page 29 of 32


6.9 Line-Conducted Test Data

§15.207; RSS-Gen [7.2.2]

PCTEST Engineering Laboratory Inc.

Company : SmartSynch Inc.
 Model Number : GridRouter CWZ
 FCC ID Code : QHC-SGRCWZ
 Standard : FCC Part 15C, 15.207

Power Source : AC120V/60Hz
 Tested Date : 12/14/2011
 Note : Tested with Zigbee Tx ON





Ver.1.1 ©PCTEST 2006.08

Plot 6-19. Line Conducted Plot with Zigbee

Notes:

1. All modes of operation were investigated and the worst-case emissions are reported.
2. The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
3. Line A = Phase; Line B = Neutral
4. Traces shown in plot are made using a peak detector.
5. Deviations to the Specifications: None.

FCC ID: QHC-SGRCWZ		FCC Pt. 15.247 802.15.4 ZIGBEE TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1111282055.QHC	Test Dates: December 12-16, 2011	EUT Type: Smart Grid Communications Hub		Page 30 of 32

Line-Conducted Test Data (Cont'd)



§15.207; RSS-Gen [7.2.2]

No.	Line	Frequency [MHz]	Factor [dB]	QP [dBμV]	Limit [dBμV]	Margin [dB]	Average [dBμV]	Limit [dBμV]	Margin [dB]
1	A	0.153	6.85	54.09	65.86	-11.77	38.66	55.86	-17.20
2	A	26.992	9.27	44.58	60.00	-15.42	38.90	50.00	-11.10
3	A	27.215	9.29	44.80	60.00	-15.20	38.84	50.00	-11.16
4	A	27.356	9.30	44.71	60.00	-15.29	38.88	50.00	-11.12
5	A	27.541	9.32	44.53	60.00	-15.47	38.50	50.00	-11.50
6	A	29.329	9.49	43.94	60.00	-16.06	37.93	50.00	-12.07
7	A	29.446	9.50	44.37	60.00	-15.63	38.28	50.00	-11.72
8	A	29.631	9.52	44.92	60.00	-15.08	38.67	50.00	-11.33
9	A	29.640	9.52	44.82	60.00	-15.18	38.58	50.00	-11.42
10	A	29.853	9.54	45.14	60.00	-14.86	38.47	50.00	-11.53
11	B	0.153	6.84	52.49	65.86	-13.37	41.32	55.86	-14.54
12	B	26.488	9.39	42.38	60.00	-17.62	36.60	50.00	-13.40
13	B	26.788	9.42	42.29	60.00	-17.71	36.66	50.00	-13.34
14	B	26.983	9.44	42.44	60.00	-17.56	36.87	50.00	-13.13
15	B	27.160	9.46	42.58	60.00	-17.42	36.95	50.00	-13.05
16	B	27.343	9.48	42.36	60.00	-17.64	36.45	50.00	-13.55
17	B	27.681	9.52	42.01	60.00	-17.99	36.02	50.00	-13.98
18	B	29.666	9.73	43.27	60.00	-16.73	36.05	50.00	-13.95
19	B	29.753	9.74	43.37	60.00	-16.63	36.10	50.00	-13.90
20	B	29.905	9.75	43.25	60.00	-16.75	35.99	50.00	-14.01

Table 6-14. Line Conducted Data with Zigbee



Notes:

1. All Modes of operation were investigated and the worst-case emissions are reported.
2. The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
3. Line A = Phase; Line B = Neutral
4. Traces shown in plot are made using a peak detector.
5. Deviations to the Specifications: None.

FCC ID: QHC-SGRCWZ		FCC Pt. 15.247 802.15.4 ZIGBEE TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1111282055.QHC	Test Dates: December 12-16, 2011	EUT Type: Smart Grid Communications Hub		Page 31 of 32

7.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **SmartSynch Smart Grid Communications Hub FCC ID: QHC-SGRCWZ** is in compliance with Part 15C of the FCC Rules.

FCC ID: QHC-SGRCWZ		FCC Pt. 15.247 802.15.4 ZIGBEE TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1111282055.QHC	Test Dates: December 12-16, 2011	EUT Type: Smart Grid Communications Hub		Page 32 of 32