

REPORT ON EXPOSURE TO ELECTROMAGNETIC FIELDS

No. 2010320STO-306

EQUIPMENT

Equipment: Radio module with Bluetooth Low Energy 1 Mbit

Type/Model: NeoNatalie Live

Manufacturer: Laerdal Medical AS

Tested by request of: Laerdal Global Health AS

SUMMARY

Based on the assessment in this statement, the equipment is determined to **comply** with the following requirements without testing:

EN 50663: 2017

CFR 47 §1.1307, §1.1310

RSS-102 Issue 5

Date of issue: June 03, 2020

Tested by:



Robert Hietala

Approved by:



Therese Littman

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Revision History

Test report number	Date	Description	Changes
2010320STO-306	June 03, 2020	First release	--

CONTENTS

	Page
1 Client Information	4
2 Equipment	4
2.1 Identification of the equipment	4
3 Test Specifications	4
3.1 Standards	4
3.2 Additions, deviations and exclusions from standards	5
4 Summary	5
5 RF Exposure, single transmitter	6
5.1 Limits	6
5.2 Calculations.....	8
5.3 Results	8

1 CLIENT INFORMATION

This assessment has been done by request of:

Company	Laerdal Global Health AS P.O. Box 377 Tanke Svilandsgt. 30, 4002 Stavanger Norway
Name of contact	Lars Roger Solem Phone +47 938 41 408

2 EQUIPMENT

2.1 Identification of the equipment

Equipment:	Radio module with Bluetooth Low Energy 1 Mbit
Type/Model:	NeoNatalie Live
Brand name:	Laerdal
Manufacturer:	Laerdal Medical AS
Transmitter frequency range:	2402 – 2480 MHz
Measured output power to antenna ¹ :	-12.1 dBm
Declared output power (EIRP):	0 dBm
Antenna gain:	-0.5 dBi
User separation distance:	5 mm
Exposure conditions:	<input type="checkbox"/> Controlled environment (occupational) <input checked="" type="checkbox"/> Uncontrolled environment (general population)
Region of body:	<input checked="" type="checkbox"/> Head or trunk <input type="checkbox"/> Limbs

¹Reference for measurement: Intertek Test report 2010320STO-303

3 TEST SPECIFICATIONS

3.1 Standards

EN 50663: 2017: Generic standard for assessment of low power electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (10 MHz - 300 GHz)

EN 62479:2010, Assessment of the compliance of low power electronic and electrical equipment with the basic restrictions related to human exposure to electromagnetic fields (10 MHz to 300 GHz)

CFR 47: Code of Federal Regulations Title 47: Telecommunications §1.1307, §1.1310
KDB447498 D01 v06

RSS-102: Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)

3.2 Additions, deviations and exclusions from standards

No additions, deviations or exclusions have been made from standards.

4 SUMMARY

The evaluation has been carried out at the Intertek Semko AB premises in Kista, Sweden. The results in this report apply only to sample tested:

Test	Result
RF Exposure, single transmitter	PASS
RF Exposure, multiple simultaneous transmitters	NA ¹

1. EUT only has a single transmitter or transmitters can't operate simultaneously

5 RF EXPOSURE, SINGLE TRANSMITTER

Result:	PASS
----------------	------

5.1 Limits

Reference: COUNCIL RECOMMENDATION of 12 July 1999 on the limitation of exposure of the general public to electromagnetic fields (0 Hz to 300 GHz) 1999/519/EC: Annex 2 Basic restrictions

Guideline / standard	SAR limit, SAR _{max} W/kg	Averaging mass, m g	P _{max} mW	Exposure tier	Region of body
199/519/EC	2	10	20	General public	Head and trunk
	4	10	40	General public	Limbs

Reference: Directive 2013/35/EU of the European Parliament and of the Council of 26 June 2013 on the minimum health and safety requirements regarding the exposure of workers to the risks arising from physical agents (electromagnetic fields): Annex III table A1

Guideline / standard	SAR limit, SAR _{max} W/kg	Averaging mass, m g	P _{max} mW	Exposure tier	Region of body
2013/35/EU	10	10	100	Occupational	Head and trunk
	20	10	200	Occupational	Limbs

Reference: CFR 47 §1.1307, §1.1310

KDB 447498 D01 General RF Exposure Guidance v06

Section 4.3.1, 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$$

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz.

Reference: RSS-102 – Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)

Section 2.5.1, Table 1: SAR evaluation – Exemptions limits for routine evaluation based on frequency and separation distance

Frequency	Exemptions limits				
	At separation distance of ≤5 mm	At separation distance of 10 mm	At separation distance of 15 mm	At separation distance of 20 mm	At separation distance of 25 mm
≤300	71 mW	101 mW	132 mW	162 mW	193 mW
450	52 mW	70 mW	88 mW	106 mW	123 mW
835	17 mW	30 mW	42 mW	55 mW	67 mW
1900	7 mW	10 mW	18 mW	34 mW	60 mW
2450	4 mW	7 mW	15 mW	30 mW	52 mW
3500	2 mW	6 mW	16 mW	32 mW	55 mW
5800	1 mW	6 mW	15 mW	27 mW	41 mW

Frequency	Exemptions limits				
	At separation distance of 30 mm	At separation distance of 35 mm	At separation distance of 40 mm	At separation distance of 45 mm	At separation distance of ≥50 mm
≤300	223 mW	254 mW	284 mW	315 mW	345 mW
450	141 mW	159 mW	177 mW	195 mW	213 mW
835	80 mW	92 mW	105 mW	117 mW	130 mW
1900	99 mW	153 mW	225 mW	316 mW	431 mW
2450	83 mW	123 mW	173 mW	235 mW	309 mW
3500	86 mW	124 mW	170 mW	225 mW	290 mW
5800	56 mW	71 mW	85 mW	97 mW	106 mW

For limb-worn devices where the 10-gram value applies, the exemption limits for routine evaluation in Table 1 are multiplied by a factor of 2.5.

5.2 Calculations

EIRP: $Power\ to\ antenna\ (dBm) + Antenna\ gain\ (dBi) = EIRP\ dBm$
 Declared EIRP = 0 dBm
 Measured EIRP = -12.6 dBm

Conversion dBm to W:

Conducted: $1\ mW * 10^{(Power\frac{dBm}{10})} = 0.06\ mW$

Measured EIRP: $1\ mW * 10^{(EIRP\frac{dBm}{10})} = 0.05\ mW$

Declared EIRP: $1\ mW * 10^{(EIRP\frac{dBm}{10})} = 1\ mW$

Low power exclusion limit:

KDB447498 D01 v06: $\frac{EIRP\ mW}{Separation\ distance\ mm} * \sqrt{Operating\ frequency\ GHz} = 0.3$

5.3 Results

Standard	Reference for limit	Value	Unit	Limit	Result
EN 50663: 2017	EN 62479	1	mW	< 20	PASS
§1.1310	KDB 447498	0.3	NA	< 3	PASS
RSS-102	RSS-102	1	mW	< 4	PASS