

7-AS-TW0020-GEPH16-005

Code		
------	--	--

Date : 2017/09/22

<h1>Approval Sheet</h1>

Description : IPEX+OD1.13+11Cm(含頭)

Model No : GEPH-023

Part No :

<p>Received & Approved by</p> <p>ON ____ date ____ month ____ year</p>



11F., No.2, Sec. 4, Jhongyang Rd., Tucheng Dist., New Taipei City, Taiwan (R.O.C), 236

Tel : +886-2-2269-4456

Fax : +886-2-2269-4451

E-mail : sanav@sanav.com

<http://www.sanav.com>

Approved by	Checked by	Issued by	
Julian	Eric	Eva Lin	

Document Amendments (Change History)

Revision	Date	Change Cause	Change Page/ Contents
1.0	2015/12/09	Initial Release	
1.0	2017/09/22	Antenna retest	P.7 Return Loss P.8 Gain table




SPECIFICATION	
1.Description	WIFI Antenna
2.Model	GEPH-023
3.Mechanical Characteristics	
Connector Type	I-PEX
Cable	OD1.13
Length	110mm±2mm
Adhesive	3M 4218P
RoHS Compliant	Yes
4.Electrical Characteristics	
Operating Frequency	2400~2500MHz/5150~5850MHz
Antenna Type	Dipole
Impedance	50ohm
Polarization	Linear
Gain	See Fig-3
5.Operating Temperature	-40°C~80°C
6.Storage Temperature	-40°C~85°C

ELECTRICAL CHARACTERISTICS 電氣特性		
ITEM 項目	TEST CONDITION 測試環境	SPECIFICATION 規格
1 RETURN LOSS 反射損耗	Using Agilent Network Analyzer E5071C to Measure Antenna S11 Return loss Characteristics 使用 Agilent 網路分析儀 E5071C 測量天線 S11 之返回損耗參數	See Fig-1
2 VSWR 電壓駐波比	Using Agilent Network Analyzer E5071C to Measure Antenna S11 VSWR Characteristics 使用 Agilent 網路分析儀 E5071C 測量天線 S11 之電壓駐波參數	See Fig-2

	發行日期:	A1.0
	修正日期:	
	受控日期	

品名: WIFI Antenna	客戶:	規格
------------------	-----	----




Operating Frequency :
2400MHz~2500MHz
5150MHz~5850MHz

Impedance:50ohm

Connector: I-PEX

檢驗項目	品質要求	檢驗方式	檢驗標準
外觀	不可有明顯刮傷、破損	目視(亮度 100Lux，正常視力，視距 30cm，視角 30°-80°)	參照樣品
尺寸	尺寸如示意圖:長度 44.5mm X 寬 7.8mm X 高 1.1mm 線材部份: 長 110mm +/-2mm	1. 游標卡尺 2. 捲尺	承認書
電氣性能	Transmission	1. 網路分析儀	承認書



NOTICE 備註

頻率: 2400~2500MHz/5150~5850MHz
PCB 使用UL796(CCN: ZPMV2)核可, 耐燃等
級V-1或是V-1以上, 溫度105℃或是105℃以上
PCB UL ND: E206991/E324115

CLASS	TOLERANCE				DATE 日期	說明	MATERIAL	TITLE 圖面名稱
	A	B	C	D				
- 8	0.03	0.05	0.1	0.2	2015/2/8	3RD ANGLE 第三角度	新禾航電股份有限公司 SAN JOSE TECHNOLOGY, INC.	
8 - 25	0.06	0.08	0.2	0.3	UNIT 單位	SCALE 比例	IPEX+OD1.13+11Cm 含頭	
25 - 80	0.08	0.12	0.3	0.4	DESIGNED 設計	CHECKED 校對	7-AS-TW0020-GEPH61-005	
80 - 250	0.12	0.20	0.4	0.5	TOLERANCE 公差	APPROVED 核准	繪圖比例	
250 -	0.20	0.30	0.5	0.6			1/1	

Antenna Return Loss:




Fig-1

Antenna VSWR:




Fig-2

Antenna 3D Gain:

3D Gain and Efficiency Report are scanned in SANAV 3D chamber, under CTIA regulation.

Frequency (MHz)	2400	2450	2500	5150	5550	5850
Efficiency (%)	53.07	42.93	39.13	52.76	53.57	58.84
Gain (dBi)	2.38	1.65	1.33	3.3	2.88	4.42
Average Gain (dB)	-2.75	-3.67	-4.08	-2.78	-2.71	-2.3




Fig-3

Antenna 3D Pattern:

2400MHz

2450 MHz




2500 MHz




5150MHz

5550 MHz

5850 MHz



SPECIFICATION

Style	UL 1979 105°C 30V	Document No : WT11300B00	
Size	32AWG	Established Date : 2006/01/09	
Standard :			
Conductor	Size	AWG	32
	Material	----	Silver-Coated Copper
	Conductors No.	----	7
	Construction Size	mm	0.080
	Stranded Diameter	mm	0.240
Insulation	Material	----	FEP
	Color	----	Clear
	Average Thickness	mm	0.22
	Diameter	mm	0.68 ± 0.02
Braid Shield	Material	----	Tinned-Coated Copper
	Construction	mm	16 / 4 / 0.050
	Coverage	%	90
	Diameter	mm	0.90 ±0.03
Jacket	Material	----	FEP
	Color	----	Black
	Average Thickness	mm	0.13
	Overall Diameter	mm	1.13 ±0.05
Marking	Non		
Drawing			

Approval : Kenneth Ho

Confirm : Keep Wu

Maker : Liang Chen

SPECIFICATION

Electrical & Physical Properties						
Item		32AWG				
Rating Temp Voltage		105°C 30V				
Conductor Resistance		545 OHM / KM / 20°C MAX.				
Insulation Resistance		1000 MEGA OHM/KM MIN.				
Dielectric Strength		AC 1.0KV/Minute				
Spark Test		2.5 KV				
Insulation	Unaged	Tensile Strength	2500 PSI MIN. (1.76 Kg / m m ²)			
		Elongation	200% MIN.			
	Aged	Tensile Strength	UNAGED MIN. 75% (168HRS×232°C)			
		Elongation	UNAGED MIN. 75% (168HRS×232°C)			
Jacket	Unaged	Tensile Strength	2500 PSI MIN. (1.76 Kg / m m ²)			
		Elongation	200% MIN.			
	Aged	Tensile Strength	UNAGED MIN. 75% (168HRS×232°C)			
		Elongation	UNAGED MIN. 75% (168HRS×232°C)			
Nom. Impedance		50 ± 3 Ohms				
Nom. Capacitance		96 ± 3 pF/m				
Nom. Vel. of Prop.		69%				
VSWR Test (0 – 6 GHZ)		Less 1.3				
Flame Test		VW-1 OK				
Attenuation (dB/1m)	1GHZ	2GHZ	2.4GHZ	3GHZ	5GHZ	6GHZ
	2.00	3.02	3.35	3.81	5.02	5.22

Approval : Kenneth Ho

Confirm : Keep Wu

Maker : Liang Chen

I-PEX Plug 20278插拔力測試

Model Name		I-PEXPlug 20278									
插拔力(N MIN)		Initial 5 N MIN以上, after 30 cycles 3N MIN以上									
		Sample1	Sample2	Sample3	Sample4	Sample5					
Raw data	Test 1	5.30	5.30	5.2	5.2	5.30					
	Test 2	5.30	5.20	5.2	5.2	5.30					
	Test 3	5.30	5.20	5.2	5.1	5.10					
	Test 4	5.30	5.10	5.1	5.1	5.10					
	Test 5	5.30	5.10	5.1	5.1	5.10					
	Test 6	5.20	5.00	5.0	5.0	5.00					
	Test 7	5.20	5.00	5.0	5.0	5.00					
	Test 8	5.00	5.00	5.0	5.0	5.00					
	Test 9	5.00	5.00	5.0	4.9	4.90					
	Test 10	4.80	5.00	5.0	4.8	4.90					
	Test 11	4.90	4.80	5.0	4.8	4.80					
	Test 12	4.80	4.80	4.7	4.7	4.80					
	Test 13	4.70	4.70	4.7	4.7	4.70					
	Test 14	4.70	4.70	4.7	4.7	4.70					
	Test 15	4.60	4.70	4.6	4.6	4.60					
	Test 16	4.50	4.50	4.6	4.5	4.50					
	Test 17	4.50	4.50	4.5	4.4	4.40					
	Test 18	4.50	4.50	4.5	4.4	4.40					
	Test 19	4.30	4.50	4.5	4.2	4.10					
	Test 20	4.20	4.30	4.2	4.2	4.10					
	Test 21	4.20	4.20	4.2	4.0	4.10					
	Test 22	4.20	4.20	4.2	4.0	4.10					
	Test 23	4.10	4.00	4.2	4.0	3.90					
	Test 24	4.10	4.00	4.1	3.9	3.90					
	Test 25	4.00	3.90	4.1	3.9	3.80					
	Test 26	4.00	3.70	4.0	3.8	3.70					
	Test 27	4.00	3.70	3.9	3.8	3.70					
	Test 28	3.80	3.60	3.7	3.7	3.70					
	Test 29	3.80	3.60	3.6	3.6	3.60					
	Test 30	3.60	3.50	3.5	3.5	3.60					

PRODUCT SPECIFICATION

製品規格

No. PRS-1176

MHF series micro coaxial connector

(Product No. Plug 20278, Rec. 20279)

Qualification Test Report No. TR-1021, TR-08020

8	S08038	K.O	Feb/29/08	EK	Prepared by	Reviewed by	Approved by
7	S3008	K.O	MAR/24/03	K.K	K.Ohbayashi	E,Kawabe	K.Katabuchi
6	S2084	K.O	DEC/19/02	K.K			
REV.	ECN	BY	DATE	APP.	JUN / 25 / 01	Jun / 25 / 01	Jun / 29 / 01
REVISION RECORD							

DOCUMENT CLASSIFICATION	TITLE	No.
Product Specification 製品規格	MHF series micro coaxial connector	PRS-1176
<p>1. Scope / 序言 MHF series micro coaxial connector is a wire to board connector for AWG#36,32,30 coaxial cable . MHF series micro coaxial connector は、AWG # 36,32,30同軸ケーブルの基板対ワイヤーコネクタである。</p> <p>2. Objectives / 目的 This specification covers the requirements for product performance and test methods of MHF series microcoaxial connector 本規格は、MHF series micro coaxial connector の性能と試験条件について規定する。</p> <p>3. Part No. , construction , material and finish / 構成、材料及び仕上げ (1) Part No. Plug : 20278-***R-08,-13,-32,-18 , Receptacle : 20279-001E-01 (2) Construction, material and finish of the connector are covered as each drawings. 構成、材料及び仕上げは、各図面に指定されている通りとする。</p> <p>4. Applicable cable / 適合ケーブル 4-1 Part No. 20278-101R-08, 20278-111R-08, 20278-102R-08, 20278-112R-08 (1) Description Inner conductor : AWG#36(7/0.05) Silver plating annealed copper wire or silver plating tin-copper alloy Dielectric core : Fluoro-plastics ,diameter 0.4(+0.04,-0.02)mm , nominal thickness 0.125mm Outer conductor : 8/5/0.05 , nominal diameter 0.65mm , silver plating annealed copper wire Jacket : Fluoro-plastics , diameter 0.81(+0.04,-0.02)mm , nominal thickness 0.08mm (2) Requirements Characteristic impedance : 50(+2,-2)ohm by TDR method Nominal capacitance(Reference value): 96 pF/m Conductor resistance of inner conductor at 293K (20°C)(Reference value) : 1400 ohm/km Insulation resistance : 1000 mega-ohm.km MIN. Dielectric withstand voltage : no breakdown at AC1000V for 1 minutes.</p> <p>(1) 構成 中心導体 : AWG # 36 (7 / 0.05), 銀メッキ軟銅線または銀メッキすず入り銅線 誘電体 : フッ素樹脂, 外径 0.4 (+0.04, -0.02), 標準厚さ 0.125mm 外部導体 : 8 / 5 / 0.05, 標準外径 0.65mm, 銀メッキ軟銅線 ジャケット : フッ素樹脂, 外径 0.81 (+0.04, -0.02)mm, 標準厚さ 0.08mm</p> <p>(2) 仕様 特性インピーダンス : 50 ± 2 Ω (TDR) 標準静電容量(参考値) : 96pF/m 293K (20°C)時の中心導体導体抵抗(参考値) : 1400 Ω /km 絶縁抵抗 : 1000MΩ ·km以上 耐電圧 : AC1000V・1分間にて絶縁破壊の無い事</p> <p>4-2 Part No. 20278-101R-13, 20278-111R-13, 20278-102R-13, 20278-112R-13 (1) Description Inner conductor : AWG#32(7/0.08) Silver plating annealed copper wire or silver plating tin-copper alloy Dielectric core : Fluoro-plastics , diameter 0.68(+0.04,-0.02)mm , nominal thickness 0.22mm Outer conductor : 16/4/0.05 , nominal diameter 0.93mm , silver plating annealed copper wire Jacket : Fluoro-plastics , diameter 1.13(+0.08,-0.05)mm , nominal thickness 0.1mm</p>		

DOCUMENT CLASSIFICATION	TITLE	No.
Product Specification 製品規格	MHF series micro coaxial connector	PRS-1176

(2) Requirements

Characteristic impedance : 50(+2,-2)ohm by TDR method

Nominal capacitance(Reference value): 97 pF/m

Conductor resistance of inner conductor at 293K (20°C)(Reference value) : 520 ohm/km

Insulation resistance : 1500 mega-ohm.km MIN.

Dielectric withstand voltage : no breakdown at AC1000V for 1 minutes.

(1) 構成

中心導体 : AWG # 32 (7/0.08), 銀メッキ軟銅線または銀メッキすず入り銅線

誘電体 : フッ素樹脂, 外径0.68(+0.04,-0.02), 標準厚さ0.22mm

外部導体 : 16/4/0.05, 標準外径0.93mm, 銀メッキ軟銅線

ジャケット : フッ素樹脂, 外径1.13(+0.08,-0.05)mm, 標準厚さ0.1mm

(2) 仕様

特性インピーダンス : $50 \pm 2 \Omega$ (TDR)

標準静電容量(参考値) : 97pF/m

293K (20°C)時の中心導体導体抵抗(参考値) : $520 \Omega / \text{km}$

絶縁抵抗 : $1500 M\Omega \cdot \text{km}$ 以上

耐電圧 : AC1000V・1分間にて絶縁破壊の無い事

4-3 Part No. 20278-101R-32, 20278-111R-32, 20278-102R-32, 20278-112R-32

(1) Description

Inner conductor : AWG#32(7/0.08)

Silver plating annealed copper wire or silver plating tin-copper alloy

Dielectric core : Fluoro-plastics , diameter 0.66(+0.05,-0.05)mm , nominal thickness 0.21mm

First outer conductor : 16/5/0.05, tin plating annealed copper wire

Second outer conductor : 16/6/0.05, nominal diameter 1.12mm , tin plating annealed copper wire

Jacket : Fluoro-plastics , diameter 1.32(+0.1,-0.1)mm , nominal thickness 0.1mm

(2) Requirements

Characteristic impedance : 50(+2,-2)ohm by TDR method

Nominal capacitance(Reference value): 95 pF/m

Conductor resistance of inner conductor at 293K (20°C) (Reference value) : 520 ohm/km

Insulation resistance : 1500 mega-ohm.km MIN.

Dielectric withstand voltage : no breakdown at AC1000V for 1 minutes.

(1) 構成

中心導体 : AWG # 32 (7/0.08), 銀メッキ軟銅線または銀メッキすず入り銅線

誘電体 : フッ素樹脂, 外径0.66(+0.05,-0.05), 標準厚さ0.21mm

外部導体(内側) : 16/5/0.05, すずメッキ軟銅線

外部導体(外側) : 16/6/0.05, 標準外径1.12mm, すずメッキ軟銅線

ジャケット : フッ素樹脂, 外径1.32(+0.1,-0.1)mm, 標準厚さ0.1mm

(2) 仕様

特性インピーダンス : $50 \pm 2 \Omega$ (TDR)

標準静電容量(参考値) : 95pF/m

293K (20°C)時の中心導体導体抵抗(参考値) : $520 \Omega / \text{km}$

絶縁抵抗 : $1500 M\Omega \cdot \text{km}$ 以上

耐電圧 : AC1000V・1分間にて絶縁破壊の無い事

DOCUMENT CLASSIFICATION	TITLE	No.
Product Specification 製品規格	MHF series micro coaxial connector	PRS-1176

4-4 Part No. 20278-101R-18, 20278-111R-18, 20278-102R-18, 20278-112R-18

RG178 B/U

(1) Description

Inner conductor : AWG#30(7/0.102) , silver plating copper clad steel wire

Dielectric core : Fluoro-plastics , diameter 0.84(+0.03,-0.03)mm , nominal thickness 0.268mm

Outer conductor : 16/3/0.1 , nominal diameter 1.35mm , silver plating copper wire

Jacket : Fluoro-plastics , diameter 1.8(+0.1,-0.1)mm , nominal thickness 0.23mm

(2) Requirements

Characteristic impedance : 50(+2,-2)ohm by TDR method

Nominal capacitance(Reference value): 95 pF/m

Conductor resistance of inner conductor at 293K (20°C) (Reference value) : 805 ohm/km

Insulation resistance : 1500 mega-ohm.km MIN.

Dielectric withstand voltage : no breakdown at AC2000V for 1 minutes.

(1) 構成

中心導体 : AWG # 30(7/0.102),銀メッキ銅被鋼線

誘電体 : フッ素樹脂,外径0.84(±0.03),標準厚さ0.268mm

外部導体 : 16/3/0.1,標準外径1.35mm,銀メッキ軟銅線

ジャケット : フッ素樹脂,外径1.8(±0.1)mm,標準厚さ0.23mm

(2) 仕様

特性インピーダンス : 50±2Ω (TDR)

標準静電容量(参考値) : 95pF/m

293K(20°C)時の中心導体導体抵抗(参考値) : 805Ω /km

絶縁抵抗 : 1500MΩ・km以上

耐電圧 : AC2000V・1分間にて絶縁破壊の無い事

5. Ratings / 定格

(1) Rated voltage / 電圧 : AC60Vrms

(2) Nominal characteristic impedance / 公称特性インピーダンス : 50Ω

(3) Frequency / 周波数 : DC~6GHz

(4) VSWR : Plug 1.3 MAX at 0.1~3GHz 1.5 MAX at 3~6GHz

Receptacle 1.3 MAX at 0.1~3GHz. 1.4 MAX at 3~6GHz

(5) Service Temperature / 使用温度範囲 : 233~363K(-40~+90°C)

6. Test methods and performance / 試験及び性能

6-1 Test condition / 試験条件

Unless otherwise specified, all tests and measurements shall be performed under the following conditions in accordance with MIL-STD-202

全ての測定と試験は、MIL-STD-202に基づき以下の条件で行う。

Temperature / 温度 : 288~308K (15~35°C)

Humidity / 湿度 : 45~75%RH

DOCUMENT CLASSIFICATION Product Specification 製品規格	TITLE MHF series micro coaxial connector	No. PRS-1176
--	--	-----------------

6-2-1 Electrical / 電氣的性能

(1) Contact Resistance / 接触抵抗

A. Testing: Solder the receptacle connector to the test board and mate the plug connector together, then measure the contact resistance as shown in Fig.1 by the four terminal method. Apply the low level condition in accordance with MIL-STD-202, Method 307.

Open circuit voltage : 20mV MAX

Circuit current : 10mA MAX. (DC or AC 1kHz)

Contact resistance of inner contact : <resistance of A-E> - <resistance of B-E>

Contact resistance of ground contact : <resistance of A-D> - <resistance of B-D>




Fig.1

B. Requirements :

Contact resistance of inner contact initial 20 milli-ohm MAX. after testing 25milli-ohm MAX.

Contact resistance of ground contact initial 10 milli-ohm MAX. after testing 15milli-ohm MAX.

A. 試験法: テスト基板にリセプタクルコネクタを半田付けし、プラグコネクタと嵌合させ、Fig. 1のように4端子法にて下記の条件で測定する。MIL-STD-202 試験法 307 に準拠。

開回路電圧: 20mV以下

試験電流 : 10mA (DCもしくはAC1kHz)

中心導体 : <A-E間の電気抵抗> - <B-E間の電気抵抗>

外部導体 : <A-D間の電気抵抗> - <B-D間の電気抵抗>

B. 必要条件: 中心導体 初期 20mΩ 以下, 試験後 25mΩ 以下

外部導体 初期 10mΩ 以下, 試験後 15mΩ 以下

(2) Insulation resistance / 絶縁抵抗

A. Testing : Mate the plug and receptacle connector together, then apply DC 100 V between the inner contact and the ground contact in accordance with MIL-STD-202, Method 302.

B. Requirements : Initial 500 Mohm MIN. after testing 100 Mohm MIN.

A. 試験法: リセプタクル及びプラグコネクタを互いに嵌合させ、中心導体と外部導体の間に DC 100Vを印加し、測定する。MIL-STD-202 試験法 302 に準拠。

B. 必要条件: 初期 500MΩ 以上 試験後 100MΩ 以上

(3) Dielectric withstanding voltage / 耐電圧

A. Testing : Mate the receptacle and plug connector together, then apply AC 200 Vrms between the inner contact and the ground contact for a minute in accordance with MIL-STD-202, Method 301.

B. Requirements : No creeping discharge, flashover, nor insulator breakdown shall occur.

A. 試験法: リセプタクル及びプラグコネクタを互いに嵌合させ、中心導体と外部導体の間にAC200V(実効値)を一分間印加する。MIL-STD-202 試験法 301 に準拠。

B. 必要条件: 浴面放電、空中放電、絶縁破壊等の異常のないこと。

DOCUMENT CLASSIFICATION	TITLE	No.
Product Specification 製品規格	MHF series micro coaxial connector	PRS-1176

(4) VSWR

A. Testing : Measure the VSWR as shown in Fig.3 by the network analyzer.

Frequency : 100M~6GHz




Fig 3

B. Requirements : Plug 1.3 MAX at 0.1~3GHz 1.5 MAX at 3~6GHz

Receptacle 1.3 MAX at 0.1~3GHz. 1.4 MAX at 3~6GHz

A. 試験法 : ネットワークアナライザーにて Fig.3 のように VSWR を測定する。

周波数 : 100M~6GHz

B. 必要条件 : Plug 1.3 以下 0.1~3GHz 1.5 以下 3~6GHz

Receptacle 1.3 以下 0.1~3GHz 1.4 以下 3~6GHz

6-2-2 Mechanical / 機械的性能

(1) Unmating force / 抜去力

A. Testing : Unmate the receptacle connector (soldered to the test board) and plug at a speed 25 ± 3 mm/minutes along the mating by the push-on/pull-off machine .

B. Requirements :

Total unmating force : Initial 5N MIN. after 30 cycles 3N MIN.

Unmating force of inner contact : Initial 0.15N MIN. after 30 cycles 0.1N MIN

A. 試験法 : 挿抜試験機を用いて、基板に半田付けしたリセプタクルとプラグを嵌合軸と平行に毎分 25 ± 3 mm の速度で挿抜する。

B. 必要条件 :

総合抜去力 : 初回抜去力 5N 以上 , 30 回後抜去力 3N 以上

中心導体 : 初回抜去力 0.15N 以上 , 30 回後抜去力 0.1N 以上

(2) Crimp strength / 引張強度

A. Testing : Pull the cable as shown in Fig.5 at a speed 25 ± 3 mm/minutes by tensile strength machine.




Fig 5

B. Requirements : 20278-1 ** R-08,13,32 : 10N MIN, 20278-1 ** R-18 : 15N MIN,

A. 試験法 : 引張試験機を用いて、毎分 25 ± 3 mm の速度でケーブルを引張り、強度を測定する。

B. 必要条件 : 20278-1 ** R-08,13,32 : 10N 以上, 20278-1 ** R-18 : 15N 以上

DOCUMENT CLASSIFICATION	TITLE	No.
Product Specification 製品規格	MHF series micro coaxial connector	PRS-1176

(3) Durability / 耐久性

A. Testing : Mate and umate the receptacle connector (soldered to the test board) and plug 30 cycles at a speed 25 ± 3 mm/minutes along the mating by the push-on/pull-off machine .

B.Requirements :

Contact resistance of inner contact initial 20 milli-ohm MAX. after testing 25milli-ohm MAX.

Contact resistance of ground contact initial 10 milli-ohm MAX. after testing 15milli-ohm MAX.

A.試験法:挿抜試験機を用いて、基板に半田付けしたリセプタクルとプラグを嵌合軸と平行に毎分 25 ± 3 mmの速度で30回挿抜する。

B.必要条件 中心導体接触抵抗 : 初期 $20m\Omega$ 以下, 試験後 $25m\Omega$ 以下
外部導体接触抵抗 : 初期 $10m\Omega$ 以下, 試験後 $15m\Omega$ 以下

(4) Contact resistance with force on the cable / ケーブルに荷重を加えた後の接触抵抗

A. Testing : Apply force on the cable as shown in Fig.2.

During the testing, run 100mA DC to check electrical discontinuity.




Fig.2

B.Requirements

Appearance : Looseness between the parts, chipping, breakage or other abnormality shall not occur.

Electrical discontinuity : No electrical discontinuity grater than 1 micro-sec. shall occur.

Contact resistance of inner contact initial 20 milli-ohm MAX. after testing 25milli-ohm MAX.

Contact resistance of ground contact initial 10 milli-ohm MAX. after testing 15milli-ohm MAX.

A.試験法:Fig. 2のようにケーブルに力を加える。尚、試験中にDC100mAの電流を流して電氣的瞬断を確認する。

B.必要条件 外観 : 部品のゆるみ、欠け、割れ、その他外観上の異常の無いこと。
電流瞬断 : 試験中、1マイクロ秒を超える電氣的瞬断の無いこと。
中心導体接触抵抗 : 初期 $20m\Omega$ 以下, 試験後 $25m\Omega$ 以下
外部導体接触抵抗 : 初期 $10m\Omega$ 以下, 試験後 $15m\Omega$ 以下

(5) Vibration / 振動

A. Testing : Apply the following vibration to the mating connector .

During the testing, run 100mA DC to check electrical discontinuity.

Frequency : 10Hz \rightarrow 100Hz \rightarrow 10Hz / approx 15 minutes.

Half amplitude ,Peak value of acceleration: 1.5mm or $59m/s^2$ (6G)

Directions , cycle : 3 mutually perpendicular direction ,

5 cycles(approx 75min)about each direction

B.Requirements

Appearance : Looseness between the parts, chipping, breakage or other abnormality shall not occur.

Electrical discontinuity : No electrical discontinuity grater than 1 micro-sec. shall occur.

Contact resistance of inner contact initial 20 milli-ohm MAX. after testing 25milli-ohm MAX.

Contact resistance of ground contact initial 10 milli-ohm MAX. after testing 15milli-ohm MAX.

DOCUMENT CLASSIFICATION	TITLE	No.
Product Specification 製品規格	MHF series micro coaxial connector	PRS-1176

A. 試験法: 嵌合状態のコネクタを、下記の振動を加える。尚、試験中にDC100mAの電流を流して電氣的瞬断を確認する。

周波数 : 10Hz→100Hz→10Hz / 約15分間

片振幅, 加速度: 1.5mm or 59m/s² (6G)

方向, サイクル: 3つの互いに直角な方向について各5サイクル(約75分)実施

B. 必要条件 外観 : 部品のゆるみ、欠け、割れ、その他外観上の異常の無いこと。
電流瞬断 : 試験中、1 マイクロ秒を超える電氣的瞬断の無いこと。
中心導体接触抵抗 : 初期 20mΩ 以下、試験後 25mΩ 以下
外部導体接触抵抗 : 初期 10mΩ 以下、試験後 15mΩ 以下

(6) Shock / 衝撃

A. Testing : Apply the following vibration to the mating connector in accordance with MIL-STD-202, Method 213, Condition B. During the testing, run 100mA DC to check electrical discontinuity.

Peak value of acceleration: 735m/s² (75G)

Duration : 11msec

Wave Form : half sinusoidal

Directions , cycle : 6 mutually perpendicular direction , 3 cycles about each direction

B. Requirements

Appearance : Looseness between the parts, chipping, breakage or other abnormality shall not occur.

Electrical discontinuity : No electrical discontinuity grater than 1 micro-sec. shall occur.

Contact resistance of inner contact initial 20 milli-ohm MAX. after testing 25milli-ohm MAX.

Contact resistance of ground contact initial 10 milli-ohm MAX. after testing 15milli-ohm MAX.

A. 試験法: 嵌合状態のコネクタを、衝撃試験機に取り付け、下記の衝撃を加える。尚、試験中にDC100mAの電流を流して電氣的瞬断を確認する。MIN-STD-202 試験法 213 試験条件 B に準拠。

最大加速度: 735m/s² (75G)

標準持続時間: 11msec.

波形: 半波正弦波

方向: 直交する6方向、各3回

B. 必要条件 外観 : 部品のゆるみ、欠け、割れ、その他外観上の異常の無いこと。
電流瞬断 : 試験中、1 マイクロ秒を超える電氣的瞬断の無いこと。
中心導体接触抵抗 : 初期 20mΩ 以下、試験後 25mΩ 以下
外部導体接触抵抗 : 初期 10mΩ 以下、試験後 15mΩ 以下

6-2-3 Environmental / 耐環境性

(1) Thermal shock/ 温度サイクル

A. Testing : Apply the following environment to the mating connector .

Temperature ,duration

:233K/30minutes→278~308K/5minutes MAX.→363K/30minutes→278~308K/5minutes MAX.

(-40°C)

(5~35°C)

(90°C)

(5~35°C)

No. of cycles : 5 cycles

B. Requirements

Appearance : Looseness between the parts, chipping, breakage or other abnormality shall not occur.

Contact resistance of inner contact initial 20 milli-ohm MAX. after testing 25milli-ohm MAX.

Contact resistance of ground contact initial 10 milli-ohm MAX. after testing 15milli-ohm MAX.

Insulation resistance : initial 500 mega-ohm MIN. after testing 100 mega-ohm MIN.

DOCUMENT CLASSIFICATION	TITLE	No.
Product Specification 製品規格	MHF series micro coaxial connector	PRS-1176

A. 試験法: 嵌合状態のコネクタを、下記の雰囲気中に放置する。

1サイクルの条件

: 233K / 30分 → 278 ~ 308K / 5分以下 → 363K / 30分 → 278 ~ 308K / 5分以下
(-40°C) (5 ~ 35°C) (90°C) (5 ~ 35°C)

実施サイクル : 5サイクル

B. 必要条件 外観 : 部品のゆるみ、欠け、割れ、その他外観上の異常の無いこと。
中心導体接触抵抗 : 初期 20mΩ 以下, 試験後 25mΩ 以下
外部導体接触抵抗 : 初期 10mΩ 以下, 試験後 15mΩ 以下
絶縁抵抗 : 初期 500MΩ 以上 試験後 100MΩ 以上

(2) Humidity / 湿度

A. Testing : Apply the following environment to the mating connector in accordance with MIL-STD-202, Method 103, Condition B.

Temperature : 313 ± 2 K (40 ± 2°C)

Humidity : 90 ~ 95%RH

Duration : 96 hours

B. Requirements

Appearance : Looseness between the parts, chipping, breakage or other abnormality shall not occur.

Contact resistance of inner contact initial 20 milli-ohm MAX. after testing 25milli-ohm MAX.

Contact resistance of ground contact initial 10 milli-ohm MAX. after testing 15milli-ohm MAX.

Insulation resistance : initial 500 mega-ohm MIN. after testing 100 mega-ohm MIN.

A. 試験法: 嵌合状態のコネクタを、下記の雰囲気中に放置する。MIL-STD-202 試験法 103 条件 B に準拠。

温度: 313 ± 2K (40 ± 2°C)

湿度: 90 ~ 95%RH

時間: 96時間

B. 必要条件 外観 : 部品のゆるみ、欠け、割れ、その他外観上の異常の無いこと。
中心導体接触抵抗 : 初期 20mΩ 以下, 試験後 25mΩ 以下
外部導体接触抵抗 : 初期 10mΩ 以下, 試験後 15mΩ 以下
絶縁抵抗 : 初期 500MΩ 以上 試験後 100MΩ 以上

(3) Salt water spray / 塩水噴霧

A. Testing : Apply the following environment to the mating connector in accordance with MIL-STD-202, Method 101, Condition B.

Temperature : 308 ± 2 K (35 ± 2°C)

Salt water density by weight : 5 ± 1%

Duration : 48 hours

B. Requirements : Appearance no abnormality adversely affecting the performance shall occur.

A. 試験法: 嵌合状態のコネクタを、下記の雰囲気中に放置する。

温度 : 308 ± 2K (35 ± 2°C)

塩水濃度: 5 ± 1% (重量比)

時間 : 48時間

B. 必要条件 : 外観 著しい腐食の無い事。

DOCUMENT CLASSIFICATION	TITLE	No.
Product Specification 製品規格	MHF series micro coaxial connector	PRS-1176

(4) High temperature life / 高温

A. Testing : Apply the following environment to the mating connector.

Temperature : 363 ± 2 K ($90 \pm 2^\circ\text{C}$) Duration : 96 hours

B. Requirements

Appearance : Looseness between the parts, chipping, breakage or other abnormality shall not occur.

Contact resistance of inner contact initial 20 milli-ohm MAX. after testing 25milli-ohm MAX.

Contact resistance of ground contact initial 10 milli-ohm MAX. after testing 15milli-ohm MAX.

A.試験法:嵌合状態のコネクタを、下記の雰囲気中に放置する。

温度: 363 ± 2 K ($90 \pm 2^\circ\text{C}$) 時間:96時間

B.必要条件 外観 : 部品のゆるみ、欠け、割れ、その他外観上の異常の無いこと。

中心導体接触抵抗 : 初期 20m Ω 以下, 試験後 25m Ω 以下

外部導体接触抵抗 : 初期 10m Ω 以下, 試験後 15m Ω 以下

6-2-4 Solder / 半田付け関連

(1) Solderability / 半田付け性

A. Testing : Dip the solder tine of the contact in the solder bath at 518 ± 5 ($245 \pm 5^\circ\text{C}$) for 5 ± 0.5 sec.

After immersing the tine in the flux of RMA or R type for 5 to 10 seconds in accordance with MIL-STD-202, Method 208.

B. Requirements : More than 95% of the dipped surface shall be evenly wet.

A.試験法:コンタクトの半田付け部を 518 ± 5 K ($245 \pm 5^\circ\text{C}$)の半田槽内に 5 ± 0.5 秒浸す。フラックスは、RMA

又はR型を使用し5~10秒間浸すものとする。MIL-STD-202, 試験法208に準拠。

B.必要条件:浸した面積の95%以上に半田がむらなく付着すること。

(2) Reflow soldering heat resistance / 半田耐熱性

A. Testing : Put on the receptacle connector to PCB, apply the heat 2 cycles as shown in Fig. 4




Fig4

B. Requirements : Appearance no abnormality adversely affecting the performance shall occur.

A.試験法:基板にリセプタクルコネクタを置き、Fig. 4の条件で2回リフローを行う。



B.必要条件:機能を損なう変形及び欠陥の無い事。

DOCUMENT CLASSIFICATION Product Specification 製品規格	TITLE MHF series micro coaxial connector	No. PRS-1176
--	--	-----------------

6-2-5 試験順序と試料数 / Test Sequence and Sample Quantity


Test Item 試験項目	Group / グループ														
	A	B	C	D	E	F	G	H	I	L	M	N	O	P	
(1) Contact Resistance 接触抵抗					1 3	1 3	1 3	1 3	1 4	1 4		1 3			
(2) Insulation resistance 絶縁抵抗									2 5	2 5					
(3) Dielectric withstanding voltage 耐電圧	1														
(4) VSWR		1													
(5) Crimp strength 引張強度			1												
(6) Unmating force 抜去力				1											
(7) Durability 耐久性					2										
(8) Contact resistance with force on the cable ケーブルに荷重を加えた後の 接触抵抗						2									
(9) Vibration 振動							2								
(10) Shock 衝撃								2							
(11) Thermal shock 温度サイクル									3						
(12) Humidity 湿度										3					
(13) Salt water spray 塩水噴霧											1				
(14) High temperature life 高温												2			
(15) Solderability 半田付け性													1		
(16) Reflow soldering heat resistance 半田耐熱性														1	
Sample QTY pcs. 試料数	Plug プラグ	10	5	10	10	10	10	10	10	10	10	10	10	----	----
	Receptacle リセプタクル	10	5	----	10	10	10	10	10	10	10	10	10	10	10
Test Board 基板数	pcs.	10	5	----	10	10	10	10	10	10	10	10	10	----	10

PART NO.
20278-***R-***






Part No. 20278-101R-08
20278-102R-08
20278-101R-13
20278-102R-13
20278-101R-32
20278-102R-32

For hand tool
(with notch)




Part No. 20278-111R-08
20278-112R-08
20278-111R-13
20278-112R-13
20278-111R-32
20278-112R-32

For semi auto
termination machine
(without notch)



Plug
P/N 20278-1**R-08
P/N 20278-1**R-13
P/N 20278-1**R-32



Receptacle
Part No. 20279-001E-01
20441-001E-01

MATING

GENERAL TOLERANCE	
6 MAX.	±0.2
6 OVER MAX. 30	±0.3
30 OVER MAX. 120	±0.5
ANGLE	±2°

19C 208056	K.O	Feb/04/08	EK	DESIGN'D BY	DATE	I-PEX Interconnect and Packaging Electronics TOKYO, JAPAN	TITLE MHF series micro coaxial connector plus vertical (ground contact : gold plating)	General
18C 207346	K.O	Jul/10/08	E.K	K. Ohbayashi	JUN/13/01			
17C 205233	K.O	May/18/05	T.H	CHK'D BY	DATE	APP'D BY	DATE	SHEET REV.
16C 205024	K.O	Jan/20/05	T.H					
15C 204398	K.O	Nov/12/04	T.H	REV. RECORD		CUSTOMER COPY	PROJECTION	SCALE UNIT DWG. No.
				SERIES No.	2814			

MATERIAL SAFETY DATA SHEET

MSDS FILE No. (KURAMI WORKS) : 05-1225

(based on Form OSHA-174)

IDENTITY (AS Used on Label and List)

Product Class : Phosphor Bronze Strip
 Trade Name : JIS H3130 C5210R (Equivalent to ASTM B103 C52100)
 CAS No. : Copper: 7440-50-8, Tin: 7440-31-5, Phosphor: 7723-14-0
 Chemical Composition

	Content(wt-%)	CAS No.
Tin(Sn)	7.0~9.0	7440-31-5
Phosphor(P)	0.03~0.35	7723-14-0
Copper(Cu)	Balance	7440-50-8
Sn+P+Cu	99.7 \leq	-

Section I

Manufacturer's Name NIKKO METAL MANUFACTURING CO., LTD. KURAMI WORKS	Date Prepared May 24th, 2005
Address 3 Kurami Samukawa-cho Kouza-gun Kanagawa prefecture 253-0101 JAPAN	Signature of Person in Charge <i>Chihiro Izumi</i> IZUMI, Chihiro Senior Technical Supervisor, Quality Assurance
Telephone Number for Information (Quality Assurance) +81-467-75-7285	Signature of Person Responsible <i>Hiroaki Watanabe</i> WATANABE, Hiroaki Manager, Quality Assurance Section
Facsimile Number for Information (Quality Assurance) +81-467-74-6971	

Section II Hazardous Ingredients / Identity Information

Hazardous Components (Specific Chemical Identity : Names OSHA Pel ACGIH TLV)

Nothing for ordinary service condition

Section III Physical / Chemical Characteristics

Boiling Point	2630 °C for Copper 2275 °C for Tin	Specific Gravity (H2O = 1)	8.80
Vapor Pressure (mmHg)	N/A	Melting Point	1025 deg. centi. for C5210 Phosphor Bronze
Vapor Density (Air = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility in Water	N/A		
Appearance and Odor	Brown - Red (solid) : Odor - None		

Section IV Fire and Explosion Hazard Data

Flash Point (Method Used)	N/A	Flammable Limits	N/A	LEL	N/A	UEL	N/A
Extinguishing Media	N/A (stable , nonflammable substance)						
Special Fire Fighting Procedures	Not specified						
Unusual Fire and Explosion Hazards	Metal products do not present fire or explosion hazards under normal conditions.						

Section V Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	

Incompatibility (Materials to Avoid)

Nothing

Hazardous Decomposition or Byproducts

Nothing

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	

Section VI Health Hazard Data

Route(s) of Entry :	Inhalation ?	Skin ?	Ingestion ?
	N/A	N/A	N/A

Health Hazardous (Acute and Chronic)

N/A

Carcinogenicity :	NTP ?	IARC Monographs ?	OSHA Regulated ?
	N/A	N/A	N/A

Signs and Symptoms of Exposure

N/A

Medical Conditions

Generally Aggravated by Exposure N/A

Emergency and First Aid Procedures

N/A

Section VII Precautions for State Handling and Use

Steps to Be Taken in Case Material Is Released or Spilled

N/A

Waste Disposal Method

Collect scrap for remelting.

Precautions to Be Taken in Handling and storing

For Handling

- Put safety gloves on to protect your hands from edges of coils which might cut your hands.
- Wear safety glasses when metal powders or chips are expected to be generated in the work.
- Put safety shoes on when handling heavy coils.

For Storing

- The environment of stocking area should be free from acid, alkali, chloride, sulfide and other corrosive chemicals to prevent from rusting or corrosion.

Other Precautions

No special requirements

Section VIII Control Measures

Respiratory Protection (Specify Type)

Wearing a mask be recommended in the work such as abrasion and buffing which generates metal powders or chips.

Ventilation	Local Exhaust	Special
	None	None
	Mechanical (General)	Other
	None	None

Protective Gloves

Put safety gloves on to protect your hands from edges of coils which might cut your hands.

Eye Protection

Wear safety glasses when metal powder is expected to be generated in the work.

Other Protective Clothing or Equipment

Put safety shoes on when handling heavy coils.

Work / Hygienic Practices

None

Influence to environments

Fish on toxicity : TLm 48 hr. on CuSO4

Salmogairdeneri : 0.038 ~ 0.8 ppm

Oryzias Latipes : 2.1 ~ 24ppm

Material Safety Data Sheet

1. Manufacturer

- Company HARADA Metal Industry Co., Ltd.
- Address 10-18 Sasamekitamati, Toda, Saitama 335-0033, Japan
TEL 048-422-1588
FAX 048-449-6303
- Counter The domestic business department business primary and second section
TEL 048-441-5115
FAX 048-444-9104
The domestic business department OSAKA service office
TEL 06-531-8094
FAX 06-531-8096
The domestic business department NAGOYA service office
TEL 052-821-9778
FAX 052-822-7500
The overseas business department export section
TEL 048-441-5115
FAX 048-444-9104
- Urgent place to contact
The quality assurance department
TEL 048-422-1588
FAX 048-449-6303

2. Products

- Phosphor bronze plates and strips for springs
- Phosphor bronze plates and strips

3. Specification of the material

- The division of mixture or single product : Single product
- The chemical name : Copper alloy
- Chemical composition and content rate(wt.%)

Element	Percent					CAS No.
	C5210	C5212	C5191	C5102	C5111	
Copper	rem.	rem.	rem.	rem.	rem.	7440-50-8
Tin	7.0~9.0	7.0~9.0	5.5~7.0	4.5~5.5	3.5~4.5	7440-31-5
Phosphorus	0.03~0.35	0.03~0.35	0.03~0.35	0.03~0.35	0.03~0.35	7723-14-0
Lead	0.05 max	0.05 max	0.05 max	0.05 max	0.05 max	7439-92-1
Iron	0.1 max	0.1 max	0.1 max	0.1 max	0.1 max	7439-89-6
Zinc	0.2 max	0.2 max	0.2 max	0.2 max	0.2 max	7440-66-6

4. Classification of harmfulness

- The name of classification : Not classified into the dangerous harmfulness material.
- The danger : No knowledge
- The harmfulness : No knowledge
- The effect for the environment : No knowledge

5. First aid

- Eyes : Flush the water. Consult the doctor, when the simulation of the eye continues.
- Skin : Flush the water.
- Inhalation : Consult the doctor, when it was large inhaled.

6. The treatment in the fire

- Nonflammable.

7. Leakage

- Not applied (because of solid)

8. Attention in handling and storage

- Stored at the ordinary—temperature and usual humidity.
- Prohibition of the rapid temperature and humidity change.

9. Treatment on the exposure prevention

- Standard control concentration : Not regulated.
- Allowable temperature : Not regulated.
- Facility countermeasure : The whole ventilation is desirable.
- Protector : For lung ,the wear of protection mask is desirable for the power handling.
For hand ,the wear of protective glove is desirable.
For eyes ,the wear of safety goggles is desirable for the power handling.
For body , the wear of protective clothing is desirable.

10. Physical and chemical characteristic

- Appearance and smell : The solid with the metallic luster. Odoless.
- Boiling point : The indistinctness.
- Solubility : Dissolves in the inorganic acid.

	C5210	C5212	C5191	C5102	C5111
Specific gravity	8.82	8.82	8.85	8.88	8.90
Melting point	1020°C	1020°C	1045°C	1050°C	1060°C

11. Information for danger

- Fire point : The indistinctness.
- Stability : Show the stability at room temperature and in the air.
- The situation to be avoided : —

12. Information for harmfulness

- The powder stimulates eyes , skin and bronchi.
- Produce the ulcer and the hepatic disorder rarely.

13. Information for environment

- No knowledge.

14. Attention for scrapping

- Possible to deal with ,as an industrial waste.

15. Attention for transportation

- No damage transportation is desirable.

16. Applying act

- —



Acrylic Foam Tape 4218P

For Professional Market Applications

Technical Data Sheet

May 1998

Supersedes Technical Data Sheet dated 1994


General Description

3M™ Acrylic Foam Tape 4218P is a medium-density, dark gray acrylic foam tape with high performance acrylic adhesives. 3M acrylic foam tape 4218P is characterized by high performance peel and shear adhesion to many automotive substrates, high internal strength, good conformability and excellent plasticizer resistance.


Typical applications would include body side moldings, rocker panels moldings and claddings, wheel lip moldings, luggage rack slats, wind and rain deflectors, and spoilers.

3M acrylic foam tape 4218P utilizes the same proprietary acrylic foam core and adhesive technology that has been proven successful on numerous OEM automotive applications. **The acrylic foam core has unique viscoelastic properties that allow it to elongate and relax when put under load, thereby minimizing stress on the adhesive bond line.** These properties allow the tape to bond more effectively to a wide variety of automotive surfaces.

Typical Applications



Product Construction



Shelf Life

One year from date of receipt by customer when stored at 22°C (72°F) and 50% relative humidity.

Technical Data Sheet 4218P

Page 2


Physical Properties

Values shown are typical values not to be used for specification purposes.

Foam:	Dark Gray Acrylic	
Adhesive:	Liner Side:	AR7 High Performance Acrylic
	Non-liner Side:	DS4 High Performance Acrylic
Thickness:	1.14 mm	(0.045 in.)
Range:	min. 1.04 mm	(0.041 in.)
	max. 1.24 mm	(0.049 in.)
Density:	688 kg/m ³	(43 lb/ft ³)
Range:	min. 608 kg/m ³	(38 lb/ft ³)
	max. 768 kg/m ³	(48 lb/ft ³)
Release Liner:	Red Polyethylene - 3M Logo Printed	
Roll widths:	min. 4 mm (0.157 in.)	
Roll Lengths:	For widths less than 8 mm (0.314 in.): Up to 65.8 m (72 yds.). For widths between 8 - 9.5 mm (0.314 - 0.375 in.): Up to 98.8 m (108 yds.). For widths greater than 9.5 mm (0.375 in.): Up to 131.6 m (144 yds.)	

Performance Properties

Performance tests are run using standard test procedures. The values presented are typical values not to be used for specification purposes.



1. Breakaway and Continuing Peel

72 hrs. at 22°C (72°F)	Breakaway Peel	9.5 kg (21 lbs.)
	Continuing Peel	5.0 kg (11 lbs.)

Breakaway and Continuing Peel tests are run with 12.7 mm (0.5 in.) wide tape on PVC test bars. Tests were run on base coat/clear coat paint at a separation rate of 305 mm/min. (12 in./min.).



2. Static Shear

Exceeds 100 hours at 70°C (158°F).
Static shear tests are run with 12.7 mm (0.5 in.) wide by 50.8 mm (2 in.) long tape on PVC test bars.
6.8 kg (15 lbs.) roll-down against stainless steel.
Static weight is 250 gm (0.55 lbs.).

IMPORTANT NOTICE: ALL STATEMENTS, TECHNICAL INFORMATION, AND RECOMMENDATIONS ARE BASED ON TESTS 3M BELIEVES ARE RELIABLE. 3M DOES NOT WARRANT OR GUARANTEE THE ACCURACY OR COMPLETENESS OF THIS INFORMATION. 3M MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of application. Because there are many factors that can affect the use and performance of the 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose, is suitable for the user's method of application, and meets the user's performance specifications and expectations.

Limitation of Remedies and Liability: If the 3M product is proved to be defective, THE EXCLUSIVE REMEDY, AT 3M'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE 3M PRODUCT. 3M shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability. No statement or recommendation not contained herein shall have any force or effect unless contained in an agreement signed by officers of seller and manufacturers.



Automotive Division
3M Center, Building 223-1S-02
St. Paul, MN 55144-1000

Recycled Paper
40% Post-consumer waste paper
10% Pre-consumer waste paper

Printed in USA
© 3M 1998

8054-EMC-A
75-3467-4642-5

3M Automotive Division

3M Center
Bldg. 0230-01-S-32
St. Paul, MN 55144-1000
651 737 7490 Office
651 575 4906 Fax
skloushin@mmm.com



May 26, 2006

Re: **3M™ Acrylic Foam Tapes 4229P 4218P**

Dear Valued 3M Customer,

Thank you for your inquiry regarding composition of the above listed products, relative to compliance with the European Union's Restriction on Hazardous Substances (RoHS) Directive (2002/95/EC), and other environmental declarations.

Substance	Product Contains	Product Does Not Contain*
Lead and its compounds		X
Mercury and its compounds		X
Cadmium and its compounds		X
Hexavalent Chromium and its compounds		X
Polybrominated Biphenyls (PBBs)		X
Polybrominated Terphenyls (PBTs)		X
Polybrominated Diphenyl Ethers (PBDEs)		X

*"Does not contain" means that the material is not intentionally added or is not present at or above 0.1% or, for cadmium, is not present at or above 0.01% (for unintentionally introduced metallic impurities). These are the *de minimus* thresholds that are contained in the RoHS Directive (2002/95/EC) and "ELV" EU Directive 2000/53/EC, Annex II (June 27, 2002).

I certify, on behalf of 3M Automotive Division, that, to the best of my knowledge, the above mentioned products comply with the requirements for heavy metals content as stated in the European Union's Restriction on Hazardous Substances (RoHS) Directive (2002/95/EC) and the European Union's End of Life Vehicles (ELV) Directive (2000/53/EC).

Thank you for using 3M products. If I can be of further assistance, please do not hesitate to contact me.

Best Regards,

Sharilyn K. Loushin
Product Stewardship Manager

MATERIAL SAFETY DATA SHEET 3M
 3M Center
 St. Paul, Minnesota
 55144-1000
 1-800-364-3577 or (651) 737-6501 (24 hours)

Copyright, 2001, Minnesota Mining and Manufacturing Company.
 All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that:

- 1) the information is copied in full with no changes unless prior agreement is obtained from 3M, and
- 2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

This material safety data sheet (MSDS) is provided as a courtesy in response to a customer request. This product is not regulated under, and a MSDS is not required for this product by the OSHA Hazard Communication Standard (29 CFR 1910.1200) because, when used as recommended or under ordinary conditions, it should not present a health and safety hazard. However, use or processing of the product not in accordance with the product's recommendations or not under ordinary conditions may affect the performance of the product and may present potential health and safety hazards.

DIVISION: AUTOMOTIVE DIVISION
 TRADE NAME:
 Acrylic Foam Tapes for Automotive Applications
 ISSUED: January 23, 2001
 SUPERSEDES: March 25, 1999
 DOCUMENT: 09-0579-4

1. INGREDIENT	C.A.S. NO.	PERCENT
MIXTURE CONSISTING PRIMARILY OF ACRYLATE POLYMERS AND/OR COPOLYMERS...	Mixture	100

2. PHYSICAL DATA

BOILING POINT:..... N/A
 VAPOR PRESSURE:..... N/A
 VAPOR DENSITY:..... N/A
 EVAPORATION RATE:..... N/A
 SOLUBILITY IN WATER:..... N/A
 SPECIFIC GRAVITY:..... 0.55 - 0.99 g/cc
 PERCENT VOLATILE:..... N/A
 pH:..... N/A
 VISCOSITY:..... N/A
 MELTING POINT:..... N/A

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

2. PHYSICAL DATA (continued)

APPEARANCE AND ODOR:

Film, black, grey, white, or translucent. Slight acrylate odor.

3. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:..... N/A
FLAMMABLE LIMITS - LEL:..... N/A
FLAMMABLE LIMITS - UEL:..... N/A
AUTOIGNITION TEMPERATURE:..... N/A

EXTINGUISHING MEDIA:

Water, Water spray, Dry chemical, Dry powder, Foam

SPECIAL FIRE FIGHTING PROCEDURES:

None known.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

No unusual fire or explosion hazards are anticipated.

NFPA HAZARD CODES: HEALTH: 0 FIRE: 1 REACTIVITY: 0
UNUSUAL REACTION HAZARD: none

OSHA FIRE HAZARD CLASS: Not applicable

4. REACTIVITY DATA

STABILITY: Stable

INCOMPATIBILITY - MATERIALS/CONDITIONS TO AVOID:

None known.

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon Monoxide and Carbon Dioxide.

5. ENVIRONMENTAL INFORMATION

SPILL RESPONSE:

Not applicable.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

5. ENVIRONMENTAL INFORMATION (continued)

RECOMMENDED DISPOSAL:

Dispose of waste product in a sanitary landfill. Disposal alternative: Incinerate in an industrial or commercial facility in the presence of a combustible material.

ENVIRONMENTAL DATA:

Not determined.

REGULATORY INFORMATION:

Volatile Organic Compounds: N/A.
VOC Less H2O & Exempt Solvents: N/A.

Since regulations vary, consult applicable regulations or authorities before disposal. U.S. EPA Hazardous Waste Number = None (Not U.S. EPA Hazardous).

EPCRA HAZARD CLASS:

FIRE HAZARD: No PRESSURE: No REACTIVITY: No ACUTE: No CHRONIC: No

6. SUGGESTED FIRST AID

EYE CONTACT:

No need for first aid is anticipated.

SKIN CONTACT:

No need for first aid is anticipated.

INHALATION:

If signs/symptoms occur, remove person to fresh air. If signs/symptoms continue, call a physician.

IF SWALLOWED:

No need for first aid is anticipated.

7. PRECAUTIONARY INFORMATION

EYE PROTECTION:

Not applicable.

SKIN PROTECTION:

Avoid prolonged or repeated skin contact.

RECOMMENDED VENTILATION:

Provide appropriate local exhaust when product is heated.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

7. PRECAUTIONARY INFORMATION (continued)

RESPIRATORY PROTECTION:

Avoid breathing of thermal decomposition products.

PREVENTION OF ACCIDENTAL INGESTION:

Not applicable.

RECOMMENDED STORAGE:

Not applicable.

FIRE AND EXPLOSION AVOIDANCE:

Not applicable.

EXPOSURE LIMITS

INGREDIENT	VALUE	UNIT	TYPE	AUTH	SKIN*
MIXTURE CONSISTING PRIMARILY OF ACRYLATE POLYMERS AND/OR COPOLYMERS.....	NONE	NONE	NONE	NONE	

* SKIN NOTATION: Listed substances indicated with 'Y' under SKIN refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

SOURCE OF EXPOSURE LIMIT DATA:

- NONE: None Established

8. HEALTH HAZARD DATA

EYE CONTACT:

Eye contact is not expected to occur during normal use of the product.

SKIN CONTACT:

Mechanical skin irritation: signs/symptoms can include itching and redness.

INHALATION:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Health effects from inhalation are not expected unless product is heated.

Vapors of heated material may cause respiratory system irritation.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

8. HEALTH HAZARD DATA (continued)

IF SWALLOWED:

Ingestion is not a likely route of exposure to this product.

OTHER HEALTH HAZARD INFORMATION:

Exposure to this material in normal storage and handling has not been reported to cause significant adverse health effects. However, under normal processing conditions, e.g. grinding or heating, this product may release fumes and vapors of variable composition based on specific process conditions. These process releases may produce irritation or any of the health effects listed above when the emissions are present at elevated concentrations. Use with appropriate local exhaust ventilation.

SECTION CHANGE DATES

ENVIRONMENTAL INFO. SECTION CHANGED SINCE March 25, 1999 ISSUE

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

File E308587
Project 06CA50326

November 30, 2006

REPORT

On

COMPONENT - APPLIANCE WIRING MATERIAL

Weiyang Technology Co., Ltd.
Taipei Hsien 236, Taiwan

Copyright © 2006 Underwriters Laboratories Inc.

Underwriters Laboratories Inc. authorizes the above-named company to reproduce this Report provided it is reproduced in its entirety.

DESCRIPTION

PRODUCT COVERED:

Appliance Wiring Material, Styles 1330, 1331, 1332, 1333, 1354, 1745, 1835, 1979, 10064, 10231, 20079, 20145, 20262, 20308, 20476 and 21071.

TEST RECORD NO. 1

SAMPLES:

Samples of Appliance Wiring Material as indicated below and constructed as described herein, were submitted by the manufacturer for examination and test.

Material	Construction	Temp, °C	Voltage, V	Thickness	
				Average, mils	Minimum at any point, mils
FEP	Non-Integral Jacket Cable	200	600	9.8	7.4
FEP	Insulated Single	200	600	6.3	6.0
FEP	Insulated Single	200	30	2.0	1.7

The above samples were tested to be representative of Styles 1330, 1331, 1332, 1333, 1354, 1745, 1835, 1979, 10064, 10231, 20079, 20145, 20262, 20308, 20476 and 21071.

GENERAL:

Test results relate only to the items tested.

The following tests were conducted.

For FEP Non-Integral Jacket Cable -

Test	Section
Thickness, Insulation	13.3
Physical Properties	14
Flexibility Test After Air Oven Conditioning	20
Heat Shock Test	21
Cold Bend Test	22
Cable Flame Test	40
VW-1 Flame Test	41
FT-2 Flame Test	43

The test methods and results of the above tests have been reviewed and found in accordance with the requirements in Underwriters Laboratories Inc. Standard UL 758, Second Edition, for Appliance Wiring Material, containing revisions through and including October 6, 2006.

UL 758 Standard Test / Section	Represented UL 758 Standard Test / Section
FT-2 Flame Test / 43	Horizontal Flame Test for Internal Wiring / 39

The above test conducted in accordance with Standard UL 758 was considered representative of another test required by Standard UL 758.

FEP Insulated Single (30 V) -

Test	Section
Thickness, Insulation	7.3
Physical Properties, Unaged and Air Oven Aged	14
Conductor Corrosion Test	18
Flexibility Test After Air Oven Conditioning	20
Heat Shock Test	21
Cold Bend Test	22
Crush Resistance Test	27
Dielectric Test, Method I	28
Dielectric Test, Method II	29
Dielectric Test, Method III	30
VW-1 Flame Test	41
FT-2 Flame Test	43

The test methods and results of the above tests have been reviewed and found in accordance with the requirements in Underwriters Laboratories Inc. Standard UL 758, Second Edition, for Appliance Wiring Material, containing revisions through and including October 6, 2006.

UL 758 Standard Test / Section	Represented UL 758 Standard Test / Section
FT-2 Flame Test / 43	Horizontal Flame Test for Internal Wiring / 39

The above test conducted in accordance with Standard UL 758 was considered representative of another test required by Standard UL 758.

FEP Insulated Single (600 V)

Test	Section
Thickness, Insulation	7.3
Physical Properties, Unaged and Air Oven Aged	14
Cold Bend Test	22
Crush Resistance Test	27
Dielectric Test, Method I	28
Dielectric Test, Method II	29
Dielectric Test, Method III	30

The test methods and results of the above tests have been reviewed and found in accordance with the requirements in Underwriters Laboratories Inc. Standard UL 758, Second Edition, for Appliance Wiring Material, containing revisions through and including October 6, 2006.

Test Record Summary:

The results of this investigation, including construction review and testing, indicate that the products evaluated comply with the applicable requirements in Underwriters Laboratories Inc. Standard UL 758, Second Edition, for Appliance Wiring Material, containing revisions through and including October 6, 2006, therefore, such products are judged eligible to bear UL's Mark as described on the Conclusion Page of this Report.

CONCLUSION

Samples of the components covered by this Report have been found to comply with the requirements covering the category and the components are judged to be eligible for Component Recognition and Follow-Up Service. Under the service, the manufacturer is authorized to use the Recognized Marking described in the Follow-Up Service Procedure on such components which comply with said Procedure and any other applicable requirements of Underwriters Laboratories Inc. Only those components which properly bear the Recognized Marking are considered as Recognized Components by Underwriters Laboratories Inc.

Report by:
LAURA CHANG
Engineer

Reviewed by:
RAYMOND LIANG
Associate Project Engineer

TINA CHEN
Conformity Assessment Specialist

Any information and documentation provided to you involving UL Mark services are provided on behalf of Underwriters Laboratories Inc.



ZPMV2.E206991 Wiring, Printed - Component

Enhanced searching capability for this category can be found in UL's iQ Family of Databases (i.ul.com).

[Page Bottom](#)

Wiring, Printed - Component

[See General Information for Wiring, Printed - Component](#)

NEW-HEART TECHNOLOGY CO LTD

E206991

11 MIN U RD
DAYUAN TOWNSHIP
TAOYUAN HSIEN, 337 TAIWAN

Type	Cond Width			SS/ DS	Max		Max		Flame Class	Meets UL796 DSR	C T I
	Min	Edge	Cond Thk		Area	Solder Limits	Oper Temp				
	mm(in)	mm(in)	mic(mil)		Diam mm(in)	C sec	C				
Multilayer printed wiring boards.											
2M	0.10 (0.004)	0.21 (0.008)	17 (0.67) Int:68	DS	76.2 (3.0)	260	10	105	-0	All	-
3M	0.14 (0.006)	0.24 (0.009)	17 (0.67) Int:32	DS	76.2 (3.0)	260	20	130	-0	All	-
3M1	0.14 (0.006)	0.24 (0.009)	17 (0.67) Int:34	DS	50.8 (2.0)	260	20	130	-0	All	
4M	0.10 (0.004)	0.21 (0.008)	17 (0.67) Int:34	DS	76.2 (3.0)	260	20	140	-0	All	-
Single layer printed wiring boards.											
1S	0.10 (0.004)	0.21 (0.008)	17 (0.67)	DS	76.2 (3.0)	260	10	130	-0	All	-
1S-1	0.10 (0.004)	0.21 (0.008)	17 (0.67)	DS	76.2 (3.0)	260	10	105	-0	All	-

- CTI Rating is marked on individual board.



Marking: Company name or trademark **NHE** and type designation. May be followed by a suffix to denote factory identification.

Last Updated on 2009-06-20

[Questions?](#)

[Notice of Disclaimer](#)

[Page Top](#)

Copyright ?2009 Underwriters Laboratories Inc.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2009 Underwriters Laboratories Inc. "

An independent organization working for a safer world with integrity, precision and knowledge.





ZPMV2.E324115
Wiring, Printed - Component

Enhanced searching capability for this category can be found in UL's iQ Family of Databases (iq.ul.com).

[Page Bottom](#)

Wiring, Printed - Component

[See General Information for Wiring, Printed - Component](#)

SYU YUAN ELECTRONIC CO LTD

E324115

261 SEC 2 GUANGMING RD
 LUZHU SHIANG
 TAOYUAN HSIEN, 338 TAIWAN

Type	Cond Width		Cond	SS/	Max		Max		Meets	C	
	Min	Edge			Area	Solder	Oper	Flame			UL796
	mm(in)	mm(in)	Thk	DS	Diam	Limits	Temp	Class	UL796	T	
Multilayer printed wiring boards.											
M	0.11 (0.004)	0.33 (0.013)	17 (0.67) Int:68	DS	25.4 (1.0)	288	10	130	V-0	All	-
M1	0.11 (0.004)	0.12 (0.005)	17 (0.67) Int:68	DS	25.4 (1.0)	288	10	140	V-0	All	-
Single layer printed wiring boards.											
D1	0.11 (0.004)	0.12 (0.005)	17 (0.67)	DS	25.4 (1.0)	288	10	140	V-0	All	-
Single layer printed wiring boards, flammability only Recognition.											
D	0.11 (0.004)	0.33 (0.013)	17 (0.67)	DS	25.4 (1.0)	288	10	130	V-0	All	-



Marking: Company name or trademark and type designation. May be followed by a suffix to denote factory identification.

Last Updated on 2008-09-17

[Questions?](#)

[Notice of Disclaimer](#)

[Page Top](#)

Copyright ?2009 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2009 Underwriters Laboratories Inc.®"



PFW2.E352498
Wiring Harnesses - Component

[Page Bottom](#)

Wiring Harnesses - Component

[See General Information for Wiring Harnesses - Component](#)

SAN JOSE TECHNOLOGY INC
11FL NO 2 SEC 4
JHONGYANG RD
TUCHENG
NEW TAIPEI, 236 TAIWAN

E352498

[Last Updated](#) on 2012-02-17

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

◆ 2015 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".

To whom it may concern

Dec. 8, 2015

Certificate of RoHS Compliance

I do declare that the following product:

Internal 2.4-2.5G WiFi Antenna GEPH-023

Internal 2.4-2.5G WiFi Antenna GEPH-062

Produced by San Jose Technology, Inc. conforms to the safety, and reliability norms of the following regulations:

RoHS Directive (2011/65/EU): The Restriction of Hazardous Substances in Electrical and Electronic Equipment Directive, passed into law by the European Union (E.U.)

We agree to take the whole responsibility in this respect.

Signed by:

Terry Lu 10/19



Terry Lu
QA Deputy Manager