

# CommScope Technologies, LLC

## TEST REPORT

**SCOPE OF WORK**

HUMAN RF EXPOSURE TESTING – RPM-A5A11-B02 with W/ 4G LTE and 5G nR waveforms With OneCell® RP5200

**REPORT NUMBER**

104915434BOX-001b

**ISSUE DATE**

February 24, 2022

**[REVISED DATE]**

March 30, 2022

**DOCUMENT CONTROL NUMBER**

Non-Specific Radio Report Shell Rev. December 2017  
© 2017 INTERTEK



## HUMAN RF EXPOSURE TEST REPORT (FULL COMPLIANCE)

**Report Number:** 104915434BOX-001b

**Project Number:** G104915434

**Report Issue Date:** February 24, 2022

**Report Issue Date:** March 30, 2022

**Model(s) Tested:** RPM-A5A11-B02 with W/ 4G LTE and 5G nR waveforms With OneCell® RP5200

**Model(s) Partially Tested:** None

**Model(s) Not Tested but declared equivalent by the client:** None

**Standards:** CFR47 FCC Part § 24 (01/2022),  
CFR47 FCC Part §1.1310 (01/2022),  
CFR47 FCC Part §1.1307(b) (01/2022)

Tested by:  
Intertek Testing Services NA, Inc.  
70 Codman Hill Road  
Boxborough, MA 01719  
USA

Client:  
CommScope Technologies LLC  
900 Chelmsford St.  
Lowell, MA 01851  
USA

Report prepared by



Kouma Sinn / EMC Engineering Supervisor

Report reviewed by



Vathana Ven / EMC Engineering Supervisor

*This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.*

Table of Contents

**1 Introduction and Conclusion ..... 4**  
**2 Test Summary ..... 4**  
**3 Client Information ..... 5**  
**4 Description of Equipment Under Test and Variant Models ..... 5**  
**5 Human RF Exposure: ..... 6**  
**6 Revision History..... 8**

## 1 Introduction and Conclusion

The tests indicated in section 2.0 were performed on the product constructed as described in section 4.0. The remaining test sections are the verbatim text from the actual data sheets used during the investigation. These test sections include the test name, the specified test Method, a list of the actual Test Equipment Used, documentation Photos, Results and raw Data. No additions, deviations, or exclusions have been made from the standard(s) unless specifically noted.

Based on the results of our investigation, we have concluded the product tested **complies** with the requirements of the standard(s) indicated. The results obtained in this test report pertain only to the item(s) tested. Intertek does not make any claims of compliance for samples or variants which were not tested.

## 2 Test Summary

Section	Test full name	Result
3	Client Information	--
4	Description of Equipment Under Test and Variant Models	--
5	Human RF Exposure CFR47 FCC Part § 24 (01/2022), CFR47 FCC Part §1.1310 (01/2022), CFR47 FCC Part §1.1307(b) (01/2022)	--
6	Revision History	Pass

**3 Client Information**

**This EUT was tested at the request of:**

**Client:** CommScope Technologies LLC  
900 Chelmsford St.  
Lowell, MA 01851  
USA

**Contact:** Zac Johnson  
**Telephone:** (978) 250-2678  
**Fax:** None  
**Email:** zac.johnson@commscope.com

**4 Description of Equipment Under Test and Variant Models**

**Manufacturer:** CommScope Telecommunications (China) Ltd.  
68 Su Hong Xi Lu, Suzhou Industrial Park.  
Suzhou, Jiangsu, 215021, China

Equipment Under Test			
Description	Manufacturer	Model Number	Serial Number
Band 2 Radio Module With OneCell® RP5200 host	CommScope Technologies LLC	RPM-A5A11-B02	20488200004
OneCell® RP5200	CommScope Technologies LLC	RP-A52xxi	19361780004

<b>Receive Date:</b>	01/19/2022
<b>Received Condition:</b>	Good
<b>Type:</b>	Production

Description of Equipment Under Test (provided by client)
<p>The Radio Module is band specific using the Analog devices RF Agile Transceiver IC, AD936x. The device combines an RF front end with a flexible mixed-signal baseband section and integrated frequency synthesizers providing a configurable digital interface to the processor. The Radio Module also contains a band specific front end, band specific antenna and required power rails. All power rails required are derived from the 12 VDC bus supplied by the Baseband card. The reference frequency for the radio IC is 38.4 MHz is derived from the from an OCXO which is disciplined from a 1588 reference clock.</p> <p>It supports bandwidths of 5, 10, 15, and 20 MHz with four modulations; TM1.1-QPSK, TM3.2-16QAM, TM3.1-64QAM, and TM3.1a-256QAM. The radio is fixed.</p>

**Variant Models:**

The following variant models were not tested as part of this evaluation, but have been identified by the manufacturer as being electrically identical models, depopulated models, or with reasonable similarity to the model(s) tested. Intertek does not make any claims of compliance for samples or variants which were not tested.

None

**5 Human RF Exposure:**

**Limit for Maximum Permissible Exposure (MPE)**

**FCC Human RF Exposure Limits:**

The FCC §1.1310 The criteria listed in table 1 was used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices shall be evaluated according to the provisions of §2.1093 of this chapter.

Part §1.1310 Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz \* = Plane-wave equivalent power density

(1) Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when a person is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure. The phrase *fully aware* in the context of applying these exposure limits means that an exposed person has received written and/or verbal information fully explaining the potential for RF exposure resulting from his or her employment. With the exception of *transient* persons, this phrase also means that an exposed person has received appropriate training regarding work practices relating to controlling or mitigating his or her exposure. Such training is not required for *transient* persons, but they must receive written and/or verbal information and notification (for example, using signs) concerning their exposure potential and appropriate means available to mitigate their exposure. The phrase *exercise control* means that an exposed person is allowed to and knows how to reduce or avoid exposure by administrative or engineering controls and work practices, such as use of personal protective equipment or time averaging of exposure.

(2) General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

**Human RF Exposure Calculation:**

RF exposure for licensed transmitter is handled at the time of licensing, however, an MPE calculation was performed in order to show the distance at which the device is compliant with the limits of §1.1310, assuming antenna gains of 0 dBi and 4 dBi. The highest measured conducted output power from Intertek Report # 104915434BOX-001b was used, adjusted by +3dB to account for two antenna MIMO operation.

FCC Limit For General Population/Uncontrolled Exposure at 1982.5 MHz = 1 mW/cm<sup>2</sup>

$$\text{Power Density} = [\text{EIRP}] / [4\pi \times (\text{D}_{\text{cm}})^2]$$

Where EIRP is in milliwatts and D is in centimeters. Setting the power density equal to the limit of 1 mW/cm<sup>2</sup> and solving for D<sub>cm</sub> yields the following results.

**Results:**

EUT EIRP = Conducted power + Array Gain + Antenna gain in dBi

The maximum conducted output power from tables below is at 23.30 dBm at 1982.5 MHz

$$\text{Power Density Limit} = [\text{EIRP}] / [4\pi \times (\text{D}_{\text{cm}})^2]$$

$$1 \text{ mW/cm}^2 = [\text{EIRP}] / [4\pi \times (\text{D}_{\text{cm}})^2]$$

$$\text{D}_{\text{cm}} = ([\text{EIRP}] / [4\pi])^{1/2}$$

For Gain = 0 dBi,

$$\text{EIRP} = 23.30 \text{ dBm} + 10 \cdot \text{LOG}(2) + 0 \text{ dBi} = 23.30 \text{ dBm} + 3 \text{ dB} + 0 \text{ dBi}$$

$$\text{EIRP} = 26.30 \text{ dBm or } 426.58 \text{ mW}$$

Therefore, the minimum safe distance D<sub>cm</sub> is  $\text{D}_{\text{cm}} = ([426.58] / [4\pi])^{1/2}$

$$\text{D}_{\text{cm}} = 5.83 \text{ cm at } 0 \text{ dBi gain two antenna MIMO}$$

For Gain = 4 dBi,

$$\text{EIRP} = 23.30 \text{ dBm} + 10 \cdot \text{LOG}(2) + 4 \text{ dBi} = 23.30 \text{ dBm} + 3 \text{ dB} + 4 \text{ dBi}$$

$$\text{EIRP} = 30.30 \text{ dBm or } 1071.52 \text{ mW}$$

Therefore, the minimum safe distance D<sub>cm</sub> is  $\text{D}_{\text{cm}} = ([1071.52] / [4\pi])^{1/2}$

$$\text{D}_{\text{cm}} = 9.23 \text{ cm at } 4 \text{ dBi gain two antenna MIMO}$$

For Gain = X dBi,

$$\text{EIRP} = 23.30 \text{ dBm} + 10 \cdot \text{LOG}(2) + X \text{ dBi} = 23.30 \text{ dBm} + 3 \text{ dB} + X \text{ dBi}$$

$$\text{EIRP} = 26.30 + X \text{ dBm or } 426.58 + 10^{(X/10)} \text{ mW}$$

Therefore, the minimum safe distance D<sub>cm</sub> is  $\text{D}_{\text{cm}} = ([426.58 + 10^{(X/10)}] / [4\pi])^{1/2}$

$$\text{D}_{\text{cm}} = 0.282 \cdot (426.58 + 10^{(X/10)})^{1/2} \text{ cm at } X \text{ dBi gain two antenna MIMO}$$

**6 Revision History**

Revision Level	Date	Report Number	Prepared By	Reviewed By	Notes
0	02/24/2022	104915434BOX-001b	KPS <i>KPS</i>	VFV <i>VFV</i>	Original Issue
1	03/30/2022	104915434BOX-001b	KPS <i>KPS</i>	VFV <i>VFV</i>	1) Updated the standard and removed all the conducted output power and plots and referenced the output power from another report for human RF exposure calculation