

CommScope Technologies, LLC

HUMAN RF EXPOSURE TEST REPORT

SCOPE OF WORK

HUMAN RF EXPOSURE – RPM-A5A11-B025 w/ 5G NR w/ OneCell® 705100

REPORT NUMBER

105029958BOX-005e

ISSUE DATE

June 9, 2022

[REVISED DATE]

Original Issue

DOCUMENT CONTROL NUMBER

Non-Specific Radio Report Shell Rev. August 2020
© 2020 INTERTEK



HUMAN RF EXPOSURE TEST REPORT

(Class II Permissive Change)

Report Number: 105029958BOX-005e

Project Number: G105029958

Report Issue Date: June 9, 2022

Model(s) Tested: RPM-A5A11-B025 w/ 5G NR w/ OneCell®
RP5100

Model(s) Partially Tested: None

Model(s) Not Tested but declared equivalent by the client: None

Standards: CFR47 FCC §1.1310 (05/2022),
CFR47 FCC §1.1307(b) (05/2022),
CFR47 FCC §2.1093 (05/2022)

Tested by:
Intertek Testing Services NA, Inc.
70 Codman Hill Road
Boxborough, MA 01719
USA


Client:
CommScope Technologies LLC
900 Chelmsford St.
Lowell, MA 01851
USA

Report prepared by



Kouma Sinn / EMC Engineering Supervisor

Report reviewed by



Vathana Ven / EMC Engineering Supervisor

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Table of Contents

1 Introduction and Conclusion..... 4

2 Test Summary 4

3 Client Information 5

4 Description of Equipment Under Test and Variant Models..... 5

5 Human RF Exposure..... 7

6 Revision History..... 9

1 Introduction and Conclusion

The tests indicated in section 2.0 were performed on the product constructed as described in section 4.0. The remaining test sections are the verbatim text from the actual data sheets used during the investigation. These test sections include the test name, the specified test Method, a list of the actual Test Equipment Used, documentation Photos, Results and raw Data. No additions, deviations, or exclusions have been made from the standard(s) unless specifically noted.

Based on the results of our investigation, we have concluded the product tested **complies** with the requirements of the standard(s) indicated. The results obtained in this test report pertain only to the item(s) tested. Intertek does not make any claims of compliance for samples or variants which were not tested.

2 Test Summary

Section	Test full name	Result
3	Client Information	--
4	Description of Equipment Under Test and Variant Models	--
5	System Setup and Method	--
6	Human RF exposure CFR47 FCC §1.1310 (05/2022), CFR47 FCC §1.1307(b) (05/2022), CFR47 FCC §2.1093 (05/2022)	Pass
7	Revision History	--

3 Client Information

This EUT was tested at the request of:

Client: CommScope Technologies LLC
 900 Chelmsford St.
 Lowell, MA 01851
 USA

Contact: Zac Johnson
Telephone: (978) 250-2678
Fax: None
Email: zac.johnson@commscope.com

4 Description of Equipment Under Test and Variant Models

Manufacturer: CommScope Telecommunications (China) Ltd.
 68 Su Hong Xi Lu, Suzhou Industrial Park.
 Suzhou, Jiangsu, 215021, China

Equipment Under Test			
Description	Manufacturer	Model Number	Serial Number
Band 25 Radio Module With OneCell® RP5100 host	CommScope Technologies LLC	RPM-A5A11-B02	20488200004
OneCell® RP5100	CommScope Technologies LLC	RP-A52xxi	T2113050973

Receive Date:	04/15/2022
Received Condition:	Good
Type:	Production

Description of Equipment Under Test (provided by client)

The Radio Module is band specific using the Analog devices RF Agile Transceiver IC, AD936x. The device combines an RF front end with a flexible mixed-signal baseband section and integrated frequency synthesizers providing a configurable digital interface to the processor. The Radio Module also contains a band specific front end, band specific antenna and required power rails. All power rails required are derived from the 12 VDC bus supplied by the Baseband card. The reference frequency for the radio IC is 38.4 MHz is derived from the from an OCXO which is disciplined from a 1588 reference clock.

It supports bandwidths of 5, 10, 15, and 20 MHz with four modulations; TM1.1-QPSK, TM3.2-16QAM, TM3.1-64QAM, and TM3.1a-256QAM. The radio is fixed.

Description of Radio Host (provided by client)

The OneCell® RP5200 family is factory configurable with 2 – 4 Radios Modules mounted to a Baseband card. The same PCB's will be used in both indoor and outdoor version of the radio point. The device is fixed.

The baseband card is the host for the modular radios. It contains a two ethernet PHY's with one supporting 100M/1G/2.5G/5G/10G ethernet and the other supporting 100M/1G. The main processor is Zynix Ultrascale+ MPSoC with 2 GB DDR3 and 4 GB Flash memory. The baseband PCBA converts POE power to +12 VDC bus voltage require as input to the radio modules.

Equipment Under Test Power Configuration			
Rated Voltage	Rated Current	Rated Frequency	Number of Phases
48 VDC	0.960 mA per pair max	DC	N/A

Variant Models:

The following variant models were not tested as part of this evaluation, but have been identified by the manufacturer as being electrically identical models, depopulated models, or with reasonable similarity to the model(s) tested. Intertek does not make any claims of compliance for samples or variants which were not tested.

None

5 Human RF Exposure

5.1 Limit for Maximum Permissible Exposure (MPE)

FCC Human RF Exposure Limits:

The FCC §1.1310 The criteria listed in table 1 was used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices shall be evaluated according to the provisions of §2.1093 of this chapter.

Part §1.1310 Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

(1) Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when a person is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure. The phrase *fully aware* in the context of applying these exposure limits means that an exposed person has received written and/or verbal information fully explaining the potential for RF exposure resulting from his or her employment. With the exception of *transient* persons, this phrase also means that an exposed person has received appropriate training regarding work practices relating to controlling or mitigating his or her exposure. Such training is not required for *transient* persons, but they must receive written and/or verbal information and notification (for example, using signs) concerning their exposure potential and appropriate means available to mitigate their exposure. The phrase *exercise control* means that an exposed person is allowed to and knows how to reduce or avoid exposure by administrative or engineering controls and work practices, such as use of personal protective equipment or time averaging of exposure.

(2) General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

5.2 Results:

RF exposure for licensed transmitter is handled at the time of licensing, however, an MPE calculation was performed in order to show the distance at which the device is compliant with the limits of §1.1310, assuming antenna gains of 0 dBi and 4 dBi. The highest measured conducted output power of 22.85 dBm at 1937.50 MHz and 1962.50 MHz from Intertek Report # 105029958BOX-005d was used, adjusted by +3 dB to account for two antenna MIMO operation.

FCC Limit For General Population/Uncontrolled Exposure at 1 mW/cm²

$$\text{Power Density} = [\text{EIRP}] / [4\pi \times (\text{D}_{\text{cm}})^2]$$

Where EIRP is in milliwatts and D is in centimeters. Setting the power density equal to the limit of 1 mW/cm² and solving for D_{cm} yields the following results.

Results:

EUT EIRP = Conducted power + Array Gain + Antenna gain in dBi

The maximum conducted output power is 22.85 dBm

$$\text{Power Density Limit} = [\text{EIRP}] / [4\pi \times (\text{D}_{\text{cm}})^2]$$

$$1 \text{ mW/cm}^2 = [\text{EIRP}] / [4\pi \times (\text{D}_{\text{cm}})^2]$$

$$\text{D}_{\text{cm}} = ([\text{EIRP}] / [4\pi])^{1/2}$$

For Gain = 0 dBi,

$$\text{EIRP} = 22.85 \text{ dBm} + 10 \cdot \text{LOG}(2) + 0 \text{ dBi} = 22.85 \text{ dBm} + 3 \text{ dB} + 0 \text{ dBi}$$

$$\text{EIRP} = 25.85 \text{ dBm or } 384.5918 \text{ mW}$$

Therefore, the minimum safe distance D_{cm} is $\text{D}_{\text{cm}} = ([384.5918] / [4\pi])^{1/2}$

$$\text{D}_{\text{cm}} = 5.532 \text{ cm at } 0 \text{ dBi gain two antenna MIMO}$$

For Gain = 4 dBi,

$$\text{EIRP} = 22.85 \text{ dBm} + 10 \cdot \text{LOG}(2) + 4 \text{ dBi} = 22.85 \text{ dBm} + 3 \text{ dB} + 4 \text{ dBi}$$

$$\text{EIRP} = 29.85 \text{ dBm or } 966.0509 \text{ mW}$$

Therefore, the minimum safe distance D_{cm} is $\text{D}_{\text{cm}} = ([966.0509] / [4\pi])^{1/2}$

$$\text{D}_{\text{cm}} = 8.768 \text{ cm at } 4 \text{ dBi gain two antenna MIMO}$$

For Gain = X dBi,

$$\text{EIRP} = 22.85 \text{ dBm} + 10 \cdot \text{LOG}(2) + X \text{ dBi} = 22.85 \text{ dBm} + 3 \text{ dB} + X \text{ dBi}$$

$$\text{EIRP} = 25.85 + X \text{ dBm or } 384.5918 + 10^{(X/10)} \text{ mW}$$

Therefore, the minimum safe distance D_{cm} is $\text{D}_{\text{cm}} = ([384.5918 + 10^{(X/10)}] / [4\pi])^{1/2}$

$$\text{D}_{\text{cm}} = 0.282 * (384.5918 + 10^{(X/10)})^{1/2} \text{ cm at } X \text{ dBi gain two antenna MIMO}$$

6 Revision History

Revision Level	Date	Report Number	Prepared By	Reviewed By	Notes
0	06/09/2022	105029958BOX-005e	KPS <i>KPS</i>	VFV <i>VFV</i>	Original Issue