

# **FCC RF Exposure Report**

Report No.: SABEDF-WTW-P21110165

FCC ID: QI3BEC-B41-15

Test Model: BEC B41-15

Received Date: Nov. 10, 2021

Test Date: Nov. 17 ~ Nov. 22, 2021

Issued Date: Dec. 28, 2021

Applicant: BILLION ELECTRIC CO., LTD.

Address: 8F., No.192, Sec. 2, Zhongxing Rd., Xindian Dist., New Taipei City 231,

Taiwan (R.O.C.)

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

**Test Location:** No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City

33383, Taiwan

FCC Registration /

**Designation Number:** 788550 / TW0003





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Report No.: SABEDF-WTW-P21110165 Page No. 1 / 5 Report Format Version: 6.1.1



## **Table of Contents**

R	elea	se Control Record	3
1		Certificate of Conformity	4
2		RF Exposure	5
	2.2	Limits for Maximum Permissible Exposure (MPE)	5
	2.3	Classification	5
3		Calculation Result of Maximum Density Power	5



### **Release Control Record**

Issue No.	Description	Date Issued
SABEDF-WTW-P21110165	Original release	Dec. 28, 2021

Report No.: SABEDF-WTW-P21110165 Page No. 3 / 5 Report Format Version: 6.1.1



### 1 Certificate of Conformity

Product: 4G LTE Cat.12 Module mPCle

Brand: BEC, BILLION

Test Model: BEC B41-15

Sample Status: Engineering sample

Applicant: BILLION ELECTRIC CO., LTD.

Test Date: Nov. 17 ~ Nov. 22, 2021

Standards: FCC Part 2 (Section 2.1091)

**References Test** 

Guidance: KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

	Pettie	( Jeen		
Prepared by :	101110	•	, Date:_	Dec. 28, 2021

Pettie Chen / Senior Specialist

Jeremy Lin / Project Engineer



### 2 RF Exposure

#### 2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Power Density Strength (A/m) (mW/cm²)		Average Time (minutes)	
Limits For General Population / Uncontrolled Exposure					
0.3-1.34	614	1.63	(100)*	30	
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30	
30-300	27.5	0.073	0.2	30	
300-1500			f/1500	30	
1500-100,000			1.0	30	

f = Frequency in MHz; \*Plane-wave equivalent power density

#### 2.2 MPE Calculation Formula

 $Pd = (Pout*G) / (4*pi*r^2)$ 

where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

pi = 3.1416

r = distance between observation point and center of the radiator in cm

#### 2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

### 3 Calculation Result of Maximum Density Power

Function	Frequency Band (MHz)	EIRP (dBm)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)
LTE Band 41	2498.5-2687.5	29.83	20	0.191	1.0

<sup>\*</sup>Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

--- END ---

<sup>\*</sup>The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.