	BUREA VERITA
	RF Exposure Report
Report No.:	SA190920C07
FCC ID:	QI3BEC-CBRS6
Test Model:	BEC CBRS-6
Received Date:	Sep. 20, 2019
Test Date:	Sep. 25 ~ Oct. 01, 2019
Issued Date:	Oct. 15, 2019
Applicant:	BILLION ELECTRIC CO., LTD.
Address:	8F., No. 192, Sec. 2, Zhongxing Rd., Xindian Dist., New Taipei City 231, Taiwan (R.O.C.)
Issued By:	Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
	Lin Kou Laboratories
Lab Address:	No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan
Test Location:	No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN
FCC Registration /	788550 / TW0003
Designation Number:	
	TAF Tac-MRA Testing Laboratory 2021
report is for your exclusive use Ap	y copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitt

only with our prior written permission. This report sets forth ourfindings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specification, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



## **Table of Contents**

Rele	ase Control Record	3
1	Certificate of Conformity	4
2	RF Exposure	5
2.2	<ul> <li>Limits for Maximum Permissible Exposure (MPE)</li> <li>MPE Calculation Formula</li> <li>Classification</li> </ul>	5
3	Calculation Result of Maximum Conducted Power	5



# **Release Control Record**

Issue No.	Description	Date Issued
SA190920C07	Original release	Oct. 15, 2019



#### 1 Certificate of Conformity

Product:	LTE module
Brand:	BEC, BILLION
Test Model:	BEC CBRS-6
Sample Status:	Engineering sample
Applicant:	BILLION ELECTRIC CO., LTD.
Test Date:	Sep. 25 ~ Oct. 01, 2019
Standards:	FCC Part 2 (Section 2.1091)
	KDB 447498 D01 General RF Exposure Guidance v06
	IEEE C95.3 -2002

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by :

, Date: Polly Chien / Specialist

Oct. 15, 2019

Approved by :

**Date:** Oct. 15, 2019

Bruce Chen / Senior Project Engineer



## 2 RF Exposure

#### 2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	ge Electric Field Magnetic Field Power Density Strength (V/m) Strength (A/m) (mW/cm <sup>2</sup> )		Average Time (minutes)		
Limits For General Population / Uncontrolled Exposure					
0.3-1.34	614	1.63	(100)*	30	
1.34-30	824/f	2.19/f	(180/f²)*	30	
30-300	27.5	0.073	0.2	30	
300-1500			f/1500	30	
1500-100,000			1.0	30	

f = Frequency in MHz; \*Plane-wave equivalent power density

## 2.2 MPE Calculation Formula

 $\begin{array}{l} \mathsf{Pd} = (\mathsf{Pout}^*\mathsf{G}) \ / \ (4^*\mathsf{pi}^*\mathsf{r}^2) \\ \text{where} \\ \mathsf{Pd} = \mathsf{power} \ \mathsf{density} \ \mathsf{in} \ \mathsf{mW}/\mathsf{cm}^2 \\ \mathsf{Pout} = \mathsf{output} \ \mathsf{power} \ \mathsf{to} \ \mathsf{antenna} \ \mathsf{in} \ \mathsf{mW} \\ \mathsf{G} = \mathsf{gain} \ \mathsf{of} \ \mathsf{antenna} \ \mathsf{in} \ \mathsf{linear} \ \mathsf{scale} \\ \mathsf{pi} = 3.1416 \\ \mathsf{r} = \mathsf{distance} \ \mathsf{between} \ \mathsf{observation} \ \mathsf{point} \ \mathsf{and} \ \mathsf{center} \ \mathsf{of} \ \mathsf{the} \ \mathsf{radiator} \ \mathsf{in} \ \mathsf{cm} \\ \end{array}$ 

## 2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

#### 3 Calculation Result of Maximum Conducted Power

Function	Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
LTE Band 48	3552.5 ~ 3697.5	8.45	14.50	20	0.039	1

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

---END----