

FCC MPE calculation Report

Product name : Wireless Awinda dongle with external antenna
Applicant : Xsens Technologies B.V.
FCC ID : QILAW-DNG2-ANT

Test report No. : 201000148 01 MPE calculation report Ver 1.0



Report number: xxxxxxxxx MPE calculation report Ver 1.0

Laboratory information

Accreditation

Telefication complies with the accreditation criteria for test laboratories as laid down in ISO/IEC 17025:2017. The accreditation covers the quality system of the laboratory as well as the specific activities as described in the authorized annex bearing the accreditation number L021 and is granted on 30 November 1990 by the Dutch Council For Accreditation (RvA: Raad voor Accreditatie).

Telefication is designated by the FCC as an Accredited Test Firm for compliance testing of equipment subject to Certification under Parts 15 & 18. The Designation number is: NL0001.

Telefication is a Wireless Device Testing laboratory recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements.

The Industry Canada company number for Telefication is: 4173A.

Telefication is a registered Conformity Assessment body (CAB) under the Japan-EC MRA (Agreement on Mutual Recognition between Japan and the European Community). The registration number is: 201.

Documentation

The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 10 years at Telefication Netherlands.

Testing Location

Test Site	Kiwa Telefication BV
Test Site location	Wilmersdorf 50 7327 AC Apeldoorn The Netherlands Tel. +31 88998 3393
Test Site FCC	NL0001
CABID	NL0001



Report number: xxxxxxxxx MPE calculation report Ver 1.0

Revision History

Version	Date	Remarks	By
v1.0	18-10-2021	Release version	PS

Table of Contents

Revision History	2
1 General Description	4
1.1 Applicant	4
1.2 Manufacturer	4
1.3 Tested Equipment Under Test (EUT).....	4
1.4 SAR Measurement Evaluation.....	5
1.4.1 Maximum Output Power	5
1.4.2 MPE Limits	5
1.4.3 MPE calculation	6
1.5 Summary	6

1 General Description

1.1 Applicant

Client name:	Xsens Technologies B.V.
Address	Pantheon 6a
Zip code:	7521 PR, Enschede, The Netherlands
Telephone:	+31(0)889736700
E-mail:	robert.gielians@xsens.com
Contact name:	Mr. R.P.G. Gielians

1.2 Manufacturer

Manufacturer name:	Xsens Technologies B.V.
Address:	Pantheon 6a
Zip code:	7521 PR, Enschede, The Netherlands
Telephone:	+31(0)889736700
E-mail:	robert.gielians@xsens.com
Contact name:	Mr. R.P.G. Gielians

1.3 Tested Equipment Under Test (EUT)

Product name:	Wireless Awinda dongle with external antenna
Brand name:	Xsens MVN Awinda
Product type:	2.4 GHz wireless data transmission equipment
FCC ID:	QILAW-DNG2-ANT
Software version:	--
Hardware version:	AA200811

1.4 SAR Measurement Evaluation

1.4.1 Maximum Output Power

The maximum radiated power including antenna gain is shown as below.

Technology	Output power (dBm)
2.4 GHz proprietary	18.5*

* from Telefication test report no: 201000148 01 Ver 1.00

1.4.2 MPE Limits

Limits for occupational/controlled exposure

Frequency Range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
0.3 – 3.0	614	1.63	100 (see note 1)	≤6
3.0 – 30	1842/f	4.89/f	900/f ² (see note 1)	≤6
30 – 300	61.4	0.163	1.0	≤6
300 – 1500	--	--	f/300	≤6
1500 – 100000	--	--	5	≤6

Limits for general population/uncontrolled exposure

Frequency Range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
0.3 – 1.34	614	1.63	100 (see note 1)	≤30
1.34 – 30	824/f	2.19/f	180/f ² (see note 1)	≤30
30 – 300	27.5	0.073	0.2	≤30
300 – 1500	--	--	f/1500	≤30
1500 – 100000	--	--	1.0	≤30

Notes :

f = frequency in MHz

1: plane wave equivalent power density

1.4.3 MPE calculation

As declared by the applicant, the EUT is a wireless device used in a mobile application, at least 20 cm from any body part of the user or nearby persons.

Calculation method of RF Safety Distance:

$$PD = \frac{P_{out} * G}{4\pi r^2} = \frac{P(eirp)}{4\pi r^2}$$

Where:

PD = Power Density in mW/cm^2

Pout = Output power in mW

G = Gain of antenna

R = Distance between observation point and centre of the radiator in cm

Calculation results

Technology	Frequency (MHz)	Max radiated power (mW)	Distance (cm)	Power density (mW/cm^2)	Limit (mW/cm^2)
2.4 GHz proprietary	2405	70.8	20	0.014	1.0

1.5 Summary

Since the result of the MPE calculation is less than 1.0 mW/cm^2 , the MPE limit is fulfilled.