



FCC ID QIPAC75i

Maximum Permissible Exposure

as specified in Table 1B of 47 CFR 1.1310 – Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure

Frequency range (MHz)	Power density (mW/cm ²)
300 – 1,500	f/1500
1,500 – 100,000	1.0

Calculations 850 MHz band

Maximum peak output power at antenna input terminal: 33.45 dBm (2.21309 W)

Predicted distance **R**: 20 cm
Predicted frequency: 824.6 MHz

MPE limit **S**: 0.5494666 mW/cm²

Equation OET bulletin 65, page 18, edition 97-01: $S = P * G / (4\pi R^2)$

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna

Maximum allowable antenna gain: **0.9621 dBi**

Prediction

The maximum allowable MPE value of 0.5494666 mW/cm² will be reached in a distance of 20 cm in case that an antenna with an antenna gain of 0.9621 dBi will be used. This means that the power density levels in a distance of 20 cm are in accordance with the FCC regulations as long as the used antenna has a gain below 0.9621 dBi.



Calculations 1900 MHz band

Maximum peak output power at antenna input terminal: 30.58 dBm (1.14288 W)

Prediction distance **R**: 20 cm
Prediction frequency: 1850.2 MHz

MPE limit **S**: 1 mW/cm²

Equation OET bulletin 65, page 18, edition 97-01: $S = P * G / (4\pi R^2)$

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna

Maximum allowable antenna gain for mobile/portable stations: **2.4303 dBi**
Maximum allowable antenna gain for other stations: **6.4327 dBi**

Prediction

The maximum allowable MPE value of 1 mW/cm² will be reached in a distance of 20 cm in case that an antenna with an antenna gain of 6.4327 dBi will be used. This means that the power density levels in a distance of 20 cm are in accordance with the FCC regulations as long as the used antenna has a gain below 6.4327 dBi.

For mobile and portable stations the EIRP is restricted to 2.0 Watts, (§24.232 (c)).

Therefore the maximum antenna gain is 2.4303 dBi.

Yours sincerely

Holger Leutfeld, Project Manager