



Certificate #4312.01

# MPE REPORT

**Product Name:** Global LTE Cat.M1/LTE Cat.NB2/2G  
Data-Only Module  
**Trade Mark:** CINTERION  
**Model No. / HVIN:** EXS82-W  
**Report Number:** 220613004RFC-1  
**Test Standards:** FCC 47 CFR Part 1 Subpart I  
RSS-102 Issue 5  
**FCC ID:** QIPEXS82-W  
**IC:** 7830A-EXS82W  
**Test Result:** PASS  
**Date of Issue:** October 19, 2022

Prepared for:

**Thales DIS AIS Deutschland GmbH**  
**Siemensdamm 50, 13629 Berlin, Germany**

Prepared by:

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**  
**Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and  
technology park, Longhua district, Shenzhen, China**  
**TEL: +86-755-2823 0888**  
**FAX: +86-755-2823 0886**

Prepared by:

Kieron Luo  
Project Engineer

Reviewed by:

Henry Lu  
Team Leader

Approved by:

Kevin Liang  
Assistant Manager

Date:

October 19, 2022

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China  
Tel: +86-755-28230888 Fax: +86-755-28230886 E-mail: info@uttlab.com <http://www.uttlab.com>  
UTTR-RF-RSS102-V1.1

**Version**

<b>Version No.</b>	<b>Date</b>	<b>Description</b>
V1.0	October 19, 2022	Original

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China  
Tel: +86-755-28230888 Fax: +86-755-28230886 E-mail: [info@uttlab.com](mailto:info@uttlab.com) <http://www.uttlab.com>  
UTTR-RF-RSS102-V1.1

## CONTENTS

<b>1.</b>	<b>Test Laboratory .....</b>	<b>4</b>
<b>2.</b>	<b>Client Information .....</b>	<b>5</b>
<b>2.1.</b>	<b>Applicant Information .....</b>	<b>5</b>
<b>2.2.</b>	<b>Manufacturer Information .....</b>	<b>5</b>
<b>3.</b>	<b>Equipment Under Test (EUT) and Ancillary Equipment (AE).....</b>	<b>6</b>
<b>3.1.</b>	<b>About EUT .....</b>	<b>6</b>
<b>4.</b>	<b>Power Output Test Results .....</b>	<b>6</b>
<b>4.1.</b>	<b>RF Power Output .....</b>	<b>6</b>
<b>4.2.</b>	<b>Duty cycle .....</b>	<b>6</b>
<b>5.</b>	<b>Reference Documents for FCC .....</b>	<b>7</b>
<b>5.1.</b>	<b>Applicable Standards .....</b>	<b>7</b>
<b>5.2.</b>	<b>Test Limits .....</b>	<b>7</b>
<b>5.3.</b>	<b>Calculation Information .....</b>	<b>8</b>
<b>5.4.</b>	<b>Max. Antenna gain calculations .....</b>	<b>9</b>
<b>5.5.</b>	<b>Conclusion for maximum admissible antenna gain (FCC).....</b>	<b>9</b>
<b>6.</b>	<b>Reference Documents for IC.....</b>	<b>10</b>
<b>6.1.</b>	<b>Applicable Standards .....</b>	<b>10</b>
<b>6.2.</b>	<b>Test Limits .....</b>	<b>10</b>
<b>6.3.</b>	<b>Calculation Information .....</b>	<b>11</b>
<b>6.4.</b>	<b>Max. Antenna gain calculations .....</b>	<b>11</b>
<b>6.5.</b>	<b>Conclusion for maximum admissible antenna gain (IC) .....</b>	<b>11</b>
<b>7.</b>	<b>Summary.....</b>	<b>11</b>

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China  
 Tel: +86-755-28230888 Fax: +86-755-28230886 E-mail: info@uttlab.com <http://www.uttlab.com>  
 UTRR-RF-RSS102-V1.1

### 1. Test Laboratory

<b>Company Name:</b>	Shenzhen UnionTrust Quality and Technology Co., Ltd.
<b>Address:</b>	Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China 518109
<b>Postal Code:</b>	518109
<b>Telephone:</b>	+86 (0) 755 2823 0888
<b>Fax:</b>	+86 (0) 755 2823 0886

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China  
 Tel: +86-755-28230888 Fax: +86-755-28230886 E-mail: info@uttlab.com <http://www.uttlab.com>  
 UTRR-RF-RSS102-V1.1

## 2. Client Information

### 2.1. Applicant Information

**Company Name:** Thales DIS AIS Deutschland GmbH  
**Address /Post:** Siemensdamm 50, 13629 Berlin, Germany  
**Telephone:** /  
**Postcode:** /

### 2.2. Manufacturer Information

**Company Name:** Thales DIS AIS Deutschland GmbH  
**Address /Post:** Werinherstr.81, 81541 Munich, Germany  
**Telephone:** /  
**Postcode:** /

### **Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China  
Tel: +86-755-28230888 Fax: +86-755-28230886 E-mail: [info@uttlab.com](mailto:info@uttlab.com) <http://www.uttlab.com>  
[UTTR-RF-RSS102-V1.1](#)

### 3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

#### 3.1. About EUT

<b>EUT Description</b>	Global LTE Cat.M1/LTE Cat.NB2/2G Data-Only Module
<b>Model No. / HVIN:</b>	EXS82-W(See Note)
<b>FVIN:</b>	01.410
<b>LTE Frequency Band</b> (Provided by the customer)	LTE Band 2/ Band 4/ Band 5/ Band 12/ Band 13/ Band 25/ Band 26/ Band 66/ Band 71/ Band 85
<b>Antenna Type</b>	External Antenna
<b>FCC ID:</b>	QIPEXS82-W
<b>IC:</b>	7830A-EXS82W
<b>Note:</b> This product EXS82-W has two forms of SIM and ESIM.	

### 4. Power Output Test Results

#### 4.1. RF Power Output

Frequency Band	Highest Power Output(dBm)
LTE Band 85	22

#### 4.2. Duty cycle

Mode	Duty Cycle
LTE	1:1

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China  
 Tel: +86-755-28230888 Fax: +86-755-28230886 E-mail: info@uttlab.com <http://www.uttlab.com>  
 UTRR-RF-RSS102-V1.1

## 5. Reference Documents for FCC

### 5.1. Applicable Standards

The MPE report was carried out on a sample equipment to demonstrate limited compliance with FCC CFR 47 Part 2.1091.

FCC CFR 47, Part 2, FREQUENCY ALLOCATIONS AND RADIO TREATY MATTERS; GENERAL RULES AND REGULATIONS, Oct 1, 2011

Section 2.1091 Radiofrequency radiation exposure evaluation.

### 5.2. Test Limits

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

Limits for Occupational / Controlled Exposure

Frequency Range [MHz]	Electric Field Strength (E) [V/m]	Magnetic Field Strength (H) [A/m]	Power Density (S) [mW/cm <sup>2</sup> ]	Averaging Times  E  <sup>2</sup> ,  H  <sup>2</sup> or S [minutes]
0.3 – 3.0	614	1.63	(100)*	6
3.0 – 30	1824/f	4.89/f	(900/f)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	--	--	F/300	6
1500 - 100000	--	--	5	6

Limits for General Population / Uncontrolled Exposure

Frequency Range [MHz]	Electric Field Strength (E) [V/m]	Magnetic Field Strength (H) [A/m]	Power Density (S) [mW/cm <sup>2</sup> ]	Averaging Times  E  <sup>2</sup> ,  H  <sup>2</sup> or S [minutes]
0.3 – 1.34	614	1.63	(100)*	30
1.34 – 30	824/f	2.19/f	(180/f)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	--	--	F/1500	30
1500 - 100000	--	--	1.0	30

Note: f=frequency in MHz; \*Plane-wave equivalent power density

For the DUT, the limits for General Population / Uncontrolled Exposure are applicable.

### Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China  
 Tel: +86-755-28230888 Fax: +86-755-28230886 E-mail: info@uttlab.com <http://www.uttlab.com>  
 UTRR-RF-RSS102-V1.1

FCC: §1.1307	Cellular Radiotelephone Service (subpart H of part 22) Non-building-mounted antennas: height above ground level to lowest point of antenna < 10 m and total power of all channels > 1000 W ERP (1640 W EIRP)
FCC §1.1307	Personal Communications Services (part 24) Broadband PCS (subpart E): non-building-mounted antennas: height above ground level to lowest point of antenna < 10 m and total power of all channels > 2000 W ERP (3280 W EIRP)
FCC §1.1310	LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE) Table 1(B) Limits for General Population/Uncontrolled Exposure 300–1500 MHz: f/1500 mW/cm <sup>2</sup> 1500–100,000 MHz: 1.0 mW/cm <sup>2</sup> Subject to routine evaluation is required when the device operate at frequencies of 1.5 GHz or below and their
FCC §2.1091	effective radiated power (ERP) is 1.5 watts or more, or if they operate at frequencies above 1.5 GHz and their ERP is 3 watts or more.(a) Base stations are limited to 1640 watts peak equivalent isotropically radiated power (e.i.r.p.) with an antenna
FCC §27.50 (C)(10)	(10) Portable stations (hand-held devices) are limited to 3 watts ERP; and

### 5.3. Calculation Information

For conservative evaluation consideration, only maximum power of each frequency band based on the tighter limits respectively are used to calculate the boundary power density.

Based on the FCC KDB 447498 D01 and 47 CFR §2.1091, the DUT is evaluated as a mobile device.

Given  $S = \frac{P \times G}{4\pi d^2}$  *Equation 1*

Where

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**



### 5.4. Max. Antenna gain calculations

Maximum antenna gain considerations for fixed/mobile operations for complying with limits:

Band	Highest Frame-Averaged Output Power (dBm)	Limit (mW/cm <sup>2</sup> )	Max antenna gain at 20cm (dBi)
LTE Band 85	22	0.465	11.68

Power limit according to §27.50(c)(10):

Band	Highest Frame-Averaged Output Power (dBm)	Limit (W) (ERP/EIRP)	Max antenna gain at 20cm(dBi)
LTE Band 85	22	3	12.77

### 5.5. Conclusion for maximum admissible antenna gain (FCC)

Band	Maximum admissible antenna gain (dBi)
LTE Band 85	11.68

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

## 6. Reference Documents for IC

### 6.1. Applicable Standards

RSS 102 Issue 5: Radio Frequency (RF) Exposure Compliance of Radio communication Apparatus (All Frequency Bands)

### 6.2. Test Limits

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $22.48/f^{0.5}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $1.31 \times 10^{-2} f^{0.6834}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

RSS -130	4.6.3 Frequency bands 698-756 MHz and 777-787 MHz The e.r.p. shall not exceed 30 watts for mobile equipment and outdoor fixed subscriber equipment. The e.r.p. shall not exceed 3 watts for portable equipment and indoor fixed subscriber equipment.
SRSP-510	5.1.2 Mobile Stations Mobile stations and hand-held portables are limited to 2 watts maximum e.i.r.p. The equipment shall employ means to limit the power to the minimum necessary for successful communication.

### **Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China  
 Tel: +86-755-28230888 Fax: +86-755-28230886 E-mail: info@uttlab.com <http://www.uttlab.com>  
 UTRR-RF-RSS102-V1.1

**6.3. Calculation Information**

at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $1.31 \times 10^{-2} f^{0.6834} W$  (adjusted for tune-up tolerance), where  $f$  is in MHz;

**6.4. Max. Antenna gain calculations**

Maximum antenna gain considerations for fixed/mobile operations for complying with limits according to RSS 102:

Band	Highest Output Power (dBm)	MPE limit (W)	Max antenna gain at 20cm (dBi)
LTE Band 85	22	1.15	8.60

Power limit according to RSS-130:

Band	Highest Frame-Averaged Output Power (dBm)	Limit (W) ERP/EIRP	Max antenna gain (dBi)
LTE Band 85	22	11.5	12.77

**6.5. Conclusion for maximum admissible antenna gain (IC)**

Band	Maximum admissible antenna gain (dBi)
LTE Band 85	8.60

**7. Summary**

Band	FCC Maximum admissible antenna gain (dBi)	IC Maximum admissible antenna gain (dBi)	Total Maximum admissible antenna gain (dBi)
LTE Band 85	11.68	8.60	8.60

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China  
 Tel: +86-755-28230888 Fax: +86-755-28230886 E-mail: info@uttlab.com <http://www.uttlab.com>  
 UTTR-RF-RSS102-V1.1

\*\*\* End of Report \*\*\*

---

---

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.

---

---

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China  
Tel: +86-755-28230888 Fax: +86-755-28230886 E-mail: [info@uttlab.com](mailto:info@uttlab.com) <http://www.uttlab.com>  
UTTR-RF-RSS102-V1.1