

FCC RF Exposure Report

Report No.: MFBHQC-WTW-P21030610F

FCC ID: QIPMV31-W

Test Model: MV31-W

Received Date: Sep. 06, 2021

Test Date: Sep. 29 ~ Oct. 10, 2021

Issued Date: Jun. 24, 2022

Applicant: THALES DIS AIS Deutschland GmbH

Address: Siemensdamm 50, Berlin, 13629, German

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, Taiwan

**FCC Registration /
Designation Number:** 788550 / TW0003



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
3.1 Limits for Maximum Permissible Exposure (MPE).....	5
3.2 MPE Calculation Formula	5
3.3 Classification	5
3 Calculation Result of Maximum Density Power	6

Release Control Record

Issue No.	Description	Date Issued
MFBHQC-WTW-P21030610F	Original release	Jun. 24, 2022

1 Certificate of Conformity

Product: Cinterion MV31-W

Brand: CINTERION

Test Model: MV31-W

Sample Status: Engineering Sample

Applicant: THALES DIS AIS Deutschland GmbH

Test Date: Sep. 29 ~ Oct. 10, 2021

Standards: FCC Part 2 (Section 2.1091)

References Test Guidance: KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Pettie Chen , **Date:** Jun. 24, 2022
Pettie Chen / Senior Specialist

Approved by : Jeremy Lin , **Date:** Jun. 24, 2022
Jeremy Lin / Project Engineer

Note: This report is prepared for FCC class II permissive change. This report is issued as a duplicate report of BV CPS report no.: SABHQC-WTW-P21030610B (FCC ID: 2AQ68T99W175). Difference compared with the original report is changing applicant, FCC ID, product name, brand and model. Due to no effect any test item, we didn't re-calculated MPE value.

2 RF Exposure

3.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

f = Frequency in MHz; *Plane-wave equivalent power density

3.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

pi = 3.1416

r = distance between observation point and center of the radiator in cm

3.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user.

So, this device is classified as **Mobile Device**.

3 Calculation Result of Maximum Density Power

Function	Frequency Band (MHz)	EIRP (dBm)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WCDMA Band 2	1850.7-1909.3	27.79	20	0.120	1
WCDMA Band 4	1710.7-1754.3	27.74	20	0.118	1
LTE Band 2	1850.7-1909.3	28.09	20	0.128	1
LTE Band 4	1710.7-1754.3	28.25	20	0.133	1
LTE Band 7	2502.5-2567.5	28.66	20	0.146	1
LTE Band 25	1850.7-1914.3	27.99	20	0.125	1
LTE Band 30	2307.5-2312.5	23.50	20	0.045	1
LTE Band 38	2572.5-2617.5	28.85	20	0.153	1
LTE Band 41	2547.5-2652.5	32.03	20	0.317	1
LTE Band 48 (Per 10M)	3552.5-3697.5	22.78	20	0.038	1
LTE Band 48 (Full Power)	3552.5-3697.5	22.92	20	0.039	1
LTE Band 42 (Per 10M)	3552.5-3597.5	22.56	20	0.036	1
LTE Band 42 (Full Power)	3552.5-3597.5	22.79	20	0.038	1
LTE Band 66	1710.7-1779.3	27.95	20	0.124	1
LTE Band 7C	2507.8-2560.0	28.71	20	0.148	1
LTE Band 38C	2580.0-2610.0	30.26	20	0.211	1
LTE Band 41C	2506.0-2680.0	30.23	20	0.210	1
LTE Band 48C (Per 10M)	3560.0-3690.0	22.53	20	0.036	1
LTE Band 48C (Full Power)	3560.0-3690.0	22.89	20	0.039	1
LTE Band 42C (Per 10M)	3552.5-3697.5	22.25	20	0.033	1
LTE Band 42C (Full Power)	3552.5-3697.5	22.68	20	0.037	1
LTE Band 66C	1720.0-1770.0	28.89	20	0.154	1
LTE Band 66B	1715.0-1775.0	28.63	20	0.145	1
5GNR (n38)	2580.0-2610.0	28.51	20	0.141	1
5GNR (n41)	2506.02-2679.99	30.81	20	0.240	1

Function	Frequency Band (MHz)	ERP (dBm)	EIRP (dBm)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WCDMA Band 5	826.4-846.6	25.15	27.30	20	0.107	0.551
LTE Band 5	824.7-848.3	25.84	27.99	20	0.125	0.550
LTE Band 26 (Part 22)	824.7-848.3	25.64	27.79	20	0.120	0.550
LTE Band 12	699.7-715.3	26.35	28.50	20	0.141	0.466
LTE Band 13	779.5-784.5	26.41	28.56	20	0.143	0.520
LTE Band 14	790.5-795.5	26.41	28.56	20	0.143	0.527
LTE Band 17	706.5-713.5	26.27	28.42	20	0.138	0.471
LTE Band 26 (Part 90)	814.7-823.3	25.78	27.93	20	0.124	0.543
LTE Band 71	665.5-695.5	25.97	28.12	20	0.129	0.444
LTE Band 5B	829.0-844.0	25.79	27.94	20	0.124	0.553

Function	Frequency Band (MHz)	ERP (dBm)	EIRP (dBm)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Co-located Ratio<1
ENDC n2	1852.5-1907.5	-	27.55	20	0.113	1	-
ENDC n2	LTE Band 5	824.7-848.3	25.04	27.19	20	0.104	0.303
	LTE Band 12	699.7-715.3	25.45	27.60	20	0.114	0.359
	LTE Band 13	779.5-784.5	25.46	27.61	20	0.115	0.334
	LTE Band 30	2307.5-2312.5	-	23.30	20	0.043	1
	LTE Band 48 (Per 10M)	3552.5-3697.5	-	22.71	20	0.037	1
	LTE Band 48 (Full Power)	3552.5-3697.5	-	22.71	20	0.037	1
	LTE Band 66	1710.7-1779.3		27.47	20	0.111	1
ENDC n5	826.5-846.5	24.96	27.11	20	0.102	0.551	-
ENDC n5	LTE Band 2	1850.7-1909.3	-	27.66	20	0.116	1
	LTE Band 7	2502.5-2567.5	-	28.49	20	0.141	1
	LTE Band 12	699.7-715.3	25.45	27.60	20	0.114	0.466
	LTE Band 48 (Per 10M)	3552.5-3697.5	-	22.71	20	0.037	1
	LTE Band 48 (Full Power)	3552.5-3697.5	-	22.69	20	0.037	1
	LTE Band 66	1710.7-1779.3	-	27.44	20	0.110	1
ENDC n7	2507.8-2560.0	-	28.51	20	0.141	1	-
ENDC n7	LTE Band 5	824.7-848.3	25.05	27.20	20	0.104	0.550
	LTE Band 12	699.7-715.3	25.45	27.60	20	0.114	0.466
ENDC n12	699.7-715.3	25.56	27.71	20	0.193	0.466	-
ENDC n12	LTE Band 2	1850.7-1909.3	-	27.66	20	0.116	1
	LTE Band 66	1710.7-1779.3	-	27.47	20	0.111	1
ENDC n41 (HPUE)	2506.02-2679.99	-	31.21	20	0.263	1	-
ENDC n41	2506.02-2679.99	-	28.90	20	0.154	1	-
ENDC n41	LTE Band 2	1850.7-1909.3	-	27.47	20	0.111	1
	LTE Band 25	1850.7-1914.3	-	27.47	20	0.111	1
	LTE Band 26 (Part 22)	824.7-848.3	24.86	27.01	20	0.100	0.550
	LTE Band 26 (Part 90)	814.7-823.3	24.86	27.01	20	0.100	0.543
	LTE Band 41 (HPUE)	2498.5-2687.5	-	30.80	20	0.239	1
	LTE Band 41	2498.5-2687.5	-	28.21	20	0.132	1
	LTE Band 66	1710.7-1779.3	-	27.46	20	0.111	1

Function	Frequency Band (MHz)	ERP (dBm)	EIRP (dBm)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Co-located Ratio<1
ENDC n66	1712.5-1777.9	-	27.67	20	0.116	1	-
ENDC n66	LTE Band 5	824.7-848.3	24.86	27.01	20	0.100	0.298
	LTE Band 12	699.7-715.3	25.46	27.61	20	0.115	0.363
	LTE Band 13	779.5-784.5	25.45	27.60	20	0.114	0.336
	LTE Band 71	665.5-695.5	25.46	27.61	20	0.115	0.375
	LTE Band 30	2307.5-2312.5	-	23.20	20	0.042	1
	LTE Band 48 (Per 10M)	3552.5-3697.5	-	22.72	20	0.037	1
	LTE Band 48 (Full Power)	3552.5-3697.5	-	22.71	20	0.037	1
ENDC n71	665.5-695.5	25.45	27.60	20	0.114	0.444	-
ENDC n71	LTE Band 2	1850.7-1909.3	-	27.67	20	0.116	1
	LTE Band 7	2502.5-2567.5	-	28.46	20	0.140	1
	LTE Band 66	1710.7-1779.3	-	27.47	20	0.111	1
ENDC n25	1852.5-1912.5	-	29.48	20	0.176	1	-
ENDC n25	LTE Band 12	699.7-715.3	27.30	29.45	20	0.175	1
ENDC n77 (Part 27O)	3710.01-3969.99	-	29.60	20	0.181	1	-
ENDC n77 (Part 27Q)	3460.02-3540.00	-	29.58	20	0.181	1	-
ENDC n77	LTE Band 2	1850.7-1909.3	-	29.13	20	0.163	1
	LTE Band 5	824.7-848.3	26.77	28.92	20	0.155	0.550
	LTE Band 7	2502.5-2567.5	-	30.45	20	0.221	1
	LTE Band 12	699.7-715.3	27.30	29.45	20	0.175	0.466
	LTE Band 13	779.5-784.5	27.32	29.47	20	0.176	0.520
	LTE Band 14	790.5-795.5	27.31	29.46	20	0.176	0.527
	LTE Band 30	2307.5-2312.5	-	23.93	20	0.049	1
	LTE Band 41	2498.5-2687.5	-	32.97	20	0.394	1
	LTE Band 66	1710.7-1779.3	-	29.16	20	0.164	1

*Part 27Q: n77, n78 (3450-3550MHz)
 Part 27O: n77 (3700-3980MHz) / n78 (3700-3800MHz)
 *EIRP = ERP + 2.15dB

*Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

--- END ---