

**InterLab<sup>®</sup>**

## RF Exposure and Maximum ERP/EIRP Assessment

For

**Cinterion<sup>®</sup> ALAS66A-US Data and Voice  
Module**

**FCC ID: QIPALAS66A-US**

**IC: 7830A-ALAS66AUS**

**Assessment Reference:** MDE\_GEMALTO\_1802\_MPEf

**Test Laboratory:**

7layers GmbH  
Borsigstrasse 11  
40880 Ratingen  
Germany



Deutsche  
Akkreditierungsstelle  
D-PL-12140-01-00

**Note:**

The following test results relate only to the devices specified in this document. This report shall not be reproduced in parts without the written approval of the test laboratory.

**7layers GmbH**

Borsigstraße 11  
40880 Ratingen, Germany  
T +49 (0) 2102 749 0  
F +49 (0) 2102 749 350

Geschäftsführer/  
Managing Directors:  
Frank Spiller  
Bernhard Retka  
Alexandre Norré-Oudard

Registergericht/registered:  
Düsseldorf HRB 75554  
USt-Id.-Nr./VAT-No. DE203159652  
Steuer-Nr./TAX-No. 147/5869/0385

*a Bureau Veritas  
Group Company*

*www.7layers.com*

## Table of Contents

<b>0</b>	<b>Summary</b>	<b>3</b>
0.1	Technical Report Summary	3
<b>1</b>	<b>Administrative Data</b>	<b>4</b>
1.1	Testing Laboratory	4
1.2	Project Data	4
1.3	Applicant Data	4
1.4	Manufacturer Data	4
<b>2</b>	<b>Test object Data</b>	<b>5</b>
2.1	General EUT Description	5
2.2	EUT Main components	5
2.3	Ancillary Equipment	5
2.4	Auxiliary Equipment	5
<b>3</b>	<b>Evaluation Results</b>	<b>6</b>
3.1	Maximum ERP / EIRP	6
3.2	RF Exposure Evaluation for Module	8
3.3	RF Exposure Evaluation for Carrier Aggregation	11

## 0 Summary

### 0.1 Technical Report Summary

#### Type of Report

RF Exposure and Maximum ERP/EIRP Assessment for a 2G/3G/4G Data and Voice radio module.

#### Applicable FCC and ISED Rules

##### For RF Exposure:

OET Bulletin 65 Edition 97-01 August 1997  
 FCC 47 CFR §1.1307  
 FCC 47 CFR §1.1310  
 RSS-102 Issue 5 – March 2015

##### For Maximum ERP/EIRP:

FCC 47 CFR §22.913  
 IC SRSP-503 Issue 7, September 2008  
 FCC 47 CFR §24.232  
 IC SRSP-510 Issue 5, February 2009  
 FCC 47 CFR §27.50(d)  
 RSS-139, Issue 3 / SRSP-513, July 2015

Report version control			
Version	Release date	Changes	Version validity
initial	2019-03-25	Initial version	Valid

Responsible for  
Accreditation Scope: \*



Responsible  
for Report: \*



\*ERP/EIRP Measurement is part of the accreditation scope

## 1 Administrative Data

### Testing Laboratory

Company Name:	7layers GmbH
Address	Borsigstr. 11 40880 Ratingen Germany
DAkKS ISO/IEC 17025 accreditation	D-PL-12140-01-00
FCC accreditation	Designation Number: DE0015 Test Firm Registration #: 929146
ISED accreditation	CAB identifier: DE0007 Test Firm Registration #: 3699A
DAkKS ISO/IEC 17025 accreditation	D-PL-12140-01-00, D-PL-12140-01-01
Responsible for Accreditation Scope:	Dipl.-Ing. Bernhard Retka Dipl.-Ing. Robert Machulec Dipl.-Ing. Andreas Petz Dipl.-Ing. Marco Kullik
Report Template Version:	2016-08-30

### Project Data

Responsible for assessment and report:	Mr. Andreas Tübel
Date of Report:	2019-03-25

### Applicant Data

Company Name:	Gemalto M2M GmbH
Address:	Siemensdamm 50 13629 Berlin Germany
Contact Person:	Mr. Axel Heike

### Manufacturer Data

Company Name:	please see applicant data
Address:	please see applicant data

## 2 Test object Data

### General EUT Description

<b>Equipment under Test</b>	2G/3G/4G Data and Voice radio module
<b>Type Designation:</b>	ALAS66A-US
<b>Kind of Device:</b>	2G/3G/4G Data and Voice radio module
<b>GPRS Multi-slot class</b>	12
<b>LTE CAT</b>	16
<b>FCC ID:</b>	QIPALAS66A-US
<b>IC ID:</b>	7830A-ALAS66AUS

### General product description:

The EUT is Cellular radio module supporting 2G/3G/4G Data and Voice.

### EUT Main components

#### Type, S/N, Short Descriptions etc. used in this Test Report

Short Description	Equipment under Test	Type Designation	Serial No.	HW Status	SW Status
EUT A (Code: DE1034040am01)	LTE Module	ALAS66A-US	004401082104247	Rev. 2.2	Rev. 00.192
Remark: EUT A is equipped with a temporary antenna connector. The Module is not sold with a predefined antenna.					

**NOTE: The short description is used to simplify the identification of the EUT in this test report.**

### Ancillary Equipment

For the purposes of this test report, ancillary equipment is defined as equipment which is used in conjunction with the EUT to provide operational and control features to the EUT. It is necessary to configure the system in a typical fashion, as a customer would normally use it. But nevertheless Ancillary Equipment can influence the test results.

Short Description	Equipment under Test	Type Designation	HW Status	SW Status	Serial no.	FCC ID
N/A						-

### Auxiliary Equipment

For the purposes of this test report, auxiliary equipment is defined as equipment which is used temporarily to enable operational and control features especially used for the tests of the EUT which is not used during normal operation or equipment that is used during the tests in combination with the EUT but is not subject of this test report. It is necessary to configure the system in a typical fashion, as a customer would normally use it. But nevertheless Auxiliary Equipment can influence the test results.

Short Description	Equipment under Test	Type Designation	Serial no.	HW Status	SW Status	FCC ID
N/A						-

### 3 Evaluation Results

#### Maximum ERP / EIRP

Standard	Frequency Band
FCC 47 CFR §22.913 IC RSS-132, Issue 3	GSM 850, UMTS FDDV, LTE eFDD5
FCC 47 CFR §24.232 IC RSS-133 Issue 6	GSM 1900, UMTS FDD II, LTE eFDD2,
FCC 47 CFR §27.50(d) RSS-139, Issue 2 / SRSP-513	UMTS FDD IV, LTE eFDD4, LTE eFDD7, LTE eFDD12, LTE eFDD13, LTE eFDD66, LTE CA_7C

#### 3.1.1 Test Limits

For the 850MHz band, FCC §22.913 states that the maximum ERP of this device shall not exceed 7 Watts. IC SRSP-503 Issue 7, states that this device shall not exceed a maximum EIRP of 11.5 Watts  
For the purposes of this test report, the 7 Watt ERP limit stipulated in FCC §22.913 has been converted to an equivalent EIRP value of 11.5 Watts.

For all other limits, refer to the values stipulated in the corresponding tables.

#### 3.1.2 Test Protocol

Band	Mode	Duty Cycle (%)	Frequency (MHZ)	Maximum Conducted output power (dBm)	Maximum Conducted output power (mW)	Freq of highest power (MHz)	FCC / IC EIRP limit (mW)	Maximum antenna gain to meet EIRP Limit (dBi)
850	GSM	50.0%	824.24 - 848.8	33.97	2494.5947	824.24	11484	6.6
1900	GSM	50.0%	1850.2 - 1909.8	31.03	1267.6519	1880.00	2000	2.0
FDD 2	UMTS	100.0%	1850 - 1907.6	25.47	352.37087	1908.83	2000	7.5
FDD 4	UMTS	100.0%	1710 - 1752.6	25.27	336.51157	1734.09	1000	4.7
FDD 5	UMTS	100.0%	824 - 846.6	25.51	355.63132	848.09	11484	15.1
eFDD 2	LTE	100.0%	1850-1910	23.93	247.17241	1907.67	2000	9.1
eFDD 4	LTE	100.0%	1710-1755	23.49	223.35722	1732.67	1000	6.5
eFDD 5	LTE	100.0%	824 - 849	23.7	234.42288	836.69	11484	16.9
CA_5A-7A Pcc	LTE_CA	100.0%	824 - 849	22.6	181.97009	824.00	11484	18.0
CA_5A-7A Scc	LTE_CA	100.0%	2500-2570	22.6	181.97009	2500.00	1000	7.4
eFDD 7	LTE	100.0%	2500-2570	23.46	221.81964	2505.10	1000	6.5
CA_7C	LTE_CA	100.0%	2500-2570	25.7	371.53523	2500.00	1000	4.3
eFDD13	LTE	100.0%	777-787	23.89	244.90632	779.71	3000	10.9
eFDD 12	LTE	100.0%	699 - 716	23.9	245.47089	707.71	3000	10.9
eFDD66	LTE	100.0%	1710 - 1780	23.58	228.03421	1745.51	1000	6.4

### 3.1.3 Conclusion

Band	Max gain to be used to comply with EIRP Limits	Max gain to be used to comply with FCC MPE Limits	Max gain to be used to comply with IC MPE Limits	Maximum gain to be compliant with all limits
850	6.6	3.4	0.1	0.1
1900	2.0	6.0	2.5	2.0
FDD 2	7.5	11.0	7.5	7.5
FDD 4	4.7	11.0	7.3	4.7
FDD 5	15.1	8.4	5.1	5.1
eFDD 2	9.1	12.0	8.5	8.5
eFDD 4	6.5	12.0	8.3	6.5
eFDD 5	16.9	9.4	6.1	6.1
CA_5A-7A Pcc	18.0	8.7	5.4	5.4
CA_5A-7A Scc	7.4	11.8	8.5	7.4
eFDD 7	6.5	14.4	11.8	6.5
CA_7C	4.3	11.3	8.7	4.3
eFDD13	10.9	9.2	5.9	5.9
eFDD12	10.9	8.7	5.6	5.6
eFDD66	6.4	12.6	8.3	6.4

All gains in (dBi)

RF Exposure Evaluation for Module

Standards
OET Bulletin 65 Edition 97-01 August 1997
FCC 47 CFR §1.1307
FCC 47 CFR §1.1310
RSS-102 Issue 5 – March 2015

3.1.4 Test limits

As specified in Table 1B of 47 CFR 1.1310 – Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure.

Frequency range (MHz)	Power density (mW/cm <sup>2</sup> )
300 – 1,500	f/1500
1,500 – 100,000	1.0

Limits specified per RSS-102, Issue 5.

Frequency range (MHz)	Power density (W/m <sup>2</sup> )	Power density (mW/cm <sup>2</sup> )
300 – 6000	0.02619 f <sup>0.6834</sup>	mW/cm <sup>2</sup> = W/m <sup>2</sup> * 0.1

Equation OET bulletin 65, page 18, edition 97-01: 
$$S = \frac{PG}{4\pi R^2} = \frac{EIRP}{4\pi R^2}$$

Where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna



### 3.1.5 Test Protocol

Maximum antenna gain to comply with MPE limits for FCC									
Band	Mode	Duty Cycle	Frequency (MHZ)	Maximum Conducted output power (dBm)	Maximum Conducted output power (mW)	Equivalent conducted output power (mW)	MPE Limit (mW/cm <sup>2</sup> )	Maximum antenna gain to meet MPE Limit (dBi)	Separation distance (cm)
850	GSM	50%	836.2	34.0	2511.89	1256.03	0.5575	<b>3.4</b>	20
1900	GSM	50%	1850.2	34.0	2511.89	1256.03	1.0000	<b>6.0</b>	20
FDD 2	UMTS	100.0%	1850.0	26.0	398.11	398.11	1.0000	<b>11.0</b>	20
FDD 4	UMTS	100.0%	1710.0	26.0	398.11	398.11	1.0000	<b>11.0</b>	20
FDD 5	UMTS	100.0%	824.0	26.0	398.11	398.11	0.5493	<b>8.4</b>	20
eFDD 2	LTE	100.0%	1850.0	25.0	316.23	316.23	1.0000	<b>12.0</b>	20
eFDD 4	LTE	100.0%	1710.0	25.0	316.23	316.23	1.0000	<b>12.0</b>	20
eFDD 5	LTE	100.0%	824.0	25.0	316.23	316.23	0.5493	<b>9.4</b>	20
CA_5A-7A Pcc	LTE_CA	100.0%	824.0	25.7	181.97	181.97	0.5493	<b>11.8</b>	20
CA_5A-7A Scc	LTE_CA	100.0%	2500.0	25.7	181.97	181.97	1.0000	<b>14.4</b>	20
eFDD 7	LTE	100.0%	2500.0	25.0	316.23	316.23	1.0000	<b>12.0</b>	20
CA_7C	LTE_CA	100.0%	2500.0	25.7	371.54	371.54	1.0000	<b>11.3</b>	20
eFDD13	LTE	100.0%	777.0	25.0	316.23	316.23	0.5180	<b>9.2</b>	20
eFDD 12	LTE	100.0%	699.0	25.0	316.23	316.23	0.4660	<b>8.7</b>	20
eFDD66	LTE	100.0%	1710.0	25.0	316.23	316.23	1.1400	<b>12.6</b>	20

\* Conducted output power values bases on "Tune-up" information provided by manufacturer.

Maximum antenna gain to comply with MPE limits for Industry Canada									
Band	Mode	Duty Cycle	Frequency (MHZ)	Maximum Conducted output power (dBm)	Maximum Conducted output power (mW)	Equivalent conducted output power (mW)	MPE Limit (mW/cm <sup>2</sup> )	Maximum antenna gain to meet MPE Limit (dBi)	Separation distance (cm)
850	GSM	50%	836.2	34.0	2511.89	1256.03	0.2602	<b>0.1</b>	20
1900	GSM	50%	1850.2	34.0	2511.89	1256.03	0.4477	<b>2.5</b>	20
FDD 2	UMTS	100%	1850.0	26.0	398.11	398.11	0.4476	<b>7.5</b>	20
FDD 4	UMTS	100%	1710.0	26.0	398.11	398.11	0.4242	<b>7.3</b>	20
FDD 5	UMTS	100%	824.0	26.0	398.11	398.11	0.2576	<b>5.1</b>	20
eFDD 2	LTE	100%	1850.0	25.0	316.23	316.23	0.4476	<b>8.5</b>	20
eFDD 4	LTE	100%	1710.0	25.0	316.23	316.23	0.4242	<b>8.3</b>	20
eFDD 5	LTE	100%	824.0	25.0	316.23	316.23	0.2576	<b>6.1</b>	20
CA_5A-7A Pcc	LTE_CA	100.0%	824.0	22.6	181.97	181.97	0.2576	<b>8.5</b>	20
CA_5A-7A Scc	LTE_CA	100.0%	2500.0	22.6	181.97	181.97	0.5499	<b>11.8</b>	20
eFDD 7	LTE	100%	2500.0	25.0	316.23	316.23	0.5499	<b>9.4</b>	20
CA_7C	LTE_CA	100%	2500.0	25.7	371.54	371.54	0.5499	<b>8.7</b>	20
eFDD 13	LTE	100%	777.0	25.0	316.23	316.23	0.2474	<b>5.9</b>	20
eFDD 12	LTE	100%	699.0	25.0	316.23	316.23	0.2302	<b>5.6</b>	20
eFDD 66	LTE	100%	1710.0	25.0	316.23	316.23	0.4242	<b>8.3</b>	20

\* Conducted output power values bases on "Tune-up" information provided by manufacturer.

### 3.1.6 Conclusion

Band	Max gain for FCC MPE Limits	Max gain for Industry Canada MPE Limits	Maximum gain to be compliant with all limits
850	3.4	0.1	0.1
1900	6.0	2.5	2.5
FDD 2	11.0	7.5	7.5
FDD 4	11.0	7.3	7.3
FDD 5	8.4	5.1	5.1
eFDD 2	12.0	8.5	8.5
eFDD 4	12.0	8.3	8.3
eFDD 5	9.4	6.1	6.1
CA_5A-7A Pcc	11.8	8.5	8.5
CA_5A-7A Scc	14.4	11.8	11.8
eFDD 7	12.0	9.4	9.4
CA_7C	11.3	8.7	8.7
eFDD 13	9.2	5.9	5.9
eFDD 12	8.7	5.6	5.6
eFDD 66	12.6	8.3	8.3

All gains in (dBi)

RF Exposure Evaluation for Carrier Aggregation

3.1.7 Intra-Band LTE CA\_7C

Antenna Gains	Band	Frequency (MHZ)	Maximum Conducted output power (dBm)	Maximum Conducted output power (mW)	Power Density (mW/cm <sup>2</sup> )	IC MPE Limit (mW/cm <sup>2</sup> )	FCC MPE Limit (mW/cm <sup>2</sup> )	Separation distance (cm)	FCC Power Density (mW/cm <sup>2</sup> ) / Limit	IC Power Density (mW/cm <sup>2</sup> ) / Limit
6.5	eFDD 7	2500	25.7	371.54	0.33	0.5499	1.0000	20	0.600	0.33
6.5	eFDD 7	2510	25.7	371.54	0.33	0.5499	1.0000	20	0.600	0.33

3.1.8 Inter-Band LTE CA\_5A-7A

Antenna Gains	Band	Frequency (MHZ)	Maximum Conducted output power (dBm)	Maximum Conducted output power (mW)	Power Density (mW/cm <sup>2</sup> )	IC MPE Limit (mW/cm <sup>2</sup> )	FCC MPE Limit (mW/cm <sup>2</sup> )	Separation distance (cm)	FCC Power Density (mW/cm <sup>2</sup> ) / Limit	IC Power Density (mW/cm <sup>2</sup> ) / Limit
6.1	eFDD 5	836.5	21.53	142.23	0.115	0.2602	0.5577	20	0.206	0.442
6.5	eFDD 7	2510.0	21.05	127.35	0.113	0.5514	1.0000	20	0.113	0.205

3.1.9 Conclusion

Band	FCC Power Density (mW/cm <sup>2</sup> ) / Limit (eFDD5+eFDD7) < 1	IC Power Density (mW/cm <sup>2</sup> ) / Limit (eFDD5+eFDD7) < 1
CA_5A-7A	0.206+0.113=0.319 PASS	0.442+0.205=0.647 PASS