










5.8 FIELD STRENGTH OF SPURIOUS RADIATION

Test Requirement: **LTE Band 2:** FCC 47 CFR Part 24.238(a), RSS-133 Issue 6, Section 6.5
LTE Band 4 & LTE Band 66: FCC 47 CFR Part 27.53(h), RSS-139 Issue 3, Section 6.6
LTE Band 12: FCC 47 CFR Part 27.53(g), RSS-130 Issue 2, Section 4.7
LTE Band 13: FCC 47 CFR Part 27.53, RSS-130 Issue 2, Section 4.7

Test Method: ANSI C63.26-2015 & KDB 971168 D01v03r01

Receiver Setup:

Frequency	Detector	RBW	VBW	Remark
0.009 MHz-30 MHz	Peak	10 kHz	30 KHz	Peak
30 MHz-1 GHz	Quasi-peak	100 kHz	300 KHz	Peak
Above 1 GHz	Peak	1 MHz	3 MHz	Peak

Limits:

FCC 47 CFR Part 24.238(a), 27.53(h)(1), 27.53(g), 27.53(c)(2):

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13 dBm.

FCC 47 CFR Part 27.53:

(c) The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

(f) Emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals. ($-70 \text{ dBW/MHz} = -40 \text{ dBm/MHz}$).

RSS-133 Issue 6, Section 6.6, RSS-139 Issue 3, Section 6.5, RSS-130 Issue 2, Section 4.7:

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13 dBm.

Test Setup: Refer to section 4.2.1 for details.

Test Procedures: KDB 971168 D01v03r01 Section 7

Equipment Used: Refer to section 3 for details.

Test Result: Pass

The measurement data as follows:

5.8.1 LTE Band 2

LTE Band 2_ 20 MHz_ QPSK_ Below 1G							
No.	Frequency	SA Reading	Correction factor	EIRP Result	Limit	Margin	Ant. Pol.
	(MHz)	(dBm)	(dB/m)	(dBm)	(dBm)	(dB)	
Lowest Channel							
1	54.135	-71.03	-5.52	-76.55	-13.00	-63.55	Horizontal
2	104.798	-76.10	-3.37	-79.47	-13.00	-66.47	Horizontal
3	952.000	-82.53	14.42	-68.11	-13.00	-55.11	Horizontal
4	52.634	-70.77	-5.57	-76.34	-13.00	-63.34	Vertical
5	121.462	-69.43	-3.65	-73.08	-13.00	-60.08	Vertical
6	938.714	-80.05	12.99	-67.06	-13.00	-54.06	Vertical
Middle Channel							
1	54.135	-70.25	-5.52	-75.77	-13.00	-62.77	Horizontal
2	101.893	-75.24	-3.33	-78.57	-13.00	-65.57	Horizontal
3	938.714	-82.27	14.08	-68.19	-13.00	-55.19	Horizontal
4	35.762	-77.39	0.35	-77.04	-13.00	-64.04	Vertical
5	123.181	-71.35	-3.64	-74.99	-13.00	-61.99	Vertical
6	925.613	-81.21	13.01	-68.20	-13.00	-55.20	Vertical
Highest Channel							
1	51.176	-71.12	-5.29	-76.41	-13.00	-63.41	Horizontal
2	129.392	-75.51	-3.59	-79.10	-13.00	-66.10	Horizontal
3	919.132	-81.35	13.48	-67.87	-13.00	-54.87	Horizontal
4	50.461	-72.05	-5.61	-77.66	-13.00	-64.66	Vertical
5	122.319	-70.69	-3.65	-74.34	-13.00	-61.34	Vertical
6	906.304	-81.19	12.83	-68.36	-13.00	-55.36	Vertical

LTE Band 2_ 20 MHz_ QPSK_ Above 1G							
No.	Frequency	SA Reading	Correction factor	EIRP Result	Limit	Margin	Ant. Pol.
	(MHz)	(dBm)	(dB/m)	(dBm)	(dBm)	(dB)	
Lowest Channel							
1	3720.000	-64.74	6.82	-57.92	-13.00	-44.92	Horizontal
2	5580.000	-65.75	10.86	-54.89	-13.00	-41.89	Horizontal
3	3720.000	-64.44	6.81	-57.63	-13.00	-44.63	Vertical
4	5580.000	-66.19	11.34	-54.85	-13.00	-41.85	Vertical
Middle Channel							
1	3760.000	-64.81	6.93	-57.88	-13.00	-44.88	Horizontal
2	5640.000	-65.69	10.84	-54.85	-13.00	-41.85	Horizontal
3	3760.000	-64.89	6.93	-57.96	-13.00	-44.96	Vertical
4	5640.000	-66.23	11.32	-54.91	-13.00	-41.91	Vertical
Highest Channel							
1	3800.000	-64.40	7.03	-57.37	-13.00	-44.37	Horizontal
2	5700.000	-65.94	10.83	-55.11	-13.00	-42.11	Horizontal
3	3800.000	-64.08	7.05	-57.03	-13.00	-44.03	Vertical
4	5700.000	-65.56	11.29	-54.27	-13.00	-41.27	Vertical

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCC4G-V1.1

5.8.2 LTE Band 4

LTE Band 4_ 20 MHz_ QPSK_ Below 1G							
No.	Frequency	SA Reading	Correction factor	EIRP Result	Limit	Margin	Ant. Pol.
	(MHz)	(dBm)	(dB/m)	(dBm)	(dBm)	(dB)	
Lowest Channel							
1	54.135	-70.50	-5.52	-76.02	-13.00	-63.02	Horizontal
2	104.064	-76.21	-3.36	-79.57	-13.00	-66.57	Horizontal
3	815.635	-80.56	11.86	-68.70	-13.00	-55.70	Horizontal
4	53.379	-72.20	-5.56	-77.76	-13.00	-64.76	Vertical
5	123.181	-70.63	-3.64	-74.27	-13.00	-61.27	Vertical
6	887.398	-80.77	12.40	-68.37	-13.00	-55.37	Vertical
Middle Channel							
1	52.634	-71.81	-5.41	-77.22	-13.00	-64.22	Horizontal
2	101.893	-76.09	-3.33	-79.42	-13.00	-66.42	Horizontal
3	952.000	-82.86	14.42	-68.44	-13.00	-55.44	Horizontal
4	52.634	-70.55	-5.57	-76.12	-13.00	-63.12	Vertical
5	120.612	-71.21	-3.66	-74.87	-13.00	-61.87	Vertical
6	932.141	-82.10	13.00	-69.10	-13.00	-56.10	Vertical
Highest Channel							
1	55.288	-70.66	-5.60	-76.26	-13.00	-63.26	Horizontal
2	101.893	-76.63	-3.33	-79.96	-13.00	-66.96	Horizontal
3	912.695	-81.02	13.32	-67.70	-13.00	-54.70	Horizontal
4	53.379	-72.26	-5.56	-77.82	-13.00	-64.82	Vertical
5	121.462	-71.83	-3.65	-75.48	-13.00	-62.48	Vertical
6	952.000	-81.51	12.97	-68.54	-13.00	-55.54	Vertical

LTE Band 4_ 20 MHz_ QPSK _ Above 1G							
No.	Frequency	SA Reading	Correction factor	EIRP Result	Limit	Margin	Ant. Pol.
	(MHz)	(dBm)	(dB/m)	(dBm)	(dBm)	(dB)	
Lowest Channel							
1	3440.000	-63.14	5.94	-57.20	-13.00	-44.20	Horizontal
2	5160.000	-65.11	9.17	-55.94	-13.00	-42.94	Horizontal
3	3440.000	-65.37	5.75	-59.62	-13.00	-46.62	Vertical
4	5160.000	-65.49	9.53	-55.96	-13.00	-42.96	Vertical
Middle Channel							
1	3465.000	-65.61	6.02	-59.59	-13.00	-46.59	Horizontal
2	5197.500	-65.08	9.31	-55.77	-13.00	-42.77	Horizontal
3	3465.000	-65.10	5.87	-59.23	-13.00	-46.23	Vertical
4	5197.500	-65.54	9.69	-55.85	-13.00	-42.85	Vertical
Highest Channel							
1	3490.000	-64.32	6.11	-58.21	-13.00	-45.21	Horizontal
2	5235.000	-65.54	9.50	-56.04	-13.00	-43.04	Horizontal
3	3490.000	-64.54	5.99	-58.55	-13.00	-45.55	Vertical
4	5235.000	-65.21	9.89	-55.32	-13.00	-42.32	Vertical

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCC4G-V1.1

5.8.3 LTE Band 12

LTE Band 12_ 10 MHz_ QPSK_ Below 1G							
No.	Frequency	SA Reading	Correction factor	EIRP Result	Limit	Margin	Ant. Pol.
	(MHz)	(dBm)	(dB/m)	(dBm)	(dBm)	(dB)	
Lowest Channel							
1	31.513	-90.68	31.95	-58.73	-13.00	-45.73	Horizontal
2	373.886	-87.15	32.92	-54.23	-13.00	-41.23	Horizontal
3	986.044	-85.64	42.90	-42.74	-13.00	-29.74	Horizontal
4	31.959	-90.78	31.77	-59.01	-13.00	-46.01	Vertical
5	512.948	-88.84	37.02	-51.82	-13.00	-38.82	Vertical
6	925.613	-86.84	42.10	-44.74	-13.00	-31.74	Vertical
Middle Channel							
1	31.513	-90.50	31.95	-58.55	-13.00	-45.55	Horizontal
2	315.860	-87.07	31.48	-55.59	-13.00	-42.59	Horizontal
3	952.000	-86.78	43.44	-43.34	-13.00	-30.34	Horizontal
4	31.292	-90.63	32.19	-58.44	-13.00	-45.44	Vertical
5	190.441	-87.50	26.97	-60.53	-13.00	-47.53	Vertical
6	899.958	-86.40	41.90	-44.50	-13.00	-31.50	Vertical
Highest Channel							
1	31.513	-90.00	31.95	-58.05	-13.00	-45.05	Horizontal
2	106.281	-87.42	25.38	-62.04	-13.00	-49.04	Horizontal
3	958.714	-87.07	43.29	-43.78	-13.00	-30.78	Horizontal
4	31.292	-90.93	32.19	-58.74	-13.00	-45.74	Vertical
5	181.300	-87.19	27.18	-60.01	-13.00	-47.01	Vertical
6	938.714	-87.12	42.04	-45.08	-13.00	-32.08	Vertical

LTE Band 12_ 10 MHz_ QPSK_ Above 1G							
No.	Frequency	SA Reading	Correction factor	EIRP Result	Limit	Margin	Ant. Pol.
	(MHz)	(dBm)	(dB/m)	(dBm)	(dBm)	(dB)	
Lowest Channel							
1	1408.000	-64.24	-0.43	-64.67	-13.00	-51.67	Horizontal
2	2112.000	-65.68	2.00	-63.68	-13.00	-50.68	Horizontal
3	1408.000	-63.75	-1.20	-64.95	-13.00	-51.95	Vertical
4	2112.000	-64.89	1.52	-63.37	-13.00	-50.37	Vertical
Middle Channel							
1	1415.000	-63.53	-0.44	-63.97	-13.00	-50.97	Horizontal
2	2122.500	-64.08	2.00	-62.08	-13.00	-49.08	Horizontal
3	1415.000	-63.59	-1.22	-64.81	-13.00	-51.81	Vertical
4	2122.500	-64.34	1.53	-62.81	-13.00	-49.81	Vertical
Highest Channel							
1	1422.000	-63.31	-0.45	-63.76	-13.00	-50.76	Horizontal
2	2133.000	-64.51	2.01	-62.50	-13.00	-49.50	Horizontal
3	1422.000	-65.45	-1.24	-66.69	-13.00	-53.69	Vertical
4	2133.000	-64.70	1.53	-63.17	-13.00	-50.17	Vertical

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCC4G-V1.1

5.8.4 LTE Band 13

LTE Band 13_5 MHz_QPSK_Below 1G							
No.	Frequency	SA Reading	Correction factor	EIRP Result	Limit	Margin	Ant. Pol.
	(MHz)	(dBm)	(dB/m)	(dBm)	(dBm)	(dB)	
Lowest Channel							
1	31.959	-90.58	31.72	-58.86	-13.00	-45.86	Horizontal
2	104.798	-87.68	25.41	-62.27	-13.00	-49.27	Horizontal
3	979.139	-86.97	42.89	-44.08	-13.00	-31.08	Horizontal
4	31.959	-90.17	31.77	-58.40	-13.00	-45.40	Vertical
5	554.171	-87.46	37.82	-49.64	-13.00	-36.64	Vertical
6	952.000	-86.31	41.99	-44.32	-13.00	-31.32	Vertical
Middle Channel							
1	32.870	-90.00	31.26	-58.74	-13.00	-45.74	Horizontal
2	418.378	-87.95	34.85	-53.10	-13.00	-40.10	Horizontal
3	925.613	-86.98	42.72	-44.26	-13.00	-31.26	Horizontal
4	33.570	-90.81	30.74	-60.07	-13.00	-47.07	Vertical
5	158.640	-87.11	26.49	-60.62	-13.00	-47.62	Vertical
6	972.283	-85.85	41.99	-43.86	-13.00	-30.86	Vertical
Highest Channel							
1	31.959	-91.28	31.72	-59.56	-13.00	-46.56	Horizontal
2	346.074	-88.24	32.86	-55.38	-13.00	-42.38	Horizontal
3	945.334	-86.67	43.34	-43.33	-13.00	-30.33	Horizontal
4	30.212	-91.25	32.88	-58.37	-13.00	-45.37	Vertical
5	280.294	-87.32	30.50	-56.82	-13.00	-43.82	Vertical
6	965.474	-87.34	41.99	-45.35	-13.00	-32.35	Vertical

LTE Band 13_5 MHz_ QPSK _ Above 1G							
No.	Frequency	SA Reading	Correction factor	EIRP Result	Limit	Margin	Ant. Pol.
	(MHz)	(dBm)	(dB/m)	(dBm)	(dBm)	(dB)	
Lowest Channel							
1	1559.000	-64.61	-0.43	-65.04	-13.00	-52.04	Horizontal
2	2338.500	-64.62	2.39	-62.23	-13.00	-49.23	Horizontal
3	1559.000	-64.17	-1.28	-65.45	-13.00	-52.45	Vertical
4	2338.500	-64.30	1.96	-62.34	-13.00	-49.34	Vertical
Middle Channel							
1	1564.000	-64.25	-0.41	-64.66	-13.00	-51.66	Horizontal
2	2346.000	-64.19	2.41	-61.78	-13.00	-48.78	Horizontal
3	1564.000	-64.29	-1.26	-65.55	-13.00	-52.55	Vertical
4	2346.000	-64.54	1.98	-62.56	-13.00	-49.56	Vertical
Highest Channel							
1	1569.000	-65.48	-0.39	-65.87	-13.00	-52.87	Horizontal
2	2353.500	-63.84	2.43	-61.41	-13.00	-48.41	Horizontal
3	1569.000	-64.72	-1.24	-65.96	-13.00	-52.96	Vertical
4	2353.500	-64.38	2.01	-62.37	-13.00	-49.37	Vertical

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCC4G-V1.1

5.8.5 LTE Band 66

LTE Band 66_ 20 MHz_ QPSK_ Below 1G							
No.	Frequency	SA Reading	Correction factor	EIRP Result	Limit	Margin	Ant. Pol.
	(MHz)	(dBm)	(dB/m)	(dBm)	(dBm)	(dB)	
Lowest Channel							
1	54.135	-71.04	-5.52	-76.56	-13.00	-63.56	Horizontal
2	101.893	-76.40	-3.33	-79.73	-13.00	-66.73	Horizontal
3	965.474	-82.31	14.13	-68.18	-13.00	-55.18	Horizontal
4	53.006	-71.43	-5.56	-76.99	-13.00	-63.99	Vertical
5	122.319	-71.35	-3.65	-75.00	-13.00	-62.00	Vertical
6	965.474	-82.26	13.00	-69.26	-13.00	-56.26	Vertical
Middle Channel							
1	54.135	-70.51	-5.52	-76.03	-13.00	-63.03	Horizontal
2	102.612	-77.57	-3.34	-80.91	-13.00	-67.91	Horizontal
3	952.000	-82.30	14.42	-67.88	-13.00	-54.88	Horizontal
4	54.135	-70.73	-5.55	-76.28	-13.00	-63.28	Vertical
5	122.319	-71.55	-3.65	-75.20	-13.00	-62.20	Vertical
6	899.958	-81.44	12.75	-68.69	-13.00	-55.69	Vertical
Highest Channel							
1	54.135	-70.08	-5.52	-75.60	-13.00	-62.60	Horizontal
2	104.798	-77.51	-3.37	-80.88	-13.00	-67.88	Horizontal
3	958.714	-81.60	14.29	-67.31	-13.00	-54.31	Horizontal
4	53.006	-71.09	-5.56	-76.65	-13.00	-63.65	Vertical
5	121.462	-71.66	-3.65	-75.31	-13.00	-62.31	Vertical
6	938.714	-81.76	12.99	-68.77	-13.00	-55.77	Vertical

LTE Band 66_ 20 MHz_ QPSK_ Above 1G							
No.	Frequency	SA Reading	Correction factor	EIRP Result	Limit	Margin	Ant. Pol.
	(MHz)	(dBm)	(dB/m)	(dBm)	(dBm)	(dB)	
Lowest Channel							
1	3440.000	-62.80	5.94	-56.86	-13.00	-43.86	Horizontal
2	5160.000	-64.36	9.17	-55.19	-13.00	-42.19	Horizontal
3	3440.000	-63.08	5.75	-57.33	-13.00	-44.33	Vertical
4	5160.000	-64.62	9.53	-55.09	-13.00	-42.09	Vertical
Middle Channel							
1	3490.000	-63.23	6.11	-57.12	-13.00	-44.12	Horizontal
2	5235.000	-64.37	9.50	-54.87	-13.00	-41.87	Horizontal
3	3490.000	-64.00	5.99	-58.01	-13.00	-45.01	Vertical
4	5235.000	-65.24	9.89	-55.35	-13.00	-42.35	Vertical
Highest Channel							
1	3540.000	-66.41	6.27	-60.14	-13.00	-47.14	Horizontal
2	5310.000	-67.56	9.89	-57.67	-13.00	-44.67	Horizontal
3	3540.000	-66.04	6.19	-59.85	-13.00	-46.85	Vertical
4	5310.000	-67.57	10.31	-57.26	-13.00	-44.26	Vertical

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCC4G-V1.1

Remark:

1. Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result – Limit



5.9 FREQUENCY STABILITY

Test Requirement: FCC 47 CFR Part 2.1055 &
FCC 47 CFR Part 24.235 &
FCC 47 CFR Part 27.54,
RSS-133 Issue 6, Section 6.3 & RSS-139 Issue 3, Section 6.4
RSS-130 Issue 2, Section 4.5

Test Method: ANSI C63.26-2015 & KDB 971168 D01v03r01

Limits:

FCC 47 CFR Part 24.235, FCC 47 CFR Part 27.54

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

RSS-133 Issue 6, Section 6.3:

The carrier frequency shall not depart from the reference frequency, in excess of ± 2.5 ppm for mobile stations and ± 1.0 ppm for base stations.

RSS-139 Issue 3, Section 6.4, RSS-130 Issue 2, Section 4.5:

The frequency stability shall be sufficient to ensure that the occupied bandwidth stays within the operating frequency block when tested to the temperature and supply voltage variations specified in RSS-Gen.

Test Setup: Refer to section 4.2.2 for details.

Test Procedures:

- 1) Use CMW 500 or CMU 200 with Frequency Error measurement capability.
 - a) Temp. = -30° to $+50^{\circ}\text{C}$
 - b) Voltage = low voltage, 3.2 Vdc, Normal, 3.8Vdc and High voltage, 4.5 Vdc.

2) Frequency Stability vs Temperature:

The EUT is placed inside a temperature chamber. The temperature is set to 20°C and allowed to stabilize. After sufficient soak time, the transmitting frequency error is measured. The temperature is increased by 10 degrees, allowed to stabilize and soak, and then the measurement is repeated. This is repeated until $+50^{\circ}\text{C}$ is reached.

3) Frequency Stability vs Voltage:

The peak frequency error is recorded (worst-case).

Equipment Used: Refer to section 3 for details.

Test Result: Pass

5.9.1 LTE Band 2

Modulation	Channel/ Frequency	Voltage	Temperature	Deviation	Deviation	Limit	Pass/ Fail
	(MHz)	(Vdc)	(°C)	(Hz)	(ppm)	(ppm)	
LTE Band 2 / 20MHz / Full RB							
QPSK	18900 / 1880.0	VL	TN	-12	-0.0064	N/A	Pass
		VN		-10	-0.0053		Pass
		VH		-8	-0.0043		Pass
		VN	50	-13	-0.0069		Pass
			40	-16	-0.0085		Pass
			30	-6	-0.0032		Pass
			20	-8	-0.0043		Pass
			10	-12	-0.0064		Pass
			0	-14	-0.0074		Pass
			-10	-15	-0.0080		Pass
			-20	-10	-0.0053		Pass
			-30	-11	-0.0059		Pass

5.9.2 LTE Band 4

Modulation	Channel/ Frequency	Voltage	Temperature	Deviation	Deviation	Limit	Pass/ Fail
	(MHz)	(Vdc)	(°C)	(Hz)	(ppm)	(ppm)	
LTE Band 4 / 20MHz / Full RB							
QPSK	20175 / 1732.5	VL	TN	-13	-0.0075	N/A	Pass
		VN		-13	-0.0075		Pass
		VH		-11	-0.0063		Pass
		VN	50	-16	-0.0092		Pass
			40	-19	-0.0110		Pass
			30	-9	-0.0052		Pass
			20	-11	-0.0063		Pass
			10	-15	-0.0087		Pass
			0	-17	-0.0098		Pass
			-10	-18	-0.0104		Pass
			-20	-13	-0.0075		Pass
			-30	-14	-0.0081		Pass

5.9.3 LTE Band 12

Modulation	Channel/ Frequency	Voltage	Temperature	Deviation	Deviation	Limit	Result
	(MHz)	(Vdc)	(°C)	(Hz)	(ppm)	(ppm)	
LTE Band 12 / 10MHz / Full RB							
QPSK	23095 / 707.5	VL	TN	-7	-0.0099	N/A	Pass
		VN		-13	-0.0184		Pass
		VH		-12	-0.0170		Pass
		VN	50	-9	-0.0127		Pass
			40	-12	-0.0170		Pass
			30	-13	-0.0184		Pass
			20	-10	-0.0141		Pass
			10	-12	-0.0170		Pass
			0	-17	-0.0240		Pass
			-10	-16	-0.0226		Pass
			-20	-13	-0.0184		Pass
			-30	-17	-0.0240		Pass

5.9.4 LTE Band 13

Modulation	Channel/ Frequency (MHz)	Voltage (Vdc)	Temperature (°C)	Deviation (Hz)	Deviation (ppm)	Limit (ppm)	Result
LTE Band 13 / 10MHz / Full RB							
QPSK	23230 / 782	VL	TN	-5	-0.0064	N/A	Pass
		VN		-4	-0.0051		Pass
		VH		-8	-0.0102		Pass
		VN	50	-12	-0.0153		Pass
			40	-9	-0.0115		Pass
			30	-11	-0.0141		Pass
			20	-10	-0.0128		Pass
			10	-6	-0.0077		Pass
			0	-8	-0.0102		Pass
			-10	-13	-0.0166		Pass
			-20	-12	-0.0153		Pass
			-30	-10	-0.0128		Pass

5.9.5 LTE Band 66

Modulation	Channel/ Frequency (MHz)	Voltage (Vdc)	Temperature (°C)	Deviation (Hz)	Deviation (ppm)	Limit (ppm)	Result
LTE Band 66 / 20MHz / Full RB							
QPSK	132322 / 1745	VL	TN	-14	-0.0080	N/A	Pass
		VN		-7	-0.0040		Pass
		VH		-8	-0.0046		Pass
		VN	50	-11	-0.0063		Pass
			40	-13	-0.0074		Pass
			30	-9	-0.0052		Pass
			20	-4	-0.0023		Pass
			10	-7	-0.0040		Pass
			0	-8	-0.0046		Pass
			-10	-12	-0.0069		Pass
			-20	-14	-0.0080		Pass
			-30	-7	-0.0040		Pass

APPENDIX 1 PHOTOS OF TEST SETUP

See test photos attached in Appendix 1 for the actual connections between Product and support equipment.

APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal photos.

*** End of Report ***

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.
