



# TEST REPORT

No. I15N00174-2G

for

**Huawei Technologies Co., Ltd.**

**Smart Phone**

**Model Name: HUAWEI ALE-L23, ALE-L23**

**FCC ID: QISALE-L23**

with

**Hardware Version: HL3ALICEM**

**Software Version: ALE-L23 V100R001C900B045**

**Issued Date: 2015-03-23**

**Test Laboratory:**

*FCC 2.948 Listed: No.342690*

**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

**Test Laboratory:**

CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT

No.52, HuayuanNorth Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633, Fax:+86(0)10-62304633Email:cttl@chinattl.com, website:www.chinattl.com



## **REPORT HISTORY**

<b>Report Number</b>	<b>Revision</b>	<b>Description</b>	<b>Issue Date</b>
I15N00174-2G	Rev.0	1st edition	2015-03-23

## **CONTENTS**

<b>1. TEST LABORATORY .....</b>	<b>4</b>
<b>1.1. TESTING LOCATION .....</b>	<b>4</b>
<b>1.2. TESTING ENVIRONMENT .....</b>	<b>4</b>
<b>1.3. PROJECT DATA .....</b>	<b>4</b>
<b>1.4. SIGNATURE.....</b>	<b>4</b>
<b>2. CLIENT INFORMATION.....</b>	<b>5</b>
<b>2.1. APPLICANT INFORMATION.....</b>	<b>5</b>
<b>2.2. MANUFACTURER INFORMATION.....</b>	<b>5</b>
<b>3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) .....</b>	<b>6</b>
<b>3.1. ABOUT EUT .....</b>	<b>6</b>
<b>3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST .....</b>	<b>6</b>
<b>3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST .....</b>	<b>6</b>
<b>3.4. EUT SET-UPS .....</b>	<b>6</b>
<b>4. REFERENCE DOCUMENTS.....</b>	<b>7</b>
<b>4.1. REFERENCE DOCUMENTS FOR TESTING.....</b>	<b>7</b>
<b>5. LABORATORY ENVIRONMENT.....</b>	<b>8</b>
<b>6. SUMMARY OF TEST RESULTS .....</b>	<b>9</b>
<b>7. TEST EQUIPMENTS UTILIZED.....</b>	<b>10</b>
<b>ANNEX A: MEASUREMENT RESULTS.....</b>	<b>11</b>
<b>A.1 OUTPUT POWER.....</b>	<b>11</b>
<b>A.2 EMISSION LIMIT.....</b>	<b>17</b>
<b>A.3 FREQUENCY STABILITY .....</b>	<b>23</b>
<b>A.4 OCCUPIED BANDWIDTH.....</b>	<b>25</b>
<b>A.5 EMISSION BANDWIDTH.....</b>	<b>37</b>
<b>A.6 BAND EDGE COMPLIANCE.....</b>	<b>49</b>
<b>A.7 CONDUCTED SPURIOUS EMISSION .....</b>	<b>55</b>
<b>A.8 PEAK-TO-AVERAGE POWER RATIO .....</b>	<b>76</b>



## 1. Test Laboratory

### 1.1. Testing Location

#### 2. Address of Shenzhen:

Company Name: CTTL ShenZhen, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT  
Address: No. 12 Building, Shangsha Innovation and Technology Park, Futian District  
Postal Code: 518048  
Telephone: +86(0)755-33322000  
Fax: +86(0)755-33322001

#### 3. Address of Beijing:

Company Name: CTTL Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT  
Address: Building Shouxiang, No.51, Xueyuan Road, Haidian District, Beijing, China  
Postal Code: 100191  
Telephone: +86(0)10-62304633  
Fax: +86(0)10-62304633

### 3.1. Testing Environment

Normal Temperature: 15-35°C  
Relative Humidity: 20-75%

### 3.2. Project data

Testing Start Date: 2015-03-02  
Testing End Date: 2015-03-23

### 3.3. Signature

Lai Minghua

(Prepared this test report)

Shen Shaoming

(Reviewed this test report)

Ma Zhiguo

Deputy Director of the laboratory  
(Approved this test report)



#### **4. Client Information**

##### **4.1. Applicant Information**

Company Name: Huawei Technologies Co., Ltd.  
Address /Post: Administration Building, Headquarters of Huawei Technologies Co.,  
Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C  
City: ShenZhen  
Postal Code: 518129  
Country: China  
Telephone: +86 029-89282965

##### **4.2. Manufacturer Information**

Company Name: Huawei Technologies Co., Ltd.  
Address /Post: Administration Building, Headquarters of Huawei Technologies Co.,  
Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C  
City: ShenZhen  
Postal Code: 518129  
Country: China  
Telephone: +86 029-89282965

## 5. Equipment Under Test (EUT) and Ancillary Equipment (AE)

### 5.1. About EUT

Description	Smart Phone
Model Name	HUAWEI ALE-L23, ALE-L23
Marketing Name	/
FCC ID	QISALE-L23
Frequency	GSM850; PCS1900; WCDMA Band II; WCDMA Band IV; WCDMA Band V
Extreme vol. Limits	3.6VDC to 4.35VDC (nominal: 3.8VDC)
Extreme temp. Tolerance	-30°C to +50°C

### 5.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
N01	004401722529407	HL3ALICEM	ALE-L23 V100R001C900B045

\*EUT ID: is used to identify the test sample in the lab internally.

### 5.3. Internal Identification of AE used during the test

AE ID*	Description	SN
AE1	Battery	/

AE1

Model	HB3742A0EZC+
Capacity	2200mAh
Manufacturer	1.SCUD (FUJIAN) Electronics Co., Ltd. 2.Sunwoda Electronic Co., LTD.

\*AE ID: is used to identify the test sample in the lab internally.

### 5.4. EUT set-ups

EUT set-up No.	Combination of EUT and AE	Remarks
Set.1	EUT1+ AE1	Charging mode

## 6. Reference Documents

### 6.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

<b>Reference</b>	<b>Title</b>	<b>Version</b>
ANSI/TIA-603-D	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards	2010
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2003
KDB971168 D01	Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems	2011
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	10-1-13 Edition
FCC Part 22	PUBLIC MOBILE SERVICES	10-1-13 Edition
FCC Part 2	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations	10-1-2010 Edition

## 7. LABORATORY ENVIRONMENT

**Semi-anechoic chamber** (11.20 meters×6.10meters×5.60meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2MΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	< ±3.5 dB, 3 m distance, from 30 to 1000 MHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz

**Control room** did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. =20 %, Max. = 80 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2MΩ
Ground system resistance	< 0.5 Ω

**Conducted chamber** did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. =35 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2MΩ
Ground system resistance	< 0.5 Ω

**Fully-anechoic chamber** (11.20 meters×6.10 meters×6.60 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2MΩ
Ground system resistance	< 0.5 Ω
Voltage Standing Wave Ratio (VSWR)	≤ 6 dB, from 1 to 6 GHz, 3 m distance



## 8. SUMMARY OF TEST RESULTS

Abbreviations used in this clause:	
P	Pass
NA	Not applicable
F	Fail

Items	List	Clause in FCC rules	Verdict
1	Output Power	22.913(a)/24.232(b)	P
2	Emission Limit	2.1051/22.917/24.238	P
3	Conducted Emission	15.107/15.207	P
4	Frequency Stability	2.1055/24.235	P
5	Occupied Bandwidth	2.1049(h)(i)	P
6	Emission Bandwidth	22.917(b)/24.238(b)	P
7	Band Edge Compliance	22.917(b)/24.238(b)	P
8	Conducted Spurious Emission	2.1057/22.917/24.238	P
9	PEAK-TO-AVERAGE POWER RATIO	KDB971168	P

Note:Items of conducted are tested in the address of Shenzhen; items of radiated are tested in the address of Beijing.

## 9. Test Equipments Utilized

NO.	Description	TYPE	SERIES NUMBER	MANUFACTURE	CAL DUE DATE
1	Test Receiver	ESU26	100235	R&S	2016.03.02
2	Universal Radio Communication Tester	E5515C	MY48361083	Agilent	2016.02.27
3	Spectrum Analyzer	E4440A	MY48250642	Agilent	2016.03.02
4	Signal Generator	N5183A	MY49060052	Agilent	2016.03.02
5	Universal Radio Communication Tester	CMU200	Rohde&Schwarz	114828	2016.01.03
6	Spectrum Analyzer	FSU	Rohde&Schwarz	200679	2016.01.03
7	Temperature Chamber	SH-241	ESPEC	92007516	2016.01.08
8	DC Power Supply	U3606A	Agilent Technologies	MY50450012	2015.11.11
9	RF Switch Matrix	OSP130	Rohde&Schwarz	100259	2016.01.03
10	Vector Signal Generator	SMU200A	Rohde&Schwarz	104072	2016.01.03
11	MXG Analog Signal Generator	N5183A	Agilent Technologies	MY50140012	2016.01.03

## **ANNEX A: MEASUREMENT RESULTS**

### **A.1 OUTPUT POWER**

#### **A.1.1 Summary**

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMU-200) to ensure max power transmission and proper modulation. This result contains output power and EIRP measurements for the EUT. In all cases, output power is within the specified limits.

#### **A.1.2 Conducted**

##### **A.1.2.1 Method of Measurements**

The EUT was set up for the max output power with pseudo random data modulation. The power was measured with Rhode & Schwarz Spectrum Analyzer FSU (peak) These measurements were done at 3 frequencies, 1850.2 MHz, 1880.0MHz and 1909.8MHz for PCS1900 band; 824.2MHz, 836.6MHz and 848.8MHz for GSM850 band. (bottom, middle and top of operational frequency range).

##### **A.1.2.2 Test Condition**

RBW	VBW	Sweep Time	Span
1MHz	1MHz	300ms	10MHz

#### **GSM850**

##### **Measurement result**

##### **GSM850 (GMSK, 1Slot)**

Frequency(MHz)	Power Step	Output power(dBm)
824.2	0	33.71
836.6	0	33.62
848.8	0	33.46

##### **GPRS850 (GMSK, 1Slot)**

Frequency(MHz)	Power Step	Output power(dBm)
824.2	3	31.54
836.6	3	31.01
848.8	3	30.87

##### **EGPRS850 (GMSK, 1Slot)**

Frequency(MHz)	Power Step	Output power(dBm)
824.2	6	31.56
836.6	6	31.04
848.8	6	30.93

#### **PCS1900**

##### **Measurement result**



**PCS1900 (GMSK, 1Slot)**

Frequency(MHz)	Power Step	Output power(dBm)
1850.2	0	30.60
1880.0	0	30.33
1909.8	0	29.57

**GPRS1900 (GMSK, 1Slot)**

Frequency(MHz)	Power Step	Output power(dBm)
1850.2	3	28.86
1880.0	3	28.61
1909.8	3	28.63

**EGPRS1900 (GMSK, 1Slot)**

Frequency(MHz)	Power Step	Output power(dBm)
1850.2	5	28.81
1880.0	5	28.52
1909.8	5	28.51

### A.1.3 Radiated

#### A.1.3.1 Description

This is the test for the maximum radiated power from the EUT.


Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage."

Rule Part 22.913(a) specifies " The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."


#### A.1.3.2 Method of Measurement

The measurements procedures in TIA-603D-2010 are used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power ( $P_{Mea}$ ) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitute Antenna. The cable loss ( $P_{cl}$ ), the Substitute Antenna Gain ( $G_a$ ) and the Amplifier Gain ( $P_{Ag}$ ) should be recorded after test.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_{Ag} - P_{cl} - G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $ERP = EIRP - 2.15\text{dBi}$ .

**GSM 850-ERP**

**Limits**

	Power Step	Burst Peak ERP (dBm)
GSM850	0	≤38.45dBm (7W)
GPRS850	3	≤38.45dBm (7W)
EGPRS850	6	≤38.45dBm (7W)

**Measurement result**

**GSM850**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	Correction (dB)	ERP(dBm)	Polarization
824.20	-11.83	2.26	-45.79	-0.96	2.15	30.51	H
836.60	-10.89	2.26	-45.66	-0.82	2.15	31.18	V
848.80	-10.06	2.28	-45.54	-0.79	2.15	31.84	V

**GPRS850**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	Correction (dB)	ERP(dBm)	Polarization
824.20	-11.82	2.26	-45.79	-0.96	2.15	30.52	V
836.60	-10.88	2.26	-45.66	-0.82	2.15	31.19	V
848.80	-10.08	2.28	-45.54	-0.79	2.15	31.82	V

**EGPRS850**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	Correction (dB)	ERP(dBm)	Polarization
824.20	-11.44	2.26	-45.79	-0.96	2.15	30.90	V
836.60	-10.03	2.26	-45.66	-0.82	2.15	32.04	V
848.80	-8.97	2.28	-45.54	-0.79	2.15	32.93	V

Note: the result contains vertical part and Horizontal part

**ANALYZER SETTINGS: RBW = VBW = 3MHz**

**PCS1900-EIRP**

**Limits**

	Power Step	Burst Peak EIRP (dBm)
PCS1900	0	≤33dBm (2W)
GPRS1900	3	≤33dBm (2W)
EGPRS1900	5	≤33dBm (2W)

**Measurement result**

**PCS1900**

Frequency(MHz)	P <sub>Mea</sub> (dBm )	P <sub>cl</sub> (dB )	P <sub>Ag</sub> (dB )	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Polarization
1850.20	-16.31	2.93	-43.75	-5.25	29.76	V
1880.00	-14.78	2.85	-43.75	-5.19	31.31	V
1909.80	-13.51	2.89	-43.77	-5.13	32.50	V

**GPRS1900**

Frequency(MHz)	P <sub>Mea</sub> (dBm )	P <sub>cl</sub> (dB )	P <sub>Ag</sub> (dB )	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Polarization
1850.20	-16.55	2.93	-43.75	-5.25	29.52	V
1880.00	-14.83	2.85	-43.75	-5.19	31.26	V
1909.80	-13.67	2.89	-43.77	-5.13	32.34	V

**EGPRS1900**

Frequency(MHz)	P <sub>Mea</sub> (dBm )	P <sub>cl</sub> (dB )	P <sub>Ag</sub> (dB )	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Polarization
1850.20	-15.83	2.93	-43.75	-5.25	30.24	H
1880.00	-13.73	2.85	-43.75	-5.19	32.36	H
1909.80	-13.07	2.89	-43.77	-5.13	32.94	H

Note: the result contains vertical part and Horizontal part

**ANALYZER SETTINGS: RBW = VBW = 3MHz**

## **A.2 EMISSION LIMIT**


### **A.2.1 Measurement Method**

The measurement procedures in TIA-603D-2010 are used.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 1910 MHz. The resolution bandwidth is set as outlined in Part 24.238 and Part 22.917. The spectrum is scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of PCS1900 and GSM850

#### **The procedure of radiated spurious emissions is as follows:**

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, a substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power ( $P_{Mea}$ ) is applied to the input of the substitution antenna, and adjusts the level of the signal generator output until the value of the receiver reach the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss ( $P_{pl}$ ) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain ( $G_a$ ) should be recorded after test.  
The Path loss ( $P_{pl}$ ) is the summation of the cable loss and the gain of the amplifier.  
The measurement results are obtained as described below:  
Power(EIRP)= $P_{Mea} - P_{pl} - G_a$
5. Use the power meter to measure the result of power in substitute antenna. Record the result of power meter( $P_{pm}$ ).  
The measurement results are obtained as described below:  
Power(EIRP)=  $P_{pm} - G_a$
6. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
7. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP -2.15dBi.

### **A.2.2 Measurement Limit**

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log(P)$  dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

### **A.2.3 Measurement Results**

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of PCS1900 (1850.2 MHz, 1880 MHz and 1909.8 MHz) and GSM850 (824.2MHz, 836.6MHz, 848.8MHz) . It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the PCS1900 and GSM850 into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

**A.2.4 Measurement Results Table**

Frequency	Channel	Frequency Range	Result
GSM 850MHz	Low	30MHz-10GHz	Pass
	Middle	30MHz-10GHz	Pass
	High	30MHz-10GHz	Pass
GSM 1900MHz	Low	30MHz-20GHz	Pass
	Middle	30MHz-20GHz	Pass
	High	30MHz-20GHz	Pass

**A.2.5 Sweep Table**

Working Frequency	Subrange (GHz)	RBW	VBW	Sweep time (s)
850MHz	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~10	1 MHz	3 MHz	3
1900MHz	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
18~20	1 MHz	3 MHz	2	

Note: the result contains vertical part and Horizontal part

**Channel 128/824.2MHz**

Frequency(MHz)	P <sub>pm</sub> (dBm)	Antenna Gain	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Polarization
2472.88	-44.46	-6.02	2.15	-45.02	-13.00	V
3297.78	-58.78	-7.71	2.15	-58.58	-13.00	V
4123.02	-55.76	-9.02	2.15	-54.69	-13.00	H
4934.19	-59.15	-9.83	2.15	-57.79	-13.00	V
5775.78	-56.34	-10.54	2.15	-54.74	-13.00	H
6585.71	-57.29	-11.1	2.15	-55.38	-13.00	H

**Channel 190/836.6MHz**

Frequency(MHz)	Ppm(dBm)	Antenna Gain	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Polarization
3350.71	-57.01	-7.84	2.15	-56.57	-13.00	H
4194.69	-57.62	-9.09	2.15	-56.61	-13.00	V
5019.38	-56.68	-9.93	2.15	-55.11	-13.00	H
5853.77	-56.55	-10.53	2.15	-54.82	-13.00	H
6678.89	-57.85	-11.21	2.15	-56.19	-13.00	V
7525.49	-58.14	-12.22	2.15	-55.55	-13.00	H

**Channel 251/848.8MHz**

Frequency(MHz)	P <sub>pm</sub> (dBm)	Antenna Gain	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Polarization
2546.31	-43.29	-6.18	2.15	-43.74	-13.00	V
3403.71	-57.97	-7.97	2.15	-57.67	-13.00	V
4241.57	-55.93	-9.14	2.15	-55.00	-13.00	H
5095.44	-58.55	-10.03	2.15	-57.15	-13.00	V
5940.28	-56.05	-10.51	2.15	-54.62	-13.00	V
6787.98	-57.78	-11.35	2.15	-55.64	-13.00	V

**Channel 512/1850.2MHz**

Frequency(MHz)	P <sub>pm</sub> (dBm)	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Polarization
3700.3	-38.63	-8.48	-35.49	-13.00	H
5550.72	-47.08	-10.59	-43.09	-13.00	H
7401.11	-40	-12.08	-35.12	-13.00	H
9251.13	-35.5	-13.25	-30.48	-13.00	V
11100.99	-38.31	-13.18	-34.05	-13.00	H
12962.57	-52.68	-13.48	-48.71	-13.00	V

**Channel 661/1880.0MHz**

Frequency(MHz)	Ppm(dBm)	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Polarization
3760.07	-41.86	-8.56	-38.44	-13.00	H
5640.36	-46.46	-10.57	-42.74	-13.00	H
7520.15	-39.06	-12.22	-34.36	-13.00	H
9399.97	-38.39	-13.34	-33.04	-13.00	V
11279.91	-39.02	-13.14	-35.09	-13.00	H
13161	-48.55	-13.73	-44.53	-13.00	H

**Channel 810/1909.8MHz**

Frequency(MHz)	Ppm(dBm)	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Polarization
3819.6	-43.55	-8.65	-40.38	-13.00	H
5729.46	-45.89	-10.55	-42.10	-13.00	H
7639.46	-37.73	-12.31	-32.99	-13.00	H
9549.4	-37.74	-13.35	-32.6	-13.00	H
11458.96	-38.34	-13.11	-34.11	-13.00	H
13372.66	-50.49	-14.02	-46.26	-13.00	V

## **A.3 FREQUENCY STABILITY**

### **A.3.1 Method of Measurement**

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on channel 661 for PCS 1900 and channel 190 for GSM850 measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 C increments from +50°C to -30°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

### **A.3.2 Measurement Limit**

#### **A.3.2.1 For Hand carried battery powered equipment**

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.5VDC and 4.2VDC, with a nominal voltage of 3.8VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

#### **A.3.2.2 For equipment powered by primary supply voltage**

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the

nominal value for other than hand carried battery equipment.

### A.3.3 Measurement results

#### GSM 850

##### Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.6	-14	0.016
3.8	-7	0.008
4.35	-4	0.005

##### Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	-13	0.015
-20	-12	0.014
-10	-16	0.018
0	-9	0.010
10	-8	0.009
20	-10	0.011
30	-9	0.010
40	-6	0.007
50	-14	0.016

#### PCS 1900

##### Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.6	24	0.012
3.8	9	0.005
4.35	11	0.006

##### Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	27	0.014
-20	18	0.009
-10	21	0.011
0	12	0.006
10	6	0.003
20	-4	0.002
30	15	0.008
40	8	0.004
50	23	0.012

## A.4 OCCUPIED BANDWIDTH

### A.4.1 Occupied Bandwidth Results


Similar to conducted emissions; occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of PCS1900 band and GSM850 band. Spectrum analyzer plots are included on the following pages.

#### GSM 850

Frequency(MHz)	Occupied Bandwidth ( kHz)
824.2	243.59
836.6	246.79
848.8	241.99


#### GSM 850

##### Channel 128-Occupied Bandwidth




Date: 1.MAR.2015 22:21:50

### Channel 190-Occupied Bandwidth



Date: 1.MAR.2015 22:23:02

### Channel 251-Occupied Bandwidth




Date: 1.MAR.2015 22:24:13

**GPRS 850**

Frequency(MHz)	Occupied Bandwidth ( kHz)
824.2	243.59
836.6	243.59
848.8	246.79


**GPRS 850**

**Channel 128-Occupied Bandwidth**




Date: 1.MAR.2015 22:47:10

### Channel 190-Occupied Bandwidth



Date: 1.MAR.2015 22:48:21

### Channel 251-Occupied Bandwidth




Date: 1.MAR.2015 22:49:31

**EGPRS 850**

Frequency(MHz)	Occupied Bandwidth ( kHz)
824.2	240.38
836.6	240.38
848.8	238.78


**EGPRS 850**

**Channel 128-Occupied Bandwidth**




Date: 1.MAR.2015 23:03:11

### Channel 190-Occupied Bandwidth



Date: 1.MAR.2015 23:04:22

### Channel 251-Occupied Bandwidth




Date: 1.MAR.2015 23:05:33

**PCS 1900**

Frequency(MHz)	Occupied Bandwidth ( kHz)
1850.2	241.99
1880.0	243.59
1909.8	246.79


**PCS 1900**

**Channel 512-Occupied Bandwidth**




Date: 2.MAR.2015 17:30:57

### Channel 661-Occupied Bandwidth



Date: 2.MAR.2015 17:22:08


### Channel 810-Occupied Bandwidth



Date: 2.MAR.2015 17:23:19




### Channel 661-Occupied Bandwidth



Date: 2.MAR.2015 17:52:29

### Channel 810-Occupied Bandwidth




Date: 2.MAR.2015 17:53:40

**EGPRS 1900**


Frequency(MHz)	Occupied Bandwidth ( kHz)
1850.2	241.99
1880.0	241.99
1909.8	241.99

**Channel 512-Occupied Bandwidth**




Date: 2.MAR.2015 19:03:56

### Channel 661-Occupied Bandwidth



Date: 2.MAR.2015 19:05:06

### Channel 810-Occupied Bandwidth



Date: 2.MAR.2015 19:06:17

## A.5 EMISSION BANDWIDTH

### A.5.1 Emission Bandwidth Results


Similar to conducted emissions; Emission bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of PCS1900 band and GSM850 band. Table below lists the measured -26dBc BW. Spectrum analyzer plots are included on the following pages.

#### GSM 850(-26dBc)

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)( kHz)
824.2	318.91
836.6	322.12
848.8	323.72

#### GSM 850

#### Channel 128-Occupied Bandwidth (-26dBc BW)



Date: 1.MAR.2015 22:25:28




**GPRS 850(-26dBc)**

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)( kHz)
824.2	317.31
836.6	325.32
848.8	323.72


**GPRS 850**

**Channel 128-Occupied Bandwidth (-26dBc BW)**




Date: 1.MAR.2015 22:50:47

### Channel 190-Occupied Bandwidth (-26dBc BW)



Date: 1.MAR.2015 22:52:00


### Channel 251-Occupied Bandwidth (-26dBc BW)



Date: 1.MAR.2015 22:53:13




### Channel 190-Occupied Bandwidth (-26dBc BW)



Date: 1.MAR.2015 23:08:02

### Channel 251-Occupied Bandwidth (-26dBc BW)




Date: 1.MAR.2015 23:09:15

**PCS 1900(-26dBc)**

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)( kHz)
1850.2	317.31
1880.0	325.32
1909.8	331.73

**PCS 1900**

**Channel 512-Occupied Bandwidth (-26dBc BW)**



Date: 2.MAR.2015 17:34:33




**GPRS 1900(-26dBc)**

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)( kHz)
1850.2	323.72
1880.0	315.71
1909.8	322.12


**GPRS 1900**

**Channel 512-Occupied Bandwidth (-26dBc BW)**




Date: 2.MAR.2015 17:54:56

### Channel 661-Occupied Bandwidth (-26dBc BW)



Date: 2.MAR.2015 17:56:08

### Channel 810-Occupied Bandwidth (-26dBc BW)




Date: 2.MAR.2015 17:57:21

**EGPRS 1900(-26dBc)**

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)( kHz)
1850.2	323.72
1880.0	322.12
1909.8	320.51

**EGPRS 1900**

**Channel 512-Occupied Bandwidth (-26dBc BW)**




Date: 2.MAR.2015 19:07:34



## A.6 BAND EDGE COMPLIANCE


### GSM 850

#### LOW BAND EDGE BLOCK-A (GSM850)-Channel 128




Date: 1.MAR.2015 22:29:45

#### HIGH BAND EDGE BLOCK-C (GSM850) -Channel 251




Date: 1.MAR.2015 22:31:33

**GPRS 850**  
**LOW BAND EDGE BLOCK-A (GSM850)-Channel 128**




Date: 1.MAR.2015 22:55:03

**HIGH BAND EDGE BLOCK-C (GSM850) –Channel 251**




Date: 1.MAR.2015 22:56:51

**EGPRS 850**  
**LOW BAND EDGE BLOCK-A (GSM850)-Channel 128**




Date: 1.MAR.2015 23:11:06

**HIGH BAND EDGE BLOCK-C (GSM850) –Channel 251**




Date: 1.MAR.2015 23:12:53

**PCS 1900**  
**LOW BAND EDGE BLOCK-A (PCS-1900)-Channel 512**




Date: 2.MAR.2015 17:38:50

**HIGH BAND EDGE BLOCK-C (PCS-1900) –Channel 810**




Date: 2.MAR.2015 17:40:38

**GPRS 1900**  
**LOW BAND EDGE BLOCK-A (PCS-1900)-Channel 512**




Date: 2.MAR.2015 17:59:12

**HIGH BAND EDGE BLOCK-C (PCS-1900) –Channel 810**




Date: 2.MAR.2015 18:00:59

**EGPRS 1900**  
**LOW BAND EDGE BLOCK-A (PCS-1900)-Channel 512**



Date: 2.MAR.2015 19:11:51

**HIGH BAND EDGE BLOCK-C (PCS-1900) –Channel 810**



Date: 2.MAR.2015 19:13:39

## **A.7 CONDUCTED SPURIOUS EMISSION**

### **A.7.1 Measurement Method**

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of PCS1900 band, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz. For GSM850, data taken from 30 MHz to 10 GHz.
2. The sweep time is set automatically by instrument itself. That should be the optimal sweep time for the span and the RBW. If the sweep time is too short, that is sweep is too fast, the sweep result is not accurate; If the sweep time is too long, that is sweep is too low, some frequency components may be lost. The instrument will give a optimal sweep time according the selected span and RBW.
3. The procedure to get the conducted spurious emission is as follows:  
The trace mode is set to MaxHold to get the highest signal at each frequency;  
Wait 25 seconds;  
Get the result.
4. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

#### **GSM850 Transmitter**

Channel	Frequency (MHz)
128	824.2
190	836.6
251	848.8

#### **PCS1900 Transmitter**

Channel	Frequency (MHz)
512	1850.2
661	1880.0
810	1909.8

### **A. 7.2 Measurement Limit**

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log (P)$  dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.


**A. 7.3 Measurement result**

**GSM850**

**A.7.3.1 Channel 128: 30MHz – 1GHz**

Spurious emission limit –13dBm.


**NOTE: peak above the limit line is the carrier frequency.**



Date: 1.MAR.2015 22:31:55


**A.7.3.2 Channel 128: 1GHz – 2.5GHz**

Spurious emission limit –13dBm.




Date: 1.MAR.2015 22:32:12

**A.7.3.3 Channel 128: 2.5GHz – 7.5GHz**  
Spurious emission limit –13dBm.



Date: 1.MAR.2015 22:32:30

**A.7.3.4 Channel 128: 7.5GHz –10GHz**  
Spurious emission limit –13dBm.




Date: 1.MAR.2015 22:32:47

### A.7.3.5 Channel 190: 30MHz – 1GHz

Spurious emission limit –13dBm


**NOTE: peak above the limit line is the carrier frequency.**



Date: 1.MAR.2015 22:33:08


### A.7.3.6 Channel 190: 1GHz –2.5GHz

Spurious emission limit –13dBm




Date: 1.MAR.2015 22:33:25

**A.7.3.7 Channel 190: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm



Date: 1.MAR.2015 22:33:43

**A.7.3.8 Channel 190: 7.5GHz –10GHz**  
Spurious emission limit –13dBm




Date: 1.MAR.2015 22:34:00

### A.7.3.9 Channel 251: 30MHz – 1GHz

Spurious emission limit –13dBm.


**NOTE: peak above the limit line is the carrier frequency.**



Date: 1.MAR.2015 22:34:21


### A.7.3.10 Channel 251: 1GHz – 2.5GHz

Spurious emission limit –13dBm.




Date: 1.MAR.2015 22:34:38

**A.7.3.11 Channel 251:2.5GHz – 7.5GHz**  
Spurious emission limit –13dBm.




Date: 1.MAR.2015 22:34:56

**A.7.3.12 Channel 251: 7.5GHz – 10GHz**  
Spurious emission limit –13dBm.




Date: 1.MAR.2015 22:35:13

**A.7.3.13 Idle mode: 30MHz – 1GHz**  
Spurious emission limit –13dBm.




Date: 1.MAR.2015 22:35:36

**A.7.3.14 Idle mode: 1GHz – 2.5GHz**  
Spurious emission limit –13dBm.




Date: 1.MAR.2015 22:35:53

**A.7.3.15 Idle mode: 2.5GHz – 7.5GHz**  
Spurious emission limit –13dBm.



Date: 1.MAR.2015 22:36:11

**A.7.3.16 Idle mode: 7.5GHz – 10GHz**  
Spurious emission limit –13dBm.




Date: 1.MAR.2015 22:36:29

PCS1900

A.7.3.17 Channel 512: 30MHz – 1GHz

Spurious emission limit –13dBm.




Date: 2.MAR.2015 17:40:59

A.7.3.18 Channel 512: 1GHz – 2.5GHz


Spurious emission limit –13dBm.

**NOTE: peak above the limit line is the carrier frequency.**




Date: 2.MAR.2015 17:41:12

**A.7.3.19 Channel 512: 2.5GHz – 7.5GHz**  
Spurious emission limit –13dBm.




Date: 2.MAR.2015 17:41:30

**A.7.3.20 Channel 512: 7.5GHz –10GHz**  
Spurious emission limit –13dBm.




Date: 2.MAR.2015 17:41:47

**A.7.3.21 Channel 512: 10GHz –15GHz**  
Spurious emission limit –13dBm.




Date: 2.MAR.2015 17:42:05

**A.7.3.22 Channel 512: 15GHz –20GHz**  
Spurious emission limit –13dBm.



Date: 2.MAR.2015 17:42:22


**A.7.3.23 Channel 661: 30MHz – 1GHz**  
Spurious emission limit –13dBm



Date: 2.MAR.2015 17:42:43


**A.7.3.24 Channel 661: 1GHz –2.5GHz**  
Spurious emission limit –13dBm

**NOTE: peak above the limit line is the carrier frequency.**




Date: 2.MAR.2015 17:42:55

**A.7.3.25 Channel 661: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm




Date: 2.MAR.2015 17:43:13

**A.7.3.26 Channel 661: 7.5GHz –10GHz**  
Spurious emission limit –13dBm




Date: 2.MAR.2015 17:43:31

**A.7.3.27 Channel 661: 10GHz –15GHz**  
Spurious emission limit –13dBm.




Date: 2.MAR.2015 17:43:48

**A.7.3.28 Channel 661: 15GHz –20GHz**  
Spurious emission limit –13dBm.



Date: 2.MAR.2015 17:44:06


**A.7.3.29 Channel 810: 30MHz – 1GHz**  
Spurious emission limit –13dBm.



Date: 2.MAR.2015 17:44:26


**A.7.3.30 Channel 810: 1GHz – 2.5GHz**  
Spurious emission limit –13dBm.

**NOTE: peak above the limit line is the carrier frequency.**




Date: 2.MAR.2015 17:44:39

**A.7.3.31 Channel 810:2.5GHz – 7.5GHz**  
Spurious emission limit –13dBm.




Date: 2.MAR.2015 17:44:56

**A.7.3.32 Channel 810: 7.5GHz – 10GHz**  
Spurious emission limit –13dBm.




Date: 2.MAR.2015 17:45:14

**A.7.3.33 Channel 810: 10GHz –15GHz**  
Spurious emission limit –13dBm.




Date: 2.MAR.2015 17:45:31

**A.7.3.34 Channel 810: 15GHz –20GHz**  
Spurious emission limit –13dBm.




Date: 2.MAR.2015 17:45:49

**A.7.3.35 Idle mode: 30MHz – 1GHz**  
Spurious emission limit –13dBm.




Date: 2.MAR.2015 17:46:11

**A.7.3.36 Idle mode: 1GHz – 2.5GHz**  
Spurious emission limit –13dBm.




Date: 2.MAR.2015 17:46:24

**A.7.3.37 Idle mode: 2.5GHz – 7.5GHz**  
Spurious emission limit –13dBm.




Date: 2.MAR.2015 17:46:42

**A.7.3.38 Idle mode: 7.5GHz – 10GHz**  
Spurious emission limit –13dBm.




Date: 2.MAR.2015 17:46:59

**A.7.3.39 Idle mode: 10GHz –15GHz**  
Spurious emission limit –13dBm.



Date: 2.MAR.2015 17:47:17

**A.7.3.40 IDLE mode: 15GHz –20GHz**  
Spurious emission limit –13dBm.



Date: 2.MAR.2015 17:47:34

## **A.8 PEAK-TO-AVERAGE POWER RATIO**

### **A.8.1 Measurement description**

According to KDB971168, the transmitter's peak-to-average power ratio (PAPR) shall not exceed 13 dB for more than 0.1% of the time using a signal corresponding to the highest PAPR during periods of continuous transmission.

The parameter of spectrum analyzer: RBW = 10MHz, detector = sample, No. of sample = 500,000

### **A.8.2 Measurement results**

#### **Frequency Error vs Temperature**

	Frequency(MHz)	PAPR(dB)
GSM850	836.60	7.32
GPRS850	836.60	7.36
EGPRS850	836.60	7.25
PCS1900	1880.00	7.49
GPRS1900	1880.00	7.41
EGPRS1900	1880.00	7.64

**\*\*\*END OF REPORT\*\*\***