



Neutron Engineering Inc.

FCC RF EXPOSURE REPORT

FCC ID: QISAP6610DN-AGN

Project No. : 1204C048C
Equipment : Outdoor Wireless LAN Access Point
Model : AP6610DN-AGN-US
Applicant : Huawei Technologies Co.,Ltd.
**Address : Administration Building, Headquarters of
Huawei Technologies Co., Ltd., Bantian,
Longgang District Shenzhen China**

According: : FCC Guidelines for Human Exposure IEEE C95.1

Neutron Engineering Inc.

No.3, Jinshagang 1st Road, ShiXia, Dalang Town, Dong Guan, China.

TEL : (0769) 8318-3000 FAX : (0769) 8319-6000



MPE CALCULATION METHOD:

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi^2} = \frac{EIRP}{4\pi^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna:

Ant.	Manufacturer	Model Name	Antenna Type / Connector	Gain (dBi)	Note
1	Guangdong Shenglu Telecommunication Tech. Co., LTD.	SL10671A	Directional Antenna / N Male	5.9	TX/RX
2	Guangdong Shenglu Telecommunication Tech. Co., LTD.	SL10671A	Directional Antenna / N Male	5.9	TX/RX

Note: The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitters and two receivers (2T2R). All transmit signals are completely uncorrelated, then, Direction gain = G_{ANT} , that is Directional gain=5.9.



TEST RESULTS

Band 2

EUT:	Outdoor Wireless LAN Access Point	Model Name :	AP6610DN-AGN-US
Temperature:	25 °C	Relative Humidity:	58 %
Test Voltage:	AC 120V/60Hz		
Test Mode :	Band 2/TX A Mode/CH52, CH56, CH64		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
5.9	3.8905	19.12	81.6582	0.06323396	1	Complies
5.9	3.8905	19.44	87.9023	0.06806916	1	Complies
5.9	3.8905	19.39	86.8960	0.06728998	1	Complies

Band 3

EUT:	Outdoor Wireless LAN Access Point	Model Name :	AP6610DN-AGN-US
Temperature:	25 °C	Relative Humidity:	58 %
Test Voltage:	AC 120V/60Hz		
Test Mode :	Band 3/TX A Mode/CH100, CH112, CH140		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
5.9	3.8905	18.65	73.2825	0.05674798	1	Complies
5.9	3.8905	19.13	81.8465	0.06337973	1	Complies
5.9	3.8905	18.11	64.7143	0.05011300	1	Complies



Neutron Engineering Inc.

Band 4

EUT:	Outdoor Wireless LAN Access Point	Model Name :	AP6610DN-AGN-US
Temperature:	25 °C	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX N20 Mode /CH149, CH157, CH165		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
5.9	3.8905	25.89	388.1504	0.30057328	1	Complies
5.9	3.8905	26.03	400.8667	0.31042048	1	Complies
5.9	3.8905	26.14	411.1497	0.31838337	1	Complies

Note: The calculated distance is 20 cm.